动态路由获取url参数和404页面路由

动态路由获取url参数

```
//1.route2文件夹下有Home.js, Main.js, router.js, info.js
Main.js是嵌套在Home主页面中的子主页面(只有主页面需要渲染的部分), router.js是主页面的路由配置
文件
//2.在Main.js中
import React, { Component } from 'react';
import { Link } from 'react-router-dom';
export default class Main extends Component {
 render() {
   return (
     <div>
       this is main page.
       <Link to="/main/test-id">嵌套路由1</Link>
       <Link to="/main/456">嵌套路由2</Link>
       {this.props.children}
     </div>
   )
 }
}
//Home.js
import React, { Component } from 'react';
import { Link } from 'react-router-dom';
class Home extends Component {
 render() {
   return (
     <HashRouter>
       <div>
         <l
           <1i>>
             <Link to="/main">Home</Link> //改动了
           <1i>>
             <Link to="/about">About</Link>
           <1i>>
             <Link to="/topics">Topics</Link>
```

```
<hr />
                                     //接收路由跳转router.js文件传过来的东西
         {this.props.children}
       </div>
     </HashRouter>
   );
 }
}
export default Home;
//3.router.js中
import ... 各种组件
render() {
 return (
   <Router>
     <Home>
       <Route path="/main" render={() =>
           <Main>
             <Route path="/main/:value" component={Info}></Route>
           </Main>
       }></Route>
       <Route path="/about" component={About}></Route>
       <Route path="/topics" component={Topic}></Route>
     </Home>
   </Router>
}
//4.info.js中
import React, { Component } from 'react';
export default class Info extends Component {
 render() {
   return (
     <div>
       这里是测试动态路由功能。
       动态路由的值是: {this.props.match.params.value}
     </div>
   )
 }
}
```

404页面路由

```
//1.route2文件夹下有Home.js, Main.js, router.js, info.js
Main.js是嵌套在Home主页面中的子主页面(只有主页面需要渲染的部分), router.js是主页面的路由配置
文件
//2.在Main.js中
import React, { Component } from 'react';
import { Link } from 'react-router-dom';
export default class Main extends Component {
 render() {
   return (
     <div>
       this is main page.
       <Link to="/main/test-id">嵌套路由1</Link>
       <Link to="/main/456">嵌套路由2</Link>
       {this.props.children}
     </div>
   )
 }
}
//Home.js
import React, { Component } from 'react';
import { Link } from 'react-router-dom';
class Home extends Component {
 render() {
   return (
     <HashRouter>
       <div>
         <1i>>
            <Link to="/main">Home</Link>
          <1i>>
            <Link to="/about">About</Link>
           <1i>>
            <Link to="/topics">Topics</Link>
          <1i>>
            <Link to="/immoc">Imooc</Link> //新增
          <hr />
         {this.props.children} //接收路由跳转router.js文件传过来的东西
       </div>
```

```
</HashRouter>
   );
 }
}
export default Home;
//3.router.js中
import ... 各种组件
import NoMatch from './NoMatch' //新增
render() {
 return (
   <Router>
      <Home>
                        //新增
       <Switch>
         <Route path="/main" render={() =>
             <Main>
               <Route path="/main/:value" component={Info}></Route>
             </Main>
         }></Route>
         <Route path="/about" component={About}></Route>
         <Route path="/topics" component={Topic}></Route>
         <Route component={NoMatch}></Route>
       </Switch>
      </Home>
   </Router>
}
//4.info.js中
import React, { Component } from 'react';
export default class Info extends Component {
 render() {
   return (
      <div>
       这里是测试动态路由功能。
       动态路由的值是: {this.props.match.params.value}
      </div>
   )
 }
}
//5.NoMatch.js
                          //新增
import React, { Component } from 'react';
export default class Info extends Component {
 render() {
```