



Storing Data: Disks and Files



Block diagram of a DBMS



Disks, Memory, and Files



A brief note on terminology

Block = Page

- Unit of transfer for disk read/write
- Typically 4KB in the book
 - And hence in formulas in slides
- 64KB is a good number today

Relation = Table

Tuple = Row = Record

Attribute = Column = Field



Disks and Files

- DBMS stores information on disks.
 - Disks are a mechanical anachronism!
- Major implications for DBMS design!
 - **READ**: transfer data from disk to main memory (RAM).
 - **WRITE**: transfer data from RAM to disk.
 - Both high-cost relative to memory references
 - Can/should plan carefully!




Recall: Components of a Disk


- Platters spin (say 120 rps = 7200 rpm)

- Arm assembly moved in or out to position a head on a desired track.
 - Tracks under heads make a cylinder (imaginary)

- Only one head reads/writes at any one time

- *page size* is a multiple of (fixed) *sector size*






Recall: Accessing a Disk Page

- Time to access (read/write) a disk page:
 - seek time* (moving arms to position disk head on track)
 - rotational delay* (waiting for page to rotate under head)
 - transfer time* (actually moving data to/from disk surface)
- Seek time and rotational delay dominate.
 - Seek time varies from 0 to 12 msec (average 4-9)
 - Rotational delay at 7200 rpm = 4.2 msec average
 - Transfer rate peak around 100 MB/sec
- Key to lower I/O cost: **reduce seek/rotation delays!** Hardware vs. software solutions?

Recall: Arranging Pages on Disk

- 'Next' page concept:
 - pages on same track, followed by
 - pages on same cylinder, followed by
 - pages on adjacent cylinder
- Arrange file pages sequentially on disk
 - minimize seek and rotational delay.
- For a sequential scan, pre-fetch
 - several pages at a time!



Disk Space Management

- Lowest layer of DBMS, manages space on disk
- Higher levels call upon this layer to:
 - allocate/de-allocate a page
 - read/write a page
- Request for a *sequence* of pages best satisfied by pages stored sequentially on disk!
 - Responsibility of disk space manager.
 - Physical details hidden from higher levels of system
 - Though they may make performance assumptions!
 - Hence disk space manager should do a decent job.

Files of Records

- Pages are the interface for I/O, but...
- Higher levels of DBMS operate on *records*, and *files of records*.
- FILE**: A collection of pages, each containing a collection of records. Must support:
 - insert/delete/modify record
 - fetch a particular record (specified using *record id*)
 - scan all records (possibly with some conditions on the records to be retrieved)
- Typically implemented as multiple OS "files"
 - Or "raw" disk space




Unordered (Heap) Files

- Collection of records in no particular order.
- As file shrinks/grows, disk pages (de)allocated
- To support record level operations, we must:
 - keep track of the *pages* in a file
 - keep track of *free space* on pages
 - keep track of the *records* on a page
- There are many alternatives for keeping track of this.
 - We'll consider 2




Heap File Implemented as a List



- Header page ID and Heap file name stored elsewhere
 - Database "catalog"
- Each page contains 2 "pointers" plus data
 - Problem for multi-page objects (blobs) – how to read blobs?



Better: Use a Page Directory



- Directory entries include #free bytes on the page.
- Directory is a collection of pages; linked list implementation is just one alternative.
 - Much smaller than linked list of all HF pages!
 - Can also point to groups of pages (say 64k chunks)




Indexes (sneak preview)

- A Heap file allows us to retrieve records:
 - by specifying the *rid*, or
 - by scanning all records sequentially
- Nice to fetch records *by value*, e.g.,
 - Find all students in the "CS" department
 - Find all students with a gpa > 3 AND blue hair
- Indexes: file structures for efficient value-based queries



Record Formats: Fixed Length




- Field types same for all records in a file.
 - Type info stored separately in *system catalog*.
- Finding *i*'th field done via arithmetic like arrays



Record Formats: Variable Length

- Two alternative formats (# fields is fixed):



Second offers direct access to *i*'th field, efficient storage of *nulls* (special *unknown* value); small directory overhead.

Page Formats: Fixed Length Records

Record id = <page id, slot #>.

In first alternative, moving records for free space management *changes rid*; may be problematic!

"Slotted Page" Format: Variable Length Records

Can move records on page without changing rid!
So, attractive for fixed-length records too.

Slotted page: a detailed view

- Note each slot entry is (start, length)
- What's the biggest tuple you can add?
 - 2 bytes of slot space
 - x bytes of storage

System Catalogs

- For each relation:
 - name, file location, file structure (e.g., Heap file)
 - attribute name and type, for each attribute
 - index name, for each index
 - integrity constraints
- For each index:
 - structure (e.g., B+ tree) and search key fields
- For each view:
 - view name and definition
- Plus statistics, authorization, buffer pool size, etc.

➤ *Catalogs are themselves stored as relations!*

Attr_Cat(attr_name, rel_name, type, position)

attr_name	rel_name	type	position
attr_name	Attribute_Cat	string	1
rel_name	Attribute_Cat	string	2
type	Attribute_Cat	string	3
position	Attribute_Cat	integer	4
sid	Students	string	1
name	Students	string	2
login	Students	string	3
age	Students	integer	4
gpa	Students	real	5
fid	Faculty	string	1
fname	Faculty	string	2
sal	Faculty	real	3







pg_attribute


```


postgres=# \d pg_attribute
Table "pg_catalog.pg_attribute"
Column | Type | Modifiers
-----+-----+-----
attrelid | oid | not null
attname | name | not null
atttypid | oid | not null
attstattarget | integer | not null
attlen | smallint | not null
attnum | smallint | not null
attndim | integer | not null
attcacheoff | integer | not null
atttypmod | integer | not null
attbyval | boolean | not null
attstorage | "char" | not null
attalign | "char" | not null
attnotnull | boolean | not null
attisdef | boolean | not null
attisdropped | boolean | not null
attislocal | boolean | not null
attinhcount | integer | not null
attcollation | oid | not null
attcoll | "collname" |
attoptions | text[] |
attfdwoptions | text[] |

Indexes:
    "pg_attribute_relid_attname_index" UNIQUE, btree (attrelid, attname)
    "pg_attribute_relid_attnum_index" UNIQUE, btree (attrelid, attnum)

postgres=#
  
```




 "Clock" Replacement Policy




- An approximation of LRU
- Arrange frames into a (logical) cycle, store one *reference bit per frame*
 - Can think of this as the *2nd chance* bit
- When pin count reduces to 0, turn on ref. bit
- When replacement necessary:


```
do for each frame in cycle {
    if (pincount == 0 && ref bit is on)
        turn off ref bit; // 2nd chance
    else if (pincount == 0 && ref bit is off)
        choose this page for replacement;
      } until a page is chosen;
```


 DBMS vs. OS File System

OS does disk space & buffer mgmt:
why not let OS manage these tasks?


- Buffer management in DBMS requires ability to:
 - pin page in buffer pool, force page to disk, order writes
 - important for implementing CC & recovery
 - adjust *replacement policy*, and *pre-fetch* pages based on access patterns in typical DB operations.
- I/O typically done via lower-level OS interfaces
 - Avoid OS "file cache"
 - Control write timing, prefetching

 Summary

- Disks provide cheap, non-volatile storage.
 - Better random access than tape, worse than RAM
 - Magnetic disks well understood; flash evolving quickly.
 - For mag disk, arrange data to minimize *seek* and *rotation* delays.
 - Depends on workload!
- DBMS vs. OS File Support
 - DBMS needs non-default features
 - Careful timing of writes, control over prefetch
- Variable length record format
 - Direct access to i'th field and null values.
- Slotted page format
 - Variable length records and intra-page reorg

 Summary (Contd.)

- DBMS "File" tracks collection of pages, records within each.
 - Pages with free space identified using linked list or directory structure
- Indexes support efficient retrieval of records based on the values in some fields.
- Catalog relations store information about relations, indexes and views.

 Summary (Contd.)

- Buffer manager brings pages into RAM.
 - Page pinned in RAM until released by requestor.
 - Dirty pages written to disk when frame replaced (sometime after requestor unpins the page).
 - Choice of frame to replace based on *replacement policy*.
 - Tries to *pre-fetch* several pages at a time.