



Sentiment Analysis: Corpus-based approaches

Carolina Scarton

`c.scarton@sheffield.ac.uk`

Text Processing
Department of Computer Science, University of Sheffield
Autumn Semester 2024

Learning objectives

- ▶ Explain the Naïve Bayes model for sentiment analysis
- ▶ Explain the Laplace smoothing technique
- ▶ Explain the Binary Naïve Bayes model
- ▶ Identify other tasks for which the same approach is applicable

Sentiment Analysis: 2 main approaches

- ▶ **Lexicon based**

- ▶ Binary
- ▶ Graggable

- ▶ **Corpus based**

- ▶ **Naive Bayes**
- ▶ Deep Learning

Corpus-based approaches: Naive Bayes

Principle

Assign the **sentiment** or **class** having the highest **posterior probability**.

Namely, determine the sentiment s^* of text T such that:

$$s^* = \underset{s_i}{\operatorname{argmax}} p(s_i | T) \text{ for } s_i \in \{\text{negative}, \text{positive}, \text{neutral}\}$$

$p(s_i | T)$ cannot be directly estimated...

Corpus-based approaches: Naive Bayes

Principle

Assign the **sentiment** or **class** having the highest **posterior probability**.

Namely, determine the sentiment s^* of text T such that:

$$s^* = \underset{s_i}{\operatorname{argmax}} p(s_i | T) \text{ for } s_i \in \{\text{negative, positive, neutral}\}$$

$p(s_i | T)$ cannot be directly estimated...

→ use the **Bayes rule**:

$$p(s_i | T) = \frac{p(T | s_i)p(s_i)}{p(T)}$$

Corpus-based approaches: Naive Bayes

Bayes classifier:

$$\mathbf{s}^* = \operatorname{argmax}_{s_i} \frac{p(T|s_i)p(s_i)}{p(T)}$$

Corpus-based approaches: Naive Bayes

Bayes classifier:

$$\mathbf{s}^* = \operatorname{argmax}_{s_i} \frac{p(T|s_i)p(s_i)}{\mathbf{p(T)}}$$

Since **evidence** $\mathbf{p(T)}$ is independent of s_i , we can ignore it

$$\mathbf{s}^* = \operatorname{argmax}_{s_i} p(T|s_i)p(s_i)$$

Corpus-based approaches: Naive Bayes

Bayes classifier:

$$\mathbf{s}^* = \operatorname{argmax}_{s_i} \frac{p(T|s_i)p(s_i)}{p(T)}$$

Since **evidence** $p(T)$ is independent of s_i , we can ignore it

$$\mathbf{s}^* = \operatorname{argmax}_{s_i} p(T|s_i)p(s_i)$$

- ▶ $p(s_i|T)$ is the **posterior probability**
- ▶ $p(T|s_i)$ is the **likelihood**
- ▶ $p(s_i)$ is the **prior probability**

Corpus-based approaches: Naive Bayes

How to compute the likelihood?

Assume that T is described by a number of **features** or attributes t_1, t_2, \dots, t_N

Corpus-based approaches: Naive Bayes

How to compute the likelihood?

Assume that T is described by a number of **features** or attributes t_1, t_2, \dots, t_N

Naive assumption: **features** are **independent**

$$p(T|s_i) = p(t_1, t_2, \dots, t_N|s_i) \approx \prod_{j=1}^N p(t_j|s_i)$$

Corpus-based approaches: Naive Bayes

How to compute the likelihood?

Assume that T is described by a number of **features** or attributes t_1, t_2, \dots, t_N

Naive assumption: **features** are **independent**

$$p(T|s_i) = p(t_1, t_2, \dots, t_N|s_i) \approx \prod_{j=1}^N p(t_j|s_i)$$

\Rightarrow product of probabilities of each **feature** value of text occurring with class s_i

Corpus-based approaches: Naive Bayes

How to compute the prior probability?

→ corresponds to the safest decision when no other information is given \sim majority voting

Corpus-based approaches: Naive Bayes

How to compute the prior probability?

→ corresponds to the safest decision when no other information is given \sim majority voting

Requires an **annotated corpus** (text along with their sentiment)

Corpus-based approaches: Naive Bayes

How to compute the prior probability?

→ corresponds to the safest decision when no other information is given \sim majority voting

Requires an **annotated corpus** (text along with their sentiment)

Compute **prior probability** by simple relative frequency

$$p(s_i) = \frac{\text{count}(s_i)}{\sum_{j=0}^J \text{count}(s_j)}$$

with J the number of different classes and $\text{count}(\cdot)$ is the counting function

Digression: corpus-based machine learning

Digression: corpus-based machine learning

- ▶ **training** set → used to **estimate probabilities**
 - ▶ input data along with the ground truth (correct labels)

Digression: corpus-based machine learning

- ▶ **training** set → used to **estimate probabilities**
 - ▶ input data along with the ground truth (correct labels)
- ▶ **development** set, also called **validation** set → used to **design** the model
 - ▶ e.g. feature selection, set meta-parameters (could be some weights)
 - ▶ ground truth (correct labels) available
 - ▶ used to select the best model

Digression: corpus-based machine learning

- ▶ **training** set → used to **estimate probabilities**
 - ▶ input data along with the ground truth (correct labels)
- ▶ **development** set, also called **validation** set → used to **design** the model
 - ▶ e.g. feature selection, set meta-parameters (could be some weights)
 - ▶ ground truth (correct labels) available
 - ▶ used to select the best model
- ▶ **test** set → used to **evaluate generalisation** power
 - ▶ unseen examples
 - ▶ best case: no access to the ground truth

Naive Bayes classifier

Final decision

$$\mathbf{s}^* = \operatorname{argmax}_{s_i} p(s_i) \prod_{j=1}^N p(t_j | s_i)$$

Naive Bayes classifier

Final decision

$$\mathbf{s}^* = \operatorname{argmax}_{s_i} p(s_i) \prod_{j=1}^N p(t_j | s_i)$$

1. Compute **prior probability** of each class

Naive Bayes classifier

Final decision

$$\mathbf{s}^* = \operatorname{argmax}_{s_i} p(s_i) \prod_{j=1}^N p(t_j | s_i)$$

1. Compute **prior probability** of each class
2. For each class:
 - ▶ Compute **likelihood** of each feature

Naive Bayes classifier

Final decision

$$\mathbf{s}^* = \operatorname{argmax}_{s_i} p(s_i) \prod_{j=1}^N p(t_j | s_i)$$

1. Compute **prior probability** of each class
2. For each class:
 - ▶ Compute **likelihood** of each feature
3. Calculate the **posterior probability** by product of previous components

Naive Bayes classifier

Final decision

$$\mathbf{s}^* = \underset{s_i}{\operatorname{argmax}} p(s_i) \prod_{j=1}^N p(t_j | s_i)$$

1. Compute **prior probability** of each class
2. For each class:
 - ▶ Compute **likelihood** of each feature
3. Calculate the **posterior probability** by product of previous components
4. Select sentiment having maximum posterior probability
→ **negative**, **positive** or **neutral**

Naive Bayes for Sentiment Analysis - Example

Consider the following dummy **training** corpus of 7 movie reviews:

Doc	Words	Class
1	great movie, excellent plot, renowned actors	positive
2	I had not seen a fantastic plot like this in good 5 years. amazing!!!	positive
3	lovely plot, amazing cast, somehow I am in love with the bad guy	positive
4	bad movie with great cast, but very poor plot and unimaginative ending	negative
5	I hate this film, it has nothing original	negative
6	great movie, but not...	negative
7	very bad movie, I have no words to express how I dislike it	negative

Naive Bayes for Sentiment Analysis - Example

Compute **prior probability** of each class by relative frequency

$$p(\text{positive}) = \frac{\text{count}(\text{positive})}{\sum_{s \in \{\text{positive}, \text{negative}\}} \text{count}(s)} = \frac{3}{7} = 0.43$$

$$p(\text{negative}) = \frac{\text{count}(\text{negative})}{\sum_{s \in \{\text{positive}, \text{negative}\}} \text{count}(s)} = \frac{4}{7} = 0.57$$

Naive Bayes for Sentiment Analysis - Example

What **features** should we consider?

- ▶ could use **all** words
 - ▶ but some might not be relevant → we are interested in the **emotion words**
- ▶ in this example: focus on **adjectives** (**bag-of-word** representation)

Doc	Words	Class
1	great movie, excellent plot, renowned actors	positive
2	I had not seen a fantastic plot like this in good 5 years. amazing !!!	positive
3	Lovely plot, amazing cast, somehow I am in love with the bad guy	positive
4	bad movie with great cast, but very poor plot and unimaginative ending	negative
5	I hate this film, it has nothing original	negative
6	great movie, but bad casting...	negative
7	Very bad movie, I have no words to express how I dislike it	negative

Naive Bayes for Sentiment Analysis - Example

What **features** should we consider?

- ▶ could use **all** words
 - ▶ but some might not be relevant → we are interested in the **emotion words**
- ▶ in this example: focus on **adjectives** (**bag-of-words** representation)

Doc	Words	Class
1	great excellent renowned	positive
2	fantastic good amazing !!!	positive
3	lovely amazing bad	positive
4	bad great poor unimaginative	negative
5	original	negative
6	great bad	negative
7	bad	negative

Naive Bayes for Sentiment Analysis - Example




Figure 4.1 Intuition of the multinomial naive Bayes classifier applied to a movie review. The position of the words is ignored (the *bag of words* assumption) and we make use of the frequency of each word.

[Jurafsky and Martin, 2021]

Naive Bayes for Sentiment Analysis - Example

Compute the **likelihoods** for all features in a given each class

Important

Assume **standard pre-processing**: tokenisation, lowercasing, punctuation removal (but keep special punctuation, e.g. "!!!")

Examples:

- ▶ GOOD = GooD = Good = good
- ▶ I'll = I will (though not relevant here)
- ▶ aren't = are not

Naive Bayes for Sentiment Analysis - Example

Compute the **likelihoods** for all features in a given each class

$$p(t_j | s_i) = \frac{\text{count}(t_j, s_i)}{\sum_f \text{count}(t_f, s_i)} \rightarrow \text{relative frequency}$$

p(amazing	positive)	= 2/10
p(bad	positive)	= 1/10
p(excellent	positive)	= 1/10
p(fantastic	positive)	= 1/10
p(good	positive)	= 1/10
p(great	positive)	= 1/10
p(love	positive)	= 1/10
p(original	positive)	= 0/10
p(poor	positive)	= 0/10
p(renowned	positive)	= 1/10
p(unimaginative	positive)	= 0/10
p(!!!	positive)	= 1/10

p(amazing	negative)	= 0/8
p(bad	negative)	= 3/8
p(excellent	negative)	= 0/8
p(fantastic	negative)	= 0/8
p(good	negative)	= 0/8
p(great	negative)	= 2/8
p(love	negative)	= 0/8
p(original	negative)	= 1/8
p(poor	negative)	= 1/8
p(renowned	negative)	= 0/8
p(unimaginative	negative)	= 1/8
p(!!!	negative)	= 0/8

Naive Bayes for Sentiment Analysis - Example

Relative frequencies for prior and likelihoods make the model in a Naive Bayes classifier

→ features are supposed to be **independent** (no covariance taken into account)

→ this is an approximation of course

Naive Bayes for Sentiment Analysis - Example

Relative frequencies for prior and likelihoods make the model in a Naive Bayes classifier

→ features are supposed to be **independent** (no covariance taken into account)

→ this is an approximation of course

What is the model?

→ the set of all prior probabilities and likelihoods

Naive Bayes for Sentiment Analysis - Example

Relative frequencies for prior and likelihoods make the model in a Naive Bayes classifier

→ features are supposed to be **independent** (no covariance taken into account)

→ this is an approximation of course

What is the model?

→ the set of all prior probabilities and likelihoods

At **test** time, this model is used to find the most likely class (sentiment) for the unknown text

$$\mathbf{s}^* = \underset{s_i}{\operatorname{argmax}} p(s_i) \prod_{j=1}^N p(t_j | s_i)$$

Naive Bayes for Sentiment Analysis - Text Ex. 1

Consider the following **test segment** to classify:

Doc	Words	Class
8	This was a fantastic story, great, lovely	?

Naive Bayes for Sentiment Analysis - Text Ex. 1

Consider the following **test segment** to classify:

1. Extract features

Doc	Words	Class
8	This was a fantastic story, great , lovely	?

Naive Bayes for Sentiment Analysis - Text Ex. 1

Consider the following **test segment** to classify:

1. Extract features
2. Build representation

Doc	Words	Class
8	fantastic great lovely	?

Naive Bayes for Sentiment Analysis - Text Ex. 1

Consider the following **test segment** to classify:

1. Extract features
2. Build representation

Doc	Words	Class
8	fantastic great lovely	?

3. Get **likelihoods**

$$\begin{array}{lcl} p(\text{fantastic} | \text{positive}) & = & 1/10 \\ p(\text{great} | \text{positive}) & = & 1/10 \\ p(\text{lovely} | \text{positive}) & = & 1/10 \end{array} \quad \left| \quad \begin{array}{lcl} p(\text{fantastic} | \text{negative}) & = & 0/8 \\ p(\text{great} | \text{negative}) & = & 2/8 \\ p(\text{lovely} | \text{negative}) & = & 0/8 \end{array}$$

Naive Bayes for Sentiment Analysis - Text Ex. 1

$$\begin{aligned} p(\text{positive}|\text{text}) &= p(\text{positive}) * p(\text{fantastic}|\text{positive}) * p(\text{great}|\text{positive}) * p(\text{lovely}|\text{positive}) \\ &= 3/7 * 1/10 * 1/10 * 1/10 \\ &= 0.00043 \end{aligned}$$

$$\begin{aligned} p(\text{negative}|\text{text}) &= p(\text{negative}) * p(\text{fantastic}|\text{negative}) * p(\text{great}|\text{negative}) * p(\text{lovely}|\text{negative}) \\ &= 4/7 * 0/8 * 2/8 * 0/8 \\ &= 0 \end{aligned}$$

Final decision: sentiment is **positive**

Naive Bayes for Sentiment Analysis - Text Ex. 2

Doc	Words	Class
1	great movie, excellent plot, renowned actors	positive
2	I had not seen a fantastic plot like this in good 5 years. amazing!!!	positive
3	lovely plot, amazing cast, somehow I am in love with the bad guy	positive
4	bad movie with great cast, but very poor plot and unimaginative ending	negative
5	I hate this film, it has nothing original	negative
6	great movie, but not...	negative
7	very bad movie, I have no words to express how I dislike it	negative

Doc	Words	Class
1	great excellent renowned	positive
2	fantastic good amazing !!!	positive
3	lovely amazing bad	positive
4	bad great poor unimaginative	negative
5	original	negative
6	great bad	negative
7	bad	negative

Consider the following **test segment** to classify:

Doc	Words	Class
9	Great great great	?

Naive Bayes for Sentiment Analysis - Text Ex. 2

Consider the following **test segment** to classify:

Doc	Words	Class
9	Great plot, great cast, great everything	?

Naive Bayes for Sentiment Analysis - Text Ex. 2

Consider the following **test segment** to classify:

1. Extract features
2. Build representation

Doc	Words	Class
9	Great great great	?

Naive Bayes for Sentiment Analysis - Text Ex. 2

Consider the following **test segment** to classify:

1. Extract features
2. Build representation

Doc	Words	Class
9	Great great great	?

3. Get likelihoods:

$$p(\text{great}|\text{positive}) = 1/10 \mid p(\text{great}|\text{negative}) = 2/8$$

Naive Bayes for Sentiment Analysis - Text Ex. 2

Consider the following **test segment** to classify:

1. Extract features
2. Build representation

Doc	Words	Class
9	Great great great	?

3. Get likelihoods:

$$p(\text{great}|\text{positive}) = 1/10 \mid p(\text{great}|\text{negative}) = 2/8$$

4. Compute posteriors

$$p(\text{positive}|\text{text}) = 3/7 * 1/10 * 1/10 * 1/10 = \mathbf{0.00043}$$

$$p(\text{negative}|\text{text}) = 4/7 * 2/8 * 2/8 * 2/8 = \mathbf{0.00893}$$

Final decision: sentiment is **negative**

Naive Bayes for Sentiment Analysis - Text Ex. 2

Consider the following **test segment** to classify:

1. Extract features
2. Build representation

Doc	Words	Class
9	Great gr	?

**Training data
should be
representative!**

3. Get likelihoods.

$$p(\text{great}|\text{positive}) = 1/10 \mid p(\text{great}|\text{negative}) = 2/8$$

4. Compute posteriors

$$p(\text{positive}|\text{text}) = 3/7 * 1/10 * 1/10 * 1/10 = \mathbf{0.00043}$$

$$p(\text{negative}|\text{text}) = 4/7 * 2/8 * 2/8 * 2/8 = \mathbf{0.00893}$$

Final decision: sentiment is **negative**

Naive Bayes for Sentiment Analysis - Text Ex. 3

Doc	Words	Class
1	great movie, excellent plot, renowned actors	positive
2	I had not seen a fantastic plot like this in good 5 years. amazing!!!	positive
3	lovely plot, amazing cast, somehow I am in love with the bad guy	positive
4	bad movie with great cast, but very poor plot and unimaginative ending	negative
5	I hate this film, it has nothing original	negative
6	great movie, but not...	negative
7	very bad movie, I have no words to express how I dislike it	negative

Doc	Words	Class
1	great excellent renowned	positive
2	fantastic good amazing !!!	positive
3	lovely amazing bad	positive
4	bad great poor unimaginative	negative
5	original	negative
6	great bad	negative
7	bad	negative

Consider the following **test segment** to classify:

Doc	Words	Class
10	Excellent cast, unimaginative ending	?

Naive Bayes for Sentiment Analysis - Text Ex. 3

Consider the following **test segment** to classify:

Doc	Words	Class
10	Excellent cast, unimaginative ending	?

Naive Bayes for Sentiment Analysis - Text Ex. 3

Consider the following **test segment** to classify:

1. Extract features
2. Build representation

Doc	Words	Class
10	Excellent unimaginative	?

Naive Bayes for Sentiment Analysis - Text Ex. 3

Consider the following **test segment** to classify:

1. Extract features
2. Build representation

Doc	Words	Class
10	Excellent unimaginative	?

3. Get likelihoods:

$$\begin{array}{lcl} p(\text{excellent} | \text{positive}) & = 1/10 & | \quad p(\text{excellent} | \text{negative}) = 0/8 \\ p(\text{unimaginative} | \text{positive}) & = 0/10 & | \quad p(\text{unimaginative} | \text{negative}) = 1/8 \end{array}$$

Naive Bayes for Sentiment Analysis - Text Ex. 3

Consider the following **test segment** to classify:

1. Extract features
2. Build representation

Doc	Words	Class
10	Excellent unimagative	?

3. Get likelihoods:

$$\begin{array}{lcl} p(\text{excellent}|\text{positive}) = 1/10 & | & p(\text{excellent}|\text{negative}) = 0/8 \\ p(\text{unimagative}|\text{positive}) = 0/10 & | & p(\text{unimagative}|\text{negative}) = 1/8 \end{array}$$

4. Compute posteriors

$$p(\text{positive}|\text{text}) = 3/7 * 1/10 * 0/10 = \mathbf{0.0}$$

$$p(\text{negative}|\text{text}) = 4/7 * 0/8 * 1/8 = \mathbf{0.0}$$

Final decision: sentiment is ???

Naive Bayes for Sentiment Analysis - Text Ex. 3

Consider the following **test segment** to classify:

1. Extract features

2. Build representation

Doc	Words	Class
10	Excellent unimaginative	?

**Training data
should be large!**

3. Get likelihoods:

$$\begin{array}{lcl} p(\text{excellent}|\text{positive}) = 1/10 & | & p(\text{excellent}|\text{negative}) = 0/8 \\ p(\text{unimaginative}|\text{positive}) = 0/10 & | & p(\text{unimaginative}|\text{negative}) = 1/8 \end{array}$$

4. Compute posteriors

$$p(\text{positive}|\text{text}) = 3/7 * 1/10 * 0/10 = \mathbf{0.0}$$

$$p(\text{negative}|\text{text}) = 4/7 * 0/8 * 1/8 = \mathbf{0.0}$$

Final decision: sentiment is ???

Exercise

Doc	Words	Class
1	A <u>sensitive</u> , <u>moving</u> , <u>brilliant</u> work	Positive
2	An <u>edgy</u> thriller that delivers a <u>surprising</u> punch	Positive
3	A <u>sensitive</u> , <u>insightful</u> , <u>flamboyant</u> film	Positive
4	Neither <u>revelatory</u> nor truly <u>edgy</u> – merely crassly <u>flamboyant</u> and comedically <u>labored</u>	Negative
5	<u>Unlikable</u> , <u>uninteresting</u> , <u>unfunny</u> , and completely, utterly <u>inept</u>	Negative
6	A sometimes <u>incisive</u> and <u>sensitive</u> portrait, targeting <u>sensitive</u> topics, that is undercut by its <u>awkward</u> structure	Negative
7	It's a sometimes <u>interesting</u> remake that doesn't compare to the <u>brilliant</u> original	Negative

Classify the following sentence using a Naive Bayes classifier based on the above training data (without smoothing).

Doc	Words	Class
8	A <u>flamboyant</u> romcom, <u>sensitive</u> but <u>awkward</u> at times.	???

Naive Bayes for Sentiment Analysis

We cannot ensure that all possible words appear in the training corpus

Naive Bayes for Sentiment Analysis

We cannot ensure that all possible words appear in the training corpus

→ apply a **smoothing** technique

$$p(t_j|s_i) = \frac{\text{count}(t_j, s_i) + 1}{\sum_f (\text{count}(t_f, s_i) + 1)}$$

Naive Bayes for Sentiment Analysis

We cannot ensure that all possible words appear in the training corpus

→ apply a **smoothing** technique

$$p(t_j|s_i) = \frac{\text{count}(t_j, s_i) + 1}{(\sum_f \text{count}(t_f, s_i)) + |\mathbf{V}|}$$

→ **Laplace** smoothing, also called **add-1** smoothing

where $|\mathbf{V}|$ is the number of **distinct features** or **types** (also called **vocabulary**)

→ **12 in our example**

great, excellent, renowned, fantastic, good, amazing, !!!, lovely, bad, poor, unimaginative, original

Naive Bayes for Sentiment Analysis - Text Ex. 3

Consider the following **test segment** to classify:

1. Extract features
2. Build representation

Doc	Words	Class
10	Excellent unimaginative	?

Naive Bayes for Sentiment Analysis - Text Ex. 3

Consider the following **test segment** to classify:

1. Extract features
2. Build representation

Doc	Words	Class
10	Excellent unimaginative	?

3. Get new likelihoods:

$$\begin{array}{lcl} p(\text{excellent}|\text{positive}) & = (1+1)/(10+12) = 2/22 & \left| \quad p(\text{excellent}|\text{negative}) = (0+1)/(8+12) = 1/20 \right. \\ p(\text{unimaginative}|\text{positive}) & = (0+1)/(10+12) = 1/22 & \left. p(\text{unimaginative}|\text{negative}) = (1+1)/(8+12) = 2/20 \right. \end{array}$$

Naive Bayes for Sentiment Analysis - Text Ex. 3

Consider the following **test segment** to classify:

1. Extract features
2. Build representation

Doc	Words	Class
10	Excellent unimagative	?

3. Get new likelihoods:

$$\begin{array}{lcl} p(\text{excellent}|\text{positive}) & = (1+1)/(10+12) = 2/22 & \left| \quad p(\text{excellent}|\text{negative}) = (0+1)/(8+12) = 1/20 \right. \\ p(\text{unimagative}|\text{positive}) & = (0+1)/(10+12) = 1/22 & \left| \quad p(\text{unimagative}|\text{negative}) = (1+1)/(8+12) = 2/20 \right. \end{array}$$

4. Compute posteriors

$$p(\text{positive}|\text{text}) = 3/7 * 2/22 * 1/22 = \mathbf{0.00176}$$

$$p(\text{negative}|\text{text}) = 4/7 * 1/20 * 2/20 = \mathbf{0.00286}$$

Final decision: sentiment is **negative**

Exercise

Doc	Words	Class
1	A <u>sensitive</u> , <u>moving</u> , <u>brilliant</u> work	Positive
2	An <u>edgy</u> thriller that delivers a <u>surprising</u> punch	Positive
3	A <u>sensitive</u> , <u>insightful</u> , <u>flamboyant</u> film	Positive
4	Neither <u>revelatory</u> nor truly <u>edgy</u> – merely crassly <u>flamboyant</u> and comedically <u>labored</u>	Negative
5	<u>Unlikable</u> , <u>uninteresting</u> , <u>unfunny</u> , and completely, utterly <u>inept</u>	Negative
6	A sometimes <u>incisive</u> and <u>sensitive</u> portrait, targeting <u>sensitive</u> topics, that is undercut by its <u>awkward</u> structure	Negative
7	It's a sometimes <u>interesting</u> remake that doesn't compare to the <u>brilliant</u> original	Negative

Classify the following sentence using a Naive Bayes classifier based on the above training data **with smoothing: Laplace (add-1)**.

Doc	Words	Class
8	A <u>flamboyant</u> romcom, <u>sensitive</u> but <u>awkward</u> at times.	???

Naive Bayes for Sentiment Analysis - Questions

Is this a good solution?

Naive Bayes for Sentiment Analysis - Questions

Is this a good solution?

- ▶ Simple solution. Works well if data is not sparse.

Naive Bayes for Sentiment Analysis - Questions

Is this a good solution?

- ▶ Simple solution. Works well if data is not sparse.

Is it robust?

Naive Bayes for Sentiment Analysis - Questions

Is this a good solution?

- ▶ Simple solution. Works well if data is not sparse.

Is it robust?

- ▶ Problem: what about new words?

Naive Bayes for Sentiment Analysis - Questions

Is this a good solution?

- ▶ Simple solution. Works well if data is not sparse.

Is it robust?

- ▶ Problem: what about new words?

What is the role of the prior?

Naive Bayes for Sentiment Analysis - Questions

Is this a good solution?

- ▶ Simple solution. Works well if data is not sparse.

Is it robust?

- ▶ Problem: what about new words?

What is the role of the prior?

- ▶ reminder: safest decision **when no other information is given** \sim majority voting
- ▶ important especially on biased cases

Naive Bayes for Sentiment Analysis - Questions

Is this a good solution?

- ▶ Simple solution. Works well if data is not sparse.

Is it robust?

- ▶ Problem: what about new words?

What is the role of the prior?

- ▶ reminder: safest decision **when no other information is given** \sim majority voting
- ▶ important especially on biased cases

Can we extend to a non-binary classification?

Naive Bayes for Sentiment Analysis - Questions

Is this a good solution?

- ▶ Simple solution. Works well if data is not sparse.

Is it robust?

- ▶ Problem: what about new words?

What is the role of the prior?

- ▶ reminder: safest decision **when no other information is given** \sim majority voting
- ▶ important especially on biased cases

Can we extend to a non-binary classification?

- ▶ Naive Bayes can be easily extended by considering more than 2 classes
- ▶ ... but beware of the **curse of dimensionality** \rightarrow sparsity

Naive Bayes for Sentiment Analysis - Questions

How can we improve this solution?

1. Consider other **features**?

- ▶ using all words in Naive Bayes works well for some tasks
- ▶ subsets of words may help → use the **development** set to decide
- ▶ previous examples consider only adjectives, this is limiting
 - ▶ **verbs**: hate, dislike
 - ▶ **intensifiers**: very, much, a lot
 - ▶ **negation**: not ← **very important!**
 - *didn't like this movie*
 - *didn't NOT_like NOT_this NOT_movie*
 - ▶ **nouns**: love, creativity
 - possibly people tend to mostly talk of those **nouns** in a **positive** or **negative** way
- ▶ pre-built polarity lexicons can be helpful

Naive Bayes for Sentiment Analysis - Questions

How can we improve this solution?

1. Consider other **features**?

- ▶ **pre-built polarity lexicons** can be helpful
 - add a feature that is counted whenever a word from a lexicon occurs
 - “word appears in positive/negative lexicon”
 - simple approach → can be effective when the data is sparse

Naive Bayes for Sentiment Analysis - Questions

How can we improve this solution?

2. Consider other **feature representations**?

- ▶ Instead of frequencies → binary count
- ▶ 1 if feature appears in a segment, 0 otherwise

	NB Counts		Binary Counts		
	+	-	+	-	
Four original documents:					
- it was pathetic the worst part was the boxing scenes	and	2	0	1	0
	boxing	0	1	0	1
	film	1	0	1	0
- no plot twists or great scenes	great	3	1	2	1
+ and satire and great plot twists	it	0	1	0	1
+ great scenes great film	no	0	1	0	1
	or	0	1	0	1
	part	0	1	0	1
	pathetic	0	1	0	1
	plot	1	1	1	1
	satire	1	0	1	0
	scenes	1	2	1	2
	the	0	2	0	1
	twists	1	1	1	1
	was	0	2	0	1
	worst	0	1	0	1
After per-document binarization:					
- it was pathetic the worst part boxing scenes					
- no plot twists or great scenes					
+ and satire great plot twists					
+ great scenes film					

Figure 4.3 An example of binarization for the binary naive Bayes algorithm.

[Jurafsky and Martin, 2021]

Naive Bayes for Sentiment Analysis - Binary example

Consider the following **training set**:

doc	“good”	“poor”	“great”	(class)
d1.	3	0	3	pos
d2.	0	1	2	pos
d3.	1	3	0	neg
d4.	1	5	2	neg
d5.	0	2	0	neg

[Jurafsky and Martin, 2021]

Predict the sentiment of the text:

”A **good**, **good** plot and **great** characters, but **poor** acting.”

Naive Bayes for Sentiment Analysis - Binary example

Consider the following **training set**:

doc	“good”	“poor”	“great”	(class)
d1.	3	0	3	pos
d2.	0	1	2	pos
d3.	1	3	0	neg
d4.	1	5	2	neg
d5.	0	2	0	neg

[Jurafsky and Martin, 2021]

Predict the sentiment of the text:

”A **good**, **good** plot and **great** characters, but **poor** acting.”

Standard NB:

$$\begin{array}{l|l} p(\text{good}|\text{positive}) = 3/9 = 1/3 & p(\text{good}|\text{negative}) = 1/14 \\ p(\text{great}|\text{positive}) = 5/9 & p(\text{great}|\text{negative}) = 2/14 = 1/7 \end{array}$$

Naive Bayes for Sentiment Analysis - Binary example

Consider the following **training set**:

doc	“good”	“poor”	“great”	(class)
d1.	3	0	3	pos
d2.	0	1	2	pos
d3.	1	3	0	neg
d4.	1	5	2	neg
d5.	0	2	0	neg

[Jurafsky and Martin, 2021]

Predict the sentiment of the text:

“A **good**, **good** plot and **great** characters, but **poor** acting.”

Binary NB:

$$\begin{array}{l|l} p(\text{good}|\text{positive}) = 1/4 & p(\text{good}|\text{negative}) = 2/6 = 1/3 \\ p(\text{great}|\text{positive}) = 2/4 = 1/2 & p(\text{great}|\text{negative}) = 1/6 \end{array}$$

Exercise

Doc	Words	Class
1	A <u>sensitive</u> , <u>moving</u> , <u>brilliant</u> work	Positive
2	An <u>edgy</u> thriller that delivers a <u>surprising</u> punch	Positive
3	A <u>sensitive</u> , <u>insightful</u> , <u>flamboyant</u> film	Positive
4	Neither <u>revelatory</u> nor truly <u>edgy</u> – merely crassly <u>flamboyant</u> and comedically <u>labored</u>	Negative
5	<u>Unlikable</u> , <u>uninteresting</u> , <u>unfunny</u> , and completely, utterly <u>inept</u>	Negative
6	A sometimes <u>incisive</u> and <u>sensitive</u> portrait, targeting <u>sensitive</u> topics, that is undercut by its <u>awkward</u> structure	Negative
7	It's a sometimes <u>interesting</u> remake that doesn't compare to the <u>brilliant</u> original	Negative

Classify the following sentence using a **Binary Naive Bayes** classifier based on the above training data **without smoothing**.

Doc	Words	Class
8	A <u>flamboyant</u> romcom, <u>sensitive</u> but <u>awkward</u> at times.	???

Naive Bayes for Sentiment Analysis - Questions

How can we improve this solution?

3. Consider other **algorithms**?

- ▶ Maximum Entropy (MaxEnt), Support Vector Machines (SVM), neural networks
- no assumption of statistical independence among features
- more complex but tend to do better

→ Take a look at Chapter 5 of [Jurafsky and Martin, 2021] for **Text Classification with Logistic Regression**

Learning objectives

- ▶ Explain the Naïve Bayes model for sentiment analysis
- ▶ Explain the Laplace smoothing technique
- ▶ Explain the Binary Naïve Bayes model
- ▶ Identify other tasks for which the same approach is applicable

Extra reading (optional)

Geriska Isabelle, Warih Maharani and Ibnu Asror (2018).
**Analysis on Opinion Mining Using Combining Lexicon-Based
Method and Multinomial Naive Bayes.**

International Conference on Industrial Enterprise and System
Engineering

Hanhoon Kang, Seong Joon Yoo and Dongil Han (2012).
**Senti-lexicon and improved Naïve Bayes algorithms for
sentiment analysis of restaurant reviews.**

Expert Systems with Applications, v.39, issue 5.

[https://www.sciencedirect.com/science/article/pii/
S0957417411016538](https://www.sciencedirect.com/science/article/pii/S0957417411016538)

References I

Jurafsky, D. and Martin, J. H. (2021).

Speech and Language Processing, see chapter 4: *Naive Bayes and Sentiment Classification*.