Status	Finished
Started	Sunday, 25 October 2026, 6:47 PM
Completed	Sunday, 25 October 2026, 6:50 PM
Duration	3 mins 42 secs
Grade	**13.00** out of 15.00 (**86.67**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which of the following is data file?

a. none of the given choices

b. Text file

c. Both text and binary file ✓

d. Binary file

The correct answer is: Both text and binary file

Question **2**

Correct

Mark 1.00 out of 1.00

How do you check if a file is closed in Python?

- a. file.closed ✓
- b. file.is_closed()
- c. file.closed()
- d. file.isclosed()

The correct answer is: file.closed

Question **3**

Correct

Mark 1.00 out of 1.00

Which of the following is true about the readlines() method?

- a. It reads the entire file and returns it as a string
- b. It reads a single line from the file
- c. It reads the entire file and returns it as a list of lines ✓
- d. It reads the file and returns it as a dictionary

The correct answer is: It reads the entire file and returns it as a list of lines

Question **4**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in read mode ('r') that does not exist?

a. The operation is ignored
b. An error is raised ✓
c. An empty file object is returned
d. A new file is created

The correct answer is: An error is raised

Question **5**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

a. readlines() ✓
b. read()
c. readlist()
d. readline()

The correct answer is: readlines()

Question **6**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

a. An error is raised

b. Hello, world! ✓

c. Hello

d. world

The correct answer is: Hello, world!

Question **7**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

a. infile = open(file = “a.txt”, “r”)

b. infile = open(file, “a.txt”, “r”)

c. infile = open(“a.txt”, “r”) ✓

d. infile = open(file = “a.txt”, “r”)

The correct answer is:
infile = open(“a.txt”, “r”)

Question **8**

Correct

Mark 1.00 out of 1.00

Default EOL character of text file in python is ,

a. \t

b. ,

c. space

d. \n ✓

The correct answer is:
\n

Question **9**

Correct

Mark 1.00 out of 1.00

What will be the output of the following code if the file "example.txt" contains "Python Programming"?

```
f = open("example.txt", "r")
print(f.read(6))
f.close()
```

a. An error is raised

b. Program

c. Python Programming

d. Python ✓

The correct answer is: Python

Question **10**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

a. 2

b. null

c. 0 ✓

d. garbage

e. 1

The correct answer is:
0

Question **11**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for writing, we use _____

a. outfile = open("c:\scores.txt", "w")

b. outfile = open("c:\\scores.txt", "w") ✓

c. outfile = open(file = "c:\scores.txt", "w")

d. outfile = open(file = "c:\\scores.txt", "w")

The correct answer is:
outfile = open("c:\\scores.txt", "w")

Question **12**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

a. move the file pointer five characters behind from the current position

b. move the file pointer five characters ahead from the current position ✓

c. move the file pointer to beginning of the file

d. moves the file pointer to the end of a file

The correct answer is:
move the file pointer five characters ahead from the current position

Question **13**

Incorrect

Mark 0.00 out of 1.00

Which of the following methods is used to read a single line from a file?

a. read()

b. readline()

c. readlines() ✗

d. readline(size)

The correct answer is: readline()

Question **14**

Correct

Mark 1.00 out of 1.00

Select the correct output of the following code

```
fp.seek(5, 1)
```

a. • Move file pointer five characters ahead from the current position. ✓

b. Move file pointer five characters ahead from the beginning

c. • Move file pointer five characters behind from the current position.

d. • Move file pointer five characters behind ahead from the end of a file.

The correct answer is:

- Move file pointer five characters ahead from the current position.

Question **15**

Incorrect

Mark 0.00 out of 1.00

Which method is used to sets the position of a file pointer

a. tell()
b. ftell()
c. fseek() ✕
d. seek()

The correct answer is: seek()