

GreenSense Pro Development Overview

Seth, Nate, Ian, Eniola (14 Eyes)

CEIAS, North Arizona University

EGR 286

Dr. Rodolfo A. Echavarria Solis

February 27th, 2024

Abstract

The GreenSense Pro is a groundbreaking greenhouse management solution centered around an Arduino Mega microcontroller housed within a protective casing. Featuring 12 I/O pins, the system enables users to connect external devices for temperature, humidity, and watering control. Three pins each are designated for upper and lower temperature limits, low humidity conditions, and timed water toggling. The user interface comprises an LCD screen and an encoder with a button, providing an intuitive platform for users to set and customize environmental parameters.

This project addresses the pressing challenges in greenhouse cultivation by granting users control over critical environmental factors. By combining temperature, humidity, and watering management, the system ensures optimal plant health and growth. The user-friendly interface enhances accessibility, allowing individuals of varying technical expertise to efficiently operate and tailor the system to their specific needs.

Materials, Circuits, Equipment

Arduino Mega Microcontroller:

- Specification: Arduino Mega 2560 with 54 digital I/O pins, 16 analog inputs, and a 16 MHz clock.
- Quantity: 1

Protective Casing:

- Material: Weather-resistant PLA plastic.
- Dimensions: 8 x 6 x 4 inches.
- Quantity: 1

LCD Screen and Encoder with Button:

- LCD Screen: 16x2 character display.
- Encoder: Rotary encoder with a built-in push button.
- Quantity: 1 each

Temperature and Humidity Sensor:

- Humidity Sensor: DHT11 digital humidity and temperature sensor.
- Quantity: 1

Introduction

In response to the intricate challenges faced by traditional greenhouse cultivation, 14 Eyes presents the GreenSense Pro—a pioneering solution that amalgamates technology and backyard agriculture. Comprising skilled engineers and enthusiasts, 14 Eyes endeavors to redefine greenhouse management by offering a sophisticated yet accessible system. This project emerges as a response to the inherent complexities of maintaining optimal environmental conditions for plant growth, with a focus on dynamic control of temperature, humidity, and watering parameters. Anchored by an Arduino Mega microcontroller and housed

within a robust protective casing, the GreenSense Pro signifies a commitment to cultivating a sustainable and efficient approach to greenhouse agriculture.

14 Eyes aims to empower users, from seasoned horticulturists to aspiring hobbyists, by providing a user-friendly interface consisting of an LCD screen and an encoder with a button. This not only facilitates precise control over environmental factors but also opens avenues for customization to cater to the unique needs of various plant species. This document delves into the intricacies of the GreenSense Pro, unraveling the materials, circuits, and equipment employed, the design considerations, experimental outcomes, and the broader implications of this collaborative effort by 14 Eyes.

Overview

The GreenSense Pro serves as a technological milestone in greenhouse management, seamlessly blending innovation with practicality. Envisioned and developed by 14 Eyes, this system represents a pivotal shift in the paradigm of agricultural technology. At its core, the project seeks to address the inherent challenges of traditional greenhouse cultivation, providing a holistic solution that not only monitors but actively manages crucial environmental parameters. The system's architecture revolves around the Arduino Mega microcontroller, a powerful and versatile platform chosen for its ability to orchestrate complex operations. Housed within a protective casing crafted by 14 Eyes, this setup ensures the resilience of the system in the face of diverse environmental conditions within a greenhouse. The 12 I/O pins, strategically designed for upper and lower temperature limits, humidity thresholds, and water control, offer users unprecedented control over their greenhouse environments.

The user interface, featuring an LCD screen and an encoder with a button, transforms the GreenSense Pro into an accessible tool for growers of all backgrounds. Whether it's optimizing conditions for specific plant species, adjusting watering cycles, or fine-tuning humidity levels, the system places the reins firmly in the hands of the user. This overview sets the stage for a detailed exploration of the GreenSense Pro, offering insights into its design principles, experimental outcomes, and the broader impact it stands to make in the realm of greenhouse agriculture.

Description of the Problem

Traditional greenhouse management systems often grapple with inherent challenges that impede widespread adoption and efficient cultivation practices. The GreenSense Pro addresses a spectrum of these issues, heralding a new era of greenhouse management.

Modularity and Ease of Use:

Many existing solutions lack the flexibility needed to accommodate a variety of greenhouse setups and user preferences. The GreenSense Pro introduces modularity, allowing users to seamlessly integrate external devices through its 12 I/O pins. This modularity not only caters to diverse user requirements but also enhances the adaptability of the system to different

crops and cultivation techniques. Moreover, the user-friendly interface, featuring an LCD screen and an encoder with a button, ensures ease of use, breaking down technological barriers and making greenhouse management accessible to a broader audience.

Cost-Effectiveness:

One of the prevalent obstacles in adopting greenhouse management systems is the often prohibitive cost associated with high-tech solutions. The GreenSense Pro, developed by 14 Eyes, is designed with cost-effectiveness in mind. By utilizing the Arduino Mega microcontroller and simple yet robust components, the system significantly reduces the financial barrier for entry into advanced greenhouse management. This affordability empowers a broader spectrum of growers, from small-scale farmers to hobbyists, fostering inclusivity in adopting modern agricultural practices.

Scalability:

As agricultural needs evolve or greenhouse operations expand, scalability becomes a critical consideration. Conventional systems may face challenges when it comes to accommodating larger cultivation areas or integrating additional functionalities. The GreenSense Pro is inherently scalable, allowing users to effortlessly scale up or modify their greenhouse setups by incorporating multiple units or extending the system's capabilities. This scalability not only future-proofs investments but also aligns with the dynamic nature of modern agriculture.

In summary, the GreenSense Pro confronts and solves the challenges of modularity, ease of use, cost-effectiveness, and scalability in greenhouse management, contributing to the democratization of advanced agricultural technologies. This multifaceted approach positions the project as a catalyst for positive change in the way we cultivate and sustain our agricultural ecosystems.

Design:

The GreenSense Pro integrates a thoughtful and comprehensive design, encompassing the Arduino Mega setup, protective casing, I/O pins, and an intuitive user interface for seamless control over temperature, humidity, and watering parameters.

Arduino Mega Setup:

At the heart of the system is the Arduino Mega microcontroller, chosen for its versatility and computational power. The Arduino Mega manages the flow of data and control signals, ensuring precise coordination between sensors, actuators, and the user interface. Its 54 digital I/O pins, 16 analog inputs, and a clock speed of 16 MHz provide the necessary capabilities to handle multiple input and output operations simultaneously.

Protective Casing:

The Arduino Mega and associated components are housed within a durable protective casing designed by 14 Eyes. Crafted from weather-resistant ABS plastic, the casing shields the internal components from environmental factors such as moisture and dust. The design ensures

the longevity and reliability of the system, allowing it to thrive in the dynamic conditions of a greenhouse.

I/O Pins and Connectivity:

The GreenSense Pro incorporates 12 I/O pins, strategically divided to address specific environmental parameters. Three pins are dedicated to upper temperature limits, three for lower temperature limits, three for humidity thresholds, and three for water control. This modular design allows users to connect external devices, such as sensors and actuators, with ease. The connectivity is achieved using male and female jumper wires, providing a secure and stable connection.

User Interface:

The user interface is designed for simplicity and efficiency, consisting of an LCD screen and an encoder with a button. The 16x2 character LCD screen provides real-time feedback on temperature, humidity, and watering parameters. Users can navigate through settings using the rotary encoder, adjusting values by turning the encoder and confirming selections by pressing the built-in button.

Control Mechanisms:

Users have full control over the greenhouse environment through the user interface. For temperature control, upper and lower limits can be set using the encoder. Similarly, humidity thresholds are adjustable, giving users the flexibility to cater to the specific needs of different plants. The watering time is controlled by setting the duration through the user interface. This dynamic control mechanism ensures that the GreenSense Pro can be customized to suit various crops and environmental conditions.

The interconnected design of the GreenSense Pro harmonizes the Arduino Mega setup, protective casing, I/O pins, and user interface, providing users with an accessible and efficient tool for greenhouse management. The modularity of the design allows for flexibility and scalability, empowering growers to optimize their cultivation practices based on their unique requirements.

Experimental Results

Standard Operation Test:

Goal: Evaluate the device's performance under normal operating conditions.

Results: The tests were executed seamlessly, demonstrating the device's capability to operate within nominal parameters. However, user feedback regarding the buzzer highlighted concerns such as it being "more annoying than helpful" and potentially scaring away birds.

Changes: In response to user feedback, the buzzer component was subsequently removed to enhance user satisfaction and minimize unintended environmental impact.

High Temperature Operation Test:

Goal: Assess the device's functionality in elevated temperatures, specifically exceeding 90 degrees Fahrenheit.

Results: Prolonged operation above 95 degrees revealed signs of damage to the models. In response, modifications were implemented, including the use of a lighter casing material to mitigate heat retention and safeguard against potential damage.

Changes: The casing was reprinted with a lighter material, effectively addressing the thermal challenges observed during high-temperature operation.

High Humidity Operation Test:

Goal: Investigate the device's resilience in high humidity conditions.

Results: The models endured the high humidity conditions without sustaining damage. However, recognizing the need for thorough examination in potential consumer scenarios, it is hypothesized that additional testing under various humidity levels may be warranted for future iterations.

Changes: No immediate modifications were deemed necessary, but the potential for further testing and refinement in future consumer versions is acknowledged.

These experimental results provide valuable insights into the device's performance under different conditions, steering the refinement process to enhance durability, user satisfaction, and overall reliability. The iterative approach to testing and implementing changes underscores the commitment to delivering a robust and adaptable greenhouse management solution through the GreenSense Pro.

References

A000067-datasheet. (2023, September 17).

<https://docs.arduino.cc/resources/datasheets/A000067-datasheet.pdf>

Li, Y., Ghosh, A., Zhang, Z., Yu, Z., & Wang, J. (2021, August 13). *Sensors and applications in agricultural and environmental monitoring*. Journal of Sensors.

<https://www.hindawi.com/journals/js/2021/9841470/>

Hatfield, J. L., & Prueger, J. H. (2015). Temperature extremes: Effect on plant growth and development. *Weather and Climate Extremes*, 10, 4–10.

<https://doi.org/10.1016/j.wace.2015.08.001>

Sensors. (n.d.).

https://www.mdpi.com/journal/sensors/special_issues/Humidity_Sensors_Industrial_Agricultural