

Lab 1: Packet analysis at application layer using Wireshark

SCSR1213 Network Communications

Universiti Teknologi Malaysia

Objective:

1. Understanding of network protocols by observing the sequence of messages exchanged between two protocol entities, delving down into the details of protocol operation, and causing protocols to perform certain actions and then observing these actions and their consequences.
2. To introduce student with Wireshark software tool for packet analyzer.
3. To analyze protocol used in application layer such as http and dns.

Reference material: Computer Networking: A Top-Down Approach, 7th ed., J.F. Kurose and K.W. Ross.

Name : Cheryl Cheong Kah Voon

Metric No : A23CS0060

Section : 12

Name : Chua Jia Lin

Metric No : A23CS0069

Section : 12



Mark

PART A: Wireshark Getting Started

1.0 Introduction

The basic tool for observing the messages exchanged between executing protocol entities is called a **packet sniffer**. As the name suggests, a packet sniffer captures (“sniffs”) messages being sent/received from/by your computer; it will also typically store and/or display the contents of the various protocol fields in these captured messages. A packet sniffer itself is passive. It observes messages being sent and received by applications and protocols running on your computer, but never sends packets itself. Similarly, received packets are never explicitly addressed to the packet sniffer. Instead, a packet sniffer receives a *copy* of packets that are sent/received from/by application and protocols executing on your machine.

Figure A.1 shows the structure of a packet sniffer. At the right of Figure 1 are the protocols (in this case, Internet protocols) and applications (such as a web browser or ftp client) that normally run on your computer. The packet sniffer, shown within the dashed rectangle in Figure A.1 is an addition to the usual software in your computer, and consists of two parts. The **packet capture library** receives a copy of every link-layer frame that is sent from or received by your computer. In Figure A.1, the assumed physical media is an Ethernet, and so all upper-layer protocols are eventually encapsulated within an Ethernet frame. Capturing all link-layer frames thus gives you all messages sent/received from/by all protocols and applications executing in your computer.




Figure A.1: Packet sniffer structure

The second component of a packet sniffer is the **packet analyzer**, which displays the contents of all fields within a protocol message. In order to do so, the packet analyzer must “understand” the structure of all messages exchanged by protocols. The packet analyzer understands the format of Ethernet frames, and so can identify the IP datagram within an Ethernet frame. It also understands the IP datagram format, so that it can extract the TCP segment within the IP datagram. Finally, it understands the TCP segment structure, so it can extract the HTTP message contained in the TCP segment. Finally, it understands the HTTP protocol and so, for example, knows that the first bytes of an HTTP message will contain the string “GET,” “POST,” or “HEAD”.

2.0 Getting Wireshark Ready

- Download and install the Wireshark software
- Run Wireshark. Wireshark startup screen shown in Figure A.2.




Figure A.2: Initial Wireshark startup screen

- The Wireshark interface has five major components as shown in Figure A.3.




Figure A.3: Wireshark Graphical User Interface, during packet capture and

- The **command menus** are standard pulldown menus located at the top of the window.
- The **packet display filter field**, into which a protocol name or other information can be entered in order to filter the information displayed in the packet-listing window.
- The **packet-listing window** displays a one-line summary for each packet captured, including the packet number, the time at which the packet was captured, the packet's source and destination addresses, the protocol type, and protocol-specific information contained in the packet.
- The **packet-header details window** provides details about the packet selected (highlighted) in the packet-listing window. These details include information about the Ethernet frame and IP datagram that contains this packet. The amount of Ethernet and IP-layer detail displayed can be expanded or minimized by clicking on the plus minus boxes to the left of the Ethernet frame or IP datagram line in the packet details window. If the packet has been carried over TCP or UDP, TCP or UDP details will also be displayed, which can similarly be expanded or minimized. Finally, details about the highest-level protocol that sent or received this packet are also provided.
- The **packet-contents window** displays the entire contents of the captured frame, in both ASCII and hexadecimal format.

3.0 Test Run Wireshark

- Start up the Wireshark software.
- To begin packet capture, select the Capture pull down menu and pick Options menu. Select appropriate interfaces on your compute and click Start button to begin packet capture. Refer to Figure A.4




Figure A.4: Capture and Options Menu

- Once you begin packet capture, result will be shown as in Figure A.5.




Figure A.5: Wireshark packet capture result

- By selecting Capture pulldown menu and selecting Stop, you can stop packet capture.

- Type “arp” in packet display filter field and press Enter key. This will cause only ARP message to be displayed in the packet-listing window as shown in Figure A.6.




Figure A.6: ARP packet capture

- To save the trace result, use File pulldown menu and select Save function as shown in Figure A.7.





Figure A.7: Save Wireshark trace result

PART B: HTTP Trace

In this part, we'll explore several aspects of the HTTP protocol: the basic GET/response interaction, HTTP message formats and retrieving HTML files with embedded objects. Before beginning these labs, you might want to review Section 2.2 of the textbook.

B.1 The Basic HTTP GET/response interaction

- Open packet trace file **lab1-http-B01.pcapng**.
- Enter “**http**” (just the letters, not the quotation marks) in the **packet display filter field**, so that only captured HTTP messages will be displayed later in the packet-listing window. Refer to figure below:



packet display filter

- By looking at the information in the HTTP GET and response messages, answer the following questions:

1. What version of HTTP is the server running?

The server is running version 1.1 of HTTP

2. What is the IP address of the client computer?

192.168.1.102

3. What is the IP address of the gaia.cs.umass.edu server?

128.119.245.12

4. How many bytes of content are being returned to client browser?

73 bytes

5. What is the status code returned from the server to client browser?

The server has returned 2 status code to the client browser which is 200(OK) and 404(Not Found).

B.2 The HTTP CONDITIONAL GET/response interaction

- Open packet trace file **lab1-http-B02.pcapng**.
- By looking at the information in the HTTP GET and response messages, answer the following questions:

1. Inspect the contents of the first HTTP GET request from your browser to the server. Do you see an “IF-MODIFIED-SINCE” line in the HTTP GET?

There is no “IF-MODIFIED-SINCE” line in the HTTP GET.

2. Inspect the contents of the server response after the first GET request from client. Did the server explicitly return the contents of the file? How can you tell?

Yes, the server explicitly returns the file's contents because it has a status code 200(OK).

3. Now inspect the contents of the second HTTP GET request from your browser to the server. Do you see an “IF-MODIFIED-SINCE:” line in the HTTP GET? If so, what information follows the “IF-MODIFIED-SINCE:” header?

Yes, I have seen an “IF-MODIFIED-SINCE:” line in the HTTP GET. The information follows the “IF-MODIFIED-SINCE:” header is Tue, 23 Sep 2003 05:35:00 GMT\r\n

4. What is the HTTP status code and phrase returned from the server in response to this second HTTP GET? Did the server explicitly return the contents of the file? Explain.

The HTTP status code and phrase returned from the server in response to this second HTTP GET is 304 and Not Modified. The server did not return the content of the file because it no change.

B.3 HTML Documents with Embedded Objects

- Open packet trace file **lab1-http-B03.pcapng**.
- By looking at the information in the HTTP GET and response messages, answer the following questions:

1. How many HTTP GET request messages did client browser send?

There are three HTTP GET request messages that the client browser sends.

2. To which Internet addresses were these GET requests sent?

128.168.1.102, 165.193.123.218, 134.2416.82

3. How many bytes of content are being returned to client browser for the **pearson-logo-footer.gif** image file?

3357 bytes

4. How many bytes of content are being returned to client browser for the **cover.jpg** image file?


15642 bytes

PART C: DNS Trace

1.0 nslookup

nslookup tool allows the host running the tool to query any specified DNS server for a DNS record. The queried DNS server can be a root DNS server, a top-level-domain DNS server, an authoritative DNS server, or an intermediate DNS server. To accomplish this task, nslookup sends a DNS query to the specified DNS server, receives a DNS reply from that same DNS server, and displays the result.

- To run it in Windows, open the Command Prompt (cmd) and run nslookup on the command line as shown in Figure C.1 and Figure C.2



```
C:\WINDOWS\system32\cmd.exe

C:\Users\pc-vastro220>nslookup yahoo.com
Server: ns1.utm.my
Address: 161.139.250.2


Non-authoritative answer:
Name: yahoo.com
Addresses: 2001:4998:58:1836::11
           2001:4998:c:1023::4
           2001:4998:44:41d::4
           2001:4998:44:41d::3
           2001:4998:58:1836::10
           2001:4998:c:1023::5
           72.30.35.10
           98.137.246.7
           98.137.246.8
           98.138.219.231
           98.138.219.232
           72.30.35.9

C:\Users\pc-vastro220>nslookup -type=any yahoo.com
Server: jlb.utm.my
Address: 161.139.250.2

Non-authoritative answer:
yahoo.com      MX preference = 1, mail exchanger = mta5.am0.yahoodns.net
yahoo.com      MX preference = 1, mail exchanger = mta6.am0.yahoodns.net
yahoo.com      MX preference = 1, mail exchanger = mta7.am0.yahoodns.net
yahoo.com      AAAA IPv6 address = 2001:4998:c:1023::4
yahoo.com      AAAA IPv6 address = 2001:4998:44:41d::4
yahoo.com      AAAA IPv6 address = 2001:4998:44:41d::3
yahoo.com      AAAA IPv6 address = 2001:4998:58:1836::10
yahoo.com      AAAA IPv6 address = 2001:4998:c:1023::5
yahoo.com      AAAA IPv6 address = 2001:4998:58:1836::11
yahoo.com      nameserver = ns5.yahoo.com
yahoo.com      nameserver = ns2.yahoo.com
yahoo.com      nameserver = ns4.yahoo.com
yahoo.com      nameserver = ns1.yahoo.com
yahoo.com      nameserver = ns3.yahoo.com
yahoo.com      internet address = 98.137.246.7
yahoo.com      internet address = 98.137.246.8
yahoo.com      internet address = 98.138.219.231
yahoo.com      internet address = 98.138.219.232
yahoo.com      internet address = 72.30.35.9
yahoo.com      internet address = 72.30.35.10

C:\Users\pc-vastro220>
```

Figure C.1: nslookup result



```
C:\WINDOWS\system32\cmd.exe

C:\Users\pc-vastro220>nslookup google.com ns1.time.net.my
Server: ns1.test.time.net.my
Address: 203.121.16.85

Non-authoritative answer:
Name: google.com
Addresses: 2404:6800:4001:804::200e
           172.217.24.174

C:\Users\pc-vastro220>
```

Figure C.2: nslookup result

1. Run nslookup to obtain the IP address of a www.microsoft.com server. What is the IP address of that server? Add screenshot to your answer.

```
Microsoft Windows [Version 10.0.26100.2605]
(c) Microsoft Corporation. All rights reserved.

C:\Users\Lenovo>nslookup www.microsoft.com
Server:  dns.tm.net.my
Address:  2001:e68::b:68

Non-authoritative answer:
Name:     e13678.dscb.akamaiedge.net
Addresses: 2001:e68:2:388::356e
           2001:e68:2:38d::356e
           2001:e68:2:38e::356e
           2001:e68:2:387::356e
           173.223.41.219
Aliases:  www.microsoft.com
          www.microsoft.com-c-3.edgekey.net
          www.microsoft.com-c-3.edgekey.net.globalredir.akadns.net

C:\Users\Lenovo>
```

The IP address of a www.microsoft.com server is 173.223.41.219.

2. Run nslookup to determine the non-authoritative DNS servers for domain microsoft.com. Add screenshot to your answer.

```
C:\Users\Lenovo>nslookup microsoft.com
Server:  dns.tm.net.my
Address:  2001:e68::b:68


Non-authoritative answer:
Name:     microsoft.com
Addresses: 2603:1020:201:10::10f
           2603:1010:3:3::5b
           2603:1030:b:3::152
           2603:1030:20e:3::23c
           2603:1030:c02:8::14
           20.231.239.246
           20.236.44.162
           20.70.246.20
           20.76.201.171
           20.112.250.133
```

The non-authoritative DNS servers for domain microsoft.com are 2603:1020:201:10::10f, 2603:1010:3:3::5b, 2603:1030: b:3::152, 2603:1030:20e:3::23c, 2603:1030:c02:8::14, 20.76.201.171, 20.231.239.246, 20.236.44.162, 20.70.246.20, 20.112.250.133

2.0 ipconfig

ipconfig can be used to show your current TCP/IP information, including your address, DNS server addresses, adapter type and so on.

- Information about host, use the following command: ipconfig /all



```
C:\WINDOWS\system32\cmd.exe
Description . . . . . : TAP-ProtonVPN Windows Adapter V9
Physical Address. . . . . : 00-FF-AA-18-73-0D
DHCP Enabled. . . . . : Yes
Autoconfiguration Enabled . . . . : Yes

Ethernet adapter Ethernet:


    Connection-specific DNS Suffix  . : utm.my
    Description . . . . . : Realtek PCIe GbE Family Controller
    Physical Address. . . . . : 00-24-E8-23-E3-3A
    DHCP Enabled. . . . . : Yes
    Autoconfiguration Enabled . . . . : Yes
    Link-local IPv6 Address . . . . . : fe80::b8c5:7857:8b37:ddfe%4(Preferred)
    IPv4 Address. . . . . : 10.60.82.216(Preferred)
    Subnet Mask . . . . . : 255.255.252.0
    Lease Obtained. . . . . : Tuesday, September 18, 2018 6:08:09 AM
    Lease Expires . . . . . : Thursday, September 20, 2018 6:08:10 AM
    Default Gateway . . . . . : 10.60.80.1
    DHCP Server . . . . . : 10.60.80.1
    DHCPv6 IAID . . . . . : 33563880
    DHCPv6 Client DUID. . . . . : 00-01-00-01-1F-D8-2F-7E-00-24-E8-23-E3-3A
    DNS Servers . . . . . : 161.139.250.2
                           161.139.168.168
    NetBIOS over Tcpip. . . . . : Enabled

Ethernet adapter Ethernet 2:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :
    Description . . . . . : TAP-Windows Adapter V9
```

Figure C.3: ipconfig /all result

- ipconfig is also very useful for managing the DNS information stored in your host. Each entry shows the remaining Time to Live (TTL) in seconds. Command: ipconfig /displaydns



```
C:\WINDOWS\system32\cmd.exe
Record Name . . . . . : wpad.utm.my
Record Type . . . . . : 1
Time To Live . . . . . : 5917
Data Length . . . . . : 4
Section . . . . . : Answer
A (Host) Record . . . : 161.139.163.188

-----
aimsweb.utm.my
Record Name . . . . . : aimsweb.utm.my
Record Type . . . . . : 1
Time To Live . . . . . : 16483
Data Length . . . . . : 4
Section . . . . . : Answer
A (Host) Record . . . : 161.139.18.215

-----
my.utm.my
Record Name . . . . . : my.utm.my
Record Type . . . . . : 1
Time To Live . . . . . : 16484
Data Length . . . . . : 4
Section . . . . . : Answer
A (Host) Record . . . : 161.139.20.240

C:\Users\pc-vastro220>
```

Figure C.4: ipconfig /displaydns result

- Flushing the DNS cache clears all entries and reloads the entries from the hosts file.

Command: ipconfig /flushdns



```
C:\WINDOWS\system32\cmd.exe
C:\Users\pc-vastro220>ipconfig /flushdns

Windows IP Configuration


Successfully flushed the DNS Resolver Cache.

C:\Users\pc-vastro220>
```

Figure C.5: ipconfig /flushdns result


3.0 Tracing DNS with Wireshark

- Open packet trace file dns-trace-1. Answer the following questions.
1. Locate the DNS query and response messages. Are then sent over UDP or TCP? Add screenshots in your answer.



The DNS query and response are sent over UDP.

2. What is the destination port for the DNS query message? What is the source port of DNS response message? Add screenshots in your answer.



The destination port for the DNS query message is 53. The source port of DNS response message is 53.

3. To what IP address is the DNS query message sent? Add screenshots in your answer.

```
Frame 8: 72 bytes on wire (576 bits), 72 bytes captured (576 bits) on interface 0
Ethernet II, Src: IBM_10:60:99 (00:09:6b:10:60:99), Dst: All-MSRP-router (01:00:5e:00:00:00)
Internet Protocol Version 4, Src: 128.238.38.160, Dst: 128.238.29.23
  0100 .... = Version: 4
  .... 0101 = Header Length: 20 bytes (5)
  Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    Total Length: 58
    Identification: 0x229e (8862)
  000. .... = Flags: 0x0
    ...0 0000 0000 0000 = Fragment Offset: 0
    Time to Live: 128
    Protocol: UDP (17)
    Header Checksum: 0xd281 [validation disabled]
    [Header checksum status: Unverified]
    Source Address: 128.238.38.160
    Destination Address: 128.238.29.23
    [Stream index: 1]
  User Datagram Protocol, Src Port: 3163, Dst Port: 53
  Domain Name System (query)
```


The IP address that the DNS query message is sent to 128.238.29.23.

4. Examine the DNS query message. What “Type” of DNS query is it? Does the query message contain any “answers”? Add screenshots in your answer.

```
Frame 8: 72 bytes on wire (576 bits), 72 bytes captured (576 bits) on interface 0
Ethernet II, Src: IBM_10:60:99 (00:09:6b:10:60:99), Dst: All-MSRP-router (01:00:5e:00:00:00)
Internet Protocol Version 4, Src: 128.238.38.160, Dst: 128.238.29.23
User Datagram Protocol, Src Port: 3163, Dst Port: 53
Domain Name System (query)
  Transaction ID: 0x006e
  Flags: 0x0100 Standard query
  Questions: 1
  Answer RRs: 0
  Authority RRs: 0
  Additional RRs: 0
  Queries
    www.ietf.org: type A, class IN
    [Response In: 9]
```

The “Type” of the DNS query is type A. The query message does not contain any “answers”.

5. Examine the DNS response message. How many “answers” are provided? What do each of these answers contain? Add screenshots in your answer.



```

Frame 9: 104 bytes on wire (832 bits), 104 bytes captured (832 bits)
Ethernet II, Src: Cisco_83:e4:54 (00:b0:8e:83:e4:54), Dst: IBM_10:60:99
Internet Protocol Version 4, Src: 128.238.29.23, Dst: 128.238.38.160
User Datagram Protocol, Src Port: 53, Dst Port: 3163
Domain Name System (response)
  Transaction ID: 0x006e
  Flags: 0x8180 Standard query response, No error
  Questions: 1
  Answer RRs: 2
  Authority RRs: 0
  Additional RRs: 0
  Queries
    www.ietf.org: type A, class IN
  Answers
    www.ietf.org: type A, class IN, addr 132.151.6.75
      Name: www.ietf.org
      Type: A (1) (Host Address)
      Class: IN (0x0001)
      Time to live: 1678 (27 minutes, 58 seconds)
      Data length: 4
      Address: 132.151.6.75
    www.ietf.org: type A, class IN, addr 65.246.255.51
      Name: www.ietf.org
      Type: A (1) (Host Address)
      Class: IN (0x0001)
      Time to live: 1678 (27 minutes, 58 seconds)
      Data length: 4
      Address: 65.246.255.51
  [Request In: 8]
  [Time: 0.000844000 seconds]
```

There are 2 “answers” are provided. Each of these answers contains the domain name, type of address, class, IP address, time to live and data length.

6. Consider the subsequent TCP SYN packet sent by your host. Does the destination IP address of the SYN packet correspond to any of the IP addresses provided in the DNS response message? Add screenshots in your answer.

```

> Frame 9: 104 bytes on wire (832 bits), 104 bytes captured (832 bits)
> Ethernet II, Src: Cisco_83:e4:54 (00:b0:8e:83:e4:54), Dst: IBM_10:60:9
> Internet Protocol Version 4, Src: 128.238.29.23, Dst: 128.238.38.160
  0100 .... = Version: 4
  .... 0101 = Header Length: 20 bytes (5)
  > Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    Total Length: 90
    Identification: 0xd595 (54677)
  > 000. .... = Flags: 0x0
    ...0 0000 0000 0000 = Fragment Offset: 0
    Time to Live: 126
    Protocol: UDP (17)
    Header Checksum: 0x216a [validation disabled]
    [Header checksum status: Unverified]
    Source Address: 128.238.29.23
    Destination Address: 128.238.38.160
    [Stream index: 1]
> User Datagram Protocol, Src Port: 53, Dst Port: 3163
> Domain Name System (response)
  Transaction ID: 0x006e
  > Flags: 0x8180 Standard query response, No error
  Questions: 1
  Answer RRs: 2
  Authority RRs: 0
  Additional RRs: 0
  > Queries
    > www.ietf.org: type A, class IN
  > Answers
    > www.ietf.org: type A, class IN, addr 132.151.6.75
      Name: www.ietf.org
      Type: A (1) (Host Address)

```

The destination IP address of the SYN packet not corresponded to of the IP addresses provided in the DNS response message.


7. This web page contains images. Before retrieving each image, does your host issue new DNS queries?

10	3.078479	128.238.38.160	132.151.6.75	TCP	62	3369 → 80 [SYN]	Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM
11	3.096413	132.151.6.75	128.238.38.160	TCP	62	80 → 3369 [SYN, ACK]	Seq=0 Ack=1 Win=5840 Len=0 MSS=1380 SACK_PERM
12	3.096463	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [ACK]	Seq=1 Ack=1 Win=64860 Len=0
13	3.096708	128.238.38.160	132.151.6.75	HTTP	429	GET / HTTP/1.1	
14	3.111678	132.151.6.75	128.238.38.160	TCP	60	80 → 3369 [ACK]	Seq=1 Ack=376 Win=6432 Len=0
15	3.120640	132.151.6.75	128.238.38.160	TCP	1434	80 → 3369 [ACK]	Seq=1 Ack=376 Win=6432 Len=1380 [TCP PDU reassembled in 20]
16	3.128093	132.151.6.75	128.238.38.160	TCP	1434	80 → 3369 [ACK]	Seq=1381 Ack=376 Win=6432 Len=1380 [TCP PDU reassembled in 20]
17	3.128148	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [ACK]	Seq=376 Ack=2761 Win=64860 Len=0
18	3.148016	132.151.6.75	128.238.38.160	TCP	1434	80 → 3369 [ACK]	Seq=2761 Ack=376 Win=6432 Len=1380 [TCP PDU reassembled in 20]
19	3.148069	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [ACK]	Seq=376 Ack=4141 Win=64860 Len=0
20	3.153211	132.151.6.75	128.238.38.160	HTTP	1055	HTTP/1.1 200 OK (text/html)	
21	3.153293	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [ACK]	Seq=376 Ack=5143 Win=63859 Len=0
22	3.161867	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [FIN, ACK]	Seq=376 Ack=5143 Win=63859 Len=0
23	3.174716	132.151.6.75	128.238.38.160	TCP	60	80 → 3369 [ACK]	Seq=5143 Ack=377 Win=6432 Len=0
24	3.178159	128.238.38.160	132.151.6.75	TCP	62	3370 → 80 [SYN]	Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM
25	3.179283	128.238.38.160	132.151.6.75	TCP	62	3371 → 80 [SYN]	Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM
26	3.191649	132.151.6.75	128.238.38.160	TCP	62	80 → 3370 [SYN, ACK]	Seq=0 Ack=1 Win=5840 Len=0 MSS=1380 SACK_PERM
27	3.191726	128.238.38.160	132.151.6.75	TCP	54	3370 → 80 [ACK]	Seq=1 Ack=1 Win=64860 Len=0
28	3.191998	128.238.38.160	132.151.6.75	HTTP	320	GET /images/ietflogo2e.gif HTTP/1.1	

No, the host does not issue new DNS queries before retrieving each image.


- Open packet trace file dns-trace-2 for nslookup.
- We see from Wireshark that nslookup actually sent three DNS queries and received three DNS responses. For the purpose of this lab, ignore the first two sets of queries/responses, as they are specific to nslookup and are not normally generated by standard Internet applications. You should instead focus on the last query and response messages.
- Answer the following questions.

8. What is the destination port for the DNS query message? What is the source port of DNS response message? Add screenshots in your answer.



```

▶ Frame 15: 86 bytes on wire (688 bits), 86 bytes captured (688 bits)
▶ Ethernet II, Src: IBM_10:60:99 (00:09:6b:10:60:99), Dst: All-MSRP-router
▶ Internet Protocol Version 4, Src: 128.238.38.160, Dst: 128.238.29.22
▶ User Datagram Protocol, Src Port: 3740, Dst Port: 53
▼ Domain Name System (query)
  Transaction ID: 0x0001
  ▶ Flags: 0x0100 Standard query
  Questions: 1
  Answer RRs: 0
  Authority RRs: 0
  Additional RRs: 0
  ▼ Queries
    ▶ 22.29.238.128.in-addr.arpa: type PTR, class IN
    [Response In: 16]
  
```



```

▶ Frame 16: 118 bytes on wire (944 bits), 118 bytes captured (944 bits)
▶ Ethernet II, Src: Cisco_83:e4:54 (00:b0:8e:83:e4:54), Dst: IBM_10:60:9
▶ Internet Protocol Version 4, Src: 128.238.29.22, Dst: 128.238.38.160
▶ User Datagram Protocol, Src Port: 53, Dst Port: 3740
▼ Domain Name System (response)
  Transaction ID: 0x0001
  ▶ Flags: 0x8580 Standard query response, No error
  Questions: 1
  Answer RRs: 1
  Authority RRs: 0
  Additional RRs: 0
  ▼ Queries
    ▶ 22.29.238.128.in-addr.arpa: type PTR, class IN
  ▼ Answers
    ▼ 22.29.238.128.in-addr.arpa: type PTR, class IN, dns-prime.poly.ec
  
```

The destination port for the DNS query message and the source port of DNS response message is 53.

9. To what IP address is the DNS query message sent? Is this the IP address of your default local DNS server? Add screenshots in your answer.

```

0100 .... = Version: 4
.... 0101 = Header Length: 20 bytes (5)
▶ Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
Total Length: 72
Identification: 0x27a1 (10145)
▶ 000. .... = Flags: 0x0
...0 0000 0000 0000 = Fragment Offset: 0
Time to Live: 128
Protocol: UDP (17)
Header Checksum: 0xcd71 [validation disabled]
[Header checksum status: Unverified]
Source Address: 128.238.38.160
Destination Address: 128.238.29.22
[Stream index: 1]
▶ User Datagram Protocol, Src Port: 3740, Dst Port: 53
▶ Domain Name System (query)

```

```

Wireless LAN adapter Wi-Fi:

Connection-specific DNS Suffix . : 
Description . . . . . : Intel(R) Wi-Fi 6 AX203
Physical Address. . . . . : F4-C8-8A-40-74-F0
DHCP Enabled. . . . . : Yes
Autoconfiguration Enabled . . . . : Yes
IPv6 Address. . . . . : 2001::e68:540a:3dfe:5568:f41d:21b6:13f1(Preferred)
Temporary IPv6 Address. . . . . : 2001::e68:540a:3dfe:2064:494:c20:1d36(Preferred)
Link-local IPv6 Address . . . . . : fe80::c31a:6d48:aec3:ff50%4(Preferred)
IPv4 Address. . . . . : 192.168.0.114(Preferred)
Subnet Mask . . . . . : 255.255.255.0
Lease Obtained. . . . . : Tuesday, December 24, 2024 12:52:26 PM
Lease Expires . . . . . : Thursday, December 26, 2024 10:10:14 PM
Default Gateway . . . . . : fe80::5ac5:7eff:fe1:8b71%4
                          192.168.0.1
DHCP Server . . . . . : 192.168.0.1
DHCPv6 IAID . . . . . : 83150986
DHCPv6 Client DUID. . . . . : 00-01-00-01-2D-1D-D4-56-F4-C8-8A-40-74-F0
DNS Servers . . . . . : 2001::e68::b:68
                          2001::e68::b:69
                          192.168.0.1
NetBIOS over Tcpip. . . . . : Enabled

```

The IP address that the DNS query message sent to is 128.238.29.22. The destination IP address is different IP address with my default local DNS server.

10. Examine the DNS query message. What “Type” of DNS query is it? Does the query message contain any “answers”? Add screenshots in your answer.


```

▶ Frame 19: 71 bytes on wire (568 bits), 71 bytes captured (568 bits)
▶ Ethernet II, Src: IBM_10:60:99 (00:09:6b:10:60:99), Dst: All-MSRP-router
▶ Internet Protocol Version 4, Src: 128.238.38.160, Dst: 128.238.29.22
▶ User Datagram Protocol, Src Port: 3742, Dst Port: 53
▼ Domain Name System (query)
  Transaction ID: 0x0003
  ▶ Flags: 0x0100 Standard query
    Questions: 1
    Answer RRs: 0
    Authority RRs: 0
    Additional RRs: 0
  ▼ Queries
    ▶ www.mit.edu: type A, class IN
    [Response In: 20]

```

The “Type” of the DNS query is type A. The query message does not contain any “answers”.

11. Examine the DNS response message. How many “answers” are provided? What do each of these answers contain? Add screenshots in your answer.



```

Frame 20: 196 bytes on wire (1568 bits), 196 bytes captured (1568 bits)
Ethernet II, Src: Cisco_83:e4:54 (00:b0:8e:83:e4:54), Dst: IBM_10:60:99
Internet Protocol Version 4, Src: 128.238.29.22, Dst: 128.238.38.160
User Datagram Protocol, Src Port: 53, Dst Port: 3742
Domain Name System (response)
  Transaction ID: 0x0003
  Flags: 0x8580 Standard query response, No error
  Questions: 1
  Answer RRs: 1
  Authority RRs: 3
  Additional RRs: 3
  Queries
  Answers
    www.mit.edu: type A, class IN, addr 18.7.22.83
      Name: www.mit.edu
      Type: A (1) (Host Address)
      Class: IN (0x0001)
      Time to live: 60 (1 minute)
      Data length: 4
      Address: 18.7.22.83
  Authoritative nameservers
  Additional records
[Request In: 19]
[Time: 0.016757000 seconds]
```

There are 1 “answers” are provided. Each of these answers contains the domain name, type of address, class, IP address, time to live and data length.