

EFF 28 SEP 06

CHANGE: Revised

# QUÉBEC/JEAN LESAGE INTL

NAD83 ◆






EFF 28 SEP 06

CHANGE: Revised

464728N 712336W (2003) QUÉBEC/JEAN LESAGE INTL

## QUÉBEC/JEAN LESAGE INTL



EFF 3 AUG 06

CHANGE: Plan view

464728N 712336W (2003)

QUÉBEC/JEAN LESAGE INTL


NAD83◆

EFF 13 APR 06

CHANGE: GPS to GNSS

QUÉBEC/JEAN LESAGE INTL

NAD83 ◆



464728N 712336W

(2003)

EFF 8 JUN 06

NDB RWY 06

CHANGE: Editorial


464728N 712336W

VAR 17°W

QUÉBEC/JEAN LESAGE INTL


QUÉBEC QC

NAD83 ◆



464728N 712336W

VAR 17°W



EFF 8 JUN 06

VOR/DMF RWY 06

CHANGE: Editorial

464728N 712336W


VAR 17°W

QUÉBEC/JEAN LESAGE INTL

QUÉBEC QC

Source of Canadian Civil Aeronautical Data : © 2008 NAV CANADA All rights reserved

#### QUÉBEC/JEAN LESAGE INTL OUÉBEC OC



EFF 8 JUN 06

CHANGE: Editorial

464728N 712336W


VAR 17°W

QUÉBEC/JEAN LESAGE INTL

NAD83 ◆


QUÉBEC/JEAN LESAGE INTL

NAD83 ◆



464728N 712336W

VAR 17°W



#### DEPARTURE ROUTE DESCRIPTION

DEPARTURE CLIMB RATE V/V (FPM)

120 140 160 180 580 680

Rwv 06:

Chart not to scale

- 1. Climb to "BV" NDB then track 064° outbound or on assigned heading by ATC for radar vectors.
- All acft maintain 4000 ASL or as assigned.

GROUND SPEED

Rwy 12:

- 1. Climb on heading 115° or as assigned by ATC for radar vectors.
- 2. Jet acft maintain 4000 ASL or as assigned. Non-jet acft maintain 3000 ASL or as assigned.

Do not proceed in north sector between Rwys 06 and 30 before reaching 1600.

Rwy 24: 1. Climb on heading 242° or as assigned by ATC for radar vectors.

90

2. Jet acft maintain 4000 ASL or as assigned. Non-jet acft maintain 3000 ASL or as assigned.

Do not proceed in north sector between Rwys 06 and 30 before reaching 1600.

Rwy 30:

- 1. Requires a minimum climb gradient of 290 ft/NM to 1600.
- 2. Maintain hdg 295° until 660 then climbing left turn hdg 274° or as assigned by ATC for radar vectors.
- 3. Jet acft maintain 4000 ASL or as assigned. Non-jet acft maintain 3000 ASL or as assigned.

#### **COMMUNICATION FAILURE**

- 1. Select transponder mode C/3 code 7600.
- 2. Climb to flight planned altitude 3 minutes after take-off, and
- 3. Proceed on course 3 minutes after selecting 7600.

QUEBEC TWO DEP (CYQB 2.)

QUÉBEC QC


### CANADA AIR PILOT

Effective 0901Z 20 NOVEMBER 2008 to 0901Z 15 JANUARY 2009

QUÉBEC/JEAN LESAGE INTL QUÉBEC QO


QUÉBEC/JEAN LESAGE INTL

NAD83



### **CANADA AIR PILOT**

Effective 0901Z 20 NOVEMBER 2008 to 0901Z 15 JANUARY 2009



EFF 30 AUG 07

CHANGE: Revised

NAD83