databricks trans / 4.calculated_race_results

(https://databricks.com)

```
dbutils.widgets.text("p_file_date", "2021-03-21")
v_file_date = dbutils.widgets.get("p_file_date")
```

```
spark.sql(f"""
              CREATE TABLE IF NOT EXISTS f1_presentation.calculated_race_results
              (
              race_year INT,
              team_name STRING,
              driver_id INT,
              driver_name STRING,
              race_id INT,
              position INT,
              points INT,
              calculated_points INT,
              created_date TIMESTAMP,
              updated_date TIMESTAMP
              )
              USING DELTA
""")
```

```
DataFrame[]
```

```
# %sql
# -- use f1_processed;
```

```

```

```
# -- select
# --     races.race_year,
# --     constructors.name as team_name,
# --     drivers.name as driver_name,
# --     results.position,
# --     results.points,
# --     11 - results.position as calculated_points
# --   from results
# --   join drivers on (drivers.driver_id = results.driver_id)
# --   join constructors on (constructors.constructor_id = results.constructor_id)
# --   join races on (races.race_id = results.race_id)
# --   where  results.position <=10  ;
```

```

```

```
# %sql
# -- create table f1_presentation.calculated_race_results
# -- using parquet
# -- as
# -- select
# --     races.race_year,
# --     constructors.name as team_name,
# --     drivers.name as driver_name,
# --     results.position,
# --     results.points,
# --     11 - results.position as calculated_points
# --   from f1_processed.results
# --   join f1_processed.drivers on (drivers.driver_id = results.driver_id)
# --   join f1_processed.constructors on (constructors.constructor_id = results.constructor_id)
# --   join f1_processed.races on (races.race_id = results.race_id)
# --   where  results.position <=10  ;
```

```
# %sql
# -- select * from f1_presentation.calculated_race_results;
```

```
spark.sql(f"""
              CREATE OR REPLACE TEMP VIEW race_result_updated
              AS
              SELECT races.race_year,
                     constructors.name AS team_name,
                     drivers.driver_id,
                     drivers.name AS driver_name,
                     races.race_id,
                     results.position,
                     results.points,
                     11 - results.position AS calculated_points
                FROM f1_processed.results
                JOIN f1_processed.drivers ON (results.driver_id = drivers.driver_id)
                JOIN f1_processed.constructors ON (results.constructor_id = constructors.constructor_id)
                JOIN f1_processed.races ON (results.race_id = races.race_id)
               WHERE results.position <= 10
                 AND results.file_date = '{v_file_date}'
""")
```

```
DataFrame[]
```

```
# %sql select * from race_result_updated where race_year = 2021;
```

Table

	race_year	team_name	driver_id	driver_name	race_id	position	points	ca
1	2021	Mercedes	1	Lewis Hamilton	1053	2	19	
2	2021	Alpine F1 Team	4	Fernando Alonso	1053	10	1	
3	2021	AlphaTauri	842	Pierre Gasly	1053	7	6	
4	2021	McLaren	817	Daniel Ricciardo	1053	6	8	
5	2021	Red Bull	830	Max Verstappen	1053	1	25	
6	2021	Ferrari	832	Carlos Sainz	1053	5	10	
7	2021	Alpine F1 Team	839	Esteban Ocon	1053	9	2	
8	2021	Aston Martin	840	Lance Stroll	1053	8	4	
9	2021	Ferrari	844	Charles Leclerc	1053	4	12	
10	2021	McLaren	846	Lando Norris	1053	3	15	

10 rows

```
# %sql select count(1) from race_result_updated;
```

Table

	count(1)
1	10

1 row

```
# %sql select count(1) from f1_presentation.calculated_race_results;
```

Table

	count(1)
1	10101

1 row

```
DataFrame[num_affected_rows: bigint, num_updated_rows: bigint, num_deleted_rows: bigint, num_inserted_rows: bigint]
```