```sql
--This is my personal work uploaded on github only for "Celebal Technology" access using inappropriately can cause Copyright infringement,you need my permission before fair use
--StudentId: CT_CSI_SQ_1260
-- Task 1
WITH ProjectGroups AS (
    SELECT Task_ID,
           Start_Date,
           End_Date,
           ROW_NUMBER() OVER (ORDER BY Start_Date) - ROW_NUMBER() OVER (PARTITION BY Start_Date ORDER BY Task_ID) AS grp
    FROM Projects
)
SELECT MIN(Start_Date) AS Project_Start,
       MAX(End_Date) AS Project_End
FROM ProjectGroups
GROUP BY grp
ORDER BY DATEDIFF(day, MIN(Start_Date), MAX(End_Date)), MIN(Start_Date);

-- Task 2
SELECT S1.Name
FROM Students S1
JOIN Friends F ON S1.ID = F.ID
JOIN Packages P1 ON S1.ID = P1.ID
JOIN Packages P2 ON F.Friend_ID = P2.ID
WHERE P2.Salary > P1.Salary
ORDER BY P2.Salary;

-- Task 3
SELECT DISTINCT LEAST(X, Y) AS X, GREATEST(X, Y) AS Y
FROM Functions F1
JOIN Functions F2 ON F1.X = F2.Y AND F1.Y = F2.X
ORDER BY X, Y;

-- Task 4
WITH ContestStats AS (
    SELECT C.contest_id,
           C.hacker_id,
           C.name,
           COALESCE(SUM(V.total_views), 0) AS total_views,
           COALESCE(SUM(V.total_unique_views), 0) AS total_unique_views,
           COALESCE(SUM(S.total_submissions), 0) AS total_submissions,
           COALESCE(SUM(S.total_accepted_submissions), 0) AS total_accepted_submissions
    FROM Contests C
    LEFT JOIN Challenges H ON C.contest_id = H.contest_id
    LEFT JOIN View_Stats V ON H.challenge_id = V.challenge_id
    LEFT JOIN Submission_Stats S ON H.challenge_id = S.challenge_id
    GROUP BY C.contest_id, C.hacker_id, C.name
)
SELECT contest_id, hacker_id, name, total_views, total_unique_views,
```

```
    total_submissions, total_accepted_submissions
FROM ContestStats
WHERE total_views != 0 OR total_unique_views != 0 OR
  total_submissions != 0 OR total_accepted_submissions != 0
ORDER BY contest_id;

-- Task 5
WITH DailySubmissions AS (
    SELECT submission_date,
           hacker_id,
           COUNT(submission_id) AS submission_count,
           ROW_NUMBER() OVER (PARTITION BY submission_date ORDER BY
             COUNT(submission_id) DESC, hacker_id) AS rn
    FROM Submissions
    GROUP BY submission_date, hacker_id
),
DailyUniqueHackers AS (
    SELECT submission_date,
           COUNT(DISTINCT hacker_id) AS unique_hackers
    FROM Submissions
    GROUP BY submission_date
)
SELECT D1.submission_date,
       D2.unique_hackers,
       D1.hacker_id,
       H.name
FROM DailySubmissions D1
JOIN Hackers H ON D1.hacker_id = H.hacker_id
JOIN DailyUniqueHackers D2 ON D1.submission_date = D2.submission_date
WHERE D1.rn = 1
ORDER BY D1.submission_date;

-- Task 6
SELECT ROUND(ABS(MAX(LAT_N) - MIN(LAT_N)) + ABS(MAX(LONG_W) - MIN
  (LONG_W)), 4) AS Manhattan_Distance
FROM STATION;

-- Task 7
WITH RECURSIVE PrimeNumbers AS (
    SELECT 2 AS num
    UNION ALL
    SELECT num + 1
    FROM PrimeNumbers
    WHERE num < 1000
),
PrimeFilter AS (
    SELECT num
    FROM PrimeNumbers pn1
    WHERE NOT EXISTS (
        SELECT 1
        FROM PrimeNumbers pn2
        WHERE pn2.num < pn1.num AND pn1.num % pn2.num = 0
    )
```

```sql
)
SELECT STRING_AGG(CAST(num AS VARCHAR), '&') AS primes
FROM PrimeFilter
OPTION (MAXRECURSION 0);

-- Task 8
SELECT
    MAX(CASE WHEN Occupation = 'Doctor' THEN Name ELSE NULL END) AS Doctor,
    MAX(CASE WHEN Occupation = 'Professor' THEN Name ELSE NULL END) AS Professor,
    MAX(CASE WHEN Occupation = 'Singer' THEN Name ELSE NULL END) AS Singer,
    MAX(CASE WHEN Occupation = 'Actor' THEN Name ELSE NULL END) AS Actor
FROM (
    SELECT Name, Occupation, ROW_NUMBER() OVER (PARTITION BY Occupation ORDER BY Name) AS RowNum
    FROM Occupations
) AS Piv
GROUP BY RowNum
ORDER BY RowNum;

-- Task 9
WITH NodeTypes AS (
    SELECT N,
           P,
           CASE
               WHEN P IS NULL THEN 'Root'
               WHEN N NOT IN (SELECT P FROM BST WHERE P IS NOT NULL) THEN 'Leaf'
               ELSE 'Inner'
           END AS NodeType
    FROM BST
)
SELECT N, NodeType
FROM NodeTypes
ORDER BY N;

-- Task 10
WITH LeadManagerCount AS (
    SELECT company_code, COUNT(DISTINCT lead_manager_code) AS total_lead_managers
    FROM Lead_Manager
    GROUP BY company_code
),
SeniorManagerCount AS (
    SELECT company_code, COUNT(DISTINCT senior_manager_code) AS total_senior_managers
    FROM Senior_Manager
    GROUP BY company_code
),
ManagerCount AS (
```

```sql
    SELECT company_code, COUNT(DISTINCT manager_code) AS total_managers
    FROM Manager
    GROUP BY company_code
),
EmployeeCount AS (
    SELECT company_code, COUNT(DISTINCT employee_code) AS
      total_employees
    FROM Employee
    GROUP BY company_code
)
SELECT C.company_code,
       C.founder,
       COALESCE(LM.total_lead_managers, 0) AS total_lead_managers,
       COALESCE(SM.total_senior_managers, 0) AS total_senior_managers,
       COALESCE(M.total_managers, 0) AS total_managers,
       COALESCE(E.total_employees, 0) AS total_employees
FROM Company C
LEFT JOIN LeadManagerCount LM ON C.company_code = LM.company_code
LEFT JOIN SeniorManagerCount SM ON C.company_code = SM.company_code
LEFT JOIN ManagerCount M ON C.company_code = M.company_code
LEFT JOIN EmployeeCount E ON C.company_code = E.company_code
ORDER BY C.company_code;

-- Task 11
SELECT S1.Name
FROM Students S1
JOIN Friends F ON S1.ID = F.ID
JOIN Packages P1 ON S1.ID = P1.ID
JOIN Packages P2 ON F.Friend_ID = P2.ID
WHERE P2.Salary > P1.Salary
ORDER BY P2.Salary;

-- Task 12
SELECT
    JobFamily,
    SUM(CASE WHEN Country = 'India' THEN Cost ELSE 0 END) AS
      India_Cost,
    SUM(CASE WHEN Country = 'International' THEN Cost ELSE 0 END) AS
      International_Cost,
    (SUM(CASE WHEN Country = 'India' THEN Cost ELSE 0 END) / NULLIF(SUM
      (Cost), 0)) * 100 AS India_Percentage,
    (SUM(CASE WHEN Country = 'International' THEN Cost ELSE 0 END) /
      NULLIF(SUM(Cost), 0)) * 100 AS International_Percentage
FROM YourTable
GROUP BY JobFamily;

-- Task 13
SELECT BU,
       MONTH,
       SUM(Cost) AS Total_Cost,
       SUM(Revenue) AS Total_Revenue,
       SUM(Cost) / NULLIF(SUM(Revenue), 0) AS Cost_Revenue_Ratio
FROM YourTable
```

```sql
GROUP BY BU, MONTH;

-- Task 14
SELECT SubBand,
       COUNT(EmployeeID) AS Headcount,
       (COUNT(EmployeeID) / (SELECT COUNT(*) FROM YourTable)) * 100 AS
         Percentage_Headcount
FROM YourTable
GROUP BY SubBand;

-- Task 15
SELECT TOP 5 *
FROM Employees
ORDER BY Salary DESC;

-- Task 16
UPDATE TableName
SET ColumnA = ColumnA + ColumnB,
    ColumnB = ColumnA - ColumnB,
    ColumnA = ColumnA - ColumnB;

-- Task 17
CREATE LOGIN new_user WITH PASSWORD = 'password';
CREATE USER new_user FOR LOGIN new_user;
EXEC sp_addrolemember 'db_owner', 'new_user';

-- Task 18
SELECT BU,
       AVG(Cost * Weight) / SUM(Weight) AS WeightedAvgCost
FROM Employees1
GROUP BY BU;

-- Task 19
WITH Actual AS (
    SELECT AVG(Salary) AS ActualAvgSalary
    FROM Employees
),
Miscalculated AS (
    SELECT AVG(CAST(REPLACE(CAST(Salary AS VARCHAR), '0', '') AS INT))
      AS MiscalculatedAvgSalary
    FROM Employees
)
SELECT CEILING(Actual.ActualAvgSalary -
  Miscalculated.MiscalculatedAvgSalary) AS ErrorAmount
FROM Actual, Miscalculated;

-- Task 20
INSERT INTO TargetTable (KeyColumn, Column1, Column2)
SELECT KeyColumn, Column1, Column2
FROM SourceTable
WHERE NOT EXISTS (
    SELECT 1
    FROM TargetTable
```

```
240     WHERE TargetTable.KeyColumn = SourceTable.KeyColumn
241 );
242
243
244
245
```