FlightLab: An Equation-Driven Interactive Visualization Framework for Aircraft Forces and Flight Performance

Chethana Sri
Madras Institute of Technology
Anna University, Chennai, India

***Abstract*—Aircraft flight mechanics involves mathematical relationships between aerodynamic forces, atmospheric conditions, aircraft configuration, and flight performance. Understanding these relationships requires connecting mathematical models with their physical interpretation. This paper presents FlightLab, an interactive aircraft simulation framework designed to connect equation-based flight mechanics with three-dimensional visualization. The platform incorporates mathematical models for atmospheric properties, aerodynamic forces, aircraft performance, propulsion, stability, and flight dynamics. A visualization component connects computed force values to graphical force representations, while an equation overlay presents the lift equation with its corresponding inputs and calculated output. The paper describes the framework, its mathematical foundations, and a proposed methodology for evaluating numerical consistency and visualization behavior. Quantitative performance and educational outcomes will be reported only after the corresponding evaluations have been conducted.**

***Index Terms*—Aircraft flight mechanics, flight simulation, aerodynamic forces, interactive visualization, aircraft performance, engineering education.**

I. Introduction

Aircraft flight mechanics studies the forces and moments acting on an aircraft and their influence on its motion and performance. Concepts such as lift, drag, thrust, weight, airspeed, atmospheric density, and angle of attack are connected through mathematical models that describe aircraft behavior under different flight conditions.

For learners studying these concepts, understanding the equations is only one part of the learning process. It is also important to understand how changes in model parameters affect force magnitudes and predicted aircraft behavior. Static equations and diagrams may not provide an immediate representation of these relationships.

Interactive simulation provides one approach to connecting mathematical models with visual representations. Previous work has investigated virtual environments for teaching aircraft flight dynamics and control concepts [1]. Mathematical aircraft-dynamics models also provide a basis for studying aircraft behavior under defined conditions [2].

This paper presents FlightLab, an interactive aircraft simulation framework that combines mathematical flight-mechanics models with a three-dimensional visualization interface. The framework aims to make the relationship between model inputs, calculated aerodynamic forces, and their visual representation explicit.

The objectives of this work are:

- To describe the integration of aircraft physics models with an interactive visualization environment.
- To connect calculated lift, drag, thrust, and weight values to graphical force representations.
- To display the lift equation with model inputs and calculated outputs.
- To define a reproducible methodology for evaluating numerical calculations and visualization consistency.

The work focuses on the design and technical evaluation of an interactive simulation framework. Any claim concerning improved student learning requires a separate educational evaluation.

II. Related Work

A. Interactive Flight Dynamics Education

Davies, Rajashekar, and Gururajan presented the design of a virtual environment intended to support teaching aircraft flight dynamics and control concepts [1]. Their work illustrates the relevance of interactive environments to aerospace engineering education. Related virtual-reality work has also explored interactive aerospace learning environments [6].

B. Aircraft Dynamics and Simulation

Mathematical aircraft-dynamics models can be used to analyze aircraft motion and investigate manoeuvres under defined conditions. Such approaches emphasize the relationship between governing equations, model assumptions, and simulated aircraft behavior [2].

C. Positioning of FlightLab

FlightLab brings several flight-mechanics model categories together with a three-dimensional interface and equation-based visualization. Its specific contribution must be established by comparing its implementation and evaluation with existing tools and published research. Integration alone does not establish research novelty.

III. Problem Statement and Objectives

This work investigates how calculated aircraft forces can be represented in an interactive environment so that users can inspect the relationship between mathematical inputs, numerical outputs, and graphical force vectors.

The central research question is:

How can equation-driven visualization connect calculated aircraft forces with their graphical representation in an interactive flight simulation environment?

A secondary question is whether this representation improves learners' conceptual understanding compared with conventional learning materials. This question requires a separate study involving learners.

IV. System Architecture

FlightLab is organized into frontend, backend and simulation, data, and reference-input components, as illustrated in Fig. 1. The frontend provides the user interface for entering simulation parameters and inspecting the resulting aircraft visualization, force vectors, equations, charts, and telemetry.

The backend and simulation components are intended to receive the user-defined parameters, coordinate the relevant physics calculations, and return computed values to the visualization interface. The flight-physics models cover atmospheric properties, aerodynamics, flight performance, propulsion, stability, and flight dynamics. The reference inputs include atmospheric properties and aircraft parameters required by the selected models.

The data-storage components shown in the figure are optional and should be retained only if they are present in the actual implementation. Similarly, the backend technologies and connections must be checked against the source code before publication. The architecture is a high-level representation of component responsibilities rather than evidence that every illustrated integration has been implemented or validated.

The intended data flow connects user inputs to physics calculations, then to computed telemetry and visualization. Numerical consistency and the mapping from computed forces to graphical vectors must be verified through controlled software tests.

A. Computational Pipeline

Fig. 2 presents a conceptual view of the data flow between flight parameters, physics calculations, telemetry, and visualization.

The figure represents the intended computational flow. The exact dependency relationships and update mechanisms must be confirmed against the implementation. Atmospheric properties and aircraft parameters are supplied to the relevant models, which calculate force and performance quantities for presentation in the interface.

V. Mathematical Foundations

A. Dynamic Pressure

Dynamic pressure is defined as

$$q = \frac{1}{2}\rho V^2, \tag{1}$$

where ρ is air density and V is airspeed. The atmospheric properties used by the model should be consistent with the selected reference atmosphere [4].

B. Lift

Lift can be represented by the standard aerodynamic relationship

$$L = \frac{1}{2}\rho V^2 S C_L, \tag{2}$$

where L is lift force in newtons, ρ is air density in kilograms per cubic metre, V is airspeed in metres per second, S is wing reference area in square metres, and C_L is the dimensionless lift coefficient. This relationship is consistent with standard introductory aerodynamics and flight-mechanics references [3], [5].

For fixed density, wing area, and lift coefficient, lift varies with the square of airspeed. Doubling airspeed under these assumptions increases calculated lift by a factor of four.

C. Drag

Drag can be represented by

$$D = \frac{1}{2}\rho V^2 S C_D, \tag{3}$$

where D is drag force and C_D is the drag coefficient.

D. Drag Polar

Where a parabolic drag-polar approximation is appropriate, the drag coefficient can be expressed as

$$C_D = C_{D0} + K C_L^2, \tag{4}$$

where C_{D0} is the zero-lift drag coefficient and K is the induced-drag factor.

A conventional approximation for this factor is

$$K = \frac{1}{\pi e AR}, \tag{5}$$

where e is the Oswald efficiency factor and AR is the wing aspect ratio. The applicability of this model depends on the aerodynamic assumptions and the implemented coefficient model.

E. Longitudinal Force Balance

For a simplified aircraft model, the longitudinal equation of motion can be written as

$$m\frac{dV}{dt} = T - D - W\sin\gamma, \tag{6}$$

where m is aircraft mass, T is thrust, D is drag, $W = mg$ is weight, and γ is flight-path angle.

For steady, level flight, with $\gamma = 0$ and $dV/dt = 0$, this simplifies to




Fig. 1. High-level system architecture of FlightLab. Optional storage and backend components should be confirmed against the implemented system before publication.




Fig. 2. Conceptual data flow connecting flight parameters, physics calculations, telemetry, and visualization.

$$T = D. \tag{7}$$

This simplified relationship is useful for defining test conditions. General manoeuvres require the appropriate equations of motion and coordinate conventions.

VI. Equation-Driven Visualization

The visualization approach connects computed telemetry to graphical representations of lift, drag, thrust, and weight. Unlike fixed-length arrows, data-driven vectors can reflect changes in calculated force magnitudes.

The equation overlay presents the lift equation and its current input values. This enables users to inspect the relationship between air density, airspeed, wing area, lift coefficient, and calculated lift.

Visual scaling requires explicit treatment. If different forces use different reference scales, their arrow lengths cannot be interpreted as directly proportional to absolute force magnitudes without accounting for those scales. The interface should communicate its normalization convention and preserve meaningful force directions.

The consistency of the numerical model, displayed values, and vector scaling forms a central part of the proposed technical evaluation.

VII. Evaluation Methodology

The evaluation is divided into numerical validation and visualization consistency. An educational study may be conducted separately if feasible.

A. Numerical Validation

Selected calculations will be compared against independently calculated reference values or trusted published references. Test cases should cover multiple airspeeds, atmospheric conditions, and aerodynamic coefficients within the valid range of the implemented models.

TABLE I
PROPOSED ANALYTICAL VALIDATION CASES

Test	Procedure	Expected relationship
T1	Double airspeed while holding density, area, and C_L constant.	Lift increases by a factor of four.
T2	Double density while holding other inputs fixed.	Lift and drag double under the same model.
T3	Change wing area while other inputs remain fixed.	Lift and drag vary linearly with area.
T4	Compare displayed lift with the equation evaluated from identical inputs.	Values agree within a predefined numerical tolerance.
T5	Change force magnitudes and inspect vector scaling.	Arrow lengths follow the documented mapping.

For each test, the input parameters, expected output, calculated output, units, and numerical difference will be recorded.

B. Visualization Consistency

The visualization will be evaluated by varying simulation parameters and checking whether:

- The displayed equation uses the corresponding model inputs.
- The displayed lift agrees with the model output.
- Force-vector directions match their definitions.
- Vector lengths follow the documented scaling rule.
- Unsupported conditions are handled appropriately.

C. Proposed Analytical Test Cases

Table I defines proposed tests. These are expected relationships, not observed experimental results.

Each test must be executed before its outcome can be reported. The chosen numerical tolerance, input ranges, software versions, and any failed tests should be documented.

D. Error Measurement

For a nonzero reference value y_{ref}, absolute error is defined as

$$E_{\mathrm{abs}} = \left| y_{\mathrm{calc}} - y_{\mathrm{ref}} \right|. \tag{8}$$

Relative error, expressed as a percentage, is

$$E_{\mathrm{rel}} = \frac{\left| y_{\mathrm{calc}} - y_{\mathrm{ref}} \right|}{\left| y_{\mathrm{ref}} \right|} \times 100\%. \tag{9}$$

Relative error is unsuitable when the reference value is zero or close to zero. In those cases, absolute error or another appropriate metric should be used.

E. Educational Evaluation

If feasible, a separate study may investigate whether the interactive representation improves learners' understanding of aircraft forces. A possible design would compare conceptual assessment scores before and after using FlightLab, with an appropriate comparison group where practical.

Such a study requires a defined participant group, assessment instrument, study protocol, and appropriate institutional approval where applicable. Educational improvement will not be claimed without collected evidence.

VIII. IMPLEMENTATION AND SIMULATION WORKFLOW

FlightLab is intended to connect user-defined flight conditions with physics calculations and interactive visual feedback. The workflow begins when a user enters the aircraft and environmental parameters through the interface. The application then evaluates the relevant models and presents the resulting values through the visualization layer. The following description explains the intended workflow; each step should be checked against the implemented source code before it is reported as a completed feature.

A. Input Parameter Processing

Inputs may include airspeed, altitude, angle of attack, wing reference area, aircraft mass, and aerodynamic coefficients. The set of available inputs depends on the aircraft model and simulation mode. Input processing should check that required values are present, numeric, and within the valid range of the selected model. Unit consistency is also important: airspeed is expressed in metres per second, density in kilograms per cubic metre, area in square metres, mass in kilograms, and force in newtons when using SI units.

B. Flight Physics Calculations

The physics stage evaluates the equations used by the selected models. For example, dynamic pressure is calculated from air density and airspeed, and lift and drag are calculated using the corresponding reference area and aerodynamic coefficients. Where the implementation supports atmospheric variation with altitude, the atmospheric model provides the density and other properties used by the force equations. The assumptions and valid ranges of each model should be documented so that users can distinguish simplified estimates from higher-fidelity predictions.

C. Visualization of Computed Forces

The visualization layer represents relevant forces, such as lift, drag, thrust, and weight, as vectors associated with the aircraft model. For the visualization to communicate quantitative changes, vector lengths should be derived from calculated values using a documented scale. If normalization or different scales are used for different forces, that choice should be disclosed; otherwise, arrow lengths may be misread as direct comparisons of absolute force magnitude. Vector directions must also follow the coordinate convention used by the physics model.

The equation overlay can display the lift relationship together with its current inputs and calculated output. This helps make the dependency between air density, airspeed, wing area, lift coefficient, and lift explicit. The displayed equation and numerical output should use the same inputs as the physics calculation to avoid discrepancies between the interface and the underlying model.

D. Simulation Output and Interpretation

The output layer may present force magnitudes, atmospheric properties, aircraft parameters, and flight-performance quantities supported by the implemented models. These outputs represent predictions produced by the selected mathematical assumptions; they should not be described as measured aircraft data unless they have been compared with suitable measurements. The interface should identify unavailable values and unsupported operating conditions rather than presenting them as valid results.

E. Validation Criteria and Reproducibility

A reproducible evaluation should record the software version, input conditions, model assumptions, reference values, calculated outputs, and acceptance criteria. For a calculated quantity X, absolute error relative to a reference value is defined as

$$E_{\mathrm{abs}} = |X_{\mathrm{sim}} - X_{\mathrm{ref}}|, \tag{10}$$

where X_{sim} is the simulation output and X_{ref} is an independently obtained reference value. For a nonzero reference value, relative error is

$$E_{\mathrm{rel}} = \frac{|X_{\mathrm{sim}} - X_{\mathrm{ref}}|}{|X_{\mathrm{ref}}|} \times 100\%. \tag{11}$$

Relative error should not be used when the reference value is zero or near zero; absolute error or another suitable metric should be used instead. A test is not considered passed until it has been executed and its result recorded. These equations define an evaluation procedure and do not imply that validation has already been completed.

IX. Results and Discussion

This section will report the outcomes of numerical validation, visualization consistency tests, and any completed educational evaluation.

For each experiment, the paper should state the test conditions, reference values, observed outputs, and limitations. Results should distinguish calculated model outputs from external reference data and real-world flight measurements.

No quantitative performance or educational conclusions are asserted here because experimental evidence has not yet been supplied.

X. Limitations and Future Work

The accuracy of FlightLab depends on the assumptions, coefficient models, parameter ranges, and numerical methods used by its individual components. A simulation may simplify nonlinear aerodynamic effects or omit phenomena that become important outside its intended operating conditions.

Future work may include broader validation against published aircraft data, additional interactive experiments, systematic usability evaluation, and a controlled study of conceptual understanding. Comparison with existing flight simulation and engineering-education tools will help establish the platform's distinct contribution.

XI. Conclusion

This paper presents FlightLab as an interactive framework for connecting equation-based aircraft flight mechanics with three-dimensional visualization. Its approach combines multiple categories of aircraft physics models with a graphical representation of force magnitudes and a live lift-equation overlay.

The proposed evaluation separates numerical correctness, visualization consistency, and educational effectiveness. Completing these evaluations will provide evidence needed to assess the framework's technical contribution and its potential value for learning aircraft flight mechanics.

References

[1] E. J. Davies, S. C. Rajashekar, and S. Gururajan, "Design and Development of a Virtual Environment to Enable Interactive Teaching of Aircraft Flight Dynamics and Control Concepts (Work in Progress)," in *2020 ASEE Virtual Annual Conference*, 2020. doi: 10.18260/1-2–34390.

[2] "Model-based manoeuvre analysis: a path to a new paradigm in aircraft flight dynamics," *Frontiers in Aerospace Engineering*, 2024. doi: 10.3389/fpace.2024.1308872.

[3] NASA Glenn Research Center, "Beginner's Guide to Aeronautics: Guide to Aerodynamics." [Online]. Available: https://www1.grc.nasa.gov/beginners-guide-to-aeronautics/learn-about-aerodynamics/.

[4] U.S. Committee on Extension to the Standard Atmosphere, *U.S. Standard Atmosphere, 1976*. Washington, DC, USA, 1976. [Online]. Available: https://ntrs.nasa.gov/citations/19770009539.

[5] R. C. Nelson, *Flight Stability and Automatic Control*, 2nd ed. New York, NY, USA: McGraw-Hill, 1998.

[6] L. Giunta, H. Wright, S. Chandra Shekar, and S. Gururajan, "Developing an Extensive Virtual Reality Environment for Learning Aerospace Concepts," in *Proceedings of the ASEE Annual Conference & Exposition*, 2022. doi: 10.18260/1-2–41814.