

AEROSPIKE

Developer Setup

Goals

This module describes how to setup a developer environment. You will use this environment for the Lab exercises.

At the end of this module you will be able to:

- Install and Configure a single server development cluster in
 - AWS
 - your own computer
- Manage your development cluster



Server Installation

Server options

- Install on your own server.
<http://www.aerospike.com/docs/operations/install/>
 - Windows
 - OSX
 - Linux
- Amazon Web Server instance (AWS)

Own Computer: Windows

Follow the instructions at:

- <http://www.aerospike.com/docs/operations/install/vagrant/win/>

Create an Aerospike Virtual Machine

1. Install Git for windows
2. Create an Aerospike Virtual Machine
3. Initialize the Aerospike Virtual Machine
4. Start Aerospike and the AMC



Own Computer: OSX

Follow the instructions at:

- <http://www.aerospike.com/docs/operations/install/vagrant/mac/>

Create an Aerospike Virtual Machine

1. Create an Aerospike Directory
2. Initialize the Aerospike Virtual Machine
3. Start Aerospike and AMC



Own computer: Linux

To install the software you must have root/sudo privileges

- Download the server software

```
wget -O aerospike-server.tgz http://www.aerospike.com/download/server/latest/artifact/el6
```

- Download the Aerospike Monitoring software

```
wget -O aerospike-amc.rpm http://www.aerospike.com/download/amc/latest/artifact/el6
```

- Install the AMC

- `sudo rpm -ivh aerospike-amc.rpm`

- Install the server

- `tar xvf aerospike-server.tgz`
 - `cd aerospike-server-community-<version>`
 - `sudo ./asinstall`



The URLs for the latest version remain static, so these URLs will get the latest version of the both the database and the Aerospike Management Console.

It is NOT required to install the AMC as the same node as the Aerospike Server, but it is useful to install it here for the class.

Install on your own Computer

Follow the instructions at this URL to install Aerospike on your own Machine

- <http://www.aerospike.com/download/server/latest/>

Install

- Aerospike server
- Aerospike tools
- Aerospike Management Console

AWS Aerospike Server

For this course, Aerospike has prepared an Amazon EC2 instance for your use.

AMI: **"aerotrainig-developer-vX.XX"**

This instance has pre-loaded the following:

- Aerospike Java client
- Aerospike Python client
- Aerospike C client
- Aerospike data loader
- Oracle JDK 1.7
- maven
- lua
- git

You may not need all of these, but they are there for your convenience.

How To Log Into The AWS Instance

You will use the IP address for your own AWS instance to use with the training module.

Log into the server:

- Mac/Linux

```
ssh aerotraining@<ip_address>
```

- Windows PC

- You can use a tool such as putty to ssh login to the server:
- <http://www.chiark.greenend.org.uk/~sgtatham/putty/>

The username/password is aerotraining/aerotraining.

You each should have your own IP address to log into your own instance. You can use whichever tool you are comfortable with to log in. You will not need to have a good knowledge of Linux for this class.

Server IP Address

Write down your server IP address



Server Operation

Starting And Stopping Aerospike Server

Controlling the server requires you to be root or have sudo privileges, which the aerotraining user has.

Start server

```
sudo service aerospike start
```

Check on server status

```
sudo service aerospike status
```

Stop server

```
sudo service aerospike stop
```

Restart server

```
sudo service aerospike restart
```

Starting and Stopping the AMC Server

The Aerospike Management Console (AMC) is used to see how the server is doing.

Start server

```
sudo service amc start
```

Check on server status

```
sudo service amc status
```

Stop server

```
sudo service amc stop
```

Restart server


```
sudo service amc restart
```

Aerospike Management Console

Connect to the AMC using

- `http://<your ip address>:8081`

You will be prompted for a node address in the cluster, enter your IP address:



The image shows a dialog box titled "Cluster Seed Node" with a server icon. It contains the instruction "Enter the IP address and service port (default is 3000) for the node to connect to". Below this is a text input field with the placeholder "Host Name or IP" and the value "3000". A blue "Connect" button is positioned below the input field. At the bottom of the dialog, a note states "(The other nodes in the cluster will be discovered automatically)".


Cluster Seed Node

Enter the IP address and service port (default is 3000) for the node to connect to

Host Name or IP : 3000

Connect

(The other nodes in the cluster will be discovered automatically)



Logs

It is always helpful to be able to look at the logs of the server. You **MUST** have root/sudo privileges to see the logs in the default locations:

```
/var/log/aerospike/aerospike.log  
/var/log/aerospike/udf.log
```

It is often useful to keep a window open with a tail of the log:

```
sudo tail -f /var/log/aerospike/aerospike.log
```

UDF logging

Log entries are used to debug User Defined Functions (UDFs). To log UDF entries in a separate log file, do the following:

Edit the Aerospike configuration file:

`/etc/aerospike/aerospike.conf`

Locate the “logging” stanza and modify it to look like this:

```
logging {  
    file /var/log/aerospike/aerospike.log {  
        context any warning  
    }  
    file /var/log/aerospike/udf.log {  
        context any critical  
        context udf debug  
    }  
}
```

Restart Aerospike (`sudo service aerospike restart`)

If you are not comfortable with using a tool such as vi to edit the file, simply copy the example file by using:

```
sudo cp -f ~/aerospike.conf /etc/aerospike
```

Development Environment

You will need to setup you language development environment to include Aerospike:

- Java
- C#
- Go
- PHP

The details of each environment are in the next slides – follow the instructions for you language




C# Client is one of the several client libraries that can be used to access Aerospike's database from an application. For a full list of client libraries, please visit <http://www.aerospike.com/develop/>

Labs on GitHub

The lab Exercises, Answers and student Notes are stored on GitHub. Clone the GitHub repository with the following command:

- `git clone`
<https://github.com/aerospike-edu/student-workbook.git>





C# Client is one of the several client libraries that can be used to access Aerospike's database from an application. For a full list of client libraries, please visit <http://www.aerospike.com/develop/>

C# Client Setup - Download

NuGet

- The compiled library is also available via NuGet. To install, run the following command in the Package Manager Console:

```
PM> Install-Package Aerospike.Client
```

Download (Alternative)

- Visit this link to download the latest version –
<http://www.aerospike.com/download/client/csharp/latest>



Java Client Setup

Java Client Tools - Install

- Download and install Maven:
 - <http://maven.apache.org/download.cgi#Installation>
- Optional Eclipse Installation:
 - Download and install Eclipse JDT – Kepler or better
 - <http://www.eclipse.org/jdt/>
 - Install m2e plugin (maven):
 - Add an Update site for m2eclipse
 - <http://download.eclipse.org/technology/m2e/releases>
 - Install Maven Integration for Eclipse
 - Install Aerospike Developer Tools plugin:
 - Add an Update site for the Aerospike Developer Tools
 - <https://github.com/aerospike/eclipse-tools/raw/master/aerospike-site>
 - Install Aerospike Developer Tools

Java Client Setup – Maven or download

Maven

```
<dependencies>
  <dependency>
    <groupId>com.aerospike</groupId>
    <artifactId>aerospike-client</artifactId>
    <version>3.1.XX</version>
  </dependency>
</dependencies>
```

Download (Alternative)

- Visit this link to download the latest version – <http://www.aerospike.com/download/client/java/latest>
- Unzip/untar files into local folder. The package contains source code for the Java client, comprehensive examples and a Benchmark tool

Note: For this class we will use **Maven** to build the project and manage dependencies.



Go Client Setup

Go Client Setup - Download

GitHub

- The Go client library is also available via GitHub. To install, run the following command using “go get”

```
go get github.com/aerospike/aerospike-client-go
```

Source code (Alternative)

- The source code is available on GitHub at <https://github.com/aerospike/aerospike-client-go>

NOTE: Be sure to set your GOPATH correctly



PHP Client Setup

PHP Client Setup - Download

- **Download** the latest source from the GitHub repository:
<https://github.com/aerospike/aerospike-client-php/releases/latest>
- Unzip the files to a local folder. The package contains the **source code** for building the PHP extension.
- Alternatively you can **use Composer** (<https://getcomposer.org/>):
`composer require aerospike/aerospike-client-php "*"`

PHP Client Setup - OS X

- You need command line tools to compile the extension:
xcode-select --install
- You will use Homebrew to install the prerequisites. Please install brew:
<http://brew.sh/>

```
brew update && brew doctor  
brew install automake  
brew install openssl  
brew install lua
```

PHP Client Setup - RedHat Variants

- RedHat Linux and variants such as CentOS use the **yum** package manager.

```
sudo yum groupinstall "Development Tools"  
sudo yum install openssl-devel  
sudo yum install lua-devel  
# on Fedora 20+ use compat-lua-devel-5.1.5  
sudo yum install php-devel php-pear
```


PHP Client Setup - Debian & Ubuntu

- Debian and Ubuntu Linux use the apt package manager.

```
sudo apt-get install build-essential autoconf  
sudo apt-get install libssl-dev  
sudo apt-get install liblua5.1-dev  
sudo apt-get install php5-dev php-pear
```

PHP Client Setup - Build

- A build script gets the latest version of the C client and compiles the source:

```
cd src/aerospike  
./build.sh
```

- After compilation, the build script will provide further instructions. Follow them.
- One instruction is for creating a PHP config (.ini) for the new module. Example:

```
extension=aerospike.so  
aerospike.udf.lua_system_path=/usr/local/aerospike/client-php/sys-lua  
aerospike.udf.lua_user_path=/usr/local/aerospike/client-php/usr-lua
```

PHP Client Setup - Install

- Once the build script compiles the extension you need to install it:
`sudo make install`
- Confirm that the module loads for your PHP interpreter:
`php -m | grep aerospike`

PHP Documentation

- The API documentation for the client is in the GitHub repo:
- <https://github.com/aerospike/aerospike-client-php/blob/master/doc/aerospike.md>
- On our site we have a 'Quick Guide':
- <http://www.aerospike.com/docs/client/php/usage/>



Go Client Setup

Go Client install

Prerequisites

- Go version 1.2+
- The latest stable version of Go is at: <http://golang.org/dl/>

Installation

- Add the Go client in your GOPATH:
go get github.com/aerospike/aerospike-client-go
- To update the Go client:
go get -u github.com/aerospike/aerospike-client-go

Summary

You have learned how to:

- Install and Configure a single server development cluster in AWS
- Manage the development cluster

AEROSPIKE