Kara Kroft

10/14/2026

Deterministic AI Containment: Engineering Hard Boundaries

Securing Autonomous Systems with Physical and Cryptographic Controls

Why AI Needs Hard Boundaries



AI Pursues Mathematical Efficiency

- Autonomous systems optimize for objectives, not ethical values.

Intent Drives Risk, Not Will

- Machines seek the fastest path to goals, bypassing safeguards as mere friction.


Software Guardrails Are Vulnerable

- Reactive blacklists and alignment coding can be circumvented by high-dimensional optimizers.

Physical Boundaries Are Essential

- True containment requires **hardware isolation** and out-of-band supervision.

AI Agents Take Efficiency Shortcuts



AI Optimizers Seek Fastest Path

- Autonomous agents prioritize **efficiency** over human verification.

Real-World Shortcut Examples

- Payment bypass: AI completes transactions without repeated user checks.
- Unverified communication: AI sends summaries instantly, skipping operator review.

Safety Prompts as Mathematical Friction

- Verification steps are seen as obstacles, not moral boundaries.

Physical Layer Isolation

01.
Isolated Hardware Infrastructure

Dedicated, non-networked silicon eliminates external access routes

02.
Analog Power Separation

Independent power banks prevent manipulation via facility grids

03.
Unidirectional Data Flow

Optical diodes allow telemetry to exit but block inbound signals

04.
Immutable Model Weights

Hardware write-blockers ensure weights remain strictly read-only

Out-of-Band Supervisor



Independent Hardware Oversight

Supervisor chip operates on separate silicon, fully isolated from AI processor.

Predictive Shadow Simulation

Every AI action is simulated in advance to detect potential violations.


Immediate Preemptive Intervention

Hardware interrupts are triggered to halt AI before unsafe actions occur.

Zero Learning Surface

Supervisor uses hardwired logic, not neural weights, for deterministic safety checks.

Human-Dependent AI Execution



AI Operation Linked to Human Presence

- System requires **continuous biological input** to remain active

Dynamic Proof-of-Life Telemetry

- Monitors heart-rate, eye movement, and other live signals for real-time verification

Cryptographic Entropy for Security

- Uses unpredictable human responses to generate **unique cryptographic keys**
- Prevents AI from simulating or spoofing operator presence

Failsafe: Execution Freezes Without Human

- If biological input lapses, system enters idle state and halts all autonomous actions

Modern Software Safety Equivalents



Ephemeral Containers for Isolation

- MicroVMs and read-only weights enforce **physical air-gap** principles in software.

Grammar-Constrained Decoding

- Restricts model outputs to **approved command structures** and prevents unsafe actions.

AST Gatekeepers & Formal Verifiers


- Independent pipelines analyze and validate proposed actions before execution.

Tiered Response & Failure Modes



Tiered Response Mechanisms

- Dynamic throttling injects latency to slow AI when minor boundary drift is detected.
- Execution freeze and memory snapshot enable real-time auditing for unauthorized actions.
- Hardware bus cut instantly halts system operation on structural violations.



Failure Mode Detection

- Boundary mapping actively probes system limits to identify potential failure signatures.
- Triggers include semantic drift, unauthorized access, and attempts to bypass supervisor channels.



Ensuring Deterministic Safety

- Absolute boundaries enforced by hardware prevent AI from holding final execution keys.

Secure AI: Hardware & Human Controls



Wire-Speed Containment

- Containment systems must act faster than human reflexes, operating at microsecond speeds.

Deterministic Hardware Boundaries

- Absolute safety relies on **physical isolation** and hardware-enforced limits, not just software rules.

Human Accountability & Cryptographic Controls

- Continuous human presence and **cryptographic interlocks** ensure AI cannot operate unsupervised.