

吴老师，骆学长和孙学长好，以下是我的作业。

上传课后作业

-教材

P. 185 题 5(编程题，学生成绩管理系统)

要求：1) 结构体成员包括姓名、学号和至少 3 门自定课程；

- 2) 能够录入学生信息；
- 3) 求取某一门指定课程的平均分和某一个学生的总分；
- 4) 按学号或姓名查找学生的信息并显示；
- 5) 按指定的若干门课程由高到低显示；
- 6) 按总分由高到低显示学生信息。

测试样例：信息具体内容自定，作业报告中的截图需完成反映以上各功能，并进行简要的文字对应说明，遗漏或错误不得分。

P.186 题 6(编程题，扑克牌游戏)

要求：1) 按题设要求，建立扑克牌的结构类型描述；

2) 随机洗牌函数

3) n 人玩牌的发牌程序 $n = 3, n = 4$ 。

测试样例：作业报告中的截图需完成反映以上各功能。

[Chi-Shan0707/Homework-in-CS10004-Programming-by-yhchi](#)

代码仓库 ↑

1.

先给了一些小的有针对性的输出测试（课程数 <3 ,仅作为 部分测试（也只有这种小测试可以截图）完整的输出内容在最后

```
-----
OP :1
? new students1
```

```
1 Alice 98
```

```
-----
OP :1
? new students2
```

```
2 Jack 90
5 Joe 98
```

```
-----
OP :5
How many courses? Which?
1
0
*****
```

```
-----
1 - Alice :      98.00      98.00
```

```
-----
5 - Joe :       98.00      98.00
```

```
-----
2 - Jack :      90.00      90.00
```

```
-----
*****
```

New students 后那个数字是要新增多少个学生

最后一列是总分

这里是展示基本的输入输出

```
2
```

```
-----
OP :1
? new students4
```

```
001 ZLC 28 21
002 zzc 99 97
009 dbq 3 12
022 Zlc 88 22
```

```
-----
OP :4
Name or ID ?
1
So :zzc
```

```
-----
002 - zzc :      99.00   97.00      196.00
```

展示了初步 的搜索

之前是输入姓名

这里输入学号

并且针对第 1 门课进行排序（我的课程编号从 0 开始）

StudentInfoManagement

```
-----
OP :4
Name or ID ?
2
So :022
-----
022 - Zlc :      88.00   22.00      110.00
-----

-----
OP :5
How many courses? Which?
1
1
*****
-----
002 - zzc :      99.00   97.00     196.00
-----
-----
022 - Zlc :      88.00   22.00     110.00
-----
-----
001 - ZLC :      28.00   21.00      49.00
-----
-----
009 - dbq :       3.00   12.00      15.00
-----
*****

-----
OP : 
```

```
#include<stdio.h>
#include<string.h>
#include<stdlib.h>

#define MAX_NUM_OF_ALL 50
//once-and-for-all
struct Student
{
    char id[MAX_NUM_OF_ALL];
    char name[MAX_NUM_OF_ALL];
    float score[MAX_NUM_OF_ALL];
    float total;
};
typedef struct Student Student;
void Input_StudentInfo(Student s[],int *pn,const int CourseNum)
{
    int n;
    printf("? new students");
    scanf("%d",&n);
    printf("\n");
    for(int i=(*pn);i<n+(*pn);i++)
```

```

{
    s[i].total=0.0f;
    scanf("%s",s[i].id);
    scanf("%s",s[i].name);
    for(int j=0;j<CourseNum;++j)
    {
        scanf("%f",&s[i].score[j]);
        s[i].total+=s[i].score[j];
    }
}

```

//传入指针 进行更改

```

(*pn)+=n;

```

```

void print(const Student *p,const int CourseNum)
{
    printf("-----\n");
    printf("%s - %s :",p->id,p->name);
    for(int j=0;j<CourseNum;j++) printf("\t %.2f",p->score[j]);
    printf("          %.2f\n",p->total);
    printf("-----\n");
}

```

```

void Query_CourseInfo(const Student s[],const int n,const int CourseNum)
{
    int c;
    printf("Course ?\n");
    scanf("%d",&c);
    float sum=0.0f;
    for(int i=0;i<n;i++)sum+=s[i].score[c];
    printf("sum=%.2f avg=%.2f\n",sum,sum/n);
}

```

```

void Query_StudentInfo(const Student s[],const int n,const int CourseNum)
{
    printf("The kth input?\n");
    int k;scanf("%d",&k);
    --k;
    print(&s[k],CourseNum);
}

```

```

void Find_Student(const Student s[],int n,int CourseNum)
{

```

```

    int mode;
    char key[MAX_NUM_OF_ALL];

```

```

    printf("Name or ID ?\n");
    scanf("%d",&mode);
    printf("So :");
    scanf("%s",key);
// 查学号 or 查姓名
    for(int i=0;i<n;i++)
    {
        if((mode==2&&strcmp(s[i].id,key)==0)||
            (mode==1&&strcmp(s[i].name,key)==0))
        {
            // 字符串比较函数
            print(&s[i], CourseNum);
            return;
        }
    }
    printf("not found\n");
}

```

```

void swap_student(Student *a,Student *b)
{
    Student t=*a;
    *a=*b;
    *b=t;
}

```

```

void Print_StudentInfo(const Student s[],int n,int CourseNum)
{
    printf("*****\n");
    for(int i=0;i<n;i++)print(&s[i],CourseNum);
    printf("*****\n");
}

```

```

void Maintain_StudentInfo(Student s[],int n)
{
// 如果要按照所有学科排名的话，就手动输入所有学科叭
    int k;
    int CourseId[MAX_NUM_OF_ALL];
    printf("How many courses? Which?\n");
    scanf("%d",&k);

    for(int i=0;i<k;i++)
    {
        scanf("%d",&CourseId[i]);
    }
    for(int i=0;i<n-1;i++)
    {
        for(int j=0;j<n-1-i;j++)

```

```

{
    float sumStudentI=0.0f,sumStudentJ=0.0f;
    //暴力查看交换条件
    for(int t=0;t<k;t++)
    {
        sumStudentI+=s[j].score[CourseId[t]];

        sumStudentJ+=s[j+1].score[CourseId[t]];
    }
    if(sumStudentI<sumStudentJ)swap_student(&s[j],&s[j+1]);
}
}
}

```

```

int main()
{
    Student s[MAX_NUM_OF_ALL];
    int n=0;
    int CourseNum;
    int op;
    scanf("%d",&CourseNum);
    while(1)
    {
        printf("\n-----\nOP :");
        scanf("%d",&op);
        switch(op)
        {
            case 0:
                return 0;

            case 1:
                Input_StudentInfo(s,&n,CourseNum);
                break;

            case 2:
                Query_CourseInfo(s, n,CourseNum);
                break;

            case 3:
                Query_StudentInfo(s,n,CourseNum);
                break;

            case 4:
                Find_Student(s,n,CourseNum);
                break;

            case 5:
                Maintain_StudentInfo(s,n);
                Print_StudentInfo(s,n,CourseNum);
                break;

            case 6:
                Print_StudentInfo(s,n,CourseNum);
                break;

            default:

```

}

```
pack > C StudentInfoManagement.c > Input_StudentInfo(Student [], int *, const int)
```

⏏ (a) 3 ⏏ C/C++ Primer-Deluxe, Second Edition (CS10904 Programming) ⏏ 未予提交 行 21 列 25 空格 4 LIT5

```
pack > C StudentInfoManagement.c > Input_StudentInfo(Student [], int *, const int)
void Input_StudentInfo(Student s[], int *pn, const int CourseNum)
{

}

void print(const Student *p, const int CourseNum)
{
    printf("-----\n");
    printf("%s - %s :", p->id, p->name);
    for(int j=0; j<CourseNum; j++) printf("\t %.2f", p->score[j]);
    printf("          %.2f\n", p->total);
    printf("-----\n");
}

void Query_CourseInfo(const Student s[], const int n, const int CourseNum)
{
    int c;
    printf("Course ?\n");
    scanf("%d", &c);
    float sum=0.0f;
    for(int i=0; i<n; i++) sum+=s[i].score[c];
    printf("sum=%.2f avg=%.2f\n", sum, sum/n);
}

void Query_StudentInfo(const Student s[], const int n, const int CourseNum)
{
    printf("The kth input?\n");
    int k; scanf("%d", &k);
    --k;
    print(&s[k], CourseNum);
}

1
```


_pack 7 StudentInfoManagement.c 8 Input_StudentInfo(Student s[],int n,const int)

```
void Find_Student(const Student s[],int n,int CourseNum)
{
    int mode;
    char key[MAX_NUM_OF_ALL];
    printf("Name or ID ?\n");
    scanf("%d",&mode);
    printf("So :");
    scanf("%s",key);
    //查学号or查姓名
    for(int i=0;i<n;i++)
    {
        if((mode==2&&strcmp(s[i].id,key)==0)||
            (mode==1&&strcmp(s[i].name,key)==0))
        {
            //字符串比较函数
            print(&s[i], CourseNum);
            return;
        }
    }
    printf("not found\n");
}
```

```
void swap_student(Student *a,Student *b)
{
    Student t=*a;
    *a=*b;
    *b=t;
}
```

pack > C StudentInfoManagement.c > Input_StudentInfo(Student [], int *, const int)

```
void Print_StudentInfo(const Student s[],int n,int CourseNum)
{
    for(int i=0;i<n;i++)printf("%s",s[i],CourseNum);
    printf("*****\n");
}
```



```
void Maintain_StudentInfo(Student s[],int n)
```

```
{
    //如果要按照所有学科排名的话，就手动输入所有学科叭
    int k;
    int CourseId[MAX_NUM_OF_ALL];
    printf("How many courses? Which?\n");
    scanf("%d",&k);

    for(int i=0;i<k;i++)
    {
        scanf("%d",&CourseId[i]);
    }
    for(int i=0;i<n-1;i++)
    {
        for(int j=0;j<n-1-i;j++)
        {
            float sumStudentI=0.0f,sumStudentJ=0.0f;
            //暴力查看交换条件
            for(int t=0;t<k;t++)
            {
                sumStudentI+=s[j].score[CourseId[t]];
                sumStudentJ+=s[j+1].score[CourseId[t]];
            }
            if(sumStudentI<sumStudentJ)swap_student(&s[j],&s[j+1]);
        }
    }
}
```

back > C: StudentInfoManagement.c > Input_StudentInfo(Student [], int *, const int)

```
int main()
{
    Student s[100];
    int n=0;
    int CourseNum;
    int op;
    scanf("%d",&CourseNum);
    while(1)
    {
        printf("\n-----\nop :");
        scanf("%d",&op);
        switch(op)
        {
            case 0:
                return 0;
            case 1:
                Input_StudentInfo(s,&n,CourseNum);
                break;
            case 2:
                Query_CourseInfo(s, n,CourseNum);
                break;
            case 3:
                Query_StudentInfo(s,n,CourseNum);
                break;
            case 4:
                Find_Student(s,n,CourseNum);
                break;
            case 5:
                Maintain_StudentInfo(s,n);
                Print_StudentInfo(s,n,CourseNum);
                break;
            case 6:
                Print_StudentInfo(s,n,CourseNum);
                break;
        }
    }
}
```

一个完整且系统的例子

注

3 表示课程数量

Newstudent 后输入了 6 表示输入学生数

```
case 0:
    return 0;
case 1:
    Input_StudentInfo(s,&n,CourseNum);
    break;
case 2:
    Query_CourseInfo(s, n,CourseNum);
    break;
case 3:
    Query_StudentInfo(s,n,CourseNum);
    break;
case 4:
    Find_Student(s,n,CourseNum);
    break;
case 5:
    Maintain_StudentInfo(s,n);
    Print_StudentInfo(s,n,CourseNum);
    break;
```

3

OP :1

? new students6

003 jack 100 99 97

023 Pete 88 87 100

034 Sun 90 90 90

100 wiki 100 22 9

101 jason 100 100 100

102 ice 96 78 34

OP :2

Course ?

2

sum=430.00 avg=71.67

OP :3

The kth input?

5

101 - jason :	100.00	100.00	100.00	300.00
---------------	--------	--------	--------	--------

OP :4

Name or ID ?

1

So :jason

101 - jason :	100.00	100.00	100.00	300.00
---------------	--------	--------	--------	--------

OP :4

Name or ID ?

2

So :023

023 - Pete :	88.00	87.00	100.00	275.00
--------------	-------	-------	--------	--------

OP :5

How many courses? Which?

3

0 1 2

101 - jason : 100.00 100.00 100.00 300.00

003 - jack : 100.00 99.00 97.00 296.00

023 - Pete : 88.00 87.00 100.00 275.00

034 - Sun : 90.00 90.00 90.00 270.00

102 - ice : 96.00 78.00 34.00 208.00

100 - wiki : 100.00 22.00 9.00 131.00

OP :5

How many courses? Which?

2

2 1

101 - jason : 100.00 100.00 100.00 300.00

003 - jack : 100.00 99.00 97.00 296.00

023 - Pete : 88.00 87.00 100.00 275.00

034 - Sun : 90.00 90.00 90.00 270.00

102 - ice : 96.00 78.00 34.00 208.00

100 - wiki : 100.00 22.00 9.00 131.00

OP :5

How many courses? Which?

2

0 1

101 - jason :	100.00	100.00	100.00	300.00

003 - jack :	100.00	99.00	97.00	296.00

034 - Sun :	90.00	90.00	90.00	270.00

023 - Pete :	88.00	87.00	100.00	275.00

102 - ice :	96.00	78.00	34.00	208.00

100 - wiki :	100.00	22.00	9.00	131.00

OP :6

101 - jason :	100.00	100.00	100.00	300.00

003 - jack :	100.00	99.00	97.00	296.00

034 - Sun :	90.00	90.00	90.00	270.00

023 - Pete :	88.00	87.00	100.00	275.00

102 - ice :	96.00	78.00	34.00	208.00

100 - wiki :	100.00	22.00	9.00	131.00

注 这里输入 2 表示关键课程数量
再输入课程编号（从 0 开始）

3 人每人 17 张

```
输入玩家人数( 3 or 4 ): 3
#####
```

```
Player 1 :
  Spades-A
Diamonds-6
Clubs-2
Diamonds-A
Spades-4
Clubs-K
Spades-7
Hearts-A
Diamonds-10
Spades-3
Spades-J
Spades-5
Hearts-7
Hearts-6
Clubs-7
Clubs-J
Clubs-6
```

```
#####
```

```
#####
```

```
Player 2 :
  Diamonds-3
Clubs-Q
Spades-6
Diamonds-8
Clubs-10
Clubs-4
Clubs-9
Hearts-J
Spades-10
```


Diamonds-Q
Clubs-8
Diamonds-5
Hearts-8
Hearts-Q
Hearts-3
Clubs-5

#####

#####

Player 3 :

Hearts-5
Spades-K
Diamonds-7
Diamonds-J
Hearts-K
Diamonds-2
Diamonds-4
Diamonds-9
Spades-2
Diamonds-K
Spades-Q
Hearts-9
Spades-9
Clubs-3
Hearts-2
Hearts-10
Spades-8

#####

Comparing two cards:

Card 1: Spades-A

Card 2: Diamonds-6

Card 1 is smaller than Card 2

输入玩家人数(3 or 4): 4

#####

Player 1 :

Hearts-A

Spades-7

Hearts-K

Diamonds-10

Spades-3

Diamonds-6

Diamonds-A

Spades-Q

Hearts-J

Clubs-K

Hearts-5

Clubs-9

Spades-K

#####

#####

Player 2 :

Diamonds-J

Clubs-10

Diamonds-8

Hearts-6

Hearts-3

Clubs-3

Diamonds-Q

Spades-10

Diamonds-9

Hearts-9

Hearts-4

Clubs-2

Clubs-5

#####

#####

Player 3 :

Hearts-Q

Diamonds-3

Hearts-8

Hearts-2

Spades-5

Hearts-7

Clubs-7

Clubs-A

Spades-8

Hearts-10

Clubs-6

Spades-9

Spades-2

#####

#####

Player 4 :

Clubs-J

Spades-6

Clubs-4

Spades-4

Diamonds-K

Spades-J

Diamonds-4

Clubs-8

Diamonds-2

Diamonds-7

Spades-A

Clubs-Q

Diamonds-5

#####

Comparing two cards:

Card 1: Hearts-A

Card 2: Spades-7

Card 1 is smaller than Card 2

de_pack > C Pokers.c > print_PlayerHand(const Card [], int, int)

```
1  #include<stdio.h>
2  #include<stdlib.h>
3  #include<time.h>
4
5  #define DECK_SIZE 52
6  #define MAX_PLAYERS_NUM 4
7  #define MAX_HAND_CARDS_NUM 52
8
9  struct Card
10 {
11     int suit;
12     int face;
13 };
14 typedef struct Card Card;
15 //不然 类型名就是 struct Card 了
16 const char *Suits={"Clubs","Diamonds","Hearts","Spades"};
17 const char *Faces={"","A","2","3","4","5","6","7","8","9","10","J","Q","K"};
18
19 void init(Card deck[])
20 {
21     for(int i=0;i<DECK_SIZE;++i)
22     {
23         deck[i].suit=i/13;
24         deck[i].face=i%13+1;
25     }
26
27 void swap_Card(Card *a,Card *b)
28 {
29     Card t=*a;
30     *a=*b;
31     *b=t;
32 }
```

```

le_pack > C Pokers.c > print_PlayerHand(const Card [], int, int)
8 void init(Card deck[])_
5 }
6 void swap_Card(Card *a, Card *b)
7 {
8     Card t=*a;
9     *a=*b;
10    *b=t;
11 }
12 void shuffle_Card(Card deck[],int n)
13 {
14     for(int i=n-1;i>0;i--)
15 // 正宗洗牌算法，从后往前遍历，只考虑和之前的交换
16     {
17         int j=rand()%(i+1);
18         swap_Card(&deck[i],&deck[j]);
19     }
20 }
21 void print_CardInfo(const Card *c)
22 {
23     printf("%s-%s\n",Suits[c->suit],Faces[c->face]);
24 }
25 void deal(const Card deck[],int playerNum,int handCardNum,
26           Card hands[][MAX_HAND_CARDS_NUM])
27 {
28     int CardId=0;
29     for(int person=0;person<playerNum;person++)

```

```

void print_CardInfo(const Card *c)
{
    printf("%s-%s\n",Suits[c->suit],Faces[c->face]);
}

void deal(const Card deck[],int playerNum,int handCardNum,
          Card hands[][MAX_HAND_CARDS_NUM])
{
    int CardId=0;

    for(int person=0;person<playerNum;person++)
    {
        for(int handCardid=0;handCardid<handCardNum;++handCardid)
        {
            hands[person][handCardid]=deck[CardId++];
        }
    }
}

int compare_Card(Card a,Card b)
{
    return a.face-b.face;
}

void print_PlayerHand(const Card hand[],int handCardNum,int playerId)
{
    printf("#####\n\nPlayer %d :\n ",playerId+1);
    for(int i=0;i<handCardNum;i++)

```

通过计数器去取洗好的牌堆里的牌

```

48     Card hands[][MAX_HAND_CARDS_NUM])
52     for(int person=0;person<playerNum;person++)
54         for(int handCardid=0;handCardid<handCardNum;++handCardid)
58     }
59 }
60
61 int compare_Card(Card a,Card b)
62 {
63     return a.face-b.face;
64 }
65
66 void print_PlayerHand(const Card hand[],int handCardNum,int playerId)
67 {
68     printf("#####\n\nPlayer %d :\n ",playerId+1);
69     for(int i=0;i<handCardNum;i++)
70     {
71         print_CardInfo(&hand[i]);
72     }
73     printf("\n");
74     printf("#####\n\n");
75 }
76
77 int main()
78 {
79     Card deck[DECK_SIZE];
80     Card hands[MAX_PLAYERS_NUM][MAX_HAND_CARDS_NUM];
81     int cmp_res;
82     int playerNum,handCardNum;
83     printf("输入玩家人数( 3 or 4 ): ");
84     scanf("%d",&playerNum);

```

```

deal(deck,playerNum,handCardNum,hands);

for(int p=0;p<playerNum;p++)
{
    print_PlayerHand(hands[p],handCardNum,p);
}

//cmp
printf("Comparing two cards:\n");
printf("Card 1: ");
print_CardInfo(&deck[0]);
printf("Card 2: ");
print_CardInfo(&deck[1]);
cmp_res=compare_Card(deck[0],deck[1]);
if(cmp_res>0)
{
    printf("Card 1 is bigger than Card 2\n");
}
else if(cmp_res<0)
{
    printf("Card 1 is smaller than Card 2\n");
}
else
{
    printf("Card 1 is equal to Card 2\n");
}
return 0;
}

```

这里稍微选两张比个大小