

MAPMANAGER

Map Manager

Table

com.ibm.tivoli.maximo.map.mapman.app.MapManagerSet

UniqueID: MAPMANAGERID

Primary key: MAPNAME

LOGICAL RELATIONSHIPS

FOREIGN KEYS INTO MAPMANAGER

Object(Parent Keys)	Target Object(Target Keys)	Rel Number	Description
MAPMANAGER(MAPNAME)	MAPTIP(MAPNAME)	1 to many	Map Manager
MAPMANAGER(MAPNAME)	MAPTIPMENU(MAPNAME)	1 to many	Map Manager

MAPMANAGER FOREIGN KEYS

Object(Parent Keys)	Target Object(Target Keys)	Rel Number	Description
LANGUAGE(MAXLANGCODE)	MAPMANAGER(LANGCODE)	1 to many	Record Language

COLUMNS

Attribute	Modifier	Title	Remarks	SameAsAttrib	SameAsObject
MAPNAME	Required	Map	The name of the map configuration.		
DESCRIPTION		Description	The description of the map.		
ACTIVE		Enable map	Enables the map for the sites that you specified.		
MAPPROVIDER	Required	Map provider name	Map provider name		
LENGTHUNIT	Required	Length and Distance Unit	Length and Distance Unit		
GMAPSLICENSE		Google client ID	To access the Google map service, enter the Google client ID.		
GMAPSHTTPS		Enable HTTPS	Enables HTTPS support for Google.		

Attribute	Modifier	Title	Remarks	SameAsAttrib	SameAsObject
BMAPSLICENSE		Bing Maps key	To access the Bing Maps map service, enter the Bing Maps license key.		
BMAPSHTTPS		Enable HTTPS	Enables HTTPS support for Bing Maps.		
SPATIALGEOCODE	Required	Geocode service URL	The URL of the ESRI geocode service that the map uses to find a location that is based on an address or point. Geocode services run on external geographic information system (GIS) servers. The default values can change if the external GIS service is modified.		
SPATIALROUTE	Required	Route service URL	The URL of the ESRI route service that is used to create routes between two points on the map. Route services run on external geographic information system (GIS) servers. The default values can change if the external GIS service is modified.		
MAPMANAGERID	Required	Unique Id	Unique Id		
HASLD	Required	Has Long Description	Boolean flag to indicate if there is any long description for this record		

Attribute	Modifier	Title	Remarks	SameAsAttrib	SameAsObject
DESCRIPTION_LONGDESCRIPTION	Nonperistent	Description Long description	Long Description for Description		
LANGCODE	Required	Language Code	Language Code	MAXLANGCODE	<u>LANGUAGE</u>
GMAPSDISTANCEMATRIX	Required	Distance matrix service URL	The URL of the Google Maps Distance Matrix service that is used to find the travel times between combinations of a set of origins and a set of destinations. Distance Matrix services run on external geographic information system (GIS) servers. The default values can change if the external GIS service is modified.		
BMAPSRROUTE	Required	Bing Maps route service URL	The URL of the Bing Maps route service that is used to create routes between two points on the map. Route services run on external geographic information system (GIS) servers. The default values can change if the external GIS service is modified.		

Attribute	Modifier	Title	Remarks	SameAsAttrib	SameAsObject
OPTCLEANUP		Optimization Cleanup	Amount of days before cached travel time data needs to be deleted from the optimization matrix table.		
BMAPSDISTANCEMATRIX	Required	Distance matrix service URL	The URL of the Bing Maps Distance Matrix service that is used to find the travel times between combinations of a set of origins and a set of destinations. Distance Matrix services run on external geographic information system (GIS) servers. The default values can change if the external GIS service is modified.		
BMAPSGEOCODE	Required	Geocode service URL	The URL of the Bing geocode service that the map uses to find a location that is based on an address or point. Geocode services run on external geographic information system (GIS) servers. The default values can change if the external GIS service is modified.		

Attribute	Modifier	Title	Remarks	SameAsAttrib	SameAsObject
SPATIALDISTANCEMATRIX	Required	Distance matrix service URL	The URL of the ESRI Maps Distance Matrix service that is used to find the travel times between combinations of a set of origins and a set of destinations. Distance Matrix services run on external geographic information system (GIS) servers. The default values can change if the external GIS service is modified.		
SPATIALUSERNAME		ESRI user name	To access ESRI Maps paid services, enter the ESRI user name.		
SPATIALPASSWORD		ESRI password	To access ESRI Maps paid services, enter the ESRI password.		

MAXIMO RELATIONSHIPS

MAXIMO OUTGOING RELATIONSHIPS

Name	Target	Remarks	Where Clause	Cardinality
MAPSITES	<u>MAPSITES</u>	Relationship to Map Sites table	mapname=:mapname	null
MAPTIP	<u>MAPTIP</u>	Relationship from mapmanager to maptipobjects	mapname=:mapname	null
MAPTIPDEFAULTS	<u>MAPTIPDEFAULTS</u>	Find all enabled Map Tip defaults.	enabled=:yes	null