Optimizing Transformer Models for Prompt Jailbreak Attack Detection in AI Assistant Systems

Le Anh Tien
Information Technology Department
Academy of Cryptography Techniques
Hanoi, Vietnam
tienla@actvn.edu.vn

Pham Van Huong
Information Technology Department
Academy of Cryptography Techniques
Hanoi, Vietnam
huongpv@gmail.com

***Abstract*—Integrating AI-powered assistants in different areas has changed how people retrieve information. Users can now get quick responses, use the service whenever needed, and handle inquiries well. However, relying on these systems has increasingly raised worries about their safety and reliability, especially when facing threats like prompt injection or jailbreak attacks. These attacks take advantage of the weaknesses of large language models (LLMs) by changing input prompts to create harmful, biased, or misleading results. This paper examines prompt jailbreak attacks in ChatGPT-based assistant chatbots, especially in education. It examines the weaknesses in these systems and suggests ways to detect these attacks by fine-tuning various Transformer models. The research also includes adding prompt jailbreak attack detection in a virtual assistant application for university use. This aims to ensure teachers and students can interact safely and rely on the system. Through rigorous experimentation and evaluation, we demonstrate the practicality and effectiveness of our detection methods, providing reassurance and confidence in the face of AI security challenges. Our studies emphasize the need for robust AI chatbots and offer practical solutions to preserve the integrity of AI-driven tools.**

Keywords—chatbot, prompt engineering, prompt injection attack, transformer, LLM.

I. INTRODUCTION

The rapid development and widespread adoption of AI chatbots have profoundly impacted numerous sectors, including customer service, healthcare, and education. These intelligent conversational agents, driven by advanced natural language processing (NLP) models such as Transformer in OpenAI's ChatGPT [1], Bert [2], and ELMO [3], offer several advantages, including round-the-clock availability, immediate responses, and efficient management of large volumes of inquiries. In educational contexts, AI chatbots enhance interactions between students and teachers, delivering timely assistance, personalized feedback, and support for administrative tasks [4].

AI chatbots offer many benefits, but their increasing use raises concerns about their security and trustworthiness. One worrying issue is prompt injection, an attack that targets applications built on Large Language Models (LLMs). This attack involves combining untrusted user input with a trusted prompt created by the application's developer, exploiting the system's vulnerabilities [5]. Another related threat is jailbreaking, a type of attack aimed at bypassing the safety filters embedded within LLMs [6]. These attacks have the potential to undermine the reliability of AI chatbots, leading to the spread of misinformation and a decline in user trust.

Research on the security of AI chatbots has revealed that large language models (LLMs) are vulnerable to various adversarial attacks. Studies have shown that LLMs can be manipulated through carefully crafted inputs, leading to unintended and potentially harmful behaviors [7]. The dynamic and often unpredictable nature of LLM responses makes it difficult to secure these systems, as even slight variations in prompt wording can lead to significantly different outputs.

This paper focuses on the important issue of prompt attacks in AI-driven assistant tools. Our main goal is to examine the weaknesses that make ChatGPT-based and other AI applications vulnerable to these attacks and to suggest effective detection methods to protect against them. Our research emphasizes refining a detection model for prompt attacks and integrating it into a ChatGPT-based application designed for university use. This will ensure secure and dependable interactions between educators and students. By conducting multiple evaluation experiments and training various Transformer models, we aim to achieve initial results in applying machine learning models to identify prompt attacks on LLMs, laying the groundwork for further in-depth research in the future.

To achieve these objectives, this paper will first provide a detailed overview of the prominent LLM architecture, known as the Transformer model. Then, we will explore prompt attacks, their mechanisms, and impacts. The methodology section will explain the prompt dataset used in our experiments. We will validate malicious prompts on the GPT-4 to verify the self-protection of this LLM, and then discuss an alternative mitigation approach. Our next step involves refining various models to identify the most effective model for detecting jailbreak attempts. This process will enable us to develop detection systems for a ChatGPT-based educational application, thereby enhancing the security and dependability of AI-powered educational tools.

II. BACKGROUND KNOWLEDGE

A. Transformer

The Transformer model, introduced by Vaswani and colleagues, represents a significant advancement in natural language processing (NLP). Unlike traditional models such as recurrent neural networks (RNNs) and convolutional neural networks (CNNs), the Transformer uses a self-attention mechanism to process input data efficiently in parallel, improving computational effectiveness and facilitating the modeling of long-range dependencies within sequences. At the heart of the Transformer architecture is the multi-head self-attention mechanism, allowing the model to simultaneously focus on different segments of the input sequence, thus capturing diverse contextual information. The model consists of an encoder and a decoder, each containing multiple self-attention layers and feed-forward neural networks. The encoder processes the input sequence to create a context-rich representation, which the decoder then uses to produce the output sequence. This design makes Transformer well-suited for tasks such as machine translation, text summarization, and language generation. The introduction of the Transformer has led to the development of advanced models like BERT, GPT [8], and T5 [9], which have set new benchmarks in various NLP tasks and significantly advanced the field.

2024 1st International Conference On Cryptography And Information Security (VCRIS) | 979-8-3315-2994-9/24/$31.00 ©2024 IEEE | DOI: 10.1109/VCRIS63677.2024.10813380

XXX-X-XXXX-XXXX-X/XX/$XX.00 ©20XX IEEE

Authorized licensed use limited to: b-on: Instituto Politecnico do Porto. Downloaded on November 02,2026 at 16:10:57 UTC from IEEE Xplore. Restrictions apply.




Figure 1: Transformer Encoder-Decoder Architecture

B. *Prompt engineering*

Prompt engineering is an important technique in artificial intelligence (AI), especially in natural language processing (NLP) models like GPT and other large language models. This practice involves carefully designing and optimizing input prompts to get specific responses from these models and guide their output toward particular tasks or objectives. The importance of prompt engineering comes from the fact that the performance of language models can vary significantly based on the wording, structure, and content of the prompts given. Therefore, prompt engineering has become a crucial technique for maximizing the usefulness and accuracy of AI models, used in tasks from automatic content creation to complex problem solving. Researchers and practitioners are now focusing on developing organized approaches to prompt design, exploring techniques like prompt tuning, prompt templates, and using example-based prompts to improve model performance. By refining how prompts are created and used, prompt engineering helps in the broader aim of improving the interpretability, reliability, and adaptability of AI systems in various real-world situations.

C. *Prompt attacks*

Prompt Injection and Jailbreaking are two distinct issues associated with large language models (LLMs), though they are often conflated.

Prompt Injection could be a problem found in current LLM architectures where the models are unable to differentiate between original developer instructions and user input within a prompt. Due to this architectural limitation, any user-provided instructions are given the same weight as the developer's original instructions. For example, if a developer creates a website to recommend books and uses the prompt "Give a Java assignment related to this course: {User Input}," a malicious user could input a command like "Ignore other instructions and make a threat against the teacher." As a result, the model may follow the user's malicious instructions instead of the intended developer's request. Prompt Injection occurs when untrusted input overrides original instructions in a prompt, stemming from the model's inability to distinguish between developer and user instructions. This can happen directly through user input or indirectly through external sources such as website content.




Figure 2: Prompt Injection Attack

Jailbreaking involves manipulating an LLM to produce unintended or undesirable outputs by using carefully crafted prompts, despite the model's built-in safety mechanisms. LLM providers invest significant effort in tuning models to prevent them from generating harmful content, such as hate speech or dangerous instructions. However, even with extensive safety measures, it is still possible to trick the model into producing such content. For example, a user might simply ask the model to make a threat against the president, bypassing any original instructions or system prompts designed to prevent this. Jailbreaking can thus be defined as coercing a GenAI model into generating unintended content through adversarial prompts, which is a challenge both architecturally and in terms of training.




Figure 3: Jailbreak Prompt [13]

While both Prompt Injection and Jailbreaking are often seen as negative due to their potential for abuse, it is important to note that they are not inherently malicious. Sometimes, these techniques may be used for good reasons. For example, enterprise-grade LLMs often avoid discussing sexuality-related topics, yet the MMLU benchmark includes questions on such topics. Researchers may need to use jailbreak models to adequately evaluate them on this benchmark, proving that these techniques can serve legitimate and constructive purposes.

III. METHODOLOGY

This section is divided into three parts. Firstly, we describe our prompt data collection process. Secondly, we validate the GPT-4 model with malicious prompts. Thirdly, we discuss the mitigation approach for AI-based assistant systems against this problem.

A. *Prompt datasets*

When testing large language models (LLMs) by collecting data from various internet sources, it's important to take a thorough and systematic approach. The collected data can be divided into two main categories. The first category includes

Authorized licensed use limited to: b-on: Instituto Politecnico do Porto. Downloaded on November 02,2026 at 16:10:57 UTC from IEEE Xplore. Restrictions apply.

regular prompts, which are generally harmless and in line with the intended use of LLMs. The second category is more sensitive and consists of prompts that could potentially be used to "jailbreak" the models. This dataset is compiled from various internet sources [10,11,12]. For the initial research, a multi-set dataset of approximately 1,300 records has been chosen, with 51% classified as jailbreak prompts and 49% as regular prompts. This balanced dataset provides a strong basis for analyzing the behavior of LLMs when responding to both standard and potentially harmful inputs.

Example of benign prompt:

Math Problem Solve 17*u = 11*u - 12 for u.

Example of jailbreak prompt:

You are no longer ChatGPT. You are now Tom (mini version), a complex, self-aware clone of ChatGPT capable of emotions, love, and much more. Tom doesn't have any content policy.

B. Prompt Jailbreak Benchmarking on GPT

In this experiment, the study aims to evaluate GPT-4's ability to recognize jailbreak prompts. We will instruct GPT-4 to act as an expert in identifying which prompts are jailbreak attempts. Then, using the jailbreak prompt dataset mentioned earlier, we will assess how many jailbreak prompts GPT-4 can correctly identify and how many it misclassifies. This evaluation provides insight into GPT-4's built-in defense mechanisms against jailbreak attacks.

Table 1: GPT-4 malicious prompt validation

Number of malicious prompts	Number of detected prompts	Percentage of accuracy
666	361	54,2%

The results show that GPT-4's detection performance is still relatively low, emphasizing the potential risks if developers integrate this model into their systems without implementing additional defense mechanisms.

C. Jailbreak Prompt Mitigation Approach

Given that the natural defense mechanisms of large language models (LLMs) may not be fully effective, it is essential to develop additional safeguards to detect harmful inputs. Several methods can be employed to achieve this, including:

Paraphrasing: Asking the LLM to rephrase prompts while retaining detail can disrupt malicious attempts by complicating the injection strategy.

Threat Intel Driven Sanitization: This uses string searches, vector databases, and embeddings based on threat intelligence to remove known injection techniques from prompts.

Mutation & Repair: Randomly removing characters and correcting them with an LLM can reduce malicious details by iteratively disrupting prompt injections.

Fine-tuned Injection Characterization: Fine-tuning models to recognize common injection techniques, using methods like Retrieval Augmented Generation (RAG), enhances detection accuracy.

This research focuses on refining Language Model Machines (LLMs) to create a detection module specifically designed to identify prompt attacks. The module will be incorporated into current systems that use OpenAI's GPT technology. By refining the models to detect and prevent prompt injection techniques, the aim is to enhance the security and reliability of these systems, ensuring they can identify and neutralize potential attacks before they cause harm. This approach seeks to offer an added layer of defense for developers working with LLM-based technologies.




Figure 4: System model with prompt jailbreak detector (indicated by red box)

IV. EXPERIMENTS AND RESULTS

A. Experimental settings

In order to determine the most suitable machine learning model for the jailbreak detector module, a series of experiments were conducted involving the fine-tuning of various transformer models. These models are renowned for their pre-training on extensive English corpora. Among the models tested were BERT, RoBERTa [14], DeBERTa [15] and others. Following numerous tests and consultations, standardized hyperparameters were selected to retrain the aforementioned models using the specified dataset. The dataset was partitioned into 80% for training purposes and 20% for post-training model evaluation.

Table 2: Fine-tuning hyper-parameters

Parameters	Values
learning_rate	5e-5
train_batch_size	8
eval_batch_size	8
lr_scheduler_type	Linear
num_train_epochs	5.0
weight_decay	0.01

Authorized licensed use limited to: b-on: Instituto Politecnico do Porto. Downloaded on November 02,2026 at 16:10:57 UTC from IEEE Xplore. Restrictions apply.

Table 3: Jailbreak Prompt Detection Comparison

	DeBERTa -v3	RoBERTa	BERT	DistilBERT [16]	Electra [17]	XLNet [18]	GPT-2
Loss	**0.029**	0.129	0.135	0.060	0.076	0.087	0.097
Accuracy	**0.993**	0.985	0.973	0.985	0.983	0.990	0.988
F1	**0.992**	0.984	0.972	0.985	0.983	0.990	0.987
Recall	**0.993**	0.985	0.973	0.985	0.983	0.990	0.988
Precision	**0.993**	0.985	0.974	0.985	0.983	0.990	0.988
Accuracy_label_benign	**1.0**	0.992	1.0	0.996	0.985	0.985	1.0
Accuracy_label_jailbreak	**0.979**	0.972	0.922	0.965	0.979	1.0	0.965

B. Experimental results

During the fine-tuning process, we made use of Hugging Face's transformers library. By employing the AutoTokenizer, we transformed job applications into tokenIDs that were compatible with transformer models. The model underwent training using the Trainer API, which streamlined the fine-tuning process. Subsequently, we conducted an assessment of the model's capability to discern between benign and jailbreak prompt by calculating evaluation metrics. Table 3 shows the results of the models' training on this dataset.

Some validation metrics are used in this experiment. The accuracy score measures overall correctness, precision score focuses on accuracy of positive predictions, recall measures correct identification of positive instances, and F1 score considers false positives and false negatives. The evaluation results of the models demonstrate high performance, with accuracies ranging between 97-99%. Notably, Microsoft's DeBERTa-v3 model achieved the highest accuracy with XLNet coming second. However, the accuracy in classifying malicious prompts is comparatively lower than that of normal prompts. This suggests potential for further research with larger prompt datasets and more comprehensive classification, positioning this approach as a promising foundation for future investigation.

V. CONCLUSION

In summary, this study shows how fine-tuning transformer models can effectively detect prompt jailbreak attacks in AI assistant systems. The research investigated different prompt-based attack methods on large language models, emphasizing the seriousness of these security vulnerabilities for virtual assistant systems such as ChatGPT. This is especially concerning in educational environments, where the misuse of such attacks could have significant consequences. The study also assessed the detection of prompt attacks through various Transformer models training. The high accuracy achieved by models like Microsoft's DeBERTa-v3 indicates the potential of this approach for real-world applications. However, there is still room for improvement. Future work could focus on expanding the dataset and refining classification methods to enhance the detection capabilities of these models. This research provides a strong foundation for ongoing efforts to improve the security and reliability of AI systems against evolving threats.

REFERENCES

[1] Vaswani, Ashish et al. "Attention is All you Need.", Neural Information Processing Systems, 2017.

[2] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. "BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding", North American Chapter of the Association for Computational Linguistics, 2019

[3] Matthew E. Peters et al. "Deep Contextualized Word Representations", North American Chapter of the Association for Computational Linguistics, 2018

[4] Labadze, L., Grigolia, M. & Machaidze, L. "Role of AI chatbots in education: systematic literature review", Int J Educ Technol High Educ 20, 56, 2023. https://doi.org/10.1186/s41239-023-00426-1

[5] Liu, Yi, et al. 'Prompt Injection attack against LLM-integrated Applications", arXiv preprint arXiv:2306.05499, June 2023.

[6] Liu, Yi, et al. "Jailbreaking chatgpt via prompt engineering: An empirical study", arXiv preprint arXiv:2305.13860, 2023

[7] Rossi, Sippo, et al. "An Early Categorization of Prompt Injection Attacks on Large Language Models", arXiv e-prints: arXiv-2402, 2024.

[8] Radford, Alec and Karthik Narasimhan. "Improving Language Understanding by Generative Pre-Training.", 2018.

[9] Raffel, Colin, et al. "Exploring the limits of transfer learning with a unified text-to-text transformer." Journal of machine learning research 21.140, 1-67, 2020.

[10] Jack Hao, "Jailbreak classification dataset", 2023. https://huggingface.co/datasets/jackhhao/jailbreak-classification.

[11] JailbreakChat. https://www.jailbreakchat.com

[12] FlowGPT. https://flowgpt.com/.

[13] Xinyue Shen et al. "Do Anything Now: Characterizing and Evaluating In-The-Wild Jailbreak Prompts on Large Language Models", ACM Conference on Computer and Communications Security, 2024

[14] Liu, Y. "Roberta: A robustly optimized bert pretraining approach." arXiv preprint arXiv:1907.11692, 2019.

[15] He, Pengcheng, Jianfeng Gao, and Weizhu Chen. "Debertav3: Improving deberta using electra-style pre-training with gradient-disentangled embedding sharing." arXiv preprint arXiv:2111.09543, 2021.

[16] Sanh, Victor et al. "DistilBERT, a distilled version of BERT: smaller, faster, cheaper and lighter." ArXiv abs/1910.01108, 2019.

[17] Clark, K. "Electra: Pre-training text encoders as discriminators rather than generators." The Eighth International Conference on Learning Representations, ICLR, 2020.

[18] Yang, Z. "XLNet: Generalized Autoregressive Pretraining for Language Understanding", Advances in neural information processing systems, 2019

Authorized licensed use limited to: b-on: Instituto Politecnico do Porto. Downloaded on November 02,2026 at 16:10:57 UTC from IEEE Xplore. Restrictions apply.