



Lab 9: Password Cracking

Lan-Da Van and Chun-Jen Tsai

Department of Computer Science

National Yang Ming Chiao Tung University

Taiwan, R.O.C.


Fall, 2025



Lab 9: Password Cracking

Lab 9

- ◆ In this lab, you will design a circuit to guess a 9-digit password scrambled with the SHA-256 hashing algorithm.
 - The password is composed of 9 decimal digits coded in ASCII codes.
 - The SHA-256 hash code of the password will be given to you.
 - The circuit must crack the password and show it on the LCD module. The time taken to crack the password must also be displayed on the LCD module.
- ◆ The lab file submission deadline is on 11/17 by 6:00pm.






Introduction to Password System

Lab 9

- ◆ The passwords of a login system are stored in a user account file in “encrypted” format.
 - The encryption algorithm for passwords is not reversible.
 - You cannot decrypt the encrypted password and restore the original password.
 - For Linux, the password file is under /etc/shadow.

```
user1:$6$6155bfdd22808014a1e2ccd198IN3zshkbyWjrrYVmrD.cm/xx
7YF2/yNaw4v9xJuYUq2QkskRd6CRKb0.G8m1mFLWCr4v.:17221:0:99999
:7:::
user2:$6$7fbf8a8b90bcb2ba650cc8b0714b739ByB51L23WwxWEE790j
rs8jVPmKcXqzO19yW2NWn2L3LK/ZX/x0j0eHDwp0S1M90:17444:0:99999
:7:::
```

The hash code of user2's password!






Hash Functions for Passwords

Lab 9

- ◆ There are many one-way hash functions for passwords: SHA-256, SHA-512, MD5, and Blowfish.
- ◆ Ideally, two different passwords will be transformed into two different hash codes by the hash functions:






SHA256 Hash Function

Lab 9

- ◆ SHA256 is a popular hash function that converts any file into a 256-bit hash code.
- ◆ There are many applications for SHA256.
 - Data integrity protection
 - Digital signature verification
 - Password hashing
 - SSL handshake (HTTPS)
 - Block chain (Bitcoins)
- ◆ SHA-256 is currently considered a secure hash function that is resistant to collision attacks.






Algorithm of SHA256 (1/2)

Lab 9

- ◆ SHA256 processes a variable-length message into a fixed-length output of 256 bits.
- ◆ The input message is divided into chunks of 256-bit blocks (eight 32-bit words); the message is padded so that its length is divisible by 256.
- ◆ SHA256 divides the hash code of 256-bit into **eight 32-bit words**; and performs complex XOR, AND, OR, NOT, choice, majority and rotation operations using the 512-bit message blocks as the input.






Algorithm of SHA256 (2/2)

Lab 9

◆ One SHA256 operation†:




$$\begin{aligned} \text{Ch}(E, F, G) &= (E \wedge F) \oplus (\neg E \wedge G) \\ \text{Ma}(A, B, C) &= (A \wedge B) \oplus (A \wedge C) \oplus (B \wedge C) \\ \Sigma_0(A) &= (A \ggg 2) \oplus (A \ggg 13) \oplus (A \ggg 22) \\ \Sigma_1(E) &= (E \ggg 6) \oplus (E \ggg 11) \oplus (E \ggg 25) \end{aligned}$$

 means addition modulo 2^{32} .

† <https://github.com/in3rsha/sha256-animation?tab=readme-ov-file>

† <https://en.wikipedia.org/wiki/SHA-2>






Parallel Computation

Lab 9

- ◆ In order to crack the code as fast as possible, you should try to instantiate multiple copies of the SHA256 cracking unit and compute the hash code in parallel.
- ◆ As soon as one of the circuits finds a match, the cracking operations can be terminated.
- ◆ Your grade will be evaluated based on the cracking speed of your circuit.





What You have to Do for Lab 9

Lab 9


- ◆ You must write an SHA256 cracking circuit using Verilog and implement it on the Arty board.
- ◆ In your circuit, the password hash code **shall be** declared as follows:

```
reg [255:0] passwd_hash = 256'hf120bb5698d520c5691b6d603a00bfd662d13bf177a04
571f9d10c0745dfa2a5
```

- ◆ Once the user presses BTN3, your circuit will crack the password and show it on the LCD module.

P	w	d	:	x	x	x	x	x	x	x	x			
T	:	t	t	t	t	t	t	t	t	t	t	t	t	t

- x : nine digit of password
- t : total clock cycle you use to crack the password (HEX)
- Note: it might takes modern PC 16.7 minutes to crack it!






Timer Requirement

Lab 9

- ◆ You will need to design a timer as follow:
 - Your timer should add 1 every 100Mz clock cycle.
 - Once your circuit detects that BTN3 logic signal is high, you should start your timer **immediately**.
 - You can only stop your timer after the circuit finish cracking the password.
- ◆ You should show your timing information on LCD.
 - Show timer [55:0] with hexadecimal on LCD display. `reg [55:0] timer;`
 - For example, If you spend 1000 cycles cracking the password, you should show: 0000000000003E8 on LCD .
 - Lock your timer if you reach the maximum number !
- ◆ If your timer or LCD display does not meet the above requirements, you are not ineligible to participate in the timing ranking.





Lab 9 Grading

Lab 9

- ◆ Functional Correctness (3~5 hidden testcases): 50%
 - TA will put the hidden testcases into your “passwd_hash” registers to valid your design correctness.
- ◆ Timing Check: 20%
 - If **all the testcases** result in WNS > 0 in your design, you will pass this part.
 - If you fail any testcases, you will lose these points.
- ◆ Speed Ranking: 20%
 - If your timer or LCD display format does not meet the requirements, you will lose all the points in this part.
 - The faster you crack, the higher score you will get. The ranked result will be divided into at most 5 level, and the point you get will depend on which level you are.
 - If you fail any testcases, you will lose these points.
- ◆ Question: 10%

