

Hibernate Architecture, Configuration

Objectives

- ◆ **Understand ORM:** Grasp the core concepts and benefits of object-relational mapping.
- ◆ **Map Entities:** Efficiently map Java classes to database tables and manage relationships.
- ◆ **Control Transactions:** Ensure data integrity with transactions and concurrency handling.
- ◆ **Integrate with Spring:** Leverage Spring Framework for dependency injection and simplified data access.
- ◆ **Gain Practical Experience:** Build projects and experiment with advanced features.

Contents

- ❖ Introduction
- ❖ Key Concepts
- ❖ Annotations
- ❖ Relationships
- ❖ Using Hibernate
- ❖ Demo
- ❖ Advantages and Disadvantages

What is Hibernate ?

- ◆ Hibernate is a powerful object-relational mapping (ORM) framework for the Java programming language.
- ◆ It acts as a bridge between the object-oriented world of Java and the relational world of databases, making it easier for developers to work with persistent data.
- ◆ Hibernate simplifies Java persistence, allowing developers to focus on the business logic of their applications rather than the intricacies of database interactions.

Key Features of Hibernate

- ◆ **ORM:** Maps Java objects to relational database tables, simplifying data access.
- ◆ **JPA Implementation:** Adheres to the JPA standard, ensuring portability and flexibility.
- ◆ **HQL (Hibernate Query Language):** Powerful object-oriented query language for retrieving and manipulating data.
- ◆ **Lazy Loading:** Loads associated data on demand, minimizing data transfer and enhancing responsiveness.
- ◆ **Transaction Management:** Ensures data consistency and integrity through transaction support.
- ◆ **Inheritance Mapping:** Handles various inheritance scenarios, mapping Java class hierarchies to database tables.

Benefits of Using Hibernate


- ◆ **Faster Development:** Spend less time on database code, more time on logic features
- ◆ **Cleaner Code:** Write concise, object-oriented code instead of complex SQL.
- ◆ **Improved Maintainability:** Easier to understand, update, and refactor your codebase.
- ◆ **Database Flexibility:** Switch between different databases without major code changes.

Benefits of Using Hibernate

- ◆ **Performance Boost:** Caching and lazy loading optimize data access for faster applications.
- ◆ **Data Integrity:** Built-in mechanisms ensure data consistency and prevent errors.
- ◆ **Industry Standard:** Widely used in the Java ecosystem, making you job-ready.
- ◆ **Spring Integration:** Works seamlessly with Spring, the leading Java framework.

.

Hibernate Architecture



Hibernate Architecture

- ❖ **Session Factory:** Manages configuration and creates Sessions
- ❖ **Session:** Provides data access methods and interacts with persistent object
- ❖ **Persistent Objects:** Java objects representing data stored in the database.
- ❖ **Transaction Management:** Ensures data consistency and integrity.
- ❖ **Connection Provider:** Handles database connections and pooling.
- ❖ **Query API:** Supports HQL, Criteria API, and native SQL for flexible querying
- ❖ **Caching:** Optimizes performance with first-level and second-level caches.
- ❖ **Event System:** Allows customization of persistence lifecycle events.
- ❖ **Dialects:** Generates database-specific SQL for portability.

Hibernate Architecture

❖ SessionFactory

- The SessionFactory is a factory of session and client of ConnectionProvider. It holds second level cache (optional) of data.
- The **org.hibernate.SessionFactory** interface provides factory method to get the object of Session.

❖ Session

- The session object provides an interface between the application and data stored in the database. It is a short-lived object and wraps the JDBC connection. It is factory of Transaction, Query and Criteria. It holds a first-level cache (mandatory) of data.
- The **org.hibernate.Session** interface provides methods to insert, update and delete the object. It also provides factory methods for Transaction, Query and Criteria.

Hibernate Architecture

❖ Transaction

- The transaction object specifies the atomic unit of work. It is optional. The `org.hibernate.Transaction` interface provides methods for transaction management.


❖ ConnectionProvider

- It is a factory of JDBC connections. It abstracts the application from `DriverManager` or `DataSource`. It is optional.

❖ TransactionFactory

- It is a factory of `Transaction`. It is optional.

Hibernate Lifecycle



Hibernate Lifecycle

- ◆ The Hibernate lifecycle refers to the various states an entity instance goes through during its interaction with the persistence framework. Understanding this lifecycle is crucial for effectively managing data and ensuring data integrity in your applications.
- ◆ Understanding the Hibernate lifecycle is essential for writing efficient and reliable persistence code. By managing entity states and transitions effectively, you can ensure data integrity and optimize the performance of your applications.

Hibernate Lifecycle

1. Transient State

- ❖ An entity instance is in a transient state when it's newly created using the new operator and not yet associated with a Hibernate session.
- ❖ Changes made to a transient instance are not tracked by Hibernate and won't be persisted to the database.

Hibernate Lifecycle

2. Persistent State

- ◆ An entity instance transitions to the persistent state when it's associated with a Hibernate session. This can happen through:
 - **persist() method:** Explicitly makes an instance persistent.
 - **Cascading:** If an associated entity is persisted and cascading is enabled, the current instance becomes persistent as well.
 - **Querying:** When an entity is retrieved from the database using `find()`, `createQuery()`, or other query methods.
- ◆ Changes made to a persistent instance are tracked by Hibernate and will be synchronized with the database upon flushing or transaction commit.

Hibernate Lifecycle

3. Detached State

- ◆ An entity instance becomes detached when it's no longer associated with a Hibernate session. This can occur when:
 - **Session is closed:** Closing the session detaches all persistent instances associated with it.
 - **detach() method:** Explicitly detaches an instance from the session.
 - **Serialization:** Serializing a persistent instance detaches it.
- ◆ Changes made to a detached instance are not tracked by Hibernate and won't be automatically persisted.

Hibernate Lifecycle

4. Removed State

- ◆ An entity instance enters the removed state when it's marked for deletion using the `remove()` method.
- ◆ The actual deletion from the database occurs upon flushing or transaction commit.

JPA vs Hibernate

JPA	Hibernate
Java Persistence API (JP.A) defines the management of relational data in the Java applications.	Hibernate is an Object-Relational Mapping (ORM) tool which is used to save the state of Java object into the database.
It is just a specification. Various ORM tools implement it for data persistence.	It is one of the most frequently used JPA implementation.
It is defined in javax.persistence package.	It is defined in org.hibernate package.
The EntityManagerFactory interface is used to interact with the entity manager factory for the persistence unit. Thus, it provides an entity manager.	It uses SessionFactory interface to create Session instances.
It uses EntityManager interface to create, read, and delete operations for instances of mapped entity classes. This interface interacts with the persistence context.	It uses Session interface to create, read, and delete operations for instances of mapped entity classes. It behaves as a runtime interface between a Java application and Hibernate.
It uses Java Persistence Query Language (JPQL) as an object-oriented query language to perform database operations.	It uses Hibernate Query Language (HQL) as an object-oriented query language to perform database operations.

Hibernate Configuration

- ❖ As Hibernate can operate in different environments, it requires a wide range of configuration parameters. These configurations contain the mapping information that provides different functionalities to Java classes. Generally, we provide database related mappings in the configuration file. Hibernate facilitates to provide the configurations either in an XML file (like `hibernate.cfg.xml`) or properties file (like `hibernate.properties`).
- ❖ An instance of Configuration class allows specifying properties and mappings to applications. This class also builds an immutable **SessionFactory**.

Properties of Hibernate Configuration

◆ Hibernate JDBC Properties

Property	Description
hibernate.connection.driver_class	It represents the JDBC driver class.
hibernate.connection.url	It represents the JDBC URL.
hibernate.connection.username	It represents the database username.
hibernate.connection.password	It represents the database password.
Hibernate.connection.pool_size	It represents the maximum number of connections available in the connection pool.

Properties of Hibernate Configuration

◆ Hibernate Datasource Properties

Property	Description
hibernate.connection.datasource	It represents datasource JNDI name which is used by Hibernate for database properties.
hibernate.jndi.url	It is optional. It represents the URL of the JNDI provider.
hibernate.jndi.class	It is optional. It represents the class of the JNDI InitialContextFactory.

Properties of Hibernate Configuration

Property	Description
hibernate.dialect	It represents the type of database used in hibernate to generate SQL statements for a particular relational database.
hibernate.show_sql	It is used to display the executed SQL statements to console.
hibernate.format_sql	It is used to print the SQL in the log and console.
hibernate.default_catalog	It qualifies unqualified table names with the given catalog in generated SQL.
hibernate.default_schema	It qualifies unqualified table names with the given schema in generated SQL.
hibernate.session_factory_name	The SessionFactory interface automatically bound to this name in JNDI after it has been created.

Properties of Hibernate Configuration

Property	Description
hibernate.default_entity_mode	It sets a default mode for entity representation for all sessions opened from this SessionFactory
hibernate.order_updates	It orders SQL updates on the basis of the updated primary key.
hibernate.use_identifier_rollback	If enabled, the generated identifier properties will be reset to default values when objects are deleted.
hibernate.generate_statistics	If enabled, the Hibernate will collect statistics useful for performance tuning.
hibernate.use_sql_comments	If enabled, the Hibernate generate comments inside the SQL. It is used to make debugging easier.

Hibernate Cache Properties

Property	Description
hibernate.cache.provider_class	It represents the classname of a custom CacheProvider.
hibernate.cache.use_minimal_puts	It is used to optimize the second-level cache. It minimizes writes, at the cost of more frequent reads.
hibernate.cache.use_query_cache	It is used to enable the query cache.
hibernate.cache.use_second_level_cache	It is used to disable the second-level cache, which is enabled by default for classes which specify a mapping.
hibernate.cache.query_cache_factory	It represents the classname of a custom QueryCache interface.
hibernate.cache.region_prefix	It specifies the prefix which is used for second-level cache region names.
hibernate.cache.use_structured_entries	It facilitates Hibernate to store data in the second-level cache in a more human-friendly format.

Properties of Hibernate Configuration

◆ Hibernate Transaction Properties

Property	Description
hibernate.transaction.factory_class	It represents the classname of a TransactionFactory which is used with Hibernate Transaction API.
hibernate.transaction.manager_lookup_class	It represents the classname of a TransactionManagerLookup. It is required when JVM-level caching is enabled.
hibernate.transaction.flush_before_completion	If it is enabled, the session will be automatically flushed during the before completion phase of the transaction.
hibernate.transaction.auto_close_session	If it is enabled, the session will be automatically closed during the after completion phase of the transaction.

Properties of Hibernate Configuration

◆ Other Hibernate Properties

Property	Description
hibernate.connection.provider_class	It represents the classname of a custom ConnectionProvider which provides JDBC connections to Hibernate.
hibernate.connection.isolation	It is used to set the JDBC transaction isolation level.
hibernate.connection.autocommit	It enables auto-commit for JDBC pooled connections. However, it is not recommended.
hibernate.connection.release_mode	It specifies when Hibernate should release JDBC connections.
hibernate.current_session_context_class	It provides a custom strategy for the scoping of the "current" Session.
hibernate.hbm2ddl.auto	It automatically generates a schema in the database with the creation of SessionFactory.

Annotations in Hibernate

Commonly Used Annotations

- ❖ **@Entity:** Marks a class as a persistent entity, indicating that it represents data stored in a database table.
- ❖ **@Table:** Specifies the name of the database table to which the entity is mapped.
- ❖ **@Id:** Identifies the primary key property of the entity.
- ❖ **@GeneratedValue:** Configures the strategy for generating identifier values (e.g., AUTO, SEQUENCE, IDENTITY).
- ❖ **@Column:** Provides details about the mapping of a property to a database column, such as the column name, data type, and nullability.

Commonly Used Annotations


- ❖ **@Basic**: Marks a property as a basic type (e.g., String, int, Date).
- ❖ **@Transient**: Excludes a property from persistence.
- ❖ **@Embedded**: Map embeddable components as value types.
- ❖ **@Temporal**: Specifies the temporal precision of a date/time property.
- ❖ **@Enumerated**: Configures the mapping of an enum type.
- ❖ **@Lob**: Marks a property as a large object (BLOB or CLOB).
- ❖ **@Version**: Enables optimistic locking with a version property.
- ❖ **@CreationTimestamp**, **@UpdateTimestamp**: Automatically set timestamps for creation and update events.

Relationships Annotations in Hibernate

- ❖ **@ManyToOne:** This annotation defines a many-to-one relationship between two entities.
- ❖ **@OneToMany:** This annotation defines a one-to-many relationship between two entities.
- ❖ **@OneToOne:** This annotation defines a one-to-one relationship between two entities.
- ❖ **@ManyToMany:** This annotation defines a many-to-many relationship between two entities.

Hibernate Query Language (HQL)

- ❖ Hibernate Query Language (HQL) is same as SQL (Structured Query Language) but it doesn't depends on the table of the database. Instead of table name, we use class name in HQL. So it is database independent query language.



Advantage of HQL

- ◆ Database independent
- ◆ Supports polymorphic queries
- ◆ Easy to learn for Java Programmer

Query Interface

- ◆ It is an object oriented representation of Hibernate Query. The object of Query can be obtained by calling the `createQuery()` method Session interface.
 - **`public int executeUpdate()`** is used to execute the update or delete query.
 - **`public List list()`** returns the result of the relation as a list.
 - **`public Query setFirstResult(int rowno)`** specifies the row number from where record will be retrieved.

Query Interface

- ◆ **public Query setMaxResult(int rowno)** specifies the no. of records to be retrieved from the relation (table).
- ◆ **public Query setParameter(int position, Object value)** it sets the value to the JDBC style query parameter.
- ◆ **public Query setParameter(String name, Object value)** it sets the value to a named query parameter.

Example of HQL paging


- ◆ Query query=session.createQuery("from Student");
- ◆ query.setFirstResult(5);
- ◆ query.setMaxResult(10);
- ◆ List list=query.list();//will return the records from 5 to 10th number

Example of HQL update query


1. *Transaction tx=session.beginTransaction();*
2. *Query q=session.createQuery("update Student set lastName=:n where id=:i");*
3. *q.setParameter("n","Sang");*
4. *q.setParameter("i",1);*
5. ***int*** *status=q.executeUpdate();*
6. *System.out.println(status);*
7. *tx.commit();*

Demo Hibernate (One To Many)


1. Open Eclipse, File | New | Maven Project



2. Check Create a simple project -> Browse Project -> Next



3. Fill the information Project -> Click Finish



4. Structure of Maven Project

The screenshot displays the Eclipse IDE interface for a Maven project named 'HSF301_Chapter_01_Ex_02_ManyToOne'. The Project Explorer on the left shows the project structure, including the 'pom.xml' file. The main editor shows the content of 'pom.xml', which is a Maven Project Object Model (POM) file. The POM file is structured as follows:

```

<?xml version="1.0" encoding="UTF-8" ?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 https://maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>
  <groupId>fe.edu.vn</groupId>
  <artifactId>HSF301_Chapter_01_Ex_02_ManyToOne</artifactId>
  <version>0.0.1-SNAPSHOT</version>
  <dependencies>
    <dependency>
      <groupId>org.hibernate</groupId>
      <artifactId>hibernate-entitymanager</artifactId>
      <version>5.6.9.Final</version>
    </dependency>
    <dependency>
      <groupId>com.microsoft.sqlserver</groupId>
      <artifactId>mssql-jdbc</artifactId>
      <version>11.2.3.jre17</version>
    </dependency>
  </dependencies>
</project>

```


The bottom of the IDE shows the Console output, which indicates that the project was successfully built. The output includes the following information:

```

[INFO] Installing E:\Teaching\FPT\JAVA\HSF301\HSF301_Chapter_01_Ex_02_ManyToOne\pom.xml to C:\Users\84767\.m2\repository\fe\edu\vn\
[INFO] Installing E:\Teaching\FPT\JAVA\HSF301\HSF301_Chapter_01_Ex_02_ManyToOne\target\HSF301_Chapter_01_Ex_02_ManyToOne-0.0.1-SNA
[INFO] BUILD SUCCESS
[INFO] Total time: 11.072 s
[INFO] Finished at: 2024-04-07T23:27:24+07:00

```

5. Create hibernate.cfg.xml



The screenshot shows the Eclipse IDE interface. The Project Explorer on the left displays the project structure for 'HSF301_Chapter_01_Ex_02_ManyToOne'. The main editor window shows the 'hibernate.cfg.xml' file being created. The XML content is as follows:


```
<?xml version="1.0" encoding="utf-8"?>
<!DOCTYPE hibernate-configuration SYSTEM
"http://www.hibernate.org/dtd/hibernate-configuration-3.0.dtd">
<hibernate-configuration>
  <session-factory>
    <property name="hbm2ddl.auto">update</property>
    <property name="dialect">org.hibernate.dialect.SQLServerDialect</property>
    <property name="connection.url">jdbc:sqlserver://localhost:1433;DatabaseName=tutorial;encrypt=true;trustServerCertificate=true</p
    <property name="connection.username">sa</property>
    <property name="connection.password">Aesx5099@@</property>
    <property name="connection.driver_class">com.microsoft.sqlserver.jdbc.SQLServerDriver</property>

    <mapping class="hsf301.fe.pojo.Student" />
    <mapping class="hsf301.fe.pojo.Book" />
  </session-factory>
</hibernate-configuration>
```

The Console window at the bottom shows the output of the Maven build process, indicating a successful build:

```
<terminated> D:\eclipse\plugins\org.eclipse.justi.openjdk.hotspot.jre.full.win32.x86_64_17.0.10.v20240120-1143\jre\bin\javaw.exe (Apr 7, 2024, 11:27:10 PM) [pid: 12940]
[INFO] Installing E:\Teaching\FPT\JAVA\HSF301\HSF301_Chapter_01_Ex_02_ManyToOne\pom.xml to C:\Users\84767\.m2\repository\fe\edu\vn\HSF301_Chap^
[INFO] Installing E:\Teaching\FPT\JAVA\HSF301\HSF301_Chapter_01_Ex_02_ManyToOne\target\HSF301_Chapter_01_Ex_02_ManyToOne-0.0.1-SNAPSHOT.jar to
[INFO] -----
[INFO] BUILD SUCCESS
[INFO] -----
[INFO] Total time: 11.072 s
[INFO] Finished at: 2024-04-07T23:27:24+07:00
[INFO] -----
```

6. Create Books in Pojo



The screenshot shows the Eclipse IDE with the following components:


- Project Explorer:** Displays the project structure for 'HSF301_Chapter_01_Ex_02_ManyToOne'. The 'src/main/java' directory contains sub-packages for 'dao', 'gui', 'pojo', 'repository', and 'service'. The 'pojo' package contains 'Book.java', 'Student.java', and 'StudentDAO.java'. The 'src/main/resources' directory contains 'hibernate.cfg.xml'.
- Editor:** Shows the code for 'Book.java'. The code defines a JPA entity 'Book' with an 'id' (generated), a 'title' (30 characters), an 'author', an 'isbn', and a 'student' (many-to-one relationship).
- Console:** Displays the output of a Maven build. It shows the installation of dependencies and a successful build.

```
1 package hsf301.fe.pojo;
2
3 *import javax.persistence.CascadeType;
12
13 @Entity
14 @Table(name = "BOOKS")
15 public class Book {
16
17     @Id
18     @GeneratedValue(strategy = GenerationType.AUTO)
19     private Long id;
20
21     @Column(name = "title", length = 30)
22     private String title;
23
24     private String author;
25
26     private String isbn;
27
28     @ManyToOne(cascade = CascadeType.ALL)
29     @JoinColumn(name = "student_id")
30     private Student student;
31
32     public Book() {
33         super();
34     }
}
```

Console Output:

```
<terminated> D:\eclipse\plugins\org.eclipse.justi.openjdk.hotspot.jre.full.win32.x86_64_17.0.10.v20240120-1143\jre\bin\javaw.exe (Apr 7, 2024, 11:27:10 PM) [pid: 12940]
[INFO] Installing E:\Teaching\FPT\JAVA\HSF301\HSF301_Chapter_01_Ex_02_ManyToOne\pom.xml to C:\Users\84767\.m2\repository\fe\edu\vn\HSF301_Chap^
[INFO] Installing E:\Teaching\FPT\JAVA\HSF301\HSF301_Chapter_01_Ex_02_ManyToOne\target\HSF301_Chapter_01_Ex_02_ManyToOne-0.0.1-SNAPSHOT.jar to
[INFO] -----
[INFO] BUILD SUCCESS
[INFO] -----
[INFO] Total time: 11.072 s
[INFO] Finished at: 2024-04-07T23:27:24+07:00
[INFO] -----
```

7. Create Students in Pojo



The screenshot shows the Eclipse IDE with the following components:

- Project Explorer:** Displays the project structure for 'HSF301_Chapter_01_Ex_02_ManyToOne'. The 'src/main/java' directory is expanded, showing the 'hsf301.fe.pojo' package containing 'Book.java' and 'Student.java'.
- Editor:** Displays the code for 'Student.java'. The code defines a JPA entity named 'Student' with the following attributes:



```

1 package hsf301.fe.pojo;
2
3 import java.util.HashSet;
4
5 @Entity
6 @Table(name = "STUDENTS")
7 public class Student {
8
9     @Id
10    @GeneratedValue(strategy = GenerationType.AUTO)
11    @Column(name = "id")
12    private int id;
13
14    @Column(name = "firstName", nullable = false, unique = true)
15    private String firstName;
16
17    @Column(name = "lastName")
18    private String lastName;
19
20    @Column(name = "marks")
21    private int marks;
22
23    @OneToMany(cascade = CascadeType.ALL)
24    @JoinColumn(name = "student_id")
25    private Set<Book> books ;
26
27 }
```
- Console:** Shows the output of a Maven build. It indicates that the project was installed successfully and that the build was successful.


```

<terminated> D:\eclipse\plugins\org.eclipse.justi.openjdk.hotspot.jre.full.win32.x86_64_17.0.10.v20240120-1143\jre\bin\javaw.exe (Apr 7, 2024, 11:27:10 PM) [pid: 12940]
[INFO] Installing E:\Teaching\FPT\JAVA\HSF301\HSF301_Chapter_01_Ex_02_ManyToOne\pom.xml to C:\Users\84767\.m2\repository\fe\edu\vn\HSF301_Chap
[INFO] Installing E:\Teaching\FPT\JAVA\HSF301\HSF301_Chapter_01_Ex_02_ManyToOne\target\HSF301_Chapter_01_Ex_02_ManyToOne-0.0.1-SNAPSHOT.jar to
[INFO] -----
[INFO] BUILD SUCCESS
[INFO] -----
[INFO] Total time: 11.072 s
[INFO] Finished at: 2024-04-07T23:27:24+07:00
[INFO] -----
```

8. Create StudentDAO




The screenshot shows the Eclipse IDE with the following details:

- Project Explorer (Left):** Displays the project structure for 'HSF301_Chapter_01_Ex_02_ManyToOne'. The 'src/main/java' directory is expanded, showing sub-packages like 'hsf301.fe.dao' (containing 'StudentDAO.java') and 'hsf301.fe.pojo' (containing 'Book.java' and 'Student.java').
- Editors (Top):** The 'StudentDAO.java' file is open and selected in the editor tab.
- Code Editor (Center):** Contains the following Java code:


```


1 package hsf301.fe.dao;
2
3 import java.util.List;
4
12
13 public class StudentDAO {
14
15     private SessionFactory sessionFactory = null;
16     private Configuration cf = null;
17
18     public StudentDAO(String persistenceName) {
19         cf = new Configuration();
20         cf = cf.configure(persistenceName);
21         sessionFactory = cf.buildSessionFactory();
22     }
23
24     public void save(Student student) {}
25
41
42     public List<Student> getStudents() {}
43
57
58     public void delete(Long studentID) {}
59
73
74     public Student findById(Long studentID) {}
75
85
86     public void update(Student student) {}
87
103 }
104
105
106
      
```
- Bottom Bar:** Shows 'Writable', 'Smart Insert', and '1:1:0'.

9. Save Student in StudentDAO



```
12
13 public class StudentDAO {
14
15     private SessionFactory sessionFactory = null;
16     private Configuration cf = null;
17
18     public StudentDAO(String persistenceName) {
19         cf = new Configuration();
20         cf = cf.configure(persistenceName);
21         sessionFactory = cf.buildSessionFactory();
22     }
23
24     public void save(Student student) {
25
26         Session session = sessionFactory.openSession();
27         Transaction t = session.beginTransaction();
28         try {
29             session.save(student);
30             t.commit();
31             System.out.println("successfully saved");
32         } catch (Exception ex) {
33             t.rollback();
34             System.out.println("Error " + ex.getMessage());
35         } finally {
36             sessionFactory.close();
37             session.close();
38         }
39     }
40
41
42     public List<Student> getStudents() {}
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58     public void delete(Long studentID) {}
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74     public Student findById(Long studentID) {}
75
76
77
78
79
80
81
82
83
84
85
86     public void update(Student student) {}
87
88
89
90
91
92
93
94
95
96
97
98
99
100 }
```

10. Get All Student in StudentDAO



```
eclipse-workspace - HSF301_Chapter_01_Ex_02_ManyToOne/src/main/java/hsf301/fe/dao/StudentDAO.java - Eclipse IDE
File Edit Source Refactor Navigate Search Project Run Window Help

Project Explorer | Servers | hibernate.cfg.xml | Bookjava | Studentjava | StudentDAO.java
  > HSF301_Chapter_01_Ex_02_ManyToOne
    > JPA Content
      > src/main/java
        > hsf301.fe.dao
          > StudentDAO.java
        > hsf301.fe.gui
        > hsf301.fe.pojo
          > Bookjava
          > Studentjava
        > hsf301.fe.repository
        > hsf301.fe.service
      > src/main/resources
        > hibernate.cfg.xml
      > JRE System Library [JavaSE-17]
      > Maven Dependencies
      > src
      > target
      > pom.xml


12
13 public class StudentDAO {
14
15     private SessionFactory sessionFactory = null;
16     private Configuration cf = null;
17
18     public StudentDAO(String persistenceName) {
19         cf = new Configuration();
20         cf = cf.configure(persistenceName);
21         sessionFactory = cf.buildSessionFactory();
22     }
23
24     public void save(Student student) {}
41
42     public List<Student> getStudents() {}
57
58     public void delete(Long studentID) {
59         Session session = sessionFactory.openSession();
60         Transaction tx = session.getTransaction();
61         try {
62             tx.begin();
63             Student student = (Student) session.get(Student.class, studentID);
64             session.delete(student);
65             tx.commit();
66         } catch (RuntimeException e) {
67             tx.rollback();
68             throw e;
69         } finally {
70             session.close();
71         }
72     }
73
74     public Student findById(Long studentID) {}
85
86     public void update(Student student) {}
103 }
104
105
Writable Smart Insert 42:1:959
```

11. Delete Student in StudentDAO

```


12
13 public class StudentDAO {
14
15     private SessionFactory sessionFactory = null;
16     private Configuration cf = null;
17
18     public StudentDAO(String persistenceName) {
19         cf = new Configuration();
20         cf = cf.configure(persistenceName);
21         sessionFactory = cf.buildSessionFactory();
22     }
23
24     public void save(Student student) {}
25
26     public List<Student> getStudents() {}
27
28     public void delete(Long studentID) {
29         Session session = sessionFactory.openSession();
30         Transaction tx = session.getTransaction();
31         try {
32             tx.begin();
33             Student student = (Student) session.get(Student.class, studentID);
34             session.delete(student);
35             tx.commit();
36         } catch (RuntimeException e) {
37             tx.rollback();
38             throw e;
39         } finally {
40             session.close();
41         }
42     }
43
44     public Student findById(Long studentID) {}
45
46     public void update(Student student) {}
47 }
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2296
2297
2298
2299
2300
2301
2302
2303
2304
2305
2306
2307
2308
2309
2310
2311
2312
2313
2314
2315
2316
2317
2318
2319
2320
2321
2322
2323
2324
2325
2326
2327
2328
2329
2330
2331
2332
2333
2334
2335
2336
2337
2338
2339
2340
2341
2342
2343
2344
2345
2346
2347
2348
2349
2350
2351
2352
2353
2354
2355
2356
2357
2358
2359
2360
2361
2362
2363
2364
2365
2366
2367
2368
2369
2370
2371
2372
2373
2374
2375
2376
2377
2378
2379
2380
2381
2382
2383
2384
2385
2386
2387
2388
2389
2390
2391
2392
2393
2394
2395
2396
2397
2398
2399
2400
2401
2402
2403
2404
2405
2406
2407
2408
2409
2410
2411
2412
2413
2414
2415
2416
2417
2418
2419
2420
2421
2422
2423
2424
2425
2426
2427
2428
2429
2430
2431
2432
2433
2434
2435
2436
2437
2438
2439
2440
2441
2442
2443
2444
2445
2446
2447
2448
2449
2450
2451
2452
2453
2454
2455
2456
2457
2458
2459
2460
2461
2462
2463
2464
2465
2466
2467
2468
2469
2470
2471
2472
2473
2474
2475
2476
2477
2478
2479
2480
2481
2482
2483
2484
2485
2486
2487
2488
2489
2490
2491
2492
2493
2494
2495
2496
2497
2498
2499
2500
2501
2502
2503
2504
2505
2506
2507
2508
2509
2510
2511
2512
2513
2514
2515
2516
2517
2518
2519
2520
2521
2522
2523
2524
2525
2526
2527
2528
2529
2530
2531
2532
2533
2534
2535
2536
2537
2538
2539
2540
2541
2542
2543
2544
2545
2546
2547
2548
2549
2550
2551
2552
2553
2554
2555
2556
2557
2558
2559
2560
2561
2562
2563
2564
2565
2566
2567
2568
2569
2570
2571
2572
2573
2574
2575
2576
2577
2578
2579
2580
2581
2582
2583
2584
2585
2586
2587
2588
2589
2590
2591
2592
2593
2594
2
```


12. Find A Student in StudentDAO



```
1 package hsf301.fe.dao;
2
3 import java.util.List;
4
5 public class StudentDAO {
6     private SessionFactory sessionFactory = null;
7     private Configuration cf = null;
8
9     public StudentDAO(String persistenceName) {
10         cf = new Configuration();
11         cf = cf.configure(persistenceName);
12         sessionFactory = cf.buildSessionFactory();
13     }
14
15     public void save(Student student) {}
16
17     public List<Student> getStudents() {}
18
19     public void delete(Long studentID) {}
20
21     public Student findById(Long studentID) {
22         Session session = sessionFactory.openSession();
23         try {
24             return (Student) session.get(Student.class, studentID);
25         } catch (RuntimeException e) {
26             throw e;
27         } finally {
28             session.close();
29         }
30     }
31
32     public void update(Student student) {}
33 }
```


13. Update a Student in StudentDAO



```
eclipse-workspace - HSF301_Chapter_01_Ex_02_ManyToOne/src/main/java/hsf301/fe/dao/StudentDAO.java - Eclipse IDE
File Edit Source Refactor Navigate Search Project Run Window Help
hibernate.cfg.xml Bookjava Studentjava StudentDAO.java x
Project Explorer Servers
HSF301_Chapter_01_Ex_02_ManyToOne
  JPA Content
  src/main/java
    hsf301.fe.dao
      StudentDAO.java
    hsf301.fe.gui
    hsf301.fe.pojo
      Bookjava
      Studentjava
    hsf301.fe.repository
    hsf301.fe.service
  src/main/resources
    hibernate.cfg.xml
  JRE System Library [JavaSE-17]
  Maven Dependencies
  src
  target
  pom.xml

12
13 public class StudentDAO {
14
15     private SessionFactory sessionFactory = null;
16     private Configuration cf = null;
17
18     public StudentDAO(String persistenceName) {
19         cf = new Configuration();
20         cf = cf.configure(persistenceName);
21         sessionFactory = cf.buildSessionFactory();
22     }
23
24     public void save(Student student) {}
41
42     public List<Student> getStudents() {}
57
58     public void delete(Long studentID) {}
73
74     public Student findById(Long studentID) {}
85
86     public void update(Student student) {
87
88         Session session = sessionFactory.openSession();
89         Transaction t = session.beginTransaction();
90         try {
91             session.update(student);
92             t.commit();
93             System.out.println("update saved");
94         } catch (Exception ex) {
95             t.rollback();
96             System.out.println("Error " + ex.getMessage());
97         } finally {
98             sessionFactory.close();
99             session.close();
100         }
101     }
102 }
103 }
```


14. Create IStudentRepository



The screenshot shows the Eclipse IDE interface. The Project Explorer on the left displays the project structure, with the file `IStudentRepository.java` selected under the `hsf301.fe.repository` package. The main editor window shows the code for `IStudentRepository.java`. The code defines a package, imports `java.util.List`, and declares a public interface `IStudentRepository` with five methods: `findAll()`, `save()`, `delete()`, `findById()`, and `update()`.

```
1 package hsf301.fe.repository;
2
3 import java.util.List;
4
5
6 public interface IStudentRepository {
7     public List<Student> findAll();
8
9
10    public void save(Student student);
11
12    public void delete(Long studentID);
13
14    public Student findById(Long studentID);
15
16    public void update(Student student);
17 }
18
```

15. Create StudentRepository




The screenshot shows the Eclipse IDE with the following components:

- Project Explorer:** Displays the project structure. The package `hsf301.fe.repository` is expanded, showing the newly created `StudentRepository.java` file.
- Editor:** Contains the code for `StudentRepository.java`. The code is as follows:


```

1 package hsf301.fe.repository;
2
3 import java.util.List;
4
5 public class StudentRepository implements IStudentRepository {
6     private StudentDAO studentDAO = null;
7
8     public StudentRepository(String fileConfig) {
9         studentDAO = new StudentDAO(fileConfig);
10    }
11    @Override
12    public void save(Student student) {
13        // TODO Auto-generated method stub
14        studentDAO.save(student);
15    }
16    @Override
17    public List<Student> findAll() {
18        // TODO Auto-generated method stub
19        return studentDAO.getStudents();
20    }
21    @Override
22    public void delete(Long studentID) {
23        studentDAO.delete(studentID);
24    }
25    @Override
26    public Student findById(Long studentID) {
27        // TODO Auto-generated method stub
28        return studentDAO.findById(studentID);
29    }
30    @Override
31    public void update(Student student) {
32        studentDAO.update(student);
33    }
34 }
      
```
- Bottom Bar:** Shows the status bar with indicators for "Writable", "Smart Insert", and the cursor position "1:1:0".

16. Create IStudentService




The screenshot shows the Eclipse IDE interface. The Project Explorer on the left displays the project structure for 'HSF301_Chapter_01_Ex_02_ManyToOne'. The 'src/main/java' directory is expanded, showing the 'hsf301.fe.service' package. The 'IStudentService.java' file is selected and open in the editor. The code in the editor defines the 'IStudentService' interface with the following methods:

```
1 package hsf301.fe.service;
2
3 import java.util.List;
4
5
6
7 public interface IStudentService {
8     public List<Student> findAll();
9
10    public void save(Student student);
11
12    public void delete(Long studentID);
13
14    public Student findById(Long studentID);
15
16    public void update(Student student);
17 }
18
19
```

The status bar at the bottom indicates 'Writable', 'Smart Insert', and the cursor position '17 : 1 : 325'.

17. Create StudentService




```
eclipse-workspace - HSF301_Chapter_01_Ex_02_ManyToOne/src/main/java/hsf301/fe/service/StudentService.java - Eclipse IDE
File Edit Source Refactor Navigate Search Project Run Window Help
hibernate.cfg.xml Book.java Student.java StudentDAO.java IStudentRepository.java StudentRepository.java IStudentService.java StudentService.java
Project Explorer Servers
HSF301_Chapter_01_Ex_02_ManyToOne
  JPA Content
  > src/main/java
    hsf301.fe.dao
      StudentDAO.java
    hsf301.fe.gui
    hsf301.fe.pojo
      Book.java
      Student.java
    hsf301.fe.repository
      IStudentRepository.java
      StudentRepository.java
    hsf301.fe.service
      IStudentService.java
      StudentService.java
  src/main/resources
    hibernate.cfg.xml
  JRE System Library [JavaSE-17]
  Maven Dependencies
  > src
  target
  pom.xml

1 package hsf301.fe.service;
2
3 import java.util.List;
4
5
6
7
8
9 public class StudentService implements IStudentService{
10     private IStudentRepository iStudentRepo = null;
11
12     public StudentService(String fileName) {
13         iStudentRepo = new StudentRepository(fileName);
14     }
15     @Override
16     public void save(Student student) {
17         // TODO Auto-generated method stub
18         iStudentRepo.save(student);
19     }
20     @Override
21     public List<Student> findAll() {
22         // TODO Auto-generated method stub
23         return iStudentRepo.findAll();
24     }
25     @Override
26     public void delete(Long studentID) {
27         iStudentRepo.delete(studentID);
28     }
29
30     @Override
31     public Student findById(Long studentID) {
32         // TODO Auto-generated method stub
33         return iStudentRepo.findById(studentID);
34     }
35     @Override
36     public void update(Student student) {
37         // TODO Auto-generated method stub
38         iStudentRepo.update(student);
39     }
40
41 }
42

Writable Smart Insert 1:1:0
```


18. Create Main function



The screenshot shows the Eclipse IDE with the file `ManyToOne.java` open. The code defines a package `hsf301.fe.gui` and a class `ManyToOne` with a `main` method. The `main` method initializes a `StudentService`, creates a `Student` object, adds a `Book` to its `getBooks()` list, and saves the student.

```
1 package hsf301.fe.gui;
2
3 import java.util.List;
4
5
6
7
8
9
10 public class ManyToOne {
11
12     public static void main(String[] args) {
13         // TODO Auto-generated method stub
14
15         //Many To One
16         String fileName = "hibernate.cfg.xml";
17         IStudentService studentService = new StudentService(fileName);
18         Student student = new Student("Lam", "Nguyen", 9);
19         Book book = new Book("Java Persistence with Spring", "Catalin Tudose", "9781617299186");
20         student.getBooks().add(book);
21         studentService.save(student);
22     }
23 }
24
25
26
```

19. Result



20. Result

SQLQuery1.sql - localhost.tutorial (sa (53)) - Microsoft SQL Server Management Studio

File Edit View Query Project Tools Window Help

tutorial

Execute

100 %

Results Messages

localhost (SQL Server 16.0.1000.6 - sa)

Databases

System Databases

Database Snapshots

Equipments2024DB

tutorial

Database Diagrams

Tables

System Tables

FileTables

External Tables

Graph Tables

dbo.BOOKS

dbo.hibernate_sequence

dbo.STUDENTS

Dropped Ledger Tables

Views

External Resources

Synonyms

Programmability

Query Store

Service Broker

Storage

Security

Security

Server Objects

Replication

Always On High Availability

Management

Integration Services Catalogs

SQLQuery1.sql - loca...st.tutorial (sa (53))

SELECT TOP (1000) [id]

,[author]

,[isbn]

,[title]

,[student_id]

FROM [tutorial].[dbo].[BOOKS]

100 %

Results Messages

id	author	isbn	title	student_id
1	2	Catalin Tudose	Java Persistence with Spring	1

Query executed successfully.

SQLQuery2.sql - localhost.tutorial (sa (62)) - Microsoft SQL Server Management Studio

File Edit View Query Project Tools Window Help

tutorial

Execute

100 %

Results Messages

localhost (SQL Server 16.0.1000.6 - sa)

Databases

System Databases

Database Snapshots

Equipments2024DB

tutorial

Database Diagrams

Tables

System Tables

FileTables

External Tables

Graph Tables

dbo.BOOKS

dbo.hibernate_sequence

dbo.STUDENTS

Dropped Ledger Tables

Views

External Resources

Synonyms

Programmability

Query Store

Service Broker

Storage

Security

Security

Server Objects

Replication

Always On High Availability

Management

Integration Services Catalogs

SQLQuery2.sql - loca...st.tutorial (sa (62))

SELECT TOP (1000) [id]

,[firstName]

,[lastName]

,[marks]

FROM [tutorial].[dbo].[STUDENTS]

100 %


Results Messages

id	firstName	lastName	marks
1	Lam	Nguyen	9

Query executed successfully.

Demo JPA (Many To Many)

1. Create Books in Pojo's Package




```

eclipse-workspace - HSF301_Chapter_01_Ex_02_ManyToMany/src/main/java/hsf301/fe/pojo/Book.java - Eclipse IDE
File Edit Source Refactor Navigate Search Project Run Window Help
Project Explorer Servers Bookjava x
HSF301_Chapter_01_Ex_02_ManyToMany
  JPA Content
  src/main/java
    hsf301.fe.dao
    hsf301.fe.gui
    hsf301.fe.pojo
      Bookjava
      Student.java
    hsf301.fe.repository
    hsf301.fe.service
  src/main/resources
  JRE System Library [JavaSE-1.8]
  Maven Dependencies
  src
  target
  pom.xml

1 package hsf301.fe.pojo;
2
3 import java.util.HashSet;
4
12
13 @Entity
14 @Table(name = "BOOKS")
15
16 public class Book {
17
18     @Id
19     @GeneratedValue(strategy = GenerationType.AUTO)
20     @Column(name = "id")
21     private Long id;
22
23     @Column(name = "title", length = 30)
24     private String title;
25
26     private String author;
27
28     private String isbn;
29
30     @ManyToMany(mappedBy = "books")
31     private Set<Student> student = new HashSet<Student>();
32
33     public Book() {
34         super();
35     }
36     public Book(String title, String author, String isbn) {
37         super();
38         this.title = title;
39         this.author = author;
40         this.isbn = isbn;
41     }
42
43     public Book(Book book) {
44         super();
45         this.title = book.title;
46         this.author = book.author;
47         this.isbn = book.isbn;
48     }
49
50     // getters and setters
51
52 }
  
```

2. Create Students in Pojo's Package




```

1 package hsf301.fe.pojo;
2
3 import java.util.HashSet;
4
5
6
7
8
9
10
11
12
13
14
15 @Entity
16 @Table(name = "STUDENTS")
17 public class Student {
18
19
20     @Id
21     @GeneratedValue(strategy = GenerationType.AUTO)
22     @Column(name = "id")
23     private int id;
24
25     @Column(name = "firstName", nullable = false, unique = false)
26     private String firstName;
27
28     @Column(name = "lastName")
29     private String lastName;
30
31     @Column(name = "marks")
32     private int marks;
33
34     @ManyToMany(cascade = CascadeType.ALL)
35     @JoinTable(name = "STUDENTS_BOOKS",
36         joinColumns = @JoinColumn(name = "student_id"),
37         inverseJoinColumns = @JoinColumn(name = "book_id"))
38     private Set<Book> books = new HashSet<Book>();
39
40     public Set<Book> getBooks() {
41         return books;
42     }
43
44     public void setBooks(Set<Book> books) {
45         this.books = books;
46     }
47
48     public Student() {
49
50


```

3. Run Program



```
1 package hsf301.fe.gui;
2
3 import hsf301.fe.pojo.Book;
4
5
6
7
8 public class ManyToMany {
9
10     public static void main(String[] args) {
11         // TODO Auto-generated method stub
12
13         //Many To
14         String fileName = "hibernate.cfg.xml";
15         IStudentService studentService = new StudentService(fileName);
16         Student student = new Student("Lam", "Nguyen", 9);
17         Book book = new Book("Java Persistence with Spring", "Catalin Tudose", "9781617299186");
18         student.getBooks().add(book);
19         studentService.save(student);
20
21     }
22
23 }
24
```

4. Result



5. Result

SQLQuery1.sql - localhost:tutorial (sa (53)) - Microsoft SQL Server Management Studio

localhost (SQL Server 16.0.1000.6 - sa)

Databases

System Databases

Database Snapshots

Equipments2024DB

tutorial

Database Diagrams

Tables

System Tables

FileTables

External Tables

Graph Tables

dbo.BOOKS

dbo.hibernate_sequence

dbo.STUDENTS

dbo.STUDENTS_BOOKS

Dropped Ledger Tables

Views

External Resources

Synonyms

Programmability

Query Store

Service Broker

Storage

Security

Server Objects

Replication

Always On High Availability

Management

```

SELECT TOP (1000) [id]
      ,[author]
      ,[isbn]
      ,[title]
FROM [tutorial].[dbo].[BOOKS]

```

100 %

Results Messages

	id	author	isbn	title	student_id
1	2	Catalin Tudose	9781617299186	Java Persistence with Spring	1

Query executed successfully. localhost (16.0 RTM) | sa (53) | tutorial | 00:00:00 | 1 rows

SQLQuery8.sql - localhost:tutorial (sa (72)) - Microsoft SQL Server Management Studio

localhost (SQL Server 16.0.1000.6 - sa)

Databases

System Databases

Database Snapshots

Equipments2024DB

tutorial

Database Diagrams

Tables

System Tables

FileTables

External Tables

Graph Tables

dbo.BOOKS

dbo.hibernate_sequence

dbo.STUDENTS

dbo.STUDENTS_BOOKS

Dropped Ledger Tables

Views

External Resources

Synonyms

Programmability

Query Store

Service Broker

Storage

Security

Server Objects

Replication

Always On High Availability

Management

```

SELECT TOP (1000) [student_id]
      ,[book_id]
FROM [tutorial].[dbo].[STUDENTS_BOOKS]

```

100 %

Results Messages

	student_id	book_id
1	1	2

Query executed successfully. localhost (16.0 RTM) | sa (72) | tutorial | 00:00:00 | 1 rows

SQLQuery7.sql - localhost:tutorial (sa (64)) - Microsoft SQL Server Management Studio

localhost (SQL Server 16.0.1000.6 - sa)

Databases

System Databases

Database Snapshots

Equipments2024DB

tutorial

Database Diagrams

Tables

System Tables

FileTables

External Tables

Graph Tables

dbo.BOOKS

dbo.hibernate_sequence

dbo.STUDENTS

dbo.STUDENTS_BOOKS

Dropped Ledger Tables

Views

External Resources

Synonyms

Programmability

Query Store

Service Broker

Storage

Security

Server Objects

Replication

Always On High Availability

Management

```

FROM [tutorial].[dbo].[STUDENTS]

```

100 %

Results Messages

	id	firstName	lastName	marks
1	1	Lam	Nguyen	9

Query executed successfully. localhost (16.0 RTM) | sa (62) | tutorial | 00:00:00 | 1 rows

Summary

- ❖ Concepts were introduced:
 - ❖ Overview about Hibernate
 - ❖ Architecture Overview new features of Hibernate
 - ❖ Explain and demo using Eclipse IDE to create Hibernate Console
 - ❖ Create and Run cross-platform Console application with Java connect to MSSQL with Repository Pattern