

SC3000/CZ3005 Artificial Intelligence

Constraint satisfaction and adversarial search

Prof Bo AN

www.ntu.edu.sg/home/boan


Email: boan@ntu.edu.sg

Office: N4-02b-55



Lesson Outline

- Constraint Satisfaction
- Adversarial search (Game Playing)




Constraint Satisfaction Problem (CSP)



Goal: discover some state that satisfies a given set of constraints

Example: Sudoku



Example: Minesweeper



Examples: Real-world CSPs



- Assignment problems
 - e.g. who teaches what class
- Timetabling problems
 - e.g. which class is offered when and where?
- Hardware configuration
- Transportation scheduling
- Factory scheduling
- Floor-planning



CSP

State

- defined by **variables** V_i with **values** from domain D_i

Example: 8-queens

- Variables: locations of each of the eight queens
- Values: squares on the board

Goal test

- a set of **constraints** specifying allowable combinations of values for subsets of variables

Example: 8-queens

- Goal test: No two queens in the same row, column or diagonal



Example: Cryptarithmic Puzzle

$$\begin{array}{r} \text{S E N D} \\ + \text{M O R E} \\ \hline \text{M O N E Y} \end{array}$$

m=1


*Starting from left
you can solve the
problem more easily:
domain knowledge*

- Variables: D, E, M, N, O, R, S, Y
- Domains: {0, 1, 2, 3, 4, 5, 6, 7, 8, 9}
- Constraints
 - $Y = D + E$ or $Y = D + E - 10$, etc
 - $D \neq E$, $D \neq M$, $D \neq N$, etc.
 - $M \neq 0$, $S \neq 0$ (**unary** constraints: concern the value of a single variable)



Example: Map Colouring *NP hard*

Colour a map so that no adjacent parts have the same colour



- Variables: Countries C_i
- Domains: {Red, Blue, Green}
- Constraints: $C_1 \neq C_2$, $C_1 \neq C_5$, etc.
 - binary** constraints



Some Definitions

- A state of the problem is defined by an **assignment** of values to some or all of the variables.
- An assignment that does not violate any constraints is called a **consistent** or **legal** assignment.
- A **solution** to a CSP is an assignment with every variable given a value (**complete**) and the assignment satisfies all the constraints.



Applying Standard Search

- **States:** defined by the values assigned so far
- **Initial state:** all variables unassigned
- **Actions:** assign a value to an unassigned variable
- **Goal test:** all variables assigned, no constraints violated



Applying Standard Search

Question: How to represent constraints?

Answer: Explicitly (e.g., $D \neq E$)


Example

- Row the 1st queen occupies: $V_1 \in \{1, 2, 3, 4, 5, 6, 7, 8\}$
(similarly, for V_2)
- No-attack constraint for V_1 and V_2 :
 $\{ \langle 1, 3 \rangle, \langle 1, 4 \rangle, \langle 1, 5 \rangle, \dots, \langle 2, 4 \rangle, \langle 2, 5 \rangle, \dots \}$

Implicitly: use a function to test for constraint satisfaction

Backtracking Search

Backtracking search: Do not waste time searching when constraints have already been violated




- Before generating successors, check for constraint violations
- If yes, backtrack to try something else

eg. -5 penalty
 $\min f(x) + g(x)$
 $s.t. g(x) \leq 0$
Language multiplier \rightarrow essentially same



Example (4-Queens)





Heuristics for CSPs


Plain backtracking is an uninformed algorithm!!

More intelligent search that takes into consideration


- Which variable to assign next
- What order of the values to try for each variable
- Implications of current variable assignments for the other unassigned variables
 - forward checking and **constraint propagation**

Constraint propagation: propagating the implications of a constraint on one variable onto other variables

Example (4-Queens) **without** Constraint Propagation




Search Tree of 4-Queens with Constraint Propagation




order might matter too!


Example (Map Colouring)




Example (Map Colouring)...



Example (Map Colouring)...



Example (Map Colouring)...




Example (Map Colouring)...



Most Constraining Variable




Example: map colouring



To reduce the branching factor on future choices by selecting the variable that is involved in the **largest number of constraints** on unassigned variables.

Least Constraining Value




Choose the value that leaves **maximum flexibility** for subsequent variable assignments

Min-Conflicts Heuristic (8-queens)



- A **local heuristic search method** for solving CSPs
- Given an **initial assignment**, selects a variable in the scope of a violated constraint and assigns it to the value that minimises the number of violated constraints



Games as Search Problems



Abstraction

- Ideal representation of real world problems
 - e.g. board games, chess, go, etc. as an abstraction of war games
 - Perfect information, i.e. fully observable
- Accurate formulation: state space representation

Uncertainty

- Account for the existence of **hostile** agents (players)
 - Other agents acting so as to diminish the agent's well-being
 - Uncertainty (about other agents' actions):
 - not due to the effect of non-deterministic actions
 - not due to randomness
- Contingency problem

Games as Search Problems...



Complexity

- Games are abstract but not simple
 - e.g. chess: average branching factor = 35, game length > 50
→ complexity = 35^{50} (only 10^{40} for legal moves)
- Games are usually time limited
 - Complete search (for the optimal solution) not possible
→ uncertainty on actions desirability
 - Search efficiency is crucial

Types of Games



| | Deterministic | Chance |
|-----------------------|------------------------------|--------------------------------------|
| Perfect information | Chess, Checkers, Go, Othello | Backgammon, Monopoly |
| Imperfect information | | Bridge, Poker, Scrabble, Nuclear war |

Perfect information

- each player has complete information about his opponent's position and about the choices available to him

Game as a Search Problem




- Initial state: initial board configuration and indication of who makes the first move
- Operators: legal moves
- Terminal test: determines when the game is over
 - states where the game has ended: **terminal states**
- Utility function (payoff function): returns a numeric score to **quantify** the outcome of a game

Example: Chess

Win (+1), loss (-1) or draw (0)

Game Tree for Tic-Tac-Toe




- The utility value of the terminal state is from the point of view of MAX
- MAX uses the search tree to determine the best move


What Search Strategy?



One-play



Two-play



Minimax Search Strategy



Search strategy

- Find a sequence of moves that leads to a terminal state (goal)

Minimax search strategy

- Maximise one's own utility and minimise the opponent's
 - Assumption is that the opponent does the same

Minimax Search Strategy



3-step process

- Generate the entire game tree down to terminal states
- Calculate utility
 - Assess the utility of each terminal state
 - Determine the best utility of the parents of the terminal state (bottom up fashion)
 - Repeat the process for their parents until the root is reached
- Select the best move (i.e. the move with the highest utility value)

Perfect Decisions by Minimax Algorithm




Perfect decisions: no time limit is imposed

- generate the complete search tree


Two players: MAX and MIN

- Choose move with best achievable payoff against best play
- MAX tries to max the utility, assuming that MIN will try to min it

Example



Othello 4




- A player can place a new piece in a position if there exists at least one straight (horizontal, vertical, or diagonal) occupied line between the new piece and another piece of the same kind, with one or more contiguous pieces from the opponent player between them
- After placing the new piece, the pieces from the opponent player will be captured and become the pieces from the same Player
- The player with the most pieces on the board wins


'X' plays first






X considers the game now




O considers the game now



X considers the game now



Game Tree Othello 4



Imperfect Decisions

Go: Huge search game tree
- difficult to generate complete game tree



For chess, branching factor ≈ 35 , each player typically makes 50 moves \rightarrow for the complete game tree, need to examine 35^{100} positions

Time/space requirements \rightarrow complete game tree search is intractable \rightarrow impractical to make perfect decisions

Modifications to minimax algorithm


- replace utility function by an **estimated** desirability of the position
 - Evaluation function**
- partial** tree search
 - E.g., depth limit
 - Replace terminal test by a **cut-off** test

this is not the terminal nodes.


Evaluation Functions



Returns an **estimate** of the expected utility of the game from a given position



Black: to move
White: slightly better



White: to move
Black: winning

Evaluation Functions...



Requirements

- Computation is **efficient**
- Agrees with utility function on **terminal** states
- Accurately** reflects the chances of winning

Trade off between accuracy and efficiency

Example (Chess)

Define **features**

- e.g., (number of white queens) – (number of black queens)
- Use a **weighted sum** of these features

$$Eval(s) = w_1 f_1(s) + w_2 f_2(s) + \dots + w_n f_n(s)$$

- Need to learn the weight

- for AlphaGo Eval
can be a deep neural
network

heuristic
no one knows the truth

Evaluation Functions for Othello 4



- A corner of the board is one of the most important positions. A piece at the corner can help capture other pieces from the opponent player
- A square at the border is also more important than any position in the middle of the board

Heuristics for 'X' is proposed as follows:

- For any non-terminal game state, the evaluation function is computed as

$$3(X_C - O_C) + 2(X_b - O_b) + (X_m - O_m)$$

where X_C is the number of X's at corners,

X_b is the number of X's at the border (excluding corners),


X_m is the number of X's in the middle of the grid,

O_C , O_b and O_m are the number of O's at the corners, the border and the middle of the board




middle
spots


Evaluation Functions for Othello 4 ...



A Toy Min-Max Example




A Toy Min-Max Example




If you over estimate your opponent your actual utility might be lower.

A Toy Min-Max Example



Step 2:
Update the value from btm to top
e.g., for node D:
We want to win \rightarrow max the value $(-1, 4)$

A Toy Min-Max Example



Step 2:
Update the value from btm to top
e.g., for node D:
I want to win \rightarrow max the value $(-1, 4)$
e.g., for node B:
You want me to lose \rightarrow min the value $(4, 6)$

A Toy Min-Max Example

