


Module 9

Efficient Rendering



Learning Objectives

- Understand hierarchical representations
- Understand two forms of scene organization
- Construct and use bounding volumes
- Design and use level of detail (LOD)

2

Sources

- Textbook (Chapter 9.3: Fast Rendering of Large Scenes)
- Wiki:
 - http://en.wikipedia.org/wiki/Bounding_volume
 - http://en.wikipedia.org/wiki/Level_of_detail

3

Outline

- §1. Lecture Review
 1. Introduction
 2. Hierarchical representation
 3. Scene organization
 4. Bounding volumes
 5. Level of detail
- §2. Example

4


1. Introduction

- In real applications, geometric datasets are usually very complicated. There is possibility to speed up rendering by well-organizing data or appropriately processing data such as
 - Hierarchical representation of models
 - Spatially-based organization of scenes
 - Bounding volumes
 - Level of detail

5

2. Hierarchical representation

- Hierarchical representation has advantages for modeling, rendering and others.



6

3. Scene organization

- Logically-partitioned organization: may not be efficient for rendering
- Spatially-partitioned organization: efficient for rendering

7


4. Bounding volumes

- Using bounding volumes is a simple and effective technique for rendering.
- A few criteria for constructing a bounding volume:
 - The bounding volume should be relatively simple geometrically. This makes the computational cost of geometrical operations with the bounding volume be low.
 - The bounding volume should bound the object tightly. This makes the use of the bounding volume for the object effective.
 - The computational cost of constructing a bounding volume for an object should be low.

8

Bounding box in FVRML


- In FVRML, bounding box can be used to speed up the rendering of implicit objects and improve the rendering quality.
- For example, we use FVRML to visualize a shape defined by: $1 - |x| - y^4 - z^4 \geq 0$.
- To achieve similar rendering quality, we can use a lower resolution with a tight bounding box.




9

Bounding box in FVRML


- With the same resolution, tighter bounding box gives better rendering quality.



resolution [40 40 40]
bboxCenter 0 0 0
bboxSize 2.2 2.2 2.2



resolution [40 40 40]
bboxCenter 0 0 0
bboxSize 4 4 4




resolution [40 40 40]
bboxCenter 0 0 0
bboxSize 6 6 6

10

4. Level of detail



- Level of detail (LOD) is an important technique for maintaining interactivity.
 - Basic idea: tradeoff among the fidelity of models, the visual fidelity, and performance
 - Basic observation: Using fewer details for distant objects will not reduce the quality of visual appearance.



11

LOD in FVRML


- In VRML, LOD node can specify various levels of detail or complexity in terms of colors and shape.



12

LOD in FVRML


- In FVRML, LODs can be controlled using the resolution for rendering implicit objects.



13

LOD in FVRML

- In FVRML, LODs can be controlled using the resolution for rendering parametric surfaces.



14

Outline

§1. Lecture Review

1. Introduction
2. Hierarchical representation
3. Scene organization
4. Bounding volumes
5. Level of detail

§2. Example

15

Example

Q: Consider a 2D object defined implicitly by

$$f(x, y) = \min(\min(1-x^2-y^2, -(1-(x/0.7)^2-(y/0.3)^2)), y) \geq 0$$

- (i) Draw a diagram to show the hierarchical representation of the object.
- (ii) Find the minimum axis-aligned bounding rectangle of the object.

16

Example (cont)

Hints :


Introduce the following notations:

A: unit disk $1-x^2-y^2 \geq 0$

One possible diagram could be

B: ellipse disk $1-(x/0.7)^2-(y/0.3)^2 \geq 0$

C: half plane $y \geq 0$




$$\min(\min(1-x^2-y^2, -1-(x/0.7)^2-(y/0.3)^2), y) \geq 0$$

17

Example (cont)

Hence the 2D object is the shaded area shown below:



It can be seen that the object is between two vertical lines: $x=-1$ and $x=1$, and between two horizontal lines: $y=0$ and $y=1$. Thus the minimum axis-aligned bounding rectangle is the one specified by two corners with coordinates $(-1,0)$ and $(1,1)$.

18

END

19