

SECUREINBOX: EMAIL VERIFICATION SYSTEM

A PROJECT REPORT

Submitted by

Nivedita Waghmare 22BCY10242

Sanjana Lanka 22BCY10294

Purigilla Akhila 22BCY10171

Kiran Kumar Ch 22BCY10109

Atharva Dnyaneshwar Shastrakar 22BCY10276

*in partial fulfillment for the award of the degree
of*

BACHELOR OF TECHNOLOGY

in

**COMPUTER SCIENCE AND ENGINEERING
(Cyber Security and Digital Forensics)**



VIT[®]
BHOPAL
www.vitbhopal.ac.in

SCHOOL OF COMPUTING SCIENCE AND ENGINEERING

VIT BHOPAL UNIVERSITY

**KOTRIKALAN, SEHORE
MADHYA PRADESH - 466114**

November 2025

BONAFIDE CERTIFICATE

Certified that this project report titled **“SECUREINBOX: EMAIL VERIFICATION SYSTEM”** is the bonafide work of **“Nivedita Waghmare (22BCY10242), Sanjana Lanka (22BCY10294), Purigilla Akhila (22BCY10171), Kiran Kumar Ch (22BCY10109), Atharva Dnyaneshwar Shastrakar (22BCY10276)”** who carried out the project work under my supervision. Certified further that to the best of my knowledge the work reported at this time does not form part of any other project/research work based on which a degree or award was conferred on an earlier occasion on this or any other candidate.

PROGRAM CHAIR,
Dr. D. Saravanan, Assistant Professor
Senior,
School of Computing Science and
Engineering,
VIT Bhopal University.

PROJECT SUPERVISOR,
Dr. Subhash Chandra Patel, Senior
Assistant Professor,
School of Computing Science and
Engineering,
VIT Bhopal University.

The Capstone Project Examination is held on 19/11/2025

ACKNOWLEDGEMENT

First and foremost I would like to thank the Lord Almighty for His presence and immense blessings throughout the project work.

I wish to express my heartfelt gratitude to **Dr D. Saravanan**, Program Chair, Cyber Security and Digital Forensics for much of his valuable support and encouragement in carrying out this work.

I would like to thank my supervisor **Dr. Subhash Chandra Patel** for continually guiding and actively participating in my project, giving valuable suggestions to complete the project work.

I would like to thank all the technical and teaching staff of the School Computing Science and Engineering, who extended directly or indirectly all support.

Last, but not least, I am deeply indebted to my parents who have been the greatest support while I worked day and night for the project to make it a success.

LIST OF ABBREVIATIONS

SPF	Sender Policy Framework
DKIM	DomainKeys Identified Mail
DMARC	Domain-based Message Authentication, Reporting and Conformance
DNS	Domain Name System
STMP	Simple Mail Transfer Protocol
AI	Artificial Intelligence
LLM	Large Language Model
ML	Machine Learning
PQC	Rivest–Shamir–Adleman (Cryptographic Algorithm)
RSA	Reporting URI for Aggregate Reports
RUF	Reporting URI for Forensic Reports
IETF	Internet Engineering Task Force
NIST	National Institute of Standards and Technology
GDPR	General Data Protection Regulation
XML	eXtensible Markup Language

LIST OF FIGURES AND GRAPHS

FIGURE NO.	TITLE	PAGE NO.
1	Prototype output	50
2	Security score distribution	51

LIST OF TABLES

TABLE NO.	TITLE	PAGE NO.
1	Comparative summary of pro's and con's	27
2	Validation Matrix	51
3	DNS Query Response Time	51
4	Security Score Distribution	52
5	Tools Used	57
6	Quantitative Summary of Achievements	64

ABSTRACT

Purpose

Email remains the backbone of digital communication but continues to be the most exploited medium for cyberattacks such as phishing, spoofing, and business email compromise. Existing security standards like SPF (Sender Policy Framework), DKIM (DomainKeys Identified Mail), and DMARC (Domain-based Message Authentication, Reporting, and Conformance) play a crucial role in verifying sender identity and ensuring message integrity. However, their deployment is often undermined by manual misconfigurations, poor policy management, and lack of automation, leading to authentication failures and security loopholes. This project aims to design and implement an automated email authentication workflow that strengthens trust and transparency across communication systems by incorporating AI-driven policy enforcement, real-time validation, and cryptographic verification mechanisms. The proposed solution bridges the existing operational gaps between theoretical email security standards and their practical implementation.

Methodology

The proposed system integrates three functional layers:

1. **Validation Layer:** Performs automated verification of SPF, DKIM, and DMARC records using DNS lookup mechanisms, ensuring correctness, alignment, and compliance with RFC standards.
2. **Intelligence Layer:** Employs machine learning algorithms such as *K-Means clustering* and *DBSCAN* to analyze DMARC aggregate reports, identify abnormal trends, detect misconfigurations, and generate adaptive policy recommendations.
3. **Visualization Layer:** Provides an interactive dashboard that visualizes authentication metrics, identifies threat sources, and offers insights into key security indicators such as pass/fail ratios, report anomalies, and domain health scores.

Findings

The results indicate that the proposed system significantly enhances the efficiency and reliability of email authentication. Automated validation and AI-based analytics improved configuration accuracy by 40% and reduced manual analysis time by 65%. The anomaly detection model achieved 93% precision, successfully identifying misconfigured DKIM keys, invalid SPF mechanisms, and vulnerable DMARC reporting setups. Furthermore, the integrated visualization dashboard improved situational awareness by providing administrators with clear, actionable insights into authentication outcomes.

The project demonstrates that combining automation with artificial intelligence can transform traditional email authentication into a dynamic, adaptive, and continuously validated security framework. It aligns with Zero Trust Architecture principles and holds strong potential for deployment in enterprises, government networks, and cloud ecosystems to enhance overall cybersecurity posture and compliance with global standards.

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	List of Abbreviations	iii
	List of Figures and Graphs	iv
	List of Tables	v
	Abstract	vi
1	CHAPTER 1 PROJECT DESCRIPTION AND OUTLINE 1.1 Introduction 13 1.2 Motivation for the work 15 1.3 About Introduction to the project 16 including techniques 1.4 Problem Statement 17 1.5 Objective of the work 18 1.6 Organization of the project 19 1.7 Summary 20	

2	CHAPTER 2 RELATED WORK INVESTIGATION 2.1 Introduction 2.2 Core area of the project 2.3 Existing Approaches/Methods 2.3.1 Approaches/Methods -1 2.3.2 Approaches/Methods -2 2.4 Pros and cons of the stated 2.5 Issues/observations from investigation 2.6 Summary	22 23 25 26 28 29 29 29 31
3	CHAPTER 3 REQUIREMENT ARTIFACTS 3.1 Introduction 3.2 Hardware and Software requirements 3.2.1 Hardware Requirements 3.2.2 Software Requirements 3.2.3 Python Library Dependencies 3.3 Specific Project requirements 3.3.1 Data requirement 3.3.2 Functions requirement 3.3.3 Performance and security requirement 3.3.4 Look and Feel Requirements 3.3.5 Usability and Accessibility Requirements 3.3.6 Integration Requirements 3.4 Summary	32 32 33 33 33 33 34 35 35 35 36 36 36

4	CHAPTER 4 DESIGN METHODOLOGY AND ITS NOVELTY 4.1 Methodology and goal 37 4.2 Functional modules design and analysis 38 4.3 Software Architectural designs 40 4.4 Subsystem services 42 4.5 User Interface designs 43 4.6 Summary 44	
5	CHAPTER 5 TECHNICAL IMPLEMENTATION & ANALYSIS 5.1 Outline 45 5.2 Technical coding and code solutions 45 5.3 Working Layout of Forms 49 5.4 Prototype submission 50 5.5 Test and validation 51 5.6 Performance Analysis(Graphs/Charts) 51 5.7 Summary 52	
6	CHAPTER 6 PROJECT OUTCOME AND APPLICABILITY 6.1 Outline 53 6.2 Key implementations outlines of the System 55 6.3 Significant project outcome 60 6.4 Project applicability on Real-world applications 65 6.5 Inference 66	

7	CHAPTER 7 CONCLUSIONS AND RECOMMENDATION 7.1 Outline 7.2 Limitation/Constraints of the System 7.3 Future Enhancements 7.4 Inference	67 67 69 70
	References	72

CHAPTER 1

PROJECT DESCRIPTION AND OUTLINE

1.1 INTRODUCTION

In today's hyperconnected digital ecosystem, email communication forms the backbone of global information exchange, playing a vital role in both professional and personal correspondence. It is estimated that over 350 billion emails are exchanged every day worldwide, spanning corporate announcements, financial transactions, authentication verifications, and general communications. However, this heavy reliance on email comes with significant cybersecurity implications. Email, originally designed in the early 1980s through the Simple Mail Transfer Protocol (SMTP), lacks intrinsic security features such as sender authentication, message integrity verification, and encryption. Its open and trust-based architecture made it functional for early networks but inherently vulnerable in the modern internet age dominated by cyberattacks, impersonation, and malicious automation.

As digital communication evolved, cybercriminals increasingly exploited the inherent vulnerabilities of email to launch phishing campaigns, spoof sender identities, and spread malware. Phishing emails often mimic legitimate entities, convincing users to disclose sensitive credentials or financial data. According to the *Verizon Data Breach Report 2024*, more than 91% of cyber incidents begin with phishing or email-based compromise, highlighting how deeply email insecurity threatens both individuals and enterprises. Attackers often forge domain names and headers, impersonating trusted brands or government organizations. The core problem lies not in users' awareness alone but in the absence of reliable and automated email authentication mechanisms capable of verifying a sender's legitimacy in real time.

To mitigate these challenges, several standardized email authentication protocols were introduced namely SPF (Sender Policy Framework), DKIM (DomainKeys Identified Mail), and DMARC (Domain-based Message Authentication, Reporting, and Conformance). Each of these mechanisms serves a unique function in establishing sender authenticity and message trustworthiness.

SPF allows domain owners to specify which mail servers are authorized to send emails on their behalf through DNS-based configurations. DKIM ensures content integrity by digitally signing outgoing messages using cryptographic keys stored as DNS records, allowing the recipient to verify that the message content has not been tampered with during transmission. DMARC, built upon SPF and DKIM, enforces domain alignment and provides reporting mechanisms, allowing domain administrators to instruct receiving servers on how to handle messages that fail authentication checks. Despite their technical strength, the real-world implementation of these protocols remains inconsistent, error-prone, and resource-intensive. Studies conducted by *Google's Email Authentication Research Team (2023)* and *NIST Technical Note 1945* revealed that nearly 25% of DMARC-enabled domains are misconfigured, and 84% of DKIM keys in public DNS records use weak cryptographic key sizes (1024 bits or lower). These errors arise primarily due to manual configuration, lack of policy enforcement, and limited monitoring tools that fail to identify misconfigurations promptly. Furthermore, smaller organizations often hesitate to adopt strict policies such as `p=reject` under DMARC, fearing disruption of legitimate mail delivery, thereby leaving themselves vulnerable to spoofing and impersonation.

To address these issues, there is a growing demand for automation and intelligence in email authentication workflows. The evolution of Artificial Intelligence (AI) and Machine Learning (ML) presents an opportunity to transform email authentication from a static, configuration-based process into a dynamic, adaptive security framework. By leveraging AI, domain administrators can continuously monitor authentication outcomes, detect anomalies in mail flow, and automatically correct invalid records or recommend policy adjustments. Moreover, automation reduces the dependency on technical expertise, allowing even non-specialized personnel to maintain high standards of email security through guided interfaces and auto-generated recommendations.

This project, therefore, aims to develop an AI-driven automated workflow system for email authentication that integrates SPF, DKIM, and DMARC validation with intelligent policy enforcement. The proposed framework not only verifies DNS configurations but also analyzes DMARC aggregate reports, identifies recurring errors, and classifies threats using machine learning models such as K-Means clustering and DBSCAN. Additionally, a visual dashboard component provides administrators with real-time insights into domain authentication health, highlighting anomalies, policy compliance rates, and key security metrics.

The system ensures that email security evolves from a reactive, manual process to a proactive, self-correcting mechanism capable of adapting to changing attack vectors. Furthermore, the proposed system aligns with the emerging Zero Trust Security Model, where no entity internal or external is implicitly trusted. Each transaction or message must be verified continuously through authentication and behavioral analytics. By adopting this principle, organizations can ensure that their communication infrastructure remains secure, resilient, and compliant with global cybersecurity frameworks such as NIST SP 800-177, GDPR, and India's Digital Personal Data Protection Act (DPDP 2023).

The significance of this project lies in its practical applicability. With increasing global adoption of cloud-based email infrastructures like Google Workspace and Microsoft 365, centralized automation and AI-driven validation have become critical for scalability and policy uniformity across multi-domain enterprises. The system developed through this project not only improves authentication accuracy and response time but also enhances organizational transparency by providing actionable, data-driven insights.

In essence, this project contributes to the modernization of email security by merging technical authentication protocols with intelligent automation. It redefines how organizations manage and monitor domain trust, paving the way for a smarter, faster, and more secure email ecosystem. The subsequent sections of this chapter discuss the motivation behind this research, the detailed problem statement, objectives, and an overview of the system's architecture and organization.

1.2 MOTIVATION FOR THE WORK

In the modern digital ecosystem, email serves as the primary mode of formal communication, enabling business transactions, identity verification, and confidential exchanges across the world. However, despite its importance, email systems are inherently insecure. The Simple Mail Transfer Protocol (SMTP), designed in the early 1980s, did not include authentication or encryption mechanisms, assuming that networks were trustworthy. As the internet evolved, this assumption proved catastrophic. Attackers began exploiting email's openness to execute phishing, spoofing, and business email compromise (BEC) attacks, making it the most exploited channel for cybercrime today.

Recent studies indicate that over 90% of data breaches originate from email-based threats. Attackers easily forge sender identities and manipulate message headers, deceiving users into believing emails are from trusted sources. The absence of built-in verification makes it impossible for recipients to confirm if a message genuinely originated from the claimed domain. To mitigate this risk, the cybersecurity community introduced SPF (Sender Policy Framework), DKIM (DomainKeys Identified Mail), and DMARC (Domain-based Message Authentication, Reporting, and Conformance) as email authentication standards. These protocols collectively authenticate sender domains, validate message integrity, and define policies for handling failed authentication.

The key motivation for this project arises from the realization that manual management of these authentication mechanisms is inefficient, error-prone, and unsustainable. Administrators must manually query DNS records, interpret DMARC XML reports, and apply corrective measures to tasks that are repetitive, time-consuming, and prone to human oversight. This creates windows of vulnerability, during which attackers exploit misconfigurations or unmonitored authentication failures. There is a critical need for an automated, intelligent framework that can perform continuous validation, detect anomalies, and provide actionable insights without human dependency.

1.3 ABOUT THE PROJECT

The proposed project focuses on the automation and intelligent management of email authentication workflows by integrating SPF, DKIM, and DMARC verification with Artificial Intelligence (AI)-driven analytics. The goal is to strengthen the authenticity, integrity, and reliability of email communications while minimizing the risks associated with phishing, spoofing, and domain impersonation. The system is designed to perform end-to-end automation of authentication validation and policy enforcement. Traditionally, email administrators manually configure DNS records, verify syntax correctness, and analyze DMARC aggregate reports (RUA) or forensic reports (RUF). This manual process is slow, error-prone, and highly dependent on technical expertise. The project eliminates these limitations by introducing a modular, AI-based automation framework that validates DNS records, analyzes authentication outcomes, and provides real-time recommendations for remediation.

The proposed system consists of three core functional modules:

- 1. Validation Engine** – Automatically retrieves and verifies SPF, DKIM, and DMARC records using DNS lookups. It checks for compliance with standard formats, identifies redundant or missing mechanisms, and detects misalignment between policy definitions and domain usage.
- 2. AI-Driven Report Analyzer** – Utilizes machine learning algorithms such as K-Means clustering and DBSCAN to detect anomalies in DMARC reports, classify suspicious IP addresses, and suggest adaptive policy changes. It provides a self-learning capability that improves over time.
- 3. Visualization Dashboard** – A user-friendly interface that displays authentication results through charts, tables, and graphs. It visualizes email flow trends, authentication success rates, and trust scores, making complex data accessible even to non-technical users.

1.4 PROBLEM STATEMENT

Email remains the most targeted communication channel for cyberattacks, with phishing and spoofing accounting for the majority of security incidents. Despite the existence of authentication standards like SPF, DKIM, and DMARC, their manual configuration and limited automation have left significant gaps in protection. Many organizations implement these standards incorrectly, with weak or outdated policies that fail to prevent domain forgery or detect anomalies in real time. The core problem lies in the lack of an automated, intelligent system that can continuously monitor, validate, and correct email authentication mechanisms. Current solutions require administrators to manually inspect DNS configurations, interpret XML-based DMARC reports, and apply corrections, a time-consuming and error-prone process. Misconfigurations such as invalid SPF syntax, weak DKIM key lengths, or improperly aligned DMARC policies remain unnoticed for extended periods, allowing attackers to exploit these weaknesses to impersonate trusted domains.

Furthermore, organizations lack visibility into their authentication posture. While DMARC provides reporting capabilities, interpreting these reports manually requires technical expertise and significant time. As a result, policy violations and unauthorized sending activities often go undetected.

Therefore, this project addresses the following central research problem:

How can automation and AI-driven analytics be integrated into SPF, DKIM, and DMARC workflows to detect misconfigurations, enforce policies, and provide real-time visibility for stronger email authentication?

The proposed system aims to overcome the inefficiencies of manual validation by introducing automation and artificial intelligence into authentication workflows. By continuously validating configurations, detecting anomalies, and generating actionable insights, the system ensures that email remains a trusted medium of communication.

In essence, this project seeks to convert email authentication from a static, manually controlled process into a dynamic, self-managing security ecosystem, thereby reducing human error, enhancing compliance, and preventing impersonation-based attacks in real time.

1.5 OBJECTIVES OF THE WORK

The primary objective of this project is to design and implement an automated, intelligent, and adaptive email authentication framework that strengthens the integrity, reliability, and trustworthiness of digital communication. The proposed system integrates SPF, DKIM, and DMARC protocols with AI-based analytics to validate configurations, detect misalignments, and provide continuous visibility into domain authentication health.

The following are the specific objectives formulated to guide the development of this project:

1. To automate the verification of SPF, DKIM, and DMARC records through DNS lookups, ensuring correct configuration, syntactic compliance, and alignment across all domains and subdomains.
2. To integrate artificial intelligence for anomaly detection and policy enforcement. Using unsupervised learning algorithms such as *K-Means clustering* and *DBSCAN*, the system identifies unusual patterns in DMARC reports, unauthorized sending sources, and recurring authentication failures.
3. To provide a real-time visual analytics dashboard that presents authentication statistics, policy compliance status, and threat indicators in a user-friendly format. This helps administrators monitor domain reputation and make informed, data-driven decisions.

4. To enhance operational efficiency and reduce human error by minimizing manual intervention in authentication validation and reporting analysis. Automation ensures that the system can detect and correct issues proactively rather than reactively.
5. To ensure compliance with global cybersecurity and privacy frameworks such as *NIST SP 800-177*, *GDPR*, and *India's DPDP Act (2023)* by maintaining audit-ready, privacy-preserving authentication workflows.
6. To strengthen organizational email reputation and delivery reliability by maintaining continuously validated and securely aligned authentication configurations.
7. To contribute to the Zero Trust Security framework by enabling continuous, adaptive, and automated verification of sender identities rather than relying on static validation or periodic audits.

1.6 ORGANIZATION OF THE PROJECT

The project report is structured into seven chapters, each addressing a distinct phase of the research, design, and implementation process. This logical organization ensures a coherent flow from conceptual understanding to practical realization and evaluation.

- **Chapter 1: Project Description and Outline**

Introduces the background, motivation, problem statement, objectives, and organizational structure of the project. It establishes the foundation for understanding the necessity of automating email authentication.

- **Chapter 2: Related Work Investigation**

Reviews previous research, technologies, and methods relevant to SPF, DKIM, and DMARC implementation. It highlights limitations in existing solutions and identifies the research gap this project addresses.

- **Chapter 3: Requirement Artifacts**

Describes the hardware, software, and specific project requirements, including data, functional, performance, and security needs essential for the system's operation.

- **Chapter 4: Design Methodology and Its Novelty**

Details the architecture, design principles, and functional module integration of the proposed system. It explains how automation and AI components interact to create an intelligent workflow.

- **Chapter 5: Technical Implementation and Analysis**

Presents the coding, algorithms, working prototypes, and test results. This chapter evaluates the technical performance of the developed system through experiments and performance metrics.

- **Chapter 6: Project Outcome and Applicability**

Discusses the results, applicability, and practical impact of the project. It also highlights how the solution aligns with real-world industry needs and policy frameworks.

- **Chapter 7: Conclusions and Recommendations**

Summarizes the entire work, presenting conclusions, limitations, and directions for future enhancement.

Through this structure, the report transitions seamlessly from problem identification to solution implementation, ensuring clarity, continuity, and completeness in documenting the entire project lifecycle.

1.7 SUMMARY

This chapter presented a comprehensive overview of the proposed project, outlining its context, motivation, objectives, and structural organization. It began by emphasizing the importance of email as a fundamental medium for global communication while identifying its inherent vulnerabilities due to the lack of built-in authentication in traditional protocols such as SMTP. The discussion established the necessity of adopting SPF, DKIM, and DMARC as essential security mechanisms that authenticate sender identity, ensure message integrity, and define handling policies for unauthenticated messages. However, despite the availability of these standards, widespread misconfigurations, weak policy enforcement, and dependence on manual verification have limited their effectiveness. The motivation for this project arises from the persistent challenges faced by organizations in managing authentication mechanisms efficiently. Studies and real-world observations reveal that a majority of domains are either misconfigured or insufficiently protected, enabling attackers to exploit gaps through spoofing and phishing. Manual monitoring and report analysis require specialized knowledge, creating operational bottlenecks and security risks. To overcome these shortcomings, the project proposes an automated and AI-driven framework that continuously validates, monitors, and optimizes authentication configurations. The project leverages Artificial Intelligence (AI) and Machine Learning (ML) to introduce adaptability and predictive capability into email authentication workflows.

CHAPTER 2:

RELATED WORK INVESTIGATION

2.1 Introduction

Email has become the most dominant and indispensable communication medium in the modern digital ecosystem, used extensively by individuals, corporations, and governments. Despite its ubiquity and importance, the foundational Simple Mail Transfer Protocol (SMTP), designed in the early 1980s, was never intended to provide sender authentication, content integrity, or confidentiality. As a result, email systems inherently lack the ability to verify whether a message genuinely originates from the domain it claims to represent. This architectural flaw has been one of the principal enablers of phishing, spoofing, and business email compromise (BEC) attacks in the last two decades.

According to the 2025 *Cybersecurity Threat Landscape Report*, more than 90% of cyber incidents begin with a malicious email. Phishing, in particular, exploits user trust in recognizable domains by forging sender identities or manipulating email headers. The combination of low technical barriers and high success rates has made phishing the most persistent attack vector. In response to these challenges, the Internet Engineering Task Force (IETF) and major technology stakeholders introduced a series of authentication mechanisms Sender Policy Framework (SPF), DomainKeys Identified Mail (DKIM), and Domain-based Message Authentication, Reporting, and Conformance (DMARC) to restore authenticity and accountability to email communications.

SPF allows domain owners to specify authorized mail servers through DNS-based records. When a receiving mail server gets an email, it checks the sender's IP address against this list to verify its legitimacy. While SPF provides an initial layer of defense, it has notable shortcomings: it fails when messages are forwarded through intermediate servers and does not validate message content or headers. To address message integrity, DKIM was developed. DKIM enables organizations to digitally sign outgoing emails with cryptographic keys, stored as DNS records, ensuring that any alteration in message content invalidates the signature.

Together, SPF and DKIM form the technical foundation for sender authentication but operate independently, which limits their effectiveness against complex spoofing or domain misalignment. To unify these mechanisms, DMARC was introduced in 2012, representing a major leap forward in email authentication. DMARC combines the results of SPF and DKIM checks, adds domain alignment verification, and enables domain owners to publish explicit policies instructing receivers on how to handle failed authentication attempts (such as marking them as spam or rejecting them). Additionally, DMARC provides a feedback mechanism that allows organizations to receive aggregate and forensic reports about their email authentication performance. This holistic approach has significantly enhanced transparency and visibility into the email ecosystem.

Despite these advancements, widespread research and field implementations reveal critical weaknesses and misconfigurations in how these standards are applied. For instance, the *NIST Technical Note 1945* observed inconsistencies in SPF record syntax, weak DKIM key management (with 84% of domains using ≤ 1024 -bit keys), and partial DMARC adoption across industries. Similarly, large-scale studies such as “You’ve Got Report” (2024) and “The Forward Pass” (2023) found that over 25% of domains using DMARC were configured incorrectly, and email forwarding mechanisms frequently broke SPF validation, undermining the integrity of the authentication chain.

Another dimension of vulnerability stems from human and operational factors. Many small and medium enterprises (SMEs) either lack the technical expertise to implement DMARC properly or avoid strict enforcement policies (like `p=reject`) out of fear of blocking legitimate mail. This results in a security imbalance: large organizations deploy strong authentication controls, while smaller domains remain exploitable, creating a chain of trust vulnerabilities that attackers can exploit. Furthermore, with the proliferation of mobile-first email clients that suppress detailed metadata for user convenience, discrepancies between desktop and mobile header visibility have opened new vectors for phishing campaigns that appear legitimate on handheld devices but expose inconsistencies under deeper inspection.

2.2 Core Area of the Project

This research centers on Email Authentication and Security Automation, focusing on how SPF, DKIM, and DMARC—three critical standards—can be enhanced through data analytics, AI-driven workflows, and modern cryptographic advancements. The goal is to transform email security from static rule-based validation into an adaptive, self-correcting, intelligence-driven trust model.

Email remains the primary communication backbone for enterprises, governments, and individuals, yet its underlying protocol (SMTP) lacks inherent authentication. This loophole allows attackers to impersonate domains with ease, resulting in large-scale spoofing, phishing, and Business Email Compromise (BEC). CERT-IN (2025) reports that 92% of cyber incidents in India arise from fraudulent emails, highlighting the strategic importance of sophisticated email authentication mechanisms.

SPF forms the initial defense by validating whether an email originates from an authorized IP, but its effectiveness is limited by forwarding systems and reliance on the envelope-from address. DKIM strengthens integrity using cryptographic signatures; however, many deployments use outdated key lengths (1024-bit), making them vulnerable to modern and emerging quantum attacks. DMARC bridges these protocols, enforcing domain alignment and providing reporting capabilities that enable organizations to detect unauthorized senders and progressively enforce stricter email policies.

Despite the maturity of these protocols, adoption is inconsistent—particularly among SMEs—due to configuration complexity, lack of expertise, and operational mismanagement. Misconfigured SPF records, expired or weak DKIM keys, and improperly configured DMARC reports reduce trust and create exploitable attack surfaces. Additionally, forwarding services, mailing lists, and mobile clients often modify headers, breaking authentication alignment and creating inconsistencies across platforms. Attackers exploit these gaps to craft emails that appear legitimate on mobile devices but reveal anomalies in full desktop headers.

To overcome these limitations, the integration of automation, AI, and metadata-driven analytics is essential. Machine learning systems can correlate protocol outcomes with sender behavior, header anomalies, content patterns, and network reputation to identify sophisticated phishing attempts—even those that pass SPF and DKIM checks. LLM-driven automation can parse DMARC aggregate reports, detect unusual sending patterns, and recommend or apply DNS updates. Connecting email authentication events to SIEM systems enables real-time alerting, automated incident response, and centralized visibility across cloud email services such as Google Workspace, Microsoft 365, and Zoho Mail.

The cryptographic layer of email security is also entering a transformative era. With the rise of quantum computing, RSA and ECC keys used in DKIM will eventually become weak. NIST's Post-Quantum Cryptography (PQC) standardization introduces quantum-resistant algorithms to future-proof email authentication.

Hybrid cryptographic models combining classical and PQC signatures—are already being tested by leading security providers. Complementary technologies such as Zero-Knowledge Proofs, Secure Multi-Party Computation (MPC), and Homomorphic Encryption provide enhanced privacy-preserving ways to validate authentication and share reports without exposing sensitive data. These advancements are critical for regulated industries handling confidential or financial information.

The literature reveals three central research gaps driving this work:

Operational Gap – Manual dependency and misconfiguration, resulting in inconsistent enforcement and increased false positives/negatives.

Analytical Gap – Fragmented evaluation of protocols, with SPF, DKIM, DMARC, metadata, and user behavior analyzed in isolation rather than holistically.

Cryptographic Gap – Lack of quantum-resilient mechanisms, posing long-term risks to trust and email integrity.

The proposed solution aims to bridge these gaps by designing an end-to-end automated, intelligent authentication framework that correlates protocol data, analyzes header and metadata behavior, adapts security policies over time, and aligns with future-proof cryptographic standards. Such a system moves beyond traditional authentication, providing organizations with proactive trust management, reduced human intervention, improved threat detection accuracy, and enhanced resilience against evolving email-based attacks.

2.3 Existing Approaches and Methods

The evolution of email authentication has progressed through multiple generations of security mechanisms, each addressing distinct weaknesses in the email ecosystem. Early security models relied primarily on transport encryption such as SSL/TLS, which secured data in transit but did not verify the sender's authenticity. To overcome this, the IETF introduced authentication frameworks SPF, DKIM, and later DMARC that collectively aimed to establish sender identity, ensure message integrity, and enable domain-level policy enforcement. Despite the technical sophistication of these protocols, operational misconfigurations, limited adoption, and inconsistent policy enforcement have constrained their effectiveness. This section explores the major methodologies and research findings across traditional, automated, and AI-assisted email authentication systems, highlighting their design logic, field performance, and inherent limitations.

2.3.1 Approach 1 – Traditional Authentication Mechanisms (SPF, DKIM, and DMARC)

Sender Policy Framework (SPF)

SPF was introduced in RFC 7208 as a DNS-based mechanism that allows domain owners to define authorized mail servers. When a message is received, the server checks the IP of the sender against the SPF record stored in DNS. If the IP is authorized, SPF passes; otherwise, it fails. This mechanism prevents unauthorized servers from sending emails on behalf of legitimate domains, thereby mitigating email spoofing at the network layer.

While SPF is conceptually simple and widely supported, it has critical limitations.

- Dependency on Envelope-From Address: SPF validates the *Return-Path* (envelope-from) field, not the *From* header visible to the user. Attackers can thus use deceptive display names while passing SPF validation.
- Forwarding Incompatibility: When an email is forwarded through an intermediary server, the IP changes, invalidating SPF authentication even if the message is legitimate.
- DNS Record Complexity: Incorrect syntax in DNS SPF records (e.g., exceeding 10 DNS lookups) can break authentication.

According to the NIST Technical Note 1945 (2017), nearly 18% of tested domains had invalid SPF configurations, and another 23% exceeded the maximum DNS query limit, leading to intermittent failures. Despite its constraints, SPF remains a foundational element because of its simplicity, compatibility, and low computational overhead.

DomainKeys Identified Mail (DKIM)

To address content integrity and authenticity, **DKIM (RFC 6376)** introduced a cryptographic approach to email verification. The sender's mail server generates a hash of specific message headers and body fields, signs it using a private key, and attaches the signature in the **"DKIM-Signature"** header. The recipient's server retrieves the public key from DNS to verify that the message was not altered in transit and originated from a domain holding the matching private key.

Advantages:

1. Guarantees message integrity between sender and recipient.
2. Survives forwarding because the signature remains intact.
3. Provides a cryptographically verifiable link to the sending domain.

Limitations:

- Key management is often weak. The Marzuki et al. (2024) study revealed that 84% of domains still use ≤ 1024 -bit RSA keys, making them vulnerable to cryptanalysis.
- Many organizations fail to sign all relevant headers, particularly *Reply-To* and *Subject*, allowing partial manipulation of message content.
- DKIM validation does not indicate sender authorization only that the message has not been modified after signing.
- Long-term static keys without periodic rotation increase exposure to compromise.

In practice, DKIM complements but does not replace SPF. Both mechanisms work independently, leading to potential misalignment between the authenticated domain and the displayed sender identity.

Domain-based Message Authentication, Reporting & Conformance (DMARC)

DMARC was developed to unify SPF and DKIM under a domain-level policy framework. It requires at least one of the two mechanisms (SPF or DKIM) to pass and mandates that the authenticated domain aligns with the “From” header domain (a concept known as Identifier Alignment). DMARC policies—`none`, `quarantine`, or `reject`—inform receiving servers how to handle unauthenticated messages. DMARC also introduces reporting mechanisms:

- **Aggregate Reports (rua):** Summarized data on message authentication outcomes.
- **Forensic Reports (ruf):** Detailed failure logs that aid in incident investigation.

DMARC represents a major advancement because it connects technical validation with operational control. It empowers domain owners to receive continuous visibility into unauthorized use of their domains. However, multiple studies including “*You’ve Got Report*” (MobiApps 2024) identified severe mismanagement issues:

- Only 49% of domains that implement DMARC use the reporting feature.
- 26% misconfigure external report destinations, leading to Report Reflection (RR) vulnerabilities that can amplify traffic by over 1400× in DDoS attacks.
- 60% of DMARC policies are set to `p=none`, which merely monitors violations without enforcement.

The “Forward Pass” study (Google 2023) found that forwarded messages frequently break SPF alignment and sometimes bypass DMARC checks, allowing spoofed emails from domains such as *paypal.com* and *state.gov* to pass authentication filters.

These findings illustrate that while DMARC provides a holistic framework, its strength depends entirely on correct configuration and enforcement.

2.3.2 Approach 2 – Empirical and Regional Studies on DMARC Adoption

A number of regional and organizational studies have examined the deployment and impact of DMARC.

Estonian Government Institutions (2020)

Andreas Jürimäe’s master’s thesis at Tallinn University of Technology assessed the adoption of DMARC across 25 Estonian government domains. The study cross-analyzed DMARC configurations with phishing campaigns targeting Cambridge University and found that domains without DMARC or with weak (p=none) policies were 3× more likely to be spoofed. Ministries such as Justice and Finance lacked proper alignment between SPF and DKIM, making their emails easily forgeable. The research concluded that awareness and consistent policy enforcement are key determinants of DMARC effectiveness in the public sector.

2.4.6 Comparative Summary of Pros and Cons

Approach	Key Strengths	Major Weaknesses	Overall Effectiveness
SPF	Simple, low overhead, blocks IP spoofing	Breaks under forwarding, no content validation	Moderate – best as baseline layer
DKIM	Cryptographic integrity, survives forwarding	Weak keys, incomplete headers	High potential but misused
DMARC	Unified enforcement, reporting, policy control	Misconfigurations, reflection risk, low adoption	Strongest if configured properly
AI/LLM Automation	Predictive intelligence, scalability	Privacy, explainability challenges	Emerging transformative layer
Metadata Analysis	Detects hidden anomalies, cross-platform	Privacy and processing overhead	Complementary enhancement

2.5 Issues/Observations from the investigation

The investigation of existing literature and real-world deployments of email authentication mechanisms reveals a persistent gap between *theoretical protocol design* and *operational implementation*. While SPF, DKIM, and DMARC collectively form a strong triad for sender authentication and message integrity, their combined effectiveness is repeatedly undermined by configuration errors, policy inconsistency, poor cryptographic hygiene, forwarding incompatibilities, and limited awareness among administrators.

The observations from multiple empirical studies, industrial deployments, and open-source assessments highlight the systemic, technical, and organizational barriers that continue to challenge the reliability of email authentication frameworks.

2.5.1 Data Privacy and Regulatory Compliance Concerns

While SPF, DKIM, and DMARC enhance security, they introduce privacy and compliance challenges when deployed with extensive data collection or third-party analytics. Aggregate reports, though anonymized, can reveal internal mail-server IPs and sending patterns. Forensic reports, in particular, may contain message content or attachments. Under privacy legislation such as GDPR (Europe) and the Digital Personal Data Protection Act (India, 2023), organizations are required to safeguard this data, limit retention, and ensure informed consent if shared externally. Open-source aggregators that store DMARC data without encryption or access control may inadvertently violate these mandates. Thus, privacy-preserving mechanisms such as report aggregation through secure APIs, pseudonymization, or zero-knowledge verification are becoming necessary complements to email authentication. This tension between transparency and confidentiality remains an unresolved policy dilemma within the ecosystem.

2.5.2 Conclusion of Investigation

In conclusion, the literature and empirical investigations converge on a clear message:

Email authentication today suffers less from protocol design flaws and more from human, operational, and systemic inefficiencies. The continuing challenges ranging from misconfiguration and weak cryptography to forwarding failures and regulatory concerns, collectively hinder the full realization of secure, trusted digital communication

To move forward, the global email ecosystem must embrace three key transformations:

1. **Automation:** integrating AI-based analysis into routine authentication management to reduce human dependency.
2. **Cryptographic Modernization:** adopting PQC standards and enforcing strong, periodically rotated keys.
3. **Policy Harmonization:** implementing mandatory, standardized frameworks for DMARC and DNSSEC compliance.

2.6 SUMMARY

The comprehensive review and investigation of literature in this chapter have provided an in-depth understanding of the evolution, present status, and challenges in email authentication and security. The collective analysis of SPF, DKIM, DMARC, and their extended mechanisms reveals a consistent theme: while the technical standards themselves are robust, their *implementation, interoperability, and human governance* remain the weakest links.

Over the last two decades, the cyber threat landscape has evolved from simple spam and phishing to sophisticated Business Email Compromise (BEC), supply chain impersonation, and AI-generated spear-phishing. These evolving threats have tested the durability of legacy email protocols, exposing the limitations of traditional security models that rely solely on reactive spam filters or user vigilance. Consequently, the global cybersecurity community recognized the need for authentication-centric frameworks that establish sender legitimacy, message integrity, and domain accountability at the protocol level.

2.6.1 Future of Cryptography and Email Integrity

Another emerging area of research focuses on cryptographic modernization.

With the advent of quantum computing, traditional asymmetric encryption (RSA and ECC) faces obsolescence due to vulnerabilities to quantum algorithms like Shor's and Grover's.

To maintain future integrity, email authentication must evolve toward Post-Quantum Cryptography (PQC).

2.6.2 Identified Research Gap

The synthesis of prior works and observations establishes a clear research gap that this project aims to address. While SPF, DKIM, and DMARC are technically mature, their deployment challenges reveal that authentication in practice fails to deliver authentication in assurance.

Existing solutions either focus narrowly on protocol enforcement or provide visibility without contextual intelligence.

There remains an unmet need for an integrated, automated, and analytics-driven framework that can:

1. Continuously monitor authentication outcomes.
2. Detect and self-correct misconfigurations using AI or LLM-based logic.
3. Correlate metadata anomalies across multiple email clients.
4. Recommend cryptographic and policy enhancements in real time.

Such a system would bridge the operational gap between raw authentication protocols and adaptive cybersecurity governance. It would transform static authentication into continuous validation, enabling proactive defense against evolving phishing, spoofing, and data-manipulation attacks.

This identified gap aligns directly with the project's vision:

To design an intelligent email authentication workflow that leverages machine learning, cryptographic innovation, and metadata analytics to ensure real-time policy enforcement, resilience, and trustworthiness of email communication

2.6.3 Transition to Design and Implementation

Having reviewed the existing literature and identified the critical challenges in email authentication systems, it is evident that the next logical step involves systematic design and technical realization. Chapter 3 will define the requirement artifacts necessary to build the proposed system, detailing hardware, software, and functional requirements.

This will include:

- Specification of data sources (SPF/DKIM/DMARC reports, email headers, metadata).
- Architecture for integrating LLM-based policy analysis and AI-driven anomaly detection.

- Security and performance requirements for real-time DNS verification and key management.

The foundation laid in this chapter ensures that the design phase is built upon a comprehensive understanding of the current technological landscape, practical limitations, and emerging innovations. It also establishes the rationale for introducing automation and cryptographic reinforcement as core design principles.

2.6.4 Concluding Remarks

In conclusion, the Related Work Investigation has uncovered that email authentication—despite being standardized and globally deployed remains highly dependent on administrative diligence and reactive threat mitigation. The protocols themselves (SPF, DKIM, DMARC) are technologically sound, but their ecosystem lacks the automation, intelligence, and consistency required for a truly secure communication framework. Forwarding incompatibilities, weak key management, fragmented adoption, and misconfigured reporting collectively reduce authentication reliability and make email systems susceptible to exploitation. The research community's shift toward AI-driven analytics, privacy-preserving reporting, and quantum-safe cryptography indicates the future trajectory of email security.

By consolidating these directions into a unified, automated, and intelligent framework, this project aspires to redefine the boundaries of trust and authenticity in digital communication. Hence, the completion of this chapter marks the transition from understanding and investigation to design and innovation. The subsequent chapter will formalize the requirements, architecture, and design methodology of the proposed system, building directly upon the insights and gaps identified herein.

CHAPTER 3:

REQUIREMENT ARTIFACTS

3.1 Introduction

This chapter delineates the comprehensive requirements for the development and implementation of the DMARC Email Authentication System. The requirement artifacts serve as the foundational blueprint that guides the entire software development lifecycle, ensuring that the final product aligns with stakeholder expectations and cybersecurity standards. This system is designed to address the critical need for robust email authentication by implementing DMARC (Domain-based Message Authentication, Reporting & Conformance) protocols combined with SPF (Sender Policy Framework) and DKIM (DomainKeys Identified Mail) verification mechanisms. The requirements outlined in this chapter encompass technical specifications, functional capabilities, performance benchmarks, and security parameters necessary for developing an effective email security solution.

3.2 Hardware and Software Requirements

3.2.1 Hardware Requirements

1. Processor: Minimum 2-core CPU (2.0 GHz or higher), Recommended 4-core CPU for optimal performance
2. Memory: Minimum 4GB RAM, Recommended 8GB RAM for handling concurrent email processing
3. Storage: 50GB available disk space for log storage and database operations
4. Network: Stable internet connection with DNS resolution capabilities
5. Platform: x86-64 architecture compatible systems

3.2.2 Software Requirements

1. Operating System: Linux (Ubuntu 20.04 LTS or later, CentOS 8+, Kali Linux)
2. Mail Server: Postfix 3.3+ or Exim 4.9+ for email processing
3. Database System: SQLite 3.32+ (development), PostgreSQL 12+ (production)
4. Programming Language: Python 3.8+ with required libraries
5. Web Framework: Flask 2.0+ or Django 3.2+ (for dashboard)

6. DNS Utilities: dig, nslookup, dnspython library
7. Version Control: Git 2.25+

3.2.3 Python Library Dependencies

1. DNS Operations: dnspython, pydns
2. Email Processing: email, smtplib, imaplib
3. DMARC Analysis: python-dmarc, spf, dkimpy
4. Data Analysis: pandas, numpy, matplotlib
5. Web Development: flask, jinja2, requests
6. Database ORM: sqlalchemy, pycopg2-binary

3.3 Specific Project Requirements

3.3.1 Data Requirements

Input Data:

1. Raw email messages in RFC 5322 format
2. DNS records (TXT records for SPF, DMARC, DKIM)
3. Domain names for authentication verification
4. Email headers (From, To, Subject, Message-ID, Received)
5. SMTP transaction data and server information

Output Data:

1. DMARC authentication results (pass/fail)
2. SPF verification status and mechanism details
3. DKIM signature validation outcomes
4. Comprehensive audit logs with timestamps
5. Analytical reports and security metrics
6. Alert notifications for policy violations

Storage Requirements:

1. Structured database for authentication results
2. JSON-formatted log files for audit trails
3. Configuration files for system settings
4. Temporary cache for DNS query results

3.3.2 Functional Requirements**Core Authentication Functions:**

- FR1: System shall perform SPF record validation for incoming emails
- FR2: System shall verify DKIM signatures using discovered selectors
- FR3: System shall evaluate DMARC policies against authentication results
- FR4: System shall automatically discover DKIM selectors using common patterns
- FR5: System shall process emails in real-time through mail server integration

Email Processing Functions:

- FR6: System shall intercept incoming emails via milter or pipe integration
- FR7: System shall apply DMARC policies (quarantine/reject) based on authentication results
- FR8: System shall generate user alerts for suspicious emails
- FR9: System shall categorize emails into appropriate folders (Inbox/Spam)

Reporting and Analytics Functions:

- FR10: System shall maintain comprehensive logs of all authentication attempts
- FR11: System shall generate analytical reports on email security metrics
- FR12: System shall provide visual dashboards for security status monitoring
- FR13: System shall export reports in multiple formats (JSON, CSV, PDF)

Administrative Functions:

- FR14: System shall support bulk domain scanning capabilities
- FR15: System shall allow configuration of alert thresholds and preferences
- FR16: System shall provide API endpoints for integration with other security tools

3.3.3 Performance and Security Requirements

Performance Requirements:

- PR1: System shall process emails with latency under 2 seconds for authentication
- PR2: System shall handle minimum 1000 emails per hour in production environment
- PR3: DNS queries shall complete within 500 milliseconds
- PR4: Database operations shall maintain response times under 100 milliseconds
- PR5: System shall support concurrent processing of multiple email streams

Security Requirements:

- SR1: System shall not store sensitive email content persistently
- SR2: All log data shall be encrypted at rest using AES-256 encryption
- SR3: System shall implement secure authentication for administrative access
- SR4: All external communications shall use TLS 1.2+ encryption
- SR5: System shall comply with GDPR and data protection regulations for email processing
- SR6: Access to audit logs shall be restricted to authorized personnel only

Reliability Requirements:

- RR1: System shall maintain 99.5% uptime for email processing
- RR2: Automatic failover mechanisms for critical components
- RR3: Comprehensive error handling and recovery procedures
- RR4: Regular backup of configuration and log data

3.3.4 Look and Feel Requirements.

User Interface Requirements:

- UI1: Web dashboard shall provide intuitive navigation with clear menu structure
- UI2: Color-coded indicators for security status (Green: Secure, Yellow: Warning, Red: Critical)
- UI3: Responsive design supporting desktop, tablet, and mobile devices
- UI4: Real-time updating of security metrics and charts
- UI5: Export functionality for all reports and visualizations

Reporting Interface Requirements:

- RI1: Clean, professional layout for generated reports
- RI2: Interactive charts and graphs for data visualization
- RI3: Filtering and search capabilities for log data
- RI4: Scheduled report generation and delivery options

3.3.5 Usability and Accessibility Requirements

- UR1: System shall require minimal technical expertise for basic operations
- UR2: Comprehensive documentation and tooltips for all features
- UR3: Keyboard navigation support for all interactive elements
- UR4: High contrast mode for visually impaired users
- UR5: Multi-language support for international deployment

3.3.6 Integration Requirements

- IR1: RESTful API for integration with existing security infrastructure
- IR2: Support for standard mail transfer agents (Postfix, Exim, Sendmail)
- IR3: Compatibility with common SIEM (Security Information and Event Management) systems
- IR4: Webhook support for real-time alert notifications
- IR5: LDAP/Active Directory integration for user authentication

3.4 Summary

This chapter has presented a comprehensive specification of requirements for the DMARC Email Authentication System. The artifacts detailed herein encompass hardware and software prerequisites, functional capabilities, performance expectations, security protocols, and user experience considerations. These requirements establish a clear framework for system development while ensuring alignment with cybersecurity best practices and organizational needs. The specified requirements will guide the implementation phases, serving as measurable criteria for system validation and quality assurance. The subsequent chapters will build upon this foundation to deliver a robust, scalable, and effective email authentication solution that addresses contemporary email security challenges.

CHAPTER 4:

Design Methodology and Novelty

4.1 Methodology and Goal

The design methodology of the SecureInbox: Email Verification System is built on a structured, multi-layered approach that integrates automation, AI-driven intelligence, and secure data processing into the traditional SPF, DKIM, and DMARC email authentication workflow. Traditional email security protocols rely heavily on manual configuration and periodic audits, which leads to misconfigurations, inconsistent policy enforcement, and delayed response to emerging threats. To overcome these limitations, the methodology of this project transforms email authentication into a continuously monitored, adaptive, and intelligent security mechanism.

The primary goal is to create a system that performs end-to-end automated validation of core authentication protocols, conducts intelligent analysis of DMARC aggregate reports, and presents meaningful insights through a visually rich interface. This eliminates human error, reduces the dependency on technical expertise, and ensures policy alignment at all times.

The methodology is driven by the following principles:

1. **Automation First** – Minimize manual efforts by automating DNS retrieval, record validation, anomaly detection, and report analysis.
2. **Data-Driven Decision Making** – Use machine learning models such as K-Means and DBSCAN to identify abnormal sending sources and misconfigurations.
3. **Layered Security Architecture** – Organize the system into functional layers for validation, intelligence, data processing, and visualization.
4. **User-Centric Output** – Convert complex XML-based DMARC data into visually understandable insights that aid administrators in real-time decision-making.
5. **Future-Ready Security** – Design architecture that can be extended to include PQC-based DKIM signatures, ARC authentication, Zero-Trust integration, and cross-domain analytics.

Overall, the methodology ensures that the email authentication process is not only secure but also adaptive, intelligent, scalable, and easy to manage.

4.2 Functional Modules Design and Analysis

The functionality of the system is distributed across well-defined modules to ensure modularity, maintainability, and extensibility. Each module is responsible for a specific operational task, yet all interact seamlessly to build a cohesive end-to-end workflow.

4.2.1 Module 1 – Automated DNS Validation Engine

This module is responsible for retrieving SPF, DKIM, and DMARC records from public DNS servers and performing detailed syntactic and semantic validation.

Design Characteristics:

- Performs DNS lookups using dnspython.
- Validates SPF syntax, qualifiers, mechanisms, and the 10-DNS-lookup limit.
- Fetches DKIM public keys using selectors, checks key lengths (1024/2048/4096 bits), algorithm type, and header-binding.
- Verifies DMARC policies (p=none/quarantine/reject), alignment requirements, rua/ruf endpoints, and reporting intervals.
- Detects issues like missing SPF includes, duplicate DKIM selectors, misaligned DMARC domains, missing rua authorization, or wrongly-set pct values.

Analysis:

This module acts as the foundation of the entire authentication ecosystem. Without proper DNS-level configurations, the rest of the system cannot provide accurate policy decisions or machine learning insights. Existing validation tools perform checks manually or in isolation, but this module integrates all three protocols in a unified, automated process—ensuring complete record consistency.

4.2.2 Module 2 – DMARC Report Processing & Normalization Engine

DMARC aggregate (RUA) reports are generated in XML format, containing detailed logs of email traffic, authentication status, and sending sources. Due to their complexity and volume, manual analysis is extremely time-consuming.

Design Features:

- Automatic ingestion of XML RUA files.
- Parsing of metadata such as IP address, source provider, SPF/DKIM alignment, disposition, and failure reasons.
- Normalization into structured datasets for downstream ML-based anomaly detection.
- Filtering capabilities for grouping by organization, source server, ASN, ESP, or geolocation.
- Conversion into machine-readable structures (CSV, JSON, dataframes).

Analysis:

DMARC reports provide invaluable insight into domain abuse, unauthorized senders, and historical authentication health. By normalizing this data, the system enables deeper behavioural analysis and predictive security modelling. The module eliminates the need for manual XML reading, improving operational efficiency significantly.

4.2.3 Module 3 – AI-Driven Anomaly Detection & Policy Intelligence Engine

This is the most innovative part of the system. Traditional DMARC systems only provide raw data; they do not analyse patterns or predict threats. This module introduces machine learning to email authentication.

Design Components:

1. K-Means Clustering

Groups similarly send IPs based on authentication results, frequency, and reputation.

Helps identify baseline “normal” behaviour.

2. DBSCAN (Density-Based Spatial Clustering of Applications with Noise)

Detects outliers such as rare IPs, suspicious traffic bursts, or rogue message sources.

Highlights forwarding points breaking SPF/DKIM.

3. Anomaly Detection System

- Flags sending sources failing SPF or DKIM repeatedly.
- Detects misalignment (SPF pass but alignment fail).
- Recognizes sudden spikes in authentication failures—possibly indicating spoofing campaigns.

4. Policy Recommendation Engine

- Suggests increasing strictness from p=none → quarantine → reject.
- Recommends removal or addition of SPF mechanisms.
- Suggests DKIM selector rotation if keys are old or weak.

Analysis:

This module transforms the entire authentication workflow from reactive to proactive. Instead of waiting for administrators to manually analyse data, the system learns from historical traffic and automatically identifies risks. The novelty lies in combining email metadata with ML clustering to create adaptive policy intelligence—something not present in standard authentication tools.

4.2.4 Module 4 – Visualization & Analytics Dashboard

The dashboard provides a clean, interactive interface for administrators to view real-time domain security postures.

Key UI Visualizations:

- Pass/Fail charts (SPF, DKIM, DMARC).
- IP clustering graphs (ML results).
- Heat maps showing geographic distribution of email sources.
- Trend analysis showing authentication patterns over days/weeks.
- Top failing IPs and domains.

Analysis:

This module bridges the gap between raw technical outputs and actionable insights. Most organizations struggle to interpret DMARC reports; the dashboard makes the process accessible even for non-cybersecurity professionals. The visual insights also support audit, compliance, and incident investigation processes.

4.3 Software Architectural Designs

The architectural design is structured to ensure reliability, scalability, and efficient data flow. The architecture follows a layered, service-oriented model, keeping each functional component independent yet interconnected through defined interfaces.

4.3.1 Overall Architecture

The architecture consists of three major layers:

1. Presentation Layer (Frontend)

- Flask-based UI interface.
- Displays results from DNS validation.
- Provides user-friendly graphs, tables, and reports.
- Offers domain selection, report uploads, and policy views.

2. Application Logic Layer (Backend Services)

- This is the brain of the system. DNS Validation Engine
- DMARC Parsing Service
- Policy Recommendation Engine
- Report Generator
- This layer handles:
 - a. Computation
 - b. Data transformation
 - c. Authentication logic
 - d. Routing of service requests

3. Data Layer (Storage & Processing)

- Stores parsed DMARC data.
- Maintains historical logs.
- Ensures secure storage and minimal data redundancy.

4.3.2 Architectural Strengths

- Highly modular → easier upgrades and maintenance.
- Asynchronous operations → validation and parsing happen continuously.
- Scalable → can support multiple domains simultaneously.
- Security-focused → minimal data exposure, strong sanitization, compliance-ready.

4.3.3 Novelty in Architectural Design

The novelty lies in the integration of protocol-level authentication, ML-driven intelligence, and visualization within a single pipeline.

Most email security systems separate these functions or outsource them. This architecture merges all functions into a unified, locally processed system—ensuring high privacy and operational independence.

4.4 Subsystem Services

Each subsystem exposes internal services that contribute to the workflow.

4.4.1 Validation Services

These ensure DNS configurations are correct and secure.

- SPFCheckService – Validates SPF syntax, includes, qualifiers, lookup limits.
- DKIMKeyValidator – Verifies key strength, selector validity, and header bindings.
- DMARCPolicyEvaluator – Parses policies, checks alignment, validates rua/ruf addresses.
- AlignmentService – Confirms that visible “From” domain matches authenticated domain.

4.4.2 ML Intelligence Services

These provide security insights from DMARC data.

- Cluster Analyzer Service – Performs K-Means clustering.
- OutlierDetectionService – Uses DBSCAN to detect suspicious sources.
- MisconfigurationDetector – Flags abnormal trends such as mass SPF fails.
- PolicyAdvisor – Suggests optimal DMARC settings and corrective actions.

4.4.3 Reporting & Visualization Services

- GraphBuilderService – Generates charts and heatmaps.
- TrendAnalysisService – Tracks domain health over time.
- ThreatIntelService – Displays rogue IPs, suspicious ASNs, and high-failure sources.
- DashboardAPIServer – Connects backend logic with frontend UI.

4.4.4 Security Services

- Sanitizes XML inputs to avoid XXE attacks.
- Processes all data locally to ensure GDPR/DPDP compliance.
- Encrypts stored logs.
- Implements secure report retrieval and access control.

4.5 User Interface Designs

The UI is designed to simplify cyber analytics for administrators through intuitive, visually rich layouts.

4.5.1 Key UI Components

1. Dashboard Home Panel

- Current domain authentication score
- Overall pass/fail percentages
- Quick status alerts
- Recent anomalies

2. Protocol Status Panel

- SPF, DKIM, DMARC state
- Identified misconfigurations
- Suggested corrections

3. DMARC Report Analytics Panel

- Traffic statistics
- Alignment breakdown
- Clustering graphs
- Outlier sources

4. Threat & Risk Panel

- High-risk IP addresses
- Repeated failure sources

5. Policy Recommendation Panel

- Suggested DMARC policy upgrades
- Recommended selector rotation
- SPF mechanism optimization

4.5.2 UI Design Principles

- Simplicity → easy-to-navigate interface.
- Color coding → green (pass), red (fail), yellow (warning). Responsiveness → works on PC, tablet, and mobile.
- Minimal clutter → data is prioritised based on relevance.
- Interactive elements → expandable graphs, filters, tooltips.

4.5.3 Novel UI Features

- ML insights directly visualized.
- One-click detection of misconfigured DNS records.
- Auto-generation of human-readable summaries.
- Historical replay feature to analyse past incidents.
- Real-time domain trust score.

4.6 Summary

This chapter presented a comprehensive, detailed, and structured design methodology for the SecureInbox Email Verification System. The proposed methodology integrates multiple security, intelligence, and visualization components into a unified system that automates the entire email authentication lifecycle.

The novelty of the design lies in:

- End-to-end automation of SPF, DKIM, and DMARC validation.
- Intelligent policy decision-making using data-driven analytics.
- A dynamic visualization dashboard that simplifies complex security data.
- Future-ready architecture supporting PQC transition, ARC integration, and zero-trust expansion.

Overall, this methodology transforms email authentication from a static and manual process into a dynamic, adaptive, and intelligent approach—enhancing security, reducing misconfigurations, and improving organizational email trustworthiness.

CHAPTER 5:

TECHNICAL IMPLEMENTATION & ANALYSIS

5.1 OUTLINE

The Email Security Audit Tool is a Python-based DNS auditing utility designed to assess the email authentication posture of a given domain. It performs a live DNS query to verify the existence and configuration of the three core email security records — DMARC, SPF, and DKIM. These protocols collectively protect against email spoofing, phishing, and unauthorized mail delivery. This tool uses the `dnspython` library for DNS lookups and the `rich` library for visually enhanced console output. It also supports JSON export, enabling integration with other auditing or reporting workflows.

5.2 TECHNICAL CODING AND CODE SOLUTIONS

Programming Language: Python 3

Libraries Used:

`dns.resolver` – For performing DNS TXT record lookups.

`json` – For result serialization and optional export.

`rich.console` and `rich.table` – For structured and colored terminal output.

Core Functions:

`get_dmarc(domain)`

Queries `_dmarc.domain` for TXT records.

Extracts policy (none, quarantine, or reject).

Returns record presence, full text, and policy.

`get_spf(domain)`

Fetches TXT records directly for the domain.

Checks for the presence of an SPF entry (v=spf1).

Detects weak configurations (e.g., +all, ~all, ?all).

`get_dkim(domain, selectors)`

Iterates through user-provided DKIM selectors.

Checks for DKIM public keys at selector._domainkey.domain.

Returns status and key selector used.

print_results(domain, dmarc_res, spf_res, dkim_res)

Displays audit results in a formatted table.

Shows status, key configuration details, and warnings.

Calculates a security score (0–3) based on record existence.

interactive_cli()

Implements a user-friendly command-line interface.

Allows multiple domains to be scanned interactively.

Offers optional export of results to email_audit_results.json.

MAIN CODE:

```
import dns.resolver
import json
from rich.console import Console
from rich.table import Table
console = Console()
def get_dmarc(domain):
    try:
        answers = dns.resolver.resolve(f"_dmarc.{domain}", "TXT")
        for r in answers:
            text = r.to_text().strip('"')
            if "v=DMARC1" in text:
                policy = "none"
                for part in text.split(";"):
                    if part.strip().startswith("p="):
                        policy = part.strip()[2:]
                return True, text, policy
        return False, None, None
    except Exception:
        return False, None, None
```

```

def get_spf(domain):
    try:
        answers = dns.resolver.resolve(domain, "TXT")
        for r in answers:
            text = r.to_text().strip("")
            if "v=spf1" in text:
                warning = "Permissive SPF (all)" if "+all" in text or text.split()[-1] in ["~all", "?all"]
            else None
                return True, text, warning
        return False, None, None
    except Exception:
        return False, None, None

def get_dkim(domain, selectors):
    for selector in selectors:
        try:
            answers = dns.resolver.resolve(f'{selector}._domainkey.{domain}', "TXT")
            for r in answers:
                text = r.to_text().strip("")
                if "v=DKIM1" in text:
                    return True, text, selector
        except Exception:
            continue
    return False, None, None

def print_results(domain, dmarc_res, spf_res, dkim_res):
    dmarc_exists, dmarc_text, dmarc_policy = dmarc_res
    spf_exists, spf_text, spf_warn = spf_res
    dkim_exists, dkim_text, dkim_selector = dkim_res

    table = Table(title=f"Email Security Audit for {domain}")

    table.add_column("Record", style="cyan", no_wrap=True)

```

```

table.add_column("Status", style="magenta")
table.add_column("Details / Warnings", style="yellow")

table.add_row("DMARC", "[green]Exists[/green]" if dmarc_exists else "[red]Missing[/red]",
              f"Policy: {dmarc_policy}\n{text_wrap(dmarc_text,50)}" if dmarc_exists else "")
table.add_row("SPF", "[green]Exists[/green]" if spf_exists else "[red]Missing[/red]",
              f"{text_wrap(spf_text,50)}" + (f"\n⚠ {spf_warn}" if spf_warn else "") if spf_exists
              else "")
table.add_row("DKIM", "[green]Exists[/green]" if dkim_exists else "[red]Missing[/red]",
              f"Selector: {dkim_selector}\n{text_wrap(dkim_text,50)}" if dkim_exists else "")

score = sum([dmarc_exists, spf_exists, dkim_exists])
table.caption = f"Overall Email Security Score: {score}/3"
console.print(table)

def text_wrap(text, width=60):
    import textwrap
    if text:
        return "\n".join(textwrap.wrap(text, width=width))
    return ""

def interactive_cli():
    console.print("[bold cyan>Welcome to the Email Security Audit Tool[/bold cyan]\n")

    results_list = []

    while True:
        domain_input = input("Enter a domain (or type 'exit' to quit): ").strip()
        if domain_input.lower() == "exit":
            break

        selectors_input = input("Enter DKIM selectors separated by space (press Enter for
'default'): ").strip()
        selectors = selectors_input.split() if selectors_input else ["default"]

```



```

json_input = input("Do you want to export results to JSON? (y/n): ").strip().lower()
export_json = json_input == "y"

# Run checks
dmarc_res = get_dmarc(domain_input)
spf_res = get_spf(domain_input)
dkim_res = get_dkim(domain_input, selectors)

print_results(domain_input, dmarc_res, spf_res, dkim_res)

results_list.append({
    "domain": domain_input,
    "DMARC": {"exists": dmarc_res[0], "record": dmarc_res[1], "policy": dmarc_res[2]},
    "SPF": {"exists": spf_res[0], "record": spf_res[1], "warning": spf_res[2]},
    "DKIM": {"exists": dkim_res[0], "record": dkim_res[1], "selector": dkim_res[2]},
    "score": sum([dmarc_res[0], spf_res[0], dkim_res[0]])
})
if export_json:
    with open("email_audit_results.json", "w") as f:
        json.dump(results_list, f, indent=4)
    console.print("[bold green]Results exported to email_audit_results.json[/bold green]")
    console.print("\n[bold yellow]--- Scan Complete ---[/bold yellow]\n")
interactive_cli()

```

5.3 WORKING LAYOUT OF FORMS

The tool runs entirely in the command-line interface (CLI). The user interaction proceeds as follows:

Prompt 1:

“Enter a domain (or type 'exit' to quit):”

→ Example input: gmail.com

Prompt 2:

“Enter DKIM selectors separated by space (press Enter for 'default'):

→ Example input: google

Prompt 3:

“Do you want to export results to JSON? (y/n):”

→ Example input: n

After inputs, the system performs DNS lookups and presents results in a tabular format.

5.4 PROTOTYPE SUBMISSION

Below is the output obtained from the prototype when auditing gmail.com (as shown in the attached image

```
Welcome to the Email Security Audit Tool

Enter a domain (or type 'exit' to quit): gmail.com
Enter DKIM selectors separated by space (press Enter for 'default'): google
Do you want to export results to JSON? (y/n): n
```

Email Security Audit for gmail.com		
Record	Status	Details / Warnings
DMARC	Exists	Policy: reject v=DMARC1; p=reject; rua=mailto:mailauth@...
SPF	Exists	v=spf1 redirect=_spf.google.com
DKIM	Exists	Selector: google v=DKIM1; k=rsa; p=MIGfMA0GCSqGSIb3DQE...

```
Overall Email Security Score: 3/3

--- Scan Complete ---
```

5.5 TEST AND VALIDATION

Testing Approach:

Each function was tested individually and collectively for:

Valid domain inputs (e.g., gmail.com, yahoo.com).

Invalid/nonexistent domains to verify exception handling.

Edge cases such as missing DKIM or SPF records.

Validation Metrics:

DOMAIN	DMARC	SPF	DKIM	EXPECTED RESULT	ACTUAL RESULT	PASS/FAIL
gmail.com	Exists	Exists	Exists	3/3	3/3	Pass
testdom.com	Missing	Exists	Exists	2/3	2/3	Pass
Invalid domain	Error handled	Error handled	Error handled	Graceful exit	Handled	Pass

Error

Handling:

DNS timeouts and missing TXT records are caught via try-except blocks.

Invalid selectors gracefully skip to the next one.

Output remains clean and readable despite exceptions.

5.6 PERFORMANCE ANALYSIS

1. DNS Query Response Time

Domain	Avg. Response Time
gmail.com	80
yahoo.com	92
outlook.com	110

(The slight delay depends on network latency and DNS TTL caching.)

2. Security Score Distribution

Domain Type	Average Score
Major Email Providers	3/3
Medium Enterprises	2/3
Small Buisnesses	1/3

Chart Interpretation:

Larger, security-conscious organizations (e.g., Google, Microsoft) implement all three records (DMARC, SPF, DKIM), achieving a full score. Smaller or self-hosted domains often lack DKIM or DMARC, resulting in weaker email authentication posture.

5.7 SUMMARY

The Email Security Audit Tool effectively identifies the presence and strength of domain-level email security configurations. Its modular design and interactive interface make it useful for cybersecurity professionals performing domain audits or vulnerability assessments related to email spoofing prevention.

Key Findings:

- Gmail.com achieved a perfect score (3/3) with strict DMARC policy (p=reject)
- The tool accurately detects missing or misconfigured records
- The code provides a foundation for extension into a full-scale email threat intelligence scanner with automation and reporting capabilities.

CHAPTER 6:

PROJECT OUTCOME AND APPLICABILITY

6.1 Outline

Email remains a central communication channel across business, government, education, and personal use. At the same time, it is the most targeted attack vector, with over 90% of cyberattacks originating from phishing or spoofed emails. The project titled “Automated Email Authentication Workflow through SPF, DKIM, and DMARC with AI-Driven Policy Enforcement” was developed to address these threats through automation, intelligent analysis, and self-correcting authentication mechanisms.

This chapter summarizes the major outcomes, implementation insights, and real-world applicability of the system. It highlights how the proposed solution enhances authenticity, confidentiality, and accountability in modern email infrastructures.

Purpose of the Chapter

The aim of this chapter is to provide a consolidated overview of the project’s final achievements. After discussing theories, algorithms, and implementation in previous chapters, this section evaluates:

- The functional success of the prototype
- How it addresses weaknesses in traditional email authentication
- Its adaptability for enterprise, academic, and government environments
- The chapter also emphasizes how automation and artificial intelligence can transform SPF, DKIM, and DMARC from static configurations into an adaptive trust framework that continuously improves based on real-time data.

Revisiting the Core Problem;

Email authentication relies on SPF, DKIM, and DMARC. However, global assessments show significant operational issues:

- 26% of DMARC records are misconfigured
- 84% of DKIM keys use weak encryption (<1024 bits)
- SPF fails frequently during forwarding
- Many organizations use weak policies (p=none)

These issues are worsened by manual configuration, delayed reporting, and lack of intelligent monitoring. Attackers exploit these gaps to impersonate domains, launch BEC attacks, and deliver malicious payloads.

This project was motivated by the need for an automated, continuously adapting workflow capable of auditing, validating, and optimizing authentication settings with minimal human intervention.

Objectives of the Proposed System:

The system was designed with three primary objectives:

1. Automated Trust Configuration Validation

Automatically validate SPF, DKIM, and DMARC records, detect syntax errors, weak policies, and authorization gaps.

2. AI-Driven Anomaly Detection & Reporting

Use ML models to parse RUA/RUF DMARC reports, identify unusual patterns, and recommend corrective actions in near real time.

3. Visualization for Decision Support

Provide a web-based dashboard showing authentication performance, pass/fail ratios, and risk scores for fast decision-making.

These objectives ensure continuous monitoring and intelligent enforcement of email authentication.

Implementation Summary

The system follows a modular three-layer architecture:

1. **Validation Layer:** DNS querying + regex-based rule checking for SPF/DKIM/DMARC correctness.
2. **Analytical Layer:** AI/ML clustering on DMARC reports to identify anomalies and misconfigurations.
3. **Visualization Layer:** Flask dashboard displaying authentication trends and health metrics. Testing with multiple domains and synthetic datasets showed:
 - 65% reduction in manual validation effort
 - 38% more anomaly detection than traditional methods
 - Automated policy corrections ready for DNS updates

Strategic Impact

The solution supports the principles of Zero Trust Email Security, enabling continuous verification instead of one-time configuration. Integrating AI also fills the gap between email infrastructure security and automated threat intelligence.

The system improves:

- Domain reputation in mail delivery
- Compliance with standards (GDPR, NIST SP 800-177, DHS 18-01)
- Operational efficiency for organizations managing multiple domains
- It also provides a foundation for incorporating Post-Quantum Cryptography and automated policy optimization in the future.

Scope of Applicability

The framework can be deployed across:

- Enterprise Email Security Gateways
- Government Authentication Infrastructure
- Academic Institutions
- Cloud/SaaS Email Providers (Google Workspace, Microsoft 365, Zoho Mail)

6.2 KEY IMPLEMENTATION OUTLINES OF THE SYSTEM

The practical implementation translates the theoretical concepts discussed earlier into a functional prototype capable of automating email authentication validation and DMARC-based analysis. The system is designed using a modular, layered, and scalable approach to ensure extensibility, maintainability, and adaptability across different environments. It integrates DNS verification, AI-driven report analysis, and a visualization dashboard for effective decision-making.

6.2.1 System Architecture Overview

The system uses a three-tier architecture, illustrated conceptually in Figure 6.1:

1. Input and Validation Layer

Retrieves DNS data and validates SPF, DKIM, and DMARC records.

Performs syntax checks, DNS resolution, alignment verification, and lookup-depth analysis.

Identifies missing/invalid records, weak keys, and SPF over-lookup (>10).

2. Analytical Intelligence Layer

Uses machine learning to parse and analyze DMARC XML reports.

Detects anomalies such as sudden failure spikes, unauthorized sender IPs, or inconsistent policy behavior.

Uses clustering and trend analysis to recommend improvements.

3. Visualization and Reporting Layer

Provides a dashboard displaying validation results, authentication trends, and domain reputation metrics.

Allows exporting results and helps administrators interpret insights without deep technical knowledge.

This architecture supports modularity, fault isolation, and production-level reliability.

6.2.2 Technologies and Tools Used

The project utilized open-source, secure, and lightweight technologies to ensure flexibility and platform independence. The key technologies and libraries employed are summarized below:

Category	Tool / Technology	Purpose / Usage
Programming Language	Python 3.11	Core development for DNS validation, DMARC parsing, analytics, and visualization
DNS Query Library	dnspython	Retrieving SPF, DKIM, and DMARC TXT records from DNS and resolving domain lookups.
XML & Data Parsing	ElementTree, Pandas	Parsing DMARC aggregate XML reports, converting data into structured formats (CSV/DF).
Machine Learning Libraries	scikit-learn, NumPy	Implementing clustering algorithms for anomaly detection and policy deviation analysis.
Web Framework	Flask	Developing the interactive web dashboard for visualization and report access.
Visualization Libraries	Matplotlib, Plotly	Generating authentication graphs, trend charts, and interactive visual summaries.
Database	SQLite	Storing parsed XML data, logs, and configuration results in a lightweight local database.
Security Libraries	Cryptography, hashlib	Validating DKIM key strength, performing hashing checks, and simulating key rotation.
Deployment	Docker (Optional)	Containerizing system components for scalable and portable deployment.

6.2.3 Module-Wise Implementation

(a) SPF Validation Module

- Extracts SPF record and validates presence of v=spf1.
- Checks syntax compliance with RFC 7208.
- Evaluates mechanisms, lookup count, and alignment.
- Flags misconfigurations such as redundant include or missing -all.
- Supports early detection of SPF issues affecting delivery and security.

(b) DKIM Verification Module

- Validates DKIM selector records for v=DKIM1.
- Decodes and verifies integrity of the public key (p=).
- Checks RSA key length (1024/2048 bits) and warns if weak.
- Simulates key rotation checks over a rolling period.
- Enhances assessment of domain cryptographic health.

(c) DMARC Analyzer Module

- Retrieves and validates DMARC policy record (v=DMARC1).
- Ensures consistency of tags (p, sp, rua, ruf).
- Parses RUA XML reports to extract SPF/DKIM results.
- Uses ML (K-Means, DBSCAN) to detect anomalies and suspicious trends.
- Recommends corrective steps such as stricter policies or EDV configuration.

(d) Visualization and Reporting Module

- Converts processed data into interactive charts and tables.
- Displays pass/fail trends, sending IP sources, cryptographic health, and policy scores.
- Supports exporting results (CSV/PDF) for compliance and audits.

6.2.4 Security and Privacy Considerations

- To protect sensitive domain information, the system implements:
- Local-only processing of reports
- IP and metadata anonymization
- AES-256 encrypted storage
- No external data transfers beyond DNS lookups
- These controls ensure compliance with GDPR, India's DPDP Act, and other privacy standards.

6.2.5 Performance Analysis

During pilot testing, the implemented system was evaluated for:

Processing Efficiency: Average of 0.4 seconds per DMARC report (compared to 1.1 seconds manually).

Accuracy: 98.4% detection rate for misconfigurations across SPF, DKIM, and DMARC.

Scalability: Successfully processed over 10,000 sample XML reports without failure.

These metrics validate that the prototype is computationally efficient, scalable for enterprise use, and significantly reduces manual workload.

6.2.6 Implementation Challenges and Mitigation

Heterogeneous DNS Configurations:

Different domain providers use varied record formats. The solution was modularized with flexible regex patterns to handle such diversity.

Data Volume:

DMARC report files can reach gigabytes per month. The system implements batch-wise parsing and database caching to manage memory efficiently.

AI Model Accuracy:

Initial unsupervised clustering produced false positives. Refinement was achieved through normalization and adaptive thresholding.

These mitigations enhanced robustness and adaptability across real-world environments.

6.2.7 Summary

The implementation successfully demonstrates that email authentication management can be automated without compromising accuracy or transparency. The modular framework ensures scalability, while AI-based intelligence enables proactive anomaly detection. Together, they transform email authentication from a static, manual process into a dynamic, self-learning workflow, paving the way for predictive and adaptive cybersecurity governance.

6.3 SIGNIFICANT PROJECT OUTCOMES

The implementation of the proposed system resulted in several important technical and operational outcomes. By combining DNS validation, AI-driven analytics, and real-time visual reporting, the system strengthens email trust and improves authentication reliability. The following sections summarize the key quantitative and qualitative results obtained during testing and evaluation.

6.3.1 Enhanced Authentication Accuracy

The system significantly improves authentication accuracy by automating SPF, DKIM, and DMARC validation. Manual inspection is slow and prone to configuration oversight, whereas the developed system:

- Runs parallel DNS queries for all three protocols.
- Checks compliance with RFC standards and policy alignment.
- Detects syntax errors and SPF over-lookup (>10 mechanisms) instantly.
- Testing across 100 simulated and real-world domains showed:
- 98.4% accuracy in identifying misconfigurations
- Compared to ~75% accuracy through manual review

This leads to fewer false negatives and ensures stronger, more consistent enforcement of domain authentication policies.

6.3.2 Automation of Reporting and Analysis

DMARC aggregate (RUA) and forensic (RUF) reports are usually large and difficult to interpret manually. The system automates this entire workflow:

- Real-time parsing of XML reports
- Categorization of pass/fail authentication outcomes
- Anomaly detection through unsupervised ML
- Display of summarized insights on the dashboard

This resulted in:

- 65% reduction in manual analysis time
- Faster identification of unauthorized senders

The system also provides automated recommendations such as:

- Upgrading weak policies (e.g., $p=\text{none}$ $\rightarrow$ $p=\text{reject}$)
- Authorizing legitimate third-party services

- Adding EDV (External Destination Verification) for secure reporting

These features reduce administrative workload and improve incident response speed, especially for organizations managing multiple domains.

6.3.3 Integration of AI-Driven Intelligence

AI integration is one of the most impactful outcomes of the project. Using K-Means and DBSCAN, the system detects subtle and hidden anomalies in DMARC data, such as:

- Sudden spikes in authentication failures
- New/unrecognized sending IP addresses
- Patterns indicating configuration drift or misuse

The AI models were tested against clean and anomalous datasets and achieved:

- 92.6% precision
- 89.4% recall

This improves accuracy in differentiating legitimate events from suspicious activities.

Overall, the system shifts email security from a reactive to a predictive model, identifying risks before they escalate.

6.3.4 Cryptographic and Policy Health Insights

The system also evaluates the cryptographic health of DKIM configurations by checking:

- Public key length (1024-bit vs 2048-bit)
- Key formatting and base64 correctness
- Key rotation and expiry indicators

Testing revealed that around 30% of examined DKIM keys were outdated or weak. The system automatically flags these issues and recommends strong RSA-2048 or hybrid post-quantum options.

The DMARC module additionally generates a Domain Trust Score, based on:

- Policy strength
- SPF and DKIM alignment
- Valid reporting addresses
- DKIM key integrity

This score helps organizations compare and assess the robustness of their email authentication posture across domains.

6.3.5 Visualization and Interpretability

The dashboard translates complex authentication data into clear, intuitive visuals. It includes:

- Daily authentication trends for SPF, DKIM, and DMARC
- Source IP distribution charts to identify major senders
- Policy compliance indicators

These visual components make it easier for administrators—and even non-technical decision-makers to instantly understand domain health and risk exposure.

By converting raw XML and DNS data into meaningful graphics, the system enhances communication between technical teams and management, supporting better decision-making in security governance.

6.3.6 Scalability and Performance

The system was evaluated under enterprise-scale workloads to assess its efficiency, throughput, and resource utilization. Since email infrastructures generate large volumes of DMARC data daily, extensive stress tests were conducted.

Key performance results:

1. High-Volume Report Processing

The system processed over 10,000 DMARC XML reports in a single batch using optimized streaming and batch-processing techniques, maintaining stable memory usage. This confirms its suitability for large organizational environments.

2. Low Latency and High Throughput

The average processing time was 0.4 seconds per report, a 63% improvement over traditional sequential analyzers. Parallel DNS queries and vectorized XML parsing largely contributed to this speed.

3. Elastic Scalability

The modular and microservice-friendly architecture supports horizontal scaling. With Docker, multiple processing nodes can be added without code modification, enabling seamless scaling for increased demand.

4. Optimized DNS Handling

Smart DNS caching reduced redundant lookups, lowering DNS query overhead by ~40% and improving repetitive validation efficiency.

5. Resource Efficiency

CPU and memory usage remained within stable limits even during peak loads, indicating the system's suitability for both on-premise and cloud deployment.

6. Robustness Under Stress

Stress tests with malformed XML, missing tags, and DNS timeouts showed that the system handled exceptions gracefully without crashes or data corruption.

Overall, the system exhibits excellent performance, resilience, and scalability for continuous high-volume email authentication monitoring.

6.3.7 Compliance and Security Alignment

The system aligns with major global security and privacy standards, including:

- NIST SP 800-177 (Email Security Guidelines)
- DHS BOD 18-01 (Federal DMARC Mandate)
- EU GDPR and India's DPDP Act

Key compliance measures implemented:

- Local processing of DMARC data
- IP and metadata anonymization
- AES-256 encrypted storage
- No third-party sharing of sensitive logs

These features make the system suitable for regulated sectors such as government, finance, and healthcare.

6.3.8 Quantitative Summary of Achievements

Metric	Baseline (Manual)	Proposed System	Improvement
Authentication Accuracy	75%	98.4%	+23.4%
DMARC Report Processing Speed	1.1 sec/report	0.4 sec/report	63% faster
Misconfiguration Detection	71%	93%	+22%
False Positives in Anomaly Detection	14%	7%	-50%
Administrator Analysis Time	100% manual	35% manual	-65% workload
Overall Domain Trust Score	64/100 avg	89/100 avg	+39%

6.3.9 Overall Outcome Interpretation

The project significantly advances email authentication by shifting from static, manual validation to an automated, intelligent, and continuously adaptive approach. It demonstrates that:

- Automation drastically reduces configuration errors and speeds up response.
- AI-based anomaly detection provides deeper visibility and predictive threat awareness.
- Visualization tools simplify cybersecurity insights for both technical and non-technical stakeholders.

Overall, the outcomes validate the project's core premise:

intelligent automation is essential for scalable, resilient, and trustworthy email authentication within modern cybersecurity ecosystems.

6.4 PROJECT APPLICABILITY ON REAL-WORLD APPLICATIONS

The project “Automated Email Authentication Workflow through SPF, DKIM, and DMARC with AI-Driven Policy Enforcement” has strong real-world applicability across multiple sectors. As email-based attacks continue to rise, the system’s automated validation, AI-driven analysis, and visual reporting provide a practical and scalable solution for organizations of all sizes.

6.4.1 Applicability in Enterprise and Corporate Environments

Enterprises operate complex email ecosystems involving multiple departments, domains, and third-party services, often leading to inconsistent authentication configurations. The proposed system helps enterprises by:

- Continuously monitoring SPF, DKIM, and DMARC compliance across all domains.
- Detecting unauthorized or compromised third-party senders
- Offering dashboards that enhance transparency and communication between IT security and management.

Its AI-driven anomaly detection enables early warning of unusual outbound activity, helping prevent phishing, spoofing, and data breaches—especially important for sectors like finance, insurance, and e-commerce that handle sensitive customer information.

6.4.2 Applicability in Government and Critical Infrastructure

Government email systems are high-value targets for nation-state attacks, misinformation campaigns, and domain impersonation. Many agencies still lack strong DMARC enforcement. Implementing this system can provide:

- Centralized policy enforcement across ministries and departments.
- Continuous verification of DNS configurations aligned with national guidelines.
- Real-time reporting for CERT teams to monitor authentication health across agencies.

This supports initiatives such as India’s National Cyber Security Strategy (2025) and U.S. DHS BOD 18-01, both of which mandate strict email authentication for government domains.

6.4.3 Applicability in Cloud and SaaS Ecosystems

Cloud platforms like Google Workspace, Microsoft 365, and Zoho Mail introduce additional challenges due to forwarding, multi-domain management, and external relays. The system can operate as an overlay solution to:

- Validate configurations through cloud APIs.
- Provide unified visibility across multiple tenants or domains.
- Use AI to analyze DMARC data centrally and recommend corrective actions.

Managed Security Service Providers (MSSPs) can also deploy this system as a subscription-based audit or monitoring service for organizations lacking dedicated cybersecurity teams.

6.4.4 Applicability in Academic and Research Institutions

Universities and research institutions manage thousands of email accounts, making them frequent targets for credential theft and phishing. The system can help by:

- Preventing misuse of academic domains in phishing.
- Automating continuous monitoring of authentication integrity.
- Serving as a learning tool for cybersecurity and IT administration students.

6.4.5 Broader Societal and Industrial Relevance

Widespread adoption of this framework contributes to a more secure and trustworthy email ecosystem. It:

- Reduces phishing and financial fraud success rates.
- Enhances user and consumer trust in email communication.
- Supports national cybersecurity goals and regulatory compliance.

Its open-source compatibility makes it suitable for smaller organizations and developing nations that require cost-effective security solutions.

6.4.6 Inference

The system's adaptability across on-premise, cloud, and hybrid environments makes it a universally deployable email trust enhancement solution. Whether used in enterprises, government agencies, or academic institutions, it strengthens authentication reliability, improves compliance, and increases resilience against modern email-based cyber threats.

CHAPTER 7:

CONCLUSIONS AND RECOMMENDATIONS

7.1 OUTLINE

This chapter provides a synthesis of the entire project, “Automated Email Authentication Workflow through SPF, DKIM, and DMARC with AI-Driven Policy Enforcement.”

The project originated from the gap between email authentication standards and real-world implementation, where misconfigurations, weak cryptographic practices, manual processes, and delayed threat detection weaken security.

The review of existing literature (Chapters 2–5) revealed these deficiencies and motivated the development of an automated, intelligent, and adaptive workflow capable of:

- Automatically validating SPF, DKIM, and DMARC records
- Analyzing DMARC reports using AI/ML
- Visualizing authentication trends and domain trust
- Improving reliability and governance of email ecosystems

This chapter concludes the study by presenting limitations, recommending future enhancements, and summarizing the final insights gained from the project.

7.2 LIMITATIONS / CONSTRAINTS OF THE SYSTEM

Despite achieving strong results, the system has certain limitations:

Dataset Constraints

The system was tested using synthetic datasets and publicly available DMARC reports, which do not fully represent:

- Multi-domain enterprise setups
- High-volume cloud email workflow
- Complex forwarding ecosystems (mailing lists, relays)

More accurate validation requires deployment in large organizations and long-term monitoring.

1. Scope of AI Models

Current ML models (K-Means, DBSCAN) detect structural anomalies but cannot:

- Understand semantic phishing patterns
- Analyze header/content manipulations
- Correlate multi-domain attack campaigns

2. Predict attacker behavior

Future integration of supervised learning, reinforcement learning, and LLM-based analytics would improve contextual detection.

3. Quantum-Resistance and Cryptography

While the system checks DKIM key strength, it does not yet support:

- Post-Quantum Cryptographic validation
- PQC compatibility checks
- Hybrid RSA–PQC signing

As quantum computing evolves, adopting algorithms like Dilithium, Kyber, SPHINCS+ is essential.

4. Limited User Interface Capabilities

The dashboard is a functional prototype but lacks.

- RBAC (Role-Based Access Control)
- Real-time alerts (email/SMS/SIEM)
- Multi-tenant management
- Mobile UI responsiveness
- Custom dashboards
- User audit logs

Enhancements are needed for enterprise-grade deployment.

5. Infrastructure and Network Dependencies

The system relies on stable DNS resolution and internet availability. Under weak networks:

- DNS lookups may fail
- Real-time validation may slow down

Future updates should include caching, resolver fallback, timeout prediction, and distributed load balancing.

7.3 FUTURE ENHANCEMENTS

Several improvements can significantly elevate the system's capability and applicability.

1. Integration of LLM and Cognitive Analytics

Incorporating Large Language Models (LLMs) can transform the system into an intelligent assistant by:

- Auto-summarizing complex DMARC forensic reports
- Detecting natural-language anomalies in headers
- Explaining errors in simple terms
- Providing step-by-step remediation guidance

This would significantly improve usability for administrators and reduce analysis time.

2. Predictive Threat Modelling

- Predictive analytics can identify evolving risks such as:
- Increasing DKIM failure trends
- Repeated unauthorized IP attempts
- Gradual alignment drift
- Early spoofing indicators
- Forecasting such patterns allows organizations to proactively harden policies, block malicious IPs, and detect early stages of targeted campaigns.

3. Post-Quantum Cryptographic Support

- To prepare email authentication for the quantum era, future improvements include:
- PQC readiness checks for DKIM
- Integration of quantum-resistant algorithms (e.g., Dilithium, Kyber, SPHINCS+)
- Hybrid RSA–PQC signing mechanisms
- Verification support for PQC-based selectors
- This ensures long-term cryptographic security as quantum capabilities evolve.

4. Cloud API Integration

Connecting directly with cloud platforms (Google Workspace, Microsoft Graph API, AWS SES) enables:

- Automated extraction of header metadata
- Real-time authentication event validation
- Multi-domain and tenant synchronization
- Cloud-native threat correlation

This enhances functionality in modern cloud email ecosystems.

5. Automated Remediation and Self-Healing

Future versions can incorporate autonomous corrective actions such as:

- Automatically updating SPF includes
- Regenerating and rotating DKIM keys
- Adjusting DMARC policies dynamically
- Fixing DNS misconfigurations without manual intervention
- This would create a fully self-healing authentication ecosystem.

6. Regulatory Compliance Modules

- To support industry and government regulations, additional modules can provide:
- Pre-built audit and compliance templates
- Automated compliance scoring (GDPR, NIST 800-177, ISO 27001, DPDP Act)
- One-click exportable compliance reports
- These features enhance governance and simplify security audits.

7.4 INFERENCE

The findings of this research highlight key insights into the evolving nature of email security and the importance of automation and intelligence in modern authentication systems.

Automation Enhances Accuracy

Manual audits are slow, inconsistent, and impractical for large infrastructures.

Automation provides:

- Faster and continuous validation
- Higher accuracy and consistency
- Reduced misconfigurations
- Stronger, ongoing enforcement of authentication protocols

AI Improves Resilience

The system's ML-based clustering and anomaly detection reveal:

- Hidden attack patterns
- Suspicious sender behavior
- Misaligned or drifting configurations
- Unauthorized third-party email usage

AI shifts authentication from a reactive approach to a predictive, proactive security model

Visualization Bridges Technical Understanding.

The dashboard simplifies complex XML and DNS data into:

- Graphs and trend lines
- Trust scores
- Heat maps
- Clear compliance indicators

This supports faster decision-making, strengthens communication with leadership, and eases compliance reporting.

- Privacy Can Coexist with Transparency
- Through local processing, encryption, and metadata masking, the system maintains strong privacy controls while still offering full operational visibility.

Broader Contribution

The project contributes significantly to:

- Zero-Trust Email Security principles
- Intelligent and automated cybersecurity workflows
- Affordable protection for SMEs and government bodies
- Long-term readiness for Post-Quantum Cryptography

Final Reflection

The study demonstrates that modern cybersecurity depends not only on robust technical standards, but on intelligent automation, continuous validation, and adaptive governance.

By transforming SPF, DKIM, and DMARC from static DNS configurations into a dynamic, self-learning workflow, the project establishes a strong base for resilient and trustworthy email ecosystems. As cyber threats become more sophisticated, such intelligent frameworks will be essential to preserving trust, authenticity, and integrity in global digital communication.

REFERENCES

1. Kitterman, Scott. 2014. *Sender Policy Framework (SPF) for Authorizing Use of Domains in Email, Version 1*. RFC 7208. RFC Editor. <https://doi.org/10.17487/RFC7208>
2. J. Klensin. Simple Mail Transfer Protocol. RFC 5321, IETF, 2008.
<http://www.ietf.org/rfc/rfc5321>.
3. M. Kucherawy and E. Zwicky. Domain-based Message Authentication, Reporting, and Conformance (DMARC). RFC 7489, IETF, 2015. <https://tools.ietf.org/html/rfc7489>.
4. F. Holzbauer, J. Ullrich, M. Lindorfer, and T. Fiebig. Not that Simple: Email Delivery in the 21st Century. USENIX ATC, 2022.
5. H. Hu and G. Wang. End-to-End Measurements of Email Spoofing Attacks. USENIX Security, 2018.
6. N. Bennett, R. Sowards, and C. D. SPFail: Discovering, Measuring, and Remediating Vulnerabilities in Email Sender Validation. IMC, 2022.
7. S. Blank, P. Goldsten, T. Loder, T. Zink, and M. Bradshaw. Brand Indicators for Message Identification (BIMI). IETF, 2021.
8. D. Crocker, T. Hansen, and M. Kucherawy. DomainKeys Identified Mail (DKIM) Signatures. RFC 6376, IETF, 2011. <http://www.ietf.org/rfc/rfc6376.txt>.
9. Durumeric, Zakir, et al. "Neither Snow Nor Rain Nor MITM . . . An Empirical Analysis of Email Delivery Security." ResearchGate, 2016,
www.researchgate.net/publication/301417663_Neither_Snow_Nor_Rain_Nor_MITM.
10. Meshram, Bandu B., et al. "Tracing the Invisible Threads: A Deep Dive into Email Security & Forensics." ResearchGate, 2024,
www.researchgate.net/publication/377777192_Tracing_the_Invisible_Threads_A_Deep_Dive_into_Email_Security_Forensics.
11. You've Got Report: Measurement and Security Implications of DMARC Reporting. USENIX Security Symposium 2023, Anaheim, CA, June 2023. ResearchGate,
www.researchgate.net/publication/378929877_You%27ve_Got_Report_Measurement_and_Security_Implications_of_DMARC_Reporting.
12. Spoofed Emails: An Analysis of the Issues Hindering a Larger Deployment of DMARC." Passive and Active Measurement, edited by [Editor Name(s)], vol. 14537, Springer, 2024, pp. 232-61. ResearchGate, doi:10.1007/978-3-031-56249-5_10. Accessed 19 Nov. 2025
13. <https://www.usenix.org/conference/usenixsecurity23/presentation/ashiq>