

# Multi-Scale Analysis of Data Based on Graph Wavelets: ADHD-200 Sample

Sinuk KANG<sup>1</sup> and Sunghyon KYEONG<sup>1</sup>

1) *National Institute for Mathematical Sciences, Deajeon 305-811, SOUTH KOREA*

Corresponding Author : Sinuk KANG, skang@nims.re.kr

## ABSTRACT

Graph wavelets are proven useful and efficient to deal with graph-like structured data [1,2]. We consider resting state functional MRI data of 216 Attention Deficit Hyperactivity Disorder (ADHD) patients and normal controls obtained from New York University [3]. From the data, a graph, or a network, is generated where its nodes represent individuals and edges are given by a proper similarity measure. We construct the scaling functions and wavelets on the graph and show that these functions at different scales retrieve meaningful information of the data at different levels.

## REFERENCES

1. Coifman, R.R., Maggioni, M., "Diffusion wavelets", *Appl. Comput. Harmon. Analysis*, Vol. 21, 2006, pp. 53-94.
2. Hammond, D.K., Vandergheynst, P., Gribonval, R., "Wavelets on graphs via spectral graph theory", *Appl. Comput. Harmon. Analysis*, Vol. 30, 2011, pp. 129-150.
3. ADHD-200 sample: [http://fcon\\_1000.projects.nitrc.org/indi/adhd200/](http://fcon_1000.projects.nitrc.org/indi/adhd200/)