

EE382N (20): Computer Architecture - Parallelism and Locality
Lecture 5 – Quick Intro to Graphics Processing

Mattan Erez



The University of Texas at Austin



A GPU Renders 3D Scenes

- A **Graphics Processing Unit (GPU)** accelerates rendering of 3D scenes
 - Input: description of scene
 - Output: colored pixels to be displayed on a screen
- Input:
 - Geometry (triangles), colors, lights, effects, textures
- Output:



State of the Art in 1985

- First movie from Pixar – Luxo Jr.
- 2 – 3 hours per frame on a Cray-1 supercomputer
- Today: $1/30^{\text{th}}$ of a second on a PC
 - Over 300,000x faster
- Still not even close to where we need to be... but look how far we've come!



GPU Scene Complexity Defined by Standard Interfaces (DirectX and OpenGL)

4

- DirectX and OpenGL define the interface between applications and the GPU
- **Geometry** describes the objects and layout
 - Triangles (vertices) describe all objects
 - Can have millions of triangles per scene
 - Can modify triangle surfaces
 - Bumps, ripples, ...
 - Lights are part of the scene geometry
- **Pixel Shaders** describe how to add color
 - Colors of triangle vertices
 - Textures (patterns)
 - How to determine color of pixels within a triangle
 - ...



GPUs in 1997 – DirectX 5

5



GPUs in 1998 – DirectX 6

6



GPUs in 2000 – DirectX 7

7



GPUs in 2001 – DirectX 8

- First programmable graphics (Shader Model 1)




GPUs in 2003 – DirectX 9

- More programmability (Shader Model 2)



GPUs in 2004 – DirectX 9.0c

- Yet more programmability (Shader Model 3)



GPUs in 2007 – DirectX 10

- Full programs in pipeline (Shader Model 4)



DirectX 9

DirectX 10



GPUs in 2010 – DirectX 11

- Even more processing power
- Fully programmable, even for compute




Complexity and Quality are Orders of Magnitude Better

13



GPU Performance is Increasing Much Faster than CPUs⁴




The GPU is Now a Fully Programmable General Purpose Processor


15

- Programmability needed by graphics – can be exploited for GP computation


**Computational
Geoscience**




**Computational
Modeling**




**Computational
Medicine**




**Computational
Biology**




**Computational
Chemistry**



**Computational
Finance**



Speedup of Applications



- GeForce 8800 GTX vs. 2.2GHz Opteron 248
 - 10x speedup in a kernel is typical, as long as the kernel can occupy enough parallel threads
 - 25x to 400x speedup if the function's data requirements and control flow suit the GPU and the application is optimized
- Keep in mind that the speedup also reflects how suitable the CPU is for executing the kernel

GPU and CPU Architectures are Starting to Converge


	CPUs	GPUs
1997	no explicit parallelism	not programmable
2000	explicit short vectors	emerging programmability (2001 – 2002), “infinite” DP
2003	explicit short vectors explicit threading (~2)	fully programmable explicit “infinite” DP no scatter
2006	explicit short vectors explicit threading (~4)	explicit vectors explicit threading (~16)
2009	explicit vectors explicit threading (>8)	explicit vectors explicit threading (>>16)
2010	explicit wide vectors explicit threading (~16)	GPUs get caches and more programmer friendly

Outline

- What is a GPU?
 - Why should we care about GPUs?
 - 3D graphics pipeline
 - Programmable GPUs
-
- Many slides courtesy David Kirk (NVIDIA) and Wen-Mei Hwu (UIUC)
 - From The University of Illinois ECE 498AI class
 - Other slides courtesy Massimiliano Faticis (NVIDIA)




The NVIDIA GeForce Graphics Pipeline




Color Framebuffer (“Display”)

- 2D array of R,G,B color *pixel* values
- 8 bits (256 levels) per color component
- Three 8-bit components can represent 16 million different colors, including 256 shades of gray
- 4th component: *alpha*; used for blending
- Typical high end: 2048x1536 pixels



Describing an Object

21



© David Kirk/NVIDIA and
Wen-mei W. Hwu, 2007

ECE 498AL, University of Illinois,
Urbana-Champaign

and Locality, Spring 2015 -- Lecture 7


Feeding the GPU

- GPU accepts a sequence of commands and data
 - Vertex positions, colors, and other shader parameters
 - Texture map images
 - Commands like “draw triangles with the following vertices until you get a command to stop drawing triangles”.
- Application pushes data using Direct3D or OpenGL
- GPU can pull commands and data from system memory or from its local memory

Host Interface

23

- Bus Interface
- DMA Engines
- Class Interfaces
 - This enables our Unified Driver Architecture
- How the CPU communicates to our GPU
- How our GPU communicates back to the CPU
- How we move data back and forth to the CPU




Transform Vertex Positions

- Why transform vertices?
 - Rotate, translate and scale each object to place it correctly among the other objects that make up the scene *model*.
 - Rotate, translate, and scale the entire scene to correctly place it relative to the camera's position, view direction, and field of view.
- How?
 - Multiply every floating point vertex position by a combined 4x4 model-view matrix to get a 4-D $[x \ y \ z \ w]$ eye-space position

Vertex Control


25

- Receives parameterized vertex data
- Inputs data to vertex cache
- Formats vertices for processing
- Data can come to our GPU in a variety of formats
- Vertex control organizes vertex data into a consistent, hardware understandable format




What's a Vertex?

- The defining “corners” of a primitive
- For GeForce that means a triangle




Vertex Cache

- Temporary store for vertices, used to gain higher efficiency
- Re-using vertices between primitives saves AGP/PCI-E bus bandwidth
- Re-using vertices between primitives saves GPU computational resources
- A vertex cache attempts to exploit “commonality” between triangles to generate vertex reuse
- Unfortunately, many applications do not use efficient triangular ordering



Geometry/Vertex Processing

- Transform & Lighting
 - Fixed set of transformations and effects



Vertex Processing Examples




- Deformation
- Warping
- Procedural Animation



- Range-based Fog
- Elevation-based Fog



- Animation
 - Morphing
 - Interpolation



- Lens Effects


© David Kirk/NVIDIA and
Wen-mei W. Hwu, 2007

ECE 498AL, University of Illinois,
Urbana-Champaign

and Locality, Spring 2015 -- Lecture 7

Geometry/Vertex Processing

- Transform & Lighting
 - Fixed set of transformations and effects
- Today: “Vertex Shading”
 - Programmable programs run on a per vertex basis
 - One vertex in → One vertex out:**DP “stream” processing**
 - “Flow-through” programming architecture





Vertex Lighting

- Vertex lighting generates a color value at each vertex.
- Simplest GPU “lighting”: application calculates and delivers an (R,G,B) triplet for every vertex.
- A more typical GPU lighting equation models the physics of light transport. We sum contributions of:
 - Ambient – uniform light from all directions
 - Emissive – light given off by the object itself
 - Specular – glossy, mirror-like reflections
 - Diffuse – dull, matte-finish reflections


Triangle Setup

- Each vertex of each polygon contains parameters used by Triangle Setup – typically 4 or more
- In Setup, this vertex data is used to create a map relating pixel coordinates with the variables that will ultimately determine their color



Rasterization

33




- Rasterization is the process of determining which pixels are contained in each triangle
- For each of these pixels, the rasterizer creates the necessary information for pixel shading
- It includes information like
 - Position
 - Color
 - Texture coordinates for each pixel
 - Pattern for rasterization (which helps fill texture cache ahead of time)
- In GeForce, it also includes Z-Occlusion

Rasterization


- Given a triangle, identify every pixel that belongs to that triangle
- Point Sampling
 - A pixel belongs to a triangle if and only if the center of the pixel is located in the interior of the triangle
 - Evaluate 3 edge equations of the form $E = Ax + By + C$, where $E = 0$ is exactly on the line, and positive E is towards the interior of the triangle.

Rasterization




Shading

- Shading is assigning color values to pixels
- Color values can be determined by:
 - Interpolated shading (ex. Gouraud or Phong)
 - Texture mapping
 - Per pixel lighting mathematics
 - Reflections
 - Complex pixel shader programs
- Shading includes Texture Mapping
- A color value can now be procedurally generated...





Gouraud Interpolation

- Also called “smooth shading”
- Linearly vary color values across the triangle interior.
- More realistic than flat shading because the facets in the model are less obvious.




Texture Mapping

- Associate points in an image to points in a geometric object



Sphere with no texture



Texture image



Sphere with texture

Mip Mapping




1024x1024

Mip Mapping is a technique to manage pixel level of detail (LOD).

Scaled versions of the original texture are generated and stored. These smaller stored textures are used for the texture samples as objects appear smaller with greater distance.



512x512



256x256




128x128




64x64

Bilinear Filtering

Individual texel colors are interpolated from the four nearest texels of the closest stored mip map.



*Random Sized Texture Needed
in a Given Frame of an Application*




Stored Mip Map Texture


Texture Filtering - Good

41

Nearest




Bilinear




Texture Filtering - Better

Bilinear




Trilinear




Trilinear Filtering


Individual texel colors are interpolated from bilinear interpolations of nearest adjacent mip maps.



Stored Mip Map Texture




*Random Sized Texture Needed
in a Given Frame of an Application*




Stored Mip Map Texture

Trilinear Filtering



Anisotropic Filtering



Stars, I have seen them
Fall, but when they drop and
Die, no star is lost at
All, from all the star-sown
Sky. The toil of all that
Be, helps not the primal
Fault; it rains into the
Sea, and still the sea is

© David Kirk/NVIDIA and

Wen-mei W. Hwu, 2007

ECE 498AL, University of Illinois,

Urbana-Champaign


and Locality, Spring 2015 -- Lecture 7

Filtering techniques

- Point sampling:
 - pixel values are calculated by choosing one texture pixel (texel) color
- Bilinear filtering:
 - interpolating colors from 4 neighboring texels. This gives a smoothing (if somewhat blurry) effect and makes the scene look more natural and prevents abrupt transitions between neighboring texels.
- Trilinear filtering:
 - interpolating bilinearly filtered samples from two mip-maps. Trilinear mip-mapping prevents moving objects from displaying a distracting “sparkle” caused by abrupt transitions between mipmaps.
- Anisotropic filtering:
 - interpolating and filtering multiple samples from one or more mip-maps to better approximate very distorted textures. Gives a sharper effect when severe perspective correction is used. Trilinear mipmapping blurs textures more.


Texture Cache

- Stores temporally local texel values to reduce bandwidth requirements
- Due to nature of texture filtering high degrees of efficiency are possible
- Efficient texture caches can achieve 75% or better hit rates
- Reduces texture (memory) bandwidth by a factor of four for bilinear filtering



Pixel Shading

- 1999 (DirectX 7)
 - Application could select from a few simple combinations of texture and interpolated color
 - Add
 - Decal
 - Modulate
- Next (DirectX 9)
 - Write a general program that executes for every pixel with a nearly unlimited number of interpolated inputs, texture lookups and math operations
 - Can afford to perform sophisticated lighting calculations at every pixel



```



# clock 3
rcp r0.a, r0.a      # reciprocal in shader 0
mul r0.rgb, r0, r0.a # div instruction in shader 0
mul r0.a, r0.a, r1.a # dual issue in shader 0
texld r2, r0, s1    # texture fetch
mad r2.rgb, r0.a, r2, c5 # mad in shader 1
abs r0.a, r0.a      # abs in shader 1
log r0.a, r0.a      # log in shader 1

# clock 4
rcp r0.a, t1.a      # reciprocal in shader 0
mul r0.rgb, t1, r0.a # div instruction in shader 0
mul r0.a, r0.a, c2.g # dual issue in shader 0
texld r1, r0, s3    # tex fetch
mad r1.rgb, r1, c4, -r2 # mad in shader 1
exp r0.a, r0.a      # dual issue in shader 1

# clock 5
texld r0, r1.bar, s2 # texture coordinates swizzle
mad r0.rgb, r0, v0, r1 # color calculation in shader 1
mul r0.a, r1, v0    # dual issue in shader 1


# clock 6
mul r1.rgb, r0.a, c5.a # mul in shader 0
mad r0.rgb, r1, r0.a, r0 # mad in shader 1
mov r0.a, c3.a        # move in shader 1
mov oC0, r0           # move in shader 1
  
```

GeForce FX Fragment/Pixel Program Examples




ROP (from Raster Operations)

- C-ROP performs frame buffer blending
 - Combinations of colors and transparency
 - Antialiasing
 - Read/Modify/Write the Color Buffer
- Z-ROP performs the Z operations
 - Determine the visible pixels
 - Discard the occluded pixels
 - Read/Modify/Write the Z-Buffer
- ROP on GeForce also performs
 - “Coalescing” of transactions
 - Z-Buffer compression/decompression




Alpha Blending

- *Alpha Blending* is used to render translucent objects.
- The pixel's alpha component contains its *opacity*.
- Read-modify-write operation to the color framebuffer
- $\text{Result} = \alpha * \text{Src} + (1 - \alpha) * \text{Dst}$




Anti-Aliasing


- Aliased rendering: color sample at pixel center is the color of the whole pixel
- Anti-aliasing accounts for the contribution of all the primitives that intersect the pixel



Triangle Geometry



Aliased



Anti-Aliased


© David Kirk/NVIDIA and
Wen-mei W. Hwu, 2007

ECE 498AL, University of Illinois,
Urbana-Champaign

E382N: Parallelism and Locality, Spring 2015 -- Lecture 7


Frame Buffer Interface (FBI)

- Manages reading from and writing to frame buffer
- Perhaps the most performance-critical component of a GPU
- GeForce's FBI is a crossbar
- Independent memory controllers for 4+ independent memory banks for more efficient access to frame buffer



The Frame Buffer

- The primary determinant of graphics performance other than the GPU
- The most expensive component of a graphics product other than the GPU
- Memory bandwidth is the key
- Frame buffer size also determines
 - Local texture storage
 - Maximum resolutions
 - AA resolution limits



Z Buffer

- A Z buffer is a 2-D array of Z values with the same (x,y) dimensions as the color framebuffer
- Every candidate pixel from the shader has a calculated Z value along with its R,G,B,A color.
- Before writing the color, perform the Z-buffer test:
 - Read the Z value from memory
 - Compare the candidate Z to the Z from memory; if the candidate Z is NOT in front of the previous Z, discard the pixel
 - Otherwise, write the new Z value to the Z buffer and write (or blend) the new color to the color framebuffer

Summary, so far...

- Introduction to several key 3D graphics concepts:
 - Framebuffers
 - Object Representation
 - Vertex Processing
 - Lighting
 - Rasterization
 - Gouraud Interpolation
 - Texture Mapping
 - Pixel Shading
 - Alpha Blending
 - Anti-Aliasing
 - Z-Buffering




Outline

- What is a GPU?
 - Why should we care about GPUs?
 - 3D graphics pipeline
 - Programmable GPUs
-
- Many slides courtesy David Kirk (NVIDIA) and Wen-Mei Hwu (UIUC)
 - From The University of Illinois ECE 498AI class
 - Other slides courtesy Massimiliano Faticis (NVIDIA)



Adding Programmability to the Graphics Pipeline



Vertex and Fragment Processing Share Unified Processing Elements


59

- Load balancing HW is a problem


Vertex Shader



Pixel Shader




Vertex Shader



Pixel Shader



Heavy Geometry
Workload Perf = 4



Heavy Pixel
Workload Perf = 8



Vertex and Fragment Processing Share Unified Processing Elements


60

- Load balancing SW is easier


Unified Shader



Unified Shader



Heavy Geometry
Workload Perf = 11



Heavy Pixel
Workload Perf = 11



Vertex and Fragment Processing is Dynamically Load Balanced

61




Less Geometry



More Geometry

Unified Shader Usage

High **pixel shader** use
Low **vertex shader** use



Balanced use of **pixel shader** and **vertex shader**



Make the Compute Core The Focus of the Architecture

62

- The future of GPUs is programmable processing
- Processors execute computing threads
- So – build the architecture around the processor
- Alternative operating mode specifically for computing

