

# Websites tested according to WCAG 2.0 Guidelines

URL:

1. <https://screwdriver.cd/>
2. <https://docs.screwdriver.cd/>

Screen reader: JAWS 2020

Browser: Firefox 87.0




Tested by: Rakshit Parashar

## Checklist

Success Criteria	Status (PASS,Fail,N/A)
Non-text Content	Fail
Audio-only and Video-only (Prerecorded)	N/A
Captions (Prerecorded)	N/A
Audio Description or Media Alternative (Prerecorded)	N/A
Captions (Live)	N/A
Audio Description (Prerecorded)	N/A
Info and Relationships	Fail
Meaningful Sequence	Pass
Sensory Characteristics	Pass
Use of Color	Pass
Audio Control	Pass
Contrast (Minimum)	Fail
Resize Text	Pass
Images of Text	Pass
Keyboard	Pass
No Keyboard Trap	Pass
Timing Adjustable	Pass



Pause, Stop, Hide	Pass
Three Flashes or Below Threshold	Pass
Bypass Blocks	Fail
Page Titled	Pass
Focus Order	Fail
Link Purpose (In Context)	Fail
Multiple Ways	Fail on <a href="https://screwdriver.cd/">https://screwdriver.cd/</a>
Headings and Labels	Fail
Focus Visible	Fail
Language of Page	Fail
Language of Parts	Pass
On Focus	Pass
On Input	Pass
Consistent Navigation	Pass
Consistent Identification	Pass
Error Identification	N/A
Labels or Instructions	Pass
Error Suggestion	N/A
Error Prevention (Legal, Financial, Data)	N/A
Parsing	Pass
Name, Role, Value	Fail


### 1.1.1 Non text purpose

<p><b>1.1.1 Non text purpose</b></p>	<p><b>Defect</b> Some images do not have alternative text value</p>
<p>Screenshots</p>	<p>These images do not have alternate text values.</p>  <p>Getting Started      Contact Us      Contributing  Documentation      Issues      Blog  Source Code      Twitter      Stack Overflow</p> <p>Copyright Yahoo Inc. 2021 Licensed by BSD-3-Clause , Theme by Rick K. , Photo by Don DeBold  Incubating Project of the Continuous Delivery Foundation</p>  

Reference	<p><b>How to fix:</b> All images should have alt text. If the image is important, it should have meaningful descriptive alt text. if image is not important, it should have empty (alt="") value</p> <p>Please use techniques shown here : <a href="https://www.w3.org/TR/WCAG20-TECHS/H37.html">https://www.w3.org/TR/WCAG20-TECHS/H37.html</a></p>
-----------	--

### 1.3.1 Info and relationships

1.3.1 Info and relationships	<p><b>Defect:</b> Some elements do not meet 1.3.1 requirements.</p>
Screenshots	<p>1. Some links are not directly under links</p>  <p>2. Some headings are not in logical order hierarchy</p> <p>Screwdriver is an open source build platform designed for Continuous Delivery.</p>  <p>These are H2</p> <p>Headings should start from H1 and increment in a hierarchical order from H1-H6, no heading level should be skipped</p> <p>This is H3</p> <p>These are H4, they should be in sequential hierarchical order</p>



### 3. Tables do not have Summary/caption

ocal ?  
cal  
nd  
j

key	description
api-url	The Screwdriver API URL of the cluster you are using
store-url	The Screwdriver Store URL of the cluster you are using
token	An <a href="#">API token</a> for the Screwdriver API of the cluster you are using
launcher-image	The launcher image (default: <code>screwdriver/launcher</code> )
launcher-version	The launcher version (default: <code>stable</code> )

## build command

This command runs builds in your local environment.

All tables do not have  
caption/summary

### Usage

Run a build for a specific job. Even if the build succeeds, other builds are not triggered.

```
$ sd-local build <job name>
```

It starts the build based on the `screwdriver.yaml` config in the current directory. Build artifacts will be created under the `"/sd-artifacts"` directory.


### Options

The following options can be used with the build command:


option	description
<code>--artifacts-dir</code>	The build artifacts destination (default: <code>"/sd-artifacts"</code> )
<code>-e, --env</code>	The environment variables in a build environment using <code>&lt;key&gt;=&lt;value&gt;</code> format (multiple variables allowed)
<code>--env-file</code>	The environment variables in a build environment using file format (refer to <a href="#">env-file format</a> )
<code>-i, --interactive</code>	Attach the build container in interactive mode
<code>-m, --memory</code>	The memory limit of the build environment (can be specified in b, k, m, or g memory unit)
<code>--meta</code>	The <a href="#">metadata</a> used in a build environment using string JSON format: e.g. <code>"({\"key\":\"value\"})"</code>
<code>--meta-file</code>	The <a href="#">metadata</a> used in build environment using file format
<code>--src-url</code>	The remote SCM URL to build ( <code>https</code> or <code>ssh</code> format)
<code>--sudo</code>	Use sudo command to execute docker runtime

Note:

### 4. Some buttons and form elements do not have proper labels



Button does not have  
any label

	
Reference	<p><b>How to fix:</b></p> <ol style="list-style-type: none"><li>1. <code>&lt;li&gt;&lt;a href="https://www.docker.com/products/docker"&gt;Docker for Mac 1.12+&lt;/a&gt;&lt;/li&gt;</code> use this format for listing links. Please use techniques shown here : <a href="https://www.w3.org/TR/WCAG20-TECHS/H37.html">https://www.w3.org/TR/WCAG20-TECHS/H37.html</a></li><li>2.<ul style="list-style-type: none"><li>• Main Heading should begin from H1.</li><li>• Sub heading of main heading should be H2 , sub-sub heading of main heading should be H3 and so on. No heading level should be skipped.</li><li>• Headings of similar kind of content should be consistent throughout the website.</li></ul></li><li>3. All tables should have descriptive summary or caption which describes the purpose of the table.</li></ol>

### 1.4.3: Contrast (Minimum)

<b>1.4.3: Contrast (Minimum)</b>	<b>Defect:</b> Defect: Many text do not meet the minimum contrast ratio of 4.5:1
Screenshots	<p>Use Color Contrast Analyzer test the text and its background Check for the contrast ratio of 4.5:1</p> <p>All links similar to the ones highlighted below do not meet minimum contrast ratio requirements, please fix all.</p> <p>Our experiences have inspired us to set out to build an intuitive, sophisticated tool to boost developer productivity. Special thanks to our original team members <a href="#">St. John Johnson</a>, <a href="#">Jeremiah Wuenschel</a>, <a href="#">Noah Katzman</a>, <a href="#">Peter Peterson</a>, <a href="#">Darren Matsumoto</a> and our resident designer <a href="#">Chas Turansky</a>. Other contributors include <a href="#">Min Zhang</a>, <a href="#">Filbert Jahia</a>, <a href="#">Pranav Ravichandran</a>, <a href="#">Ben Dang</a>, <a href="#">Zhongtang Tian</a>, <a href="#">Reetika Rastogi</a>, <a href="#">Cynthia Xin Li</a>, <a href="#">Yufeng Gao</a>, <a href="#">Philip Scott</a>, <a href="#">Joel Sequeira</a>, <a href="#">Ian Fox</a>, <a href="#">Brian Wang</a>, <a href="#">Nicolai Ferraris</a>, <a href="#">Jerry Zhang</a>, <a href="#">Ryosuke Nakayama</a>, <a href="#">Yomei Komiya</a>, <a href="#">Yuta Ohkawara</a> and our friends from Yahoo Japan.</p> <p>The Screwdriver team is based in Sunnyvale, CA.</p> <p>We've built Screwdriver with easy configurability and isolation as security in mind.</p> <ul style="list-style-type: none"><li>✓ Pick and choose plugins that make sense for you</li><li>✓ Not tied to any one compute platform</li><li>✓ RESTful, fully documented API</li><li>✓ Keep track of your config in code</li><li>✓ Control your own cluster</li><li>✓ It's free!!</li></ul> <p>Colour Contrast Analyser</p> <p>Options Image Help</p> <p>Foreground</p> <p>Colour select: Hex: #188FFF</p> <p>Background</p> <p>Colour select: Hex: #F5F5F5</p> <p>Result - luminosity</p> <p>Text</p> <ul style="list-style-type: none"><li>✗ Fail (AA)</li><li>✗ Fail (AAA)</li></ul> <p>Large text</p> <ul style="list-style-type: none"><li>✓ Pass (AA)</li><li>✗ Fail (AAA)</li></ul> <p>Foreground: #188FFF Background: #F5F5F5 The contrast ratio is: 3.0:1</p> <p>Text failed at Level AA Text failed at Level AAA Large text passed at Level AA Large text failed at Level AAA</p> <p><input type="checkbox"/> Show contrast result for colour blindness</p> <p>Copy results</p>

TRY IT TODAY

Colour Contrast Analyser

Options Image Help

Foreground

Colour select:



Hex:

#FFFFFF

Background

Colour select:



Hex:

#188FFF

Result - luminosity

Text



Fail (AA)



Fail (AAA)

Large text



Pass (AA)



Fail (AAA)

Foreground:#FFFFFF

Background:#188FFF

The contrast ratio is: 3.3:1

Text failed at Level AA

Text failed at Level AAA

Large text passed at Level AA

Large text failed at Level AAA

☐ Show contrast result for colour blindness

Copy results

Options Image Help

Foreground

Colour select:



Hex:

#777777

Background

Colour select:



Hex:

#F5F5F5

Result - luminosity

Text



Fail (AA)



Fail (AAA)

Large text



Pass (AA)



Fail (AAA)

Foreground:#777777

Background:#F5F5F5

The contrast ratio is: 4.1:1

Text failed at Level AA

Text failed at Level AAA

Large text passed at Level AA

Large text failed at Level AAA

☐ Show contrast result for colour blindness

Copy results

We've built Screwdriver with easy configurability and isolation as security in mind.


Choose plugins that make sense for you

✓ Keep track of your config in code

Up to any one compute platform

✓ Control your own cluster





	 <p>All similar text do not meet minimum contrast ratio requirements</p> <p>Sign in to Screwdriver</p> <p>driver uses your source code management solution to handle  driver access to your repos will allow us to automatically add  same permissions model to pipelines as you have already se</p> <p>Clicking this button will open a new window with your</p> <p>Sign in with GitHub  Sign in with Guest Access</p> <p>Colour Contrast Analyser</p> <p>Options Image Help</p> <p>Foreground</p> <p>Colour select: Hex: #21527C</p> <p>Background</p> <p>Colour select: Hex: #003ABC</p> <p>Result - luminosity</p> <p>Text</p> <p>Fail (AA)  Fail (AA)</p> <p>Large text</p> <p>Fail (AA)  Fail (AAA)</p> <p>Foreground: #21527C  Background: #003ABC</p> <p>The contrast ratio is: 1.1:1</p> <p>Text failed at Level AA  Text failed at Level AAA  Large text failed at Level AA  Large text failed at Level AAA</p> <p><input type="checkbox"/> Show contrast result for colour blindness</p> <p>Copy results</p>
Reference	<p><b>How to fix:</b> How to fix: The text and its background combination need to meet the minimum contrast ratio of 4.5:1</p> <p><a href="https://www.w3.org/WAI/WCAG21/Understanding/contrast-minimum.html">https://www.w3.org/WAI/WCAG21/Understanding/contrast-minimum.html</a></p>

### 2.4.1: Bypass Blocks

<b>2.4.1 Bypass Blocks</b>	<b>Defect</b> There are no bypass blocks on the website
	The intent of this Success Criterion is to allow people who navigate sequentially through content more direct access to the primary content of the Web page.
Reference	<p><b>How to fix:</b> Adding a link at the top of each page that goes directly to the main content area</p> <p>Please use techniques shown here :  <a href="https://www.w3.org/WAI/WCAG21/Understanding/bypass-blocks.html">https://www.w3.org/WAI/WCAG21/Understanding/bypass-blocks.html</a></p>


### 2.4.3 Focus order

<b>2.4.3 Focus order</b>	<b>Defect:</b> Menus do not have logical focus order
Screen shots	1. The complete menu does not have logical focus order

	 <p>2. Modal dialogs do not have logical focus order,</p> <ul style="list-style-type: none"> <li>On pressing ESC key, focus does not move to previously active element</li> <li>On multiple tab press, focus moves out of the dialog box.</li> </ul> 
Reference	<p><b>How to fix:</b></p> <ol style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>How a the highlighted menubutton and its menu and menuitems should behave -</li> <li>On pressing Enter/Space on menubutton – Opens/Closes the menu and sets focus on the first menuitem in the menu.</li> <li>Pressing ESC should close the menu and focus should move back to previously active parent element.</li> <li>On pressing Up/Down arrow key - Moves focus to the previous/next menu item. If focus is on the first/last menu item, moves focus to the last/first menu item.</li> </ul> </li> </ol> <p>Screen reader should announce the name of menuitem as they receive focus.</p>

	<a href="https://www.w3.org/TR/wai-aria-practices/examples/menubar/menubar-1/menubar-1.html">https://www.w3.org/TR/wai-aria-practices/examples/menubar/menubar-1/menubar-1.html</a>
	<p>2.</p> <ul style="list-style-type: none"> <li>When user presses Esc key, it should close the modal dialog and focus should move back to the previously active focusable element.</li> <li>For most dialogs, the expected behavior is that the dialog's tab order wraps, which means that when the user tabs through the focusable elements in the dialog, the first focusable element will be focused after the last one has been reached. In other words, the tab order should be contained within and by the dialog.</li> <li>On shift+tab key press: Moves focus to previous focusable element inside the dialog. When focus is on the first focusable element in the dialog, moves focus to the last focusable element in the dialog.</li> </ul>

## 2.4.4 Link Purpose


2.4.4 Link Purpose	Defect: Some links do not have descriptive label,
Screenshots	 <p>Screen reader announces link URL for ex: "http://&lt;github&gt;"</p> <p>Alan Dong adong</p> <p>Dao Lam DL</p> <p>Dekus Lam Over 8000</p> <p>Jithin Emmanuel RE:STalman</p> <p>Kevin Lu as himself</p> <p>Lakshminarasimhan Parthasarathy lparth</p> <p>Pritam Paul likes hikes</p> <p>Tiffany Kyi Turtle Addict</p> <p>Copyright Yahoo Inc. 2021 Licensed by <a href="#">BSD-3-Clause</a>, Theme by Rick K., Photo by Don DeBold</p> <p>Incubating Project of the <a href="#">Continuous Delivery Foundation</a></p> <p>generic quickstart in this example.</p> <ul style="list-style-type: none"> <li>generic*</li> <li>Golang</li> <li>Nodejs</li> <li>Ruby</li> </ul> <p>Screen reader should announce * if its significant</p> <pre>\$ git clone git@github.com:&lt;YOUR_USERNAME_&gt; \$ cd quickstart-generic/</pre>
Reference	<p><b>How to fix:</b> The description lets a user distinguish this link from links in the Web page that lead to other destinations and helps the user determine whether</p>



	<p>to follow the link. The URI of the destination is generally not sufficiently descriptive.</p> <p>Please use techniques shown here <a href="https://www.w3.org/TR/2016/NOTE-WCAG20-TECHS-20161007/G91">https://www.w3.org/TR/2016/NOTE-WCAG20-TECHS-20161007/G91</a>.</p>
--	---

#### 2.4.5 Multiple Ways

<b>2.4.5 Multiple Ways</b>	<b>Defect</b> There are no bypass blocks on the website
	The intent of this Success Criterion is to make it possible for users to locate content in a manner that best meets their needs. Users may find one technique easier or more comprehensible to use than another.
Reference	<p><b>How to fix:</b> Providing table of contents/search mechanism</p> <p>Please use techniques shown here : <a href="https://www.w3.org/TR/UNDERSTANDING-WCAG20/navigation-mechanisms-mult-loc.html">https://www.w3.org/TR/UNDERSTANDING-WCAG20/navigation-mechanisms-mult-loc.html</a></p>



#### 2.4.7: Focus Visible

<b>2.4.7: Focus Visible</b>	<b>Defect:</b> Many interactive elements do not have visible focus.
Screenshots	<p>In the screenshots below focus is not visible to users.</p>  <p>The screenshot shows a dark background with a grid of hexagonal shapes. A red rectangular box highlights the Screwdriver.cd logo in the top left. Below the box, the text 'Focus is not visible here' is written in red. In the bottom right corner, the word 'SCREW' is written in large blue letters, and 'Build.' is written in white below it.</p>


	<p>Focus not visible while using tab key</p>  <p>OUR AMAZING TEAM</p> <p>Alan Dong adong</p> <p>Dao Lam D2</p> <p>Dekus Lam Over 9000</p> <p>In the screenshots below links, although Technique C15 (using CSS to distinguish focus) is used, It is still not enough for users to identify with color related disabilities. Please fix this issue for all similar elements</p>  <p>✓ Pick and choose plugins that make sense for you</p> <p>✓ Not tied to any one compute platform</p> <p>✓ RESTful, fully documented API</p> <p>Focus is here but it is not much distinguishable</p> <p>✓ Keep track of your config in code</p> <p>✓ Control your own cluster</p> <p>✓ It's free!!</p> <p>This command will run a script that will create a Docker Compose file for you locally, complete with OAuth credentials using a generated JWT and a user-provided OAuth Client ID and secret. If you choose to do so, it will then Docker pull the Screwdriver API, UI, and log store images to bring up an entire Screwdriver instance locally for you to play with. All data written to a database will be stored in a data/ directory. For more configuration details, see our <a href="#">SD-in-a-box documentation</a>.</p> <p>For setting up a production environment, take a look at our <a href="#">documentation for cluster management</a>.</p> <p>Minimum Requirements:</p> <ul style="list-style-type: none"> <li>• Python 2.7</li> <li>• Docker for Mac 1.12+</li> <li>• Docker Compose 1.8.1+</li> <li>• Mac OSX 10.10+</li> </ul>
Reference	<p>How to fix: When the user places focus on an element, using the mouse, tab key, arrow keys, keyboard shortcuts, or any other method, the application should make that focus more visible, using a combination of a highly contrasting color, a thick line, and other visual indicators such as a glow.</p> <p>Please use techniques shown here : <a href="https://www.w3.org/WAI/WCAG21/Understanding/focus-visible">https://www.w3.org/WAI/WCAG21/Understanding/focus-visible</a></p>

#### 4.1.3 Names and roles

4.1.3 Names and roles	Defect: Elements used as menus should have proper roles
Screenshots	1. Some list of links are used as menu but they do not have correct roles

	 <p>2. Screen reader does not announce title of modal dialogs</p> 
Reference	<p><b>How to fix-</b></p> <ol style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>For Menu bar – Menu bar should have role=”menubar” which identifies the element as a menu bar container for a set of menu item elements and it is not focusable. It should have aria-label=”string” which defines an accessible name for menu bar.</li> <li>Elements identified as menu items inside a menu bar should have role=”menuitems”. Menuitems should have aria-haspopup, aria-expanded attributes. Implied “listitem” role of the li element should be removed with use of role=”none”.</li> <li>For Submenu – Element as a menu container for a set of menu items should have role=”menu”. Other roles for submenu follow the same usage as given for menu bar.</li> </ul> </li> <li>Provide title attribute for dialog boxes</li> </ol>

### 3.1.1 Language of Page

2.4.4 Link Purpose	Defect Website does not have the value of the LANG attribute set to one of the ISO 639 languages
Screenshots	
Reference	<p><b>How to fix:</b> How to fix: Website should have English as mentioned language. &lt;html lang="en"&gt;</p> <p>Please use techniques shown here : <a href="https://www.w3.org/WAI/WCAG21/Understanding/language-of-page.html">https://www.w3.org/WAI/WCAG21/Understanding/language-of-page.html</a></p>