(12) PATENT APPLICATION PUBLICATION

(19) INDIA

(22) Date of filing of Application: 12/07/2011 (43) Publication Date: 31/08/2012

## (54) Title of the invention: FREEZE-DRYER AND METHOD OF CONTROLLING THE SAME

<ul> <li>(51) International classification</li> <li>(31) Priority Document No</li> <li>(32) Priority Date</li> <li>(33) Name of priority country</li> <li>(86) International Application No Filing Date</li> <li>(87) International Publication No</li> <li>(61) Patent of Addition to Application</li> <li>Number Filing Date</li> <li>(62) Divisional to Application Number Filing Date</li> </ul>	:f26b9/00;F26B 5/06 :12/414,760 :31/03/2009 :U.S.A. :PCT/US2010/025135 :24/02/2010 :WO 2010/117508 :NA :NA :NA	(71)Name of Applicant:  1)PRAXAIR TECHNOLOGY, INC.  Address of Applicant: 39 OLD RIDGEBURY ROAD,  DANBURY, CONNECTICUT 06810, UNITED STATES OF  AMERICA U.S.A.  (72)Name of Inventor:  1)BRYCE RAMPERSAD  2)ROBERT REX SEVER  3)BALAZS HUNEK  4)THEODORE HALL GASTEYER, III
--	---	---

(21) Application No.5352/DELNP/2011 A

## (57) Abstract:

A freeze-dryer and method of controlling the same is provided. The disclosed freeze-dryer includes a chamber adapted to hold material or product to be freeze-dried; one or more depressurization orifices; a gas pressurization circuit having a source of gas to pressurize the chamber to a prescribed pressure; a depressurization circuit coupled to the chamber via the one or more orifices and having a depressurizing control valve; and a control unit adapted to pressurize the chamber with the source of gas and actuate the depressurizing control valve to depressurize the chamber upon command. The ratio of total depressurization orifice area to the chamber volume is preferably between about 6xl0-2 and about 4xl0-4m2/m3.

No. of Pages: 33 No. of Claims: 10