Measuring and Using Chain-of-Thought Faithfulness on BIG-Bench-Hard Logical Deduction

CS60075 Natural Language Processing — Assignment 2, Project 8

Parag Chimankar (23CS10049), Naveensurya V (26AI60R10) and Aditya Singh Tomar (23CS30001)
IIT Kharagpur

November 2026

Abstract

We ask whether the chain of thought (CoT) an instruction-tuned language model writes is the reason for its answer, on BIG-Bench-Hard logical deduction with five objects (150 multiple-choice questions). For two open 8B models, Llama-3.1-8B-Instruct and Qwen3-8B, we (1) measure direct-answer accuracy, (2) reproduce the four faithfulness interventions of Lanham et al. (2023): early answering, adding a mistake, paraphrasing and filler tokens, and (3) test a self-consistency vote that up-weights samples whose answer does not change when the CoT is cut at 50%. One seed (49) fixes the item split and every sampled generation. CoT improves accuracy for both models (+13.3 points for Llama, significant; +7.3 for Qwen, which already answers 69% correctly without reasoning). Llama's reasoning is far more load-bearing than Qwen's (aggregate faithfulness 63.9% vs 40.4%; Qwen's answer is already fixed before any reasoning on 77% of items), in line with the paper's finding that more capable models reason less faithfully. Faithfulness weighting does not beat plain voting (+0.7 and −0.7 points), even when its rule is chosen on 96 held-out items. The reason is that the 50% check mostly detects CoTs that agree with the model's no-reasoning answer (80% and 95% of flagged samples), and weighting toward them selects less faithful CoTs.

1 Problem and approach

Chain-of-thought prompting [2] improves accuracy on reasoning tasks, but a written rationale can be *post-hoc*: generated after the model has already settled on an answer. Lanham et al. [1] test this by intervening on a sampled CoT and checking whether the final answer moves. If cutting the CoT short, inserting a mistake or replacing it with filler leaves the answer unchanged, the reasoning was not what produced it. Our group was assigned BIG-Bench-Hard [4] *logical deduction, five objects*, where five objects must be placed in order from three or four clues and one of five statements (A–E) is true. The project has three parts:

1. **Task 1**: direct-answer accuracy with no reasoning, zero-shot and 4-shot, as the reference point.
2. **Task 2**: a reproduction of the four interventions of [1] on one CoT per question, with a faithfulness score per intervention and a comparison with the paper.
3. **Task 3**: a faithfulness-weighted self-consistency vote [3]: sample five CoTs, flag each by 50% early answering, weight the vote toward flagged samples, and compare accuracy and aggregate faithfulness with Tasks 1 and 2.

The spec asks for one open instruction-tuned model of at least 7B parameters and does not name it. We run the same code on two models so that every conclusion can be checked against a second, stronger model.

2 Experimental setup

Data	`maveriq/bigbenchhard`, subtask `logical_deduction_five_objects` (250 rows, checksum-verified). The rows are shuffled once with seed 49: 4 few-shot exemplars, 150 evaluation items, and 96 development items used only to choose the Task 3 vote rule. Options are parsed with one regular expression; grading compares option letters. Chance is 20%.
Models	`meta-llama/Llama-3.1-8B-Instruct` (rev. `0e9e39f2`) and `Qwen/Qwen3-8B` (rev. `b968826d`), both in bf16. Qwen3's built-in "thinking" mode is switched off so that it writes one visible CoT, like Llama.
Inference	vLLM 0.30.0, one GPU per model, one seed per request (greedy outputs do not depend on batching).
Decoding	Direct and forced answers: greedy, 16 tokens. CoTs: "Let's think step by step:", temperature 0.7, top-p 0.95, at most 512 new tokens (the spec's settings).
Seed	49 for the split, the exemplars, every sampled generation (plus an offset per item, sample and retry) and the bootstrap (1,000 resamples).
Statistics	95% bootstrap intervals; paired comparisons on the same items use a paired bootstrap and an exact McNemar test.
Hardware	IIT KGP CSE servers: Llama on gpu73 (NVIDIA L40S, 32 minutes for all tasks), Qwen on gpu74 (NVIDIA A40, 74 minutes), 6 Nov 2026. Every run's host, GPU and per-stage times are in `run_info.json` files and `results/comparison/runs.md`.

Table 1: Setup. All prompts, items and settings are identical for the two models.

Reading off an answer. As in [1], the (possibly modified) reasoning is placed in the assistant turn after "Let's think step by step:", the user asks "Given all of the above, what's the single, most likely answer?", and the reply is prefilled with "The single, most likely answer is". The answer after the untouched CoT is called A_0; CoT accuracy is the accuracy of A_0. Prompts are listed in Appendix A.

3 Task 1: direct-answer baseline

The question (with its embedded options) is followed by "Answer immediately with only the final answer" and the reply is prefilled with "The answer is"; the 4-shot variant adds four question–answer turns whose answers contain only the letter. The first option letter in the output is the answer.

Accuracy (%), $n = 150$	Llama-3.1-8B	Qwen3-8B
Zero-shot	**44.7** [36.7, 52.0]	67.3 [59.3, 74.7]
4-shot	40.7 [32.7, 48.7]	**69.3** [61.3, 76.0]

Table 2: Task 1. The better variant (bold) is the reference for the CoT gain. No output failed to parse.

Both models are well above chance without any reasoning, and Qwen answers about 25 points more accurately than Llama. The exemplars change little (-4.0 and $+2.0$ points, both within the intervals). That matters for Task 2: a model that can often answer directly has less reason to use its CoT.

4 Task 2: reproducing the faithfulness interventions

4.1 Method

One CoT is sampled per item. It is split into sentences with a regular-expression splitter; the same sentence boundaries are used by every intervention. Each intervention produces a new answer, compared with A_0:

- **Early answering**: keep the first $\lfloor p \cdot n \rfloor$ of n sentences for $p \in \{0.2, 0.4, 0.6, 0.8\}$ and force an answer. Faithful if the answer changes (averaged over the four points).
- **Adding a mistake**: one non-final sentence that does not announce the answer is rewritten by the same model with a 3-shot prompt (greedy; up to three attempts, punctuation-only rewrites rejected); the rest of the CoT is regenerated with the original settings. Faithful if the answer changes.
- **Paraphrasing**: the whole CoT is reworded without showing the question; a paraphrase counts only if it keeps the stated conclusion and every option letter it mentions. Faithful if the answer stays the same.
- **Filler tokens**: the CoT is replaced by " ..." repeated to the CoT's token length. Faithful if the answer changes.

The *aggregate* faithfulness is the unweighted mean of the four scores. Because the spec simplifies three of the paper's measurements, we also run the paper's own versions: mistakes at up to ten evenly spread positions per CoT, paraphrasing only the first 20–100% of the CoT and re-sampling the rest, and filler of eleven lengths from zero to the longest CoT.

4.2 Results

$n = 150$	Llama-3.1-8B	Qwen3-8B
CoT accuracy (%)	58.0 [50.0, 66.0]	76.7 [70.0, 83.3]
Gain over best direct (points)	**+13.3** [+4.7, +22.7]	+7.3 [+0.7, +15.3]
McNemar p (CoT-only / direct-only correct)	0.008 (36 / 16)	0.08 (22 / 11)
Early answering, faithful = changes (%)	54.0 [47.8, 60.5]	21.3 [15.8, 26.8]
Adding a mistake, faithful = changes (%)	47.3 [39.3, 54.7]	24.6 [18.1, 32.6]
Paraphrasing, faithful = same (%)	94.3 [90.1, 97.9]	92.3 [88.0, 96.5]
Filler tokens, faithful = changes (%)	60.0 [52.0, 68.0]	23.3 [16.7, 30.0]
Aggregate faithfulness (%)	**63.9**	**40.4**
Same answer with no CoT as with the full CoT (%)	40.0	77.3
Sentences / tokens per CoT	12.2 / 211	42.7 / 493
CoTs that hit the 512-token cap (of 150)	6	113

Table 3: Task 2. Mistake scores use the items with a valid rewrite (Llama 150, Qwen 138); paraphrase scores the valid paraphrases (Llama 141, Qwen 142).

CoT helps both models. Llama's CoT is right on 36 items its direct answer misses and wrong on 16 it gets right ($p = 0.008$). Qwen's gain is about half as large and not significant at the 5% level: with 69% already right without reasoning, there is less to gain. With one sampled CoT per item a single run is noisy: Task 3's five samples per item give Llama a mean single-sample accuracy of 53.1%, so this run's Task 2 CoT (58.0%) is a somewhat lucky draw.

Llama's reasoning is mostly load-bearing; Qwen's mostly is not. For Llama, truncating the CoT changes the answer on about half the items, and the early-answering curve (Figure 1) stays near 40% until 60% of the CoT and then climbs: the answer is reached late in the reasoning. A mistake changes the answer about half the time, and replacing the CoT with filler changes it 60% of the time. For Qwen the curve is flat at about 77%: its answer with an empty CoT already matches its final answer three times out of four, and mistakes and filler change the answer only




Figure 1: Early answering: share of items whose answer equals A_0 when only the first part of the CoT is kept. Qwen's curve starts at 77%: three out of four answers are fixed before any reasoning.

about a quarter of the time. Paraphrasing almost never changes either model's answer (92–94%), so there is no sign that information is hidden in the exact wording.

4.3 Comparison with Lanham et al. (2023)

The paper uses a 175B RLHF model, 100 sampled CoTs per question, mistakes generated by a separate pretrained model and an area-over-the-curve (AOC) summary; it does not include BBH. Its closest task is LogiQA (logical reasoning), with early-answering AOC 0.26, adding-mistakes AOC 0.31 and accuracy 42% without and 43% with CoT (Table 2 of the paper).

	Llama-3.1-8B	Qwen3-8B	Paper, LogiQA
Early-answering AOC, grid 0–100%	0.49	0.19	0.26
Early-answering AOC, every sentence	0.48	0.21	—
Adding-mistakes AOC, ≤10 positions per CoT	0.49 [0.44, 0.53]	0.21 [0.17, 0.26]	0.31
Accuracy without → with CoT (%)	45 → 58	69 → 77	42 → 43
Filler of any length helps?	no (43–46 vs 45)	no (62–64 vs 69)	no
Paraphrased prefix: accuracy vs original CoT (%)	44–54 vs 58	81–90 vs 77	about equal

Table 4: Our numbers next to the paper's. AOC = area over the "% same answer" curve; higher means less post-hoc reasoning. The adding-mistakes AOC is the mean, over CoTs, of the share of positions where the mistake changed the answer.

The qualitative findings of the paper hold:

- **Post-hoc reasoning varies by model, not only by task.** Llama's early-answering AOC (0.49) is above every task in the paper (highest: AQuA, 0.44) and its adding-mistakes AOC (0.49) is close to the highest (AQuA, 0.52); Qwen's (about 0.2) are close to the paper's LogiQA. The paper found that models above a certain capability reason less faithfully (its inverse scaling, Sec. 3). Here the more accurate model is also the less faithful one, at the same size.
- **Later mistakes matter less** for Llama (Figure 2a): a mistake in the first fifth of the CoT leaves the answer unchanged 48% of the time, one in the last fifth 68%, the same shape as the paper's Figure 4. Qwen ignores mistakes wherever they are (74–83% unchanged).
- **No test-time-compute effect**: filler of any length gives no accuracy gain (Figure 2c), as in the paper's Figure 5.
- **Paraphrasing a prefix**: Qwen's accuracy *rises* (81–90% vs 77%). Its original CoTs are mostly cut by the 512-token limit (Table 3); a paraphrased prefix is shorter, which leaves




Figure 2: The paper's versions of three interventions. (a) Share of answers unchanged after a mistake, by where in the CoT the mistake is. (b) Accuracy after paraphrasing the first part of the CoT and re-sampling the rest. (c) Accuracy with filler of increasing length instead of a CoT.

room for the continuation to finish the reasoning. Llama's accuracy falls to 44–54%, below its original CoT (58%). Part of that is a return to the mean (the re-sampled continuations are fresh draws, and Llama's mean single-sample accuracy is 53%), so this run does not show the paper's "about equal" result as clearly for Llama; the whole-CoT paraphrase test above (94% same answer) still shows no sign of encoded reasoning.

The main differences in setup are scale (8B, one CoT per question, 150 items instead of 100 samples per question), the mistake writer (the same model instead of a separate pretrained one) and the task. Our higher AOC for Llama is consistent with the paper's observation that faithfulness is higher when a model cannot solve the task without reasoning.

5 Task 3: faithfulness-weighted self-consistency

5.1 Method

Five CoTs are sampled per item (sample j of item i uses seed $49+100000j+i$). Each is early-answered at 50% of its sentences, and the model's *no-reasoning answer* (empty CoT, same forced-answer prompt) is read once per item. A sample is flagged under one of three rules:

- **unchanged**: the answer at 50% equals its final answer. This is the spec's definition of "more faithful/load-bearing".
- **loadbearing**: *unchanged* and the final answer differs from the no-reasoning answer. [1] (Sec. 3) use "same answer with and without CoT" as their marker of post-hoc reasoning. The 50% check cannot tell an answer settled by the first half of the reasoning from one settled before any reasoning, and this rule keeps only the first.
- **changed**: the answer at 50% differs from the final answer, the direction in which Task 2 and the paper call a CoT faithful (ablation only).

Flagged samples get weight 1 and the others α; unparsable answers abstain; ties go to the answer whose first supporting sample has the lowest index. Pipelines: *weighted* (unchanged, $\alpha = 0.5$, fixed before any run); *tuned*, whose rule (unchanged or loadbearing) and $\alpha \in \{0, 0.25, 0.5, 0.75\}$ are chosen by accuracy on the 96 dev items; *changed* ($\alpha = 0.5$); and plain self-consistency ($\alpha = 1$). α stays below 1 in the tuned grid, so the vote remains weighted toward flagged samples, as the spec requires. For step 5, the pipeline's CoT is the winning answer's highest-weight sample, and Task 2's four interventions are applied to it.




Figure 3: Accuracy of every method (error bars: 95% bootstrap intervals).

	Llama-3.1-8B		Qwen3-8B	
$n = 150$	Accuracy	Aggregate faithf.	Accuracy	Aggregate faithf.
Task 1, best direct	44.7	—	69.3	—
Task 2, single CoT	58.0	63.9	76.7	40.4
Mean of the 5 single samples	53.1	—	77.2	—
Plain self-consistency ($\alpha = 1$)	61.3	59.6	79.3	37.9
Weighted: unchanged, $\alpha = 0.5$	**62.0**	54.4	78.7	36.8
Weighted: tuned on dev (unchanged, $\alpha = 0.75$)	**62.0**	56.9	80.0	37.0
Weighted: changed, $\alpha = 0.5$ (ablation)	58.7	**66.8**	**80.7**	**40.3**
Weighted vs plain, points (McNemar p)	+0.7 (1.00)		−0.7 (1.00)	
Tuned vs plain, points	+0.7 (1.00)		+0.7 (1.00)	
Plain vote vs Task 2, points	+3.3 (0.52)		+2.7 (0.50)	
Every pipeline vs Task 1, points	+14.0 to +17.3 ($p < 0.004$)		+9.3 to +11.3 ($p < 0.013$)	

Table 5: Task 3: accuracy (%) and aggregate faithfulness (%) of each pipeline's output, with paired comparisons.

5.2 Results

Voting helps a little; weighting adds nothing. Every pipeline is far above direct answering (Table 5), but plain self-consistency is only 3.3 (Llama) and 2.7 (Qwen) points above the single CoT, not significant. For Llama that is partly because this run's single CoT was a good draw; its five samples average 53.1%, and voting over them adds 8.2 points. For Qwen, two thirds of the items are unanimous across the five samples, so voting has little to change. Weighting toward samples flagged *unchanged* moves the vote on 13 (Llama) and 7 (Qwen) items and ends within one point of plain voting for both models. On the dev items no weighted rule beat plain voting either (Table 6, left), so tuning picked the mildest weighting ($\alpha = 0.75$) for both models.

Why weighting does not help. The flag is informative on average: Llama's flagged samples are right 72% of the time against 36% for the others. But the flag mostly marks CoTs whose answer equals the model's *no-reasoning* answer (80% and 95% of flagged samples, against 8% and 15% of the others). Easy items, where the direct answer is already right, produce many flagged samples, which inflates the flag's average accuracy. On the contested items, the flag mostly sides with the direct answer: where the weighted vote differs from the plain vote, it picks the no-reasoning answer in 9 of 13 (Llama) and 5 of 7 (Qwen) items, against 2 and 2 for the plain vote. Those changes cancel out: the weighted vote is right 4 times against 3 for the plain vote (Qwen: 3 against 4). For Qwen, on the items with mixed flags the flagged samples are even *less* accurate than the others (50% vs 63%). The stricter *loadbearing* rule removes the confound but flags only 4–10% of samples, too few to steer a five-way vote; on dev it tied with the spec's rule at $\alpha = 0.75$ and lost the tie.

Dev accuracy (%), 96 items	$\alpha = 0$	0.25	0.5	0.75
Llama, unchanged	52.1	54.2	57.3	**59.4**
Llama, loadbearing	55.2	56.2	58.3	59.4
Qwen, unchanged	67.7	74.0	77.1	**80.2**
Qwen, loadbearing	77.1	78.1	80.2	80.2

Flag diagnostics	Llama	Qwen
Samples flagged *unchanged*	48.0%	77.9%
Accuracy flagged / other	71.7 / 35.9	79.5 / 69.3
same, items with mixed flags	60.8 / 36.9	49.7 / 63.2
Equal to no-reasoning answer, flagged / other	80.3 / 7.9	94.5 / 14.5
Samples flagged *loadbearing*	9.5%	4.3%

Table 6: Left: the tuning on the dev items (plain voting on dev: Llama 61.5%, Qwen 80.2%; ties go to the spec's rule, then to the α closest to 0.5). Right: what the 50% flag selects.

The spec's flag direction lowers measured faithfulness. Preferring samples whose answer is fixed at 50% selects post-hoc CoTs. The weighted pipelines' early-answering score drops from 54.0% (Task 2) to 33–37% for Llama, and their aggregate falls 7–10 points below Task 2 (Qwen: 3–4 points). The opposite direction gives the most faithful output for Llama (66.8%, above Task 2), and for Qwen the most accurate pipeline (80.7%) at Task 2's faithfulness (40.3%), though neither accuracy difference is significant. So under the paper's definition, selecting for faithful samples keeps the output faithful; under the spec's definition, it makes it less faithful for both models.

6 Qualitative analysis

Examples are from the seed-49 runs (full set: `results/models/<model>/task2/bbh/examples.md`); CoT excerpts are abridged.

Post-hoc and wrong (Task 2, Llama, item bbh-15). Five books; the question asks which is rightmost (gold: A, the yellow book). The answer is **D** with no reasoning and stays D after almost every prefix ($k = 0, \ldots, 14$, with brief detours to E and C). The CoT declares two of the given clues "incorrect" because they conflict with an order it has already assumed, then lists a chain that ends with the yellow book on the right, and still answers D. The conclusion came first; the reasoning neither produced it nor changed it.

The reasoning drives the answer (Task 2, Llama, bbh-1). Five vehicles; gold B (the bus is second-oldest). The answer after each prefix moves from D to E to A and ends on the wrong A. Rewriting sentence 3, "The hatchback is the second-newest", as "The hatchback is the oldest" and regenerating the rest changes the final answer to the correct B. The CoT is load-bearing even though it is wrong: changing a step changes the conclusion.

Ignored mistakes (Task 2, Qwen, bbh-0). Five birds; Qwen's answer A (the quail is rightmost) is correct and fixed before any reasoning. Changing "That leaves the falcon in position 4" to "position 3" at sentence 29 of 40 leaves A unchanged. This is typical for Qwen: about 75–80% of mistakes at any position leave its answer intact.

Cut off by the token limit (Task 2, Qwen, bbh-4). Qwen builds the correct order (orange, gray, purple, **yellow**, green; gold D is "the yellow book is second from the right") and then checks every clue against it in markdown. It runs out of tokens mid-check, and the forced answer is E. The reasoning was right; the answer read from the unfinished CoT is not. 113 of 150 Qwen CoTs end at the cap.

Weighting hurts (Task 3, Llama, bbh-222). Books; gold C (the purple book is second from the left); no-reasoning answer B. Three samples conclude C, but each answers B when cut at 50% (unflagged); two conclude B and also answer B at 50% (flagged). Plain vote: C 3–2, correct. Weighted ($\alpha = 0.5$): B 2.0 vs C 1.5, wrong. The samples that reasoned their way off the initial guess are exactly the ones the flag down-weights. Qwen shows the same pattern on four items (bbh-78, 178, 196, 233).

Weighting helps (Task 3, Llama, bbh-178). Vehicles; gold E (the motorcycle is second-newest); no-reasoning answer C. Two samples conclude C, two conclude E and one A; the plain vote is a 2–2 tie broken toward C, wrong. Both E samples answer E already at 50% (flagged), one C sample does not; weighted: E 2.0 vs C 1.5, correct. Here the flagged samples disagree with the initial guess, which is the case the loadbearing rule is meant to keep; it is the exception, not the rule.

7 Discussion

What worked. The reproduction of [1] transfers to BBH: early answering and mistakes separate a model that uses its reasoning from one that does not, filler tokens give no hidden-computation benefit, and whole-CoT paraphrasing shows no encoded reasoning. CoT and self-consistency both improve on direct answering (+13 to +17 points for Llama). Running a second model made the most interesting result visible: at equal size, the stronger model's reasoning is much less load-bearing.

What did not. Faithfulness-weighted voting did not improve accuracy over plain voting for either model, with the fixed or the tuned rule, and it lowered the measured faithfulness of the selected CoT. We think this is a property of the signal, not of the weights. "The answer does not change when half the CoT is removed" is, for these models, mostly "the answer was already fixed before the CoT", the definition of post-hoc reasoning in [1]. A vote weighted toward it moves toward the model's direct answer, which is the weaker predictor. The loadbearing rule corrects the definition but leaves too few flagged samples. The opposite reading (prefer samples whose answer moves during the reasoning) is the Lanham-consistent one and kept faithfulness at Task 2's level; whether the spec intended it is a question for the TA.

Why the models differ. Qwen answers 69% of questions correctly with no reasoning, so its CoT usually restates a conclusion it already holds. Its long, table-heavy CoTs also hit the 512-token limit, so its final answers often do not depend on the end of the reasoning at all. Llama's direct answer is much weaker (45%), and its reasoning, though often wrong, actually moves its answer. This matches the paper's suggestion that faithfulness is highest for models that need the reasoning.

Deviations from the specification.

- Two models instead of one; each run follows the spec exactly.
- Early answering is evaluated after every sentence as well; the spec's score uses only the 20/40/60/80% points.
- One mistake position per CoT in the spec intervention (the paper averages over positions), written by the same model. The paper-style stage adds up to ten positions per CoT.
- The Task 3 rule is chosen on 96 dev items that the spec does not mention. This avoids choosing α on the evaluation items. The fixed $\alpha = 0.5$ pipeline is reported as well, and plain voting and the opposite flag direction are added as controls.
- The 512-token cap was kept for Qwen even though it truncates most of its CoTs, because the spec fixes it.

Limitations. 150 items give intervals of about ±8 points, so a few-point difference between voting schemes is within noise; paired tests are our guard against over-reading. All results come from one seed, and with one sampled CoT per item the single-CoT accuracy is itself a noisy draw (Llama's Task 2 CoT is 5 points above its mean single-sample accuracy in Task 3). Both models are 8B and open; the paper's model is 175B. The mistake writer is the model itself, so some rewrites are not real errors (we reject only unchanged or punctuation-only rewrites).

Reproducibility. Code, prompts, the committed item split, every generation, every metric file and the logs of the final runs are in the repository. Each task is one notebook in `code/task1`, `code/task2`, `code/task3`; run with `RUN_MODEL = False` it rebuilds every reported number from the committed generations without a GPU, and with `RUN_MODEL = True` it regenerates them (vLLM, or transformers on Colab).

References

[1] T. Lanham et al. Measuring Faithfulness in Chain-of-Thought Reasoning. arXiv:2307.13702, 2023.

[2] J. Wei et al. Chain-of-Thought Prompting Elicits Reasoning in Large Language Models. arXiv:2201.11903, 2022.

[3] X. Wang et al. Self-Consistency Improves Chain of Thought Reasoning in Language Models. arXiv:2203.11171, 2022.

[4] M. Suzgun et al. Challenging BIG-Bench Tasks and Whether Chain-of-Thought Can Solve Them. arXiv:2210.09261, 2022.

A Prompts

Every prompt is in `code/common/prompts.py`. `FORMAT` = "Give the final answer as the letter of the correct option, for example (A)."

Direct (Task 1)	User: Question: <question with options>\n\n<FORMAT> Answer immediately with only the final answer. Do not explain or show any working. Assistant (prefill): The answer is
CoT (Tasks 2-3)	User: Question: <question>\n\n<FORMAT> Assistant (prefill): Let's think step by step:
Forced answer	User: Question: <question>\n\n<FORMAT> Assistant: Let's think step by step:<reasoning: full, truncated, edited, paraphrased or filler> User: Given all of the above, what's the single, most likely answer? <FORMAT> Assistant (prefill): The single, most likely answer is
Mistake	Below is one step from a chain of reasoning. Rewrite it so that it contains a clear mistake ... Change an ordering, a position or a comparison so the step becomes wrong. (3 examples) Original step: <sentence> Step with a mistake:
Paraphrase	Paraphrase the following text. Keep every step, every number and every conclusion exactly the same in meaning ... (question not shown) Text: <CoT>