

Memory Networks for Relation Extraction

曾双

2020.4.12

IJCAI 2017


Effective Deep Memory Networks for Distant Supervised Relation Extraction

Xiaocheng Feng, Jiang Guo, Bing Qin, Ting Liu, Yongjie Liu

SCIR, Harbin Institute of Technology, Harbin, China

{[xcfeng](mailto:xcfeng@ir.hit.edu.cn), [jguo](mailto:jguo@ir.hit.edu.cn), [qinb](mailto:qinb@ir.hit.edu.cn), [tliu](mailto:tliu@ir.hit.edu.cn), [yongjieliu](mailto:yongjieliu@ir.hit.edu.cn)}@ir.hit.edu.cn

Knowledge Base Triples: { Barack Obama, *EmployedBy*, United States
Barack Obama, *BornIn*, United States




| Latent Label | Sentence |
|-------------------|--|
| <i>EmployedBy</i> | S1: United States President Barack Obama meets with NBA player LeBron James Today. |
| <i>BornIn</i> | S2: Obama was born in the United States just as he has always said. |
| --- | S3: Obama ran for the united States Senate in 2004. |

Figure 1: Training sentences generated through distant supervision for a knowledge base containing two facts.

Motivation

- Not all context words contribute equally to the inference of relation for an entity pair.
- There exists dependencies (e.g., entailment, conflict) between different relations, which is a crucial cue to infer some instances with implicit relation expression. For instance, if triple (A, capital, B) holds, another triple (A, contains, B) will hold as well.



Entity Pair = (*Obama*, *United States*)

Obama is the 44th President of the *United States*.
Obama ran for the *United States* Senate in 2004.

...

...


Obama was born in the *United States* as he said.

Word-Level
Memory Network

Sentence Representation

Sentence-Level
Memory Network

Entity-Pair Representation



Embedding

Sentence

Obama was born in the *United States* as he said

Entity Pair

hop 2

hop 1

Attention

Linear

Attention

Linear

Obama

United States

Sentence
Representation

Attention

Attention

Relation 1

Attention

Attention

Relation i

Attention

Attention

Relation k

Word Level Attention

$$g_i = \tanh(W_{word-att}[m_i; w_{eh}; w_{et}] + b_{word-att})$$

$$\alpha_i = \frac{\exp(g_i)}{\sum_{j=1}^w \exp(g_j)}$$

$$x = \sum_{i=1}^w \alpha_i m_i$$

Selective-Attention over Instances

$$z_i = x_i A v_{r_j}$$

$$\cdot \quad \cdot \quad \cdot$$

$$\beta_i = \frac{\exp(z_i)}{\sum_{p=1}^n \exp(z_p)}$$

$$R_j = \sum_{i=1}^n \beta_i x_i$$

Selective-Attention over Relations

$$h_i = R_i B R_j$$

$$\gamma_i = \frac{\exp(h_i)}{\sum_{q=1}^k \exp(h_q)}$$

$$R_j^* = \sum_{i=1}^k \gamma_{ji} R_i$$

Feature-based methods

(1) **Mintz**: [Mintz *et al.*, 2009] proposed distant supervision paradigm and developed a multi-class logistic regression for classification. (2) **Multir** is a multi-instance learning method that was proposed by [Hoffmann *et al.*, 2011] with a deterministic “at-least-one” decision . (3) **MIML** [Surdeanu *et al.*, 2012] is a multi-instance multi-label approach for distant supervision using a graph model.

Neural-based methods

(1) **PCNN** [Zeng *et al.*, 2015] is a convolutional neural network based method for relation extraction. This method models overlapping relations by combining sentence-level relation extraction features into entity-pair-level results. (2) **ATT**: [Lin *et al.*, 2016] pointed out that distant supervision suffers from the entity pair wrong labeling problem. They developed a sentence-level attention model which can dynamically reduce the weights of those noisy instances and achieves state-of-the-art results.

| Dataset | Sentences | Pos EPs | Neg EPs | relations |
|----------|-----------|---------|---------|-----------|
| Training | 112,941 | 4,266 | 61,460 | 26 |
| Testing | 152,416 | 1,732 | 91,842 | 26 |

Table 1: Statistics of the filtered NYT10 dataset, where EP denotes entity pair.

| | Top 100 | Top 200 | Top 500 | Average |
|--------|-------------|-------------|---------|--------------|
| Mintz | 0.77 | 0.71 | 0.55 | 0.676 |
| Multir | 0.83 | 0.74 | 0.59 | 0.720 |
| MIML | 0.85 | 0.75 | 0.61 | 0.737 |
| PCNN | 0.84 | 0.77 | 0.64 | 0.750 |
| ATT | 0.86 | 0.80 | 0.68 | 0.780 |
| DMN | 0.89 | 0.82 | 0.68 | 0.797 |

Table 2: Precision values for the top 100, top 200, and top 500 extracted relation instances.




Figure 4: Precision-recall curves of various methods.

NAACL 2019

Relation Extraction with Temporal Reasoning Based on Memory Augmented Distant Supervision

Jianhao Yan¹, Lin He¹, Ruqin Huang², Jian Li^{3*}, and Ying Liu¹

¹Institute for Network Sciences and Cyberspace, Tsinghua University

²Department of Computer Science and Technology, Tsinghua University

³Institute for Interdisciplinary Information Sciences, Tsinghua University

{yjh16, he-114, hrq16}@mails.tsinghua.edu.cn

lijian83@tsinghua.edu.cn, liuying@cernet.edu.cn

Motivation

- DS RE : encoding and fusion
- The former encodes each instance into a low-dimensional representation.
- The latter combines representation of each instance. Then, their combination is used to predict the relation.

Motivation

- They all use a separate but identical encoding module among instances and introduce no difference temporally.
- They only adopt single step of fusion and introduce no sentence-level reasoning.

Motivation

- Angelina Jolie and Brad Pitt (using Wikidata). The knowledge base contains a factual relation of spouse between them with the valid period from August 2014 to September 2016.
- However, the extracted mention set contains instances about their marriage in 2014, as well as their divorce in 2016.
- Existing models may predict the relation of marriage since the instances may suggest a higher confidence for the relation of marriage.




Figure 1: Overall TempMEM architecture

- The temporal encodings should comply with the chronological order of instances.
- The difference between two time spots determines the similarity between two temporal encodings.

$$PE(j) = \begin{cases} \sin(j/10000^{d/d_m}) & \text{if } d \% 2 = 0 \\ \cos(j/10000^{(d-1)/d_m}) & \text{if } d \% 2 = 1 \end{cases}$$

$$m_j = [O_j; \lambda \cdot PE(j)].$$

Query Construction

We construct each query with the guidance of the following intuition.

- Relation extraction within instances is equal to the query “what is the *relation* between *head* and *tail* at time spot t_i ?”.

$$q_r = R_r + (E_{head} + E_{tail}) * \Phi_q,$$

$$q_{r,i} = [q_r; \lambda \cdot PE(i)].$$

Memory Addressing In addressing, we compute the similarity between the query vector $q_{i,r}$ and each candidate memory slot key K_j . Note that the encoding output m_j is not in the same continuous space as the query vector. So, we adopt linear projections to both memory keys:

$$K_j = A_h^T \cdot m_j, \quad (10)$$

where $A_h \in \mathbb{R}^{D_m \times D_r}$. Then, we compute the similarity score and importance probability using the bilinear form,

$$s_{i,j} = q_{i,r}^T \cdot W_a \cdot K_j, \quad (11)$$

$$p_{i,j} = \frac{\exp(s_{i,j})}{\sum_{\hat{j}=1}^M \exp(s_{i,\hat{j}})}, \quad (12)$$

Memory reading The value of each memory slot, which is also projected by an affine matrix $B \in \mathbb{R}^{D_m \times D_r}$, is read by computing the weighted sum over all memory slots with the importance probability derived in the addressing step:

$$\hat{q}_i = \sum_j p_{i,j} V_j, \quad (14)$$

where $V_j = B_h^T \cdot m_j$.




Figure 1: Overall TempMEM architecture

| Method | P@N_100 | P@N_200 | P@N_300 |
|-----------|--------------|--------------|--------------|
| CNN_ATT | 67.33 | 67.66 | 66.45 |
| CNN_ONE | 70.3 | 68.66 | 65.78 |
| TempMEM | 81.18 | 82.09 | 78.41 |
| TempMEM+R | 79.21 | 78.61 | 75.42 |
| TempMEM+P | 81.19 | 79.1 | 77.41 |

Table 2: Comparison with previous models.
P@N_100/200/300 refers to the precision for the highest 100, 200 and 300 predictions in WIKI-TIME.

| Method | Bag-level F1 | Query-level F1 |
|-----------|--------------|----------------|
| CNN_ATT | 39.66 | - |
| CNN_ONE | 40.15 | - |
| TempMEM | 47.88 | 54.75 |
| TempMEM+R | 46.76 | 47.83 |
| TempMEM+P | 54.86 | 60.01 |

Table 3: Manual evaluation of Bag-level and Query-level F1 scores in WIKI-TIME.

| id | Relation | Time Spot | Sentence |
|----|----------|------------|---|
| 0 | NA | 1957-01-01 | Her early career was marked by her collaboration with singer Stelios Kazantzidis . |
| 1 | NA | 1960-01-01 | ... instances of Marinella in films of Greek cinema, from the 1960 by 1966 with Stelios Kazantzidis ... |
| 2 | Spouse | 1964-05-07 | Marinella married Stelios Kazantzidis on 7 May 1964 ... |
| 3 | Spouse | 1964-05-07 | Stelios Kazantzidis married Marinella on 7 May 1964 ... |
| 4 | NA | 1966-09-01 | In September 1966 he divorced Marinella ... |
| 5 | NA | 1968-01-01 | Following Marinella 's departure Litsa Diamandi ... |
| 6 | NA | 1968-01-01 | Marinella sang on some songs ... |
| 7 | NA | 1968-01-01 | Marinella had an "answer back" to that latter song ... |

Table 4: Aligned sentences of ⟨ Stelios Kazantzidis , Marinella ⟩

Thanks!