

```
SQL> CREATE TABLE Customers (  
2   CustomerID INTEGER PRIMARY KEY,  
3   FirstName varchar(20),  
4   LastName varchar(20),  
5   City varchar(20)  
6 );
```

Table created.

```
SQL> INSERT INTO Customers VALUES (1, 'John', 'Doe', 'New York');
```

1 row created.

```
SQL> INSERT INTO Customers VALUES (2, 'Jane', 'Smith', 'Los Angeles');
```

1 row created.

```
SQL> INSERT INTO Customers VALUES (3, 'Mike', 'Brown', 'Chicago');
```

1 row created.

```
SQL> INSERT INTO Customers VALUES (4, 'Sara', 'Wilson', 'Houston');
```

1 row created.

```
SQL> INSERT INTO Customers VALUES (5, 'David', 'Lee', 'San Francisco');
```

1 row created.

```
SQL> INSERT INTO Customers VALUES (6, 'Emily', 'Clark', 'Seattle');
```

1 row created.

```
SQL> INSERT INTO Customers VALUES (7, 'Robert', 'Taylor', 'Miami');
```

1 row created.

```
SQL> INSERT INTO Customers VALUES (8, 'Sophia', 'Anderson', 'Boston');
```

1 row created.

```
SQL> select * from Customers;
```

CUSTOMERID	FIRSTNAME	LASTNAME	CITY
1	John	Doe	New York
2	Jane	Smith	Los Angeles
3	Mike	Brown	Chicago
4	Sara	Wilson	Houston
5	David	Lee	San Francisco
6	Emily	Clark	Seattle
7	Robert	Taylor	Miami
8	Sophia	Anderson	Boston

8 rows selected.

```
CREATE TABLE Orders (  
    OrderID INTEGER PRIMARY KEY,
```

```
CustomerID INTEGER,  
OrderDate varchar(20),  
Amount REAL,  
FOREIGN KEY (CustomerID) REFERENCES Customers(CustomerID)  
);  
Table created.
```

```
SQL> INSERT INTO Orders VALUES (101, 1, '2024-01-10', 250.00);
```

1 row created.

```
SQL> INSERT INTO Orders VALUES (102, 1, '2024-03-15', 450.00);
```

1 row created.

```
SQL> INSERT INTO Orders VALUES (103, 2, '2024-02-20', 300.00);
```

1 row created.

```
SQL> INSERT INTO Orders VALUES (104, 2, '2024-03-25', 275.00);
```

1 row created.

```
SQL> INSERT INTO Orders VALUES (105, 3, '2024-04-05', 500.00);
```

1 row created.

```
SQL> INSERT INTO Orders VALUES (106, 4, '2024-04-18', 150.00);
```

1 row created.

```
SQL> INSERT INTO Orders VALUES (107, 5, '2024-05-01', 700.00);
```

1 row created.

```
SQL> INSERT INTO Orders VALUES (108, 5, '2024-05-20', 650.00);
```

1 row created.

```
SQL> select * from Orders;
```

ORDERID	CUSTOMERID	ORDERDATE	AMOUNT
101	1	2024-01-10	250
102	1	2024-03-15	450
103	2	2024-02-20	300
104	2	2024-03-25	275
105	3	2024-04-05	500
106	4	2024-04-18	150
107	5	2024-05-01	700
108	5	2024-05-20	650

8 rows selected.

```
SQL> CREATE VIEW CustomerFullName AS
```

```
2 SELECT CustomerID, FirstName || ' ' || LastName AS FullName, City
```

```
3 FROM Customers;
```

View created.

```
SQL> CREATE VIEW OrderDetails AS
```

```
2 SELECT
```

```
3   Orders.OrderID,
```

```
4   Customers.FirstName || ' ' || Customers.LastName AS CustomerName,
```

```
5   Orders.OrderDate,
```

```
6   Orders.Amount
```

```
7 FROM Orders
```

```
8 JOIN Customers ON Orders.CustomerID = Customers.CustomerID;
```

View created.

```
SQL> SELECT * FROM CustomerFullName;
```

CUSTOMERID FULLNAME

CITY

1 John Doe	New York
2 Jane Smith	Los Angeles
3 Mike Brown	Chicago
4 Sara Wilson	Houston
5 David Lee	San Francisco
6 Emily Clark	Seattle
7 Robert Taylor	Miami
8 Sophia Anderson	Boston

8 rows selected.

```
SQL> SELECT * FROM OrderDetails WHERE Amount > 300;
```

ORDERID	CUSTOMERNAME	ORDERDATE
102	John Doe	2024-03-15
		450
105	Mike Brown	2024-04-05
		500
107	David Lee	2024-05-01
		700

ORDERID	CUSTOMERNAME	ORDERDATE
108	David Lee	2024-05-20
		650

```
SQL> CREATE VIEW SimpleCustomerView AS
```

```
2 SELECT CustomerID, City
```

```
3 FROM Customers;
```

View created.

```
SQL> UPDATE SimpleCustomerView
```

```
2 SET City = 'San Francisco'
```

```
3 WHERE CustomerID = 2;
```

1 row updated.

```
SQL> DROP VIEW OrderDetails;
```

View dropped.

```
SQL> DROP VIEW CustomerFullName;
```

View dropped.