

CSE 543: Information Assurance and Security

Group 11 - Course Project Report

A Security Framework for Injection and Context Integrity Attacks in Smart Home and IoT Applications

Team Members

Name	Role	Mail
Chaitanya Muzumdar	Leader	cmuzumda@asu.edu
Chioma Okeke	Co-Leader	cpokeke@asu.edu
Abhishek Singh	Member	asing807@asu.edu
Advait Kankati	Member	akankati@asu.edu
Chetan Chadalawada	Member	cchadal2@asu.edu
Dan Pham	Member	dhpham2@asu.edu
Divanshu Chauhan	Member	divchauhan@asu.edu
Harsha Koushik Teja Aila	Member	haila1@asu.edu

1. Introduction....4
1.1. Motivation....4
1.2. Background....5
1.3. Scope....5
1.4. Goals....6
2. Summary....7
3. Responsibilities and Accomplishments of Each Group Member....10
3.1. Chaitanya Muzumdar....10
3.2. Chioma Okeke....11
3.3. Abhishek Singh....11
3.4. Advait Kankati....11
3.5. Chetan Chadalawada....12
3.6. Dan Pham....13
3.7. Divanshu Chauhan....13
3.8. Harsha Koushik Teja Aila....14
4. Results - Implementation Architecture and Testbed Validation....16
4.1. Foundations of the Security Problem in LLM-Enabled Smart Homes....16
4.1.1. Why Smart Homes Create a Unique Attack Surface....16
4.1.2. The Role of IoT and AIoT Security Challenges....17
4.1.3. Why Existing Smart-Home Security Is Not Enough....17
4.2. Prompt Injection Attack Taxonomy and Threat Models....18
4.2.1. Direct Prompt Injection Attacks....19
4.2.2. Indirect Prompt Injection Attacks....20
4.2.3. Tool-Integrated and Agentic Attacks....21
4.2.4. Compound and Combined Attacks....22
4.2.5. Threat Model Implications for the Project Testbed....23
4.3. Machine Learning-Based Detection of Prompt Injection....24
4.3.1. Embedding-Based Classification as a Semantic Defense Layer....25
4.3.2. Why Random Forest and Similar Classical Models Matter....25
4.3.3. What ML Detection Can and Cannot Do....26
4.3.4. Why Detector-LLMs Are a Poor Substitute....26
4.3.5. Implications for the Present Implementation....27
4.4. Privacy-Preserving and Distributed Detection Models....27
4.4.1. Federated Learning as a Privacy-Preserving Defense Direction....27
4.4.2. Broader IoT Privacy and Integrity Considerations....28
4.4.3. Practical Constraints of Federated Detection in Smart Homes....28
4.4.4. Why Privacy Matters to the Credibility of the Framework....28
4.5. System-Level Safeguards and Context-Aware Controls....29
4.5.1. Action Allowlisting and Strict Output Mediation....29
4.5.2. Contextual Integrity and Runtime Permission Logic....29
4.5.3. Behavior-Aware Security in the Smart-Home Environment....30

4.5.4. Why LLM-Based Detection Alone Fails..... 30
4.5.5. Why Layered Security Is the Only Credible Design.....31
4.5.6. Architectural Diagram..... 32
4.6. Performance Evaluation and Key Metrics.....33
4.6.1. Attack-Centric Metrics for Injection Resilience..... 35
4.6.2. Detection-Centric Metrics for the ML Layer..... 35
4.6.3. System-Centric Metrics for Real Smart-Home Use.....36
4.6.4. Robustness, Utility, and Risk-Sensitive Metrics.....36
4.7. Implications of the Research Findings.....37
4.7.1. Prompt Injection Is a Structural, Not Incidental, Risk..... 37
4.7.2. Smart-Home Security Must Become LLM-Aware.....38
4.7.3. Security and Privacy Must Be Co-Designed..... 38
4.7.4. Why Layered Mitigation Is a More Honest Contribution than “Complete Prevention”.....38
4.8. Deployment Challenges, Trade-Offs, and Future Directions.....39
4.8.1. Security vs Usability.....40
4.8.2. Security vs Latency.....40
4.8.3. Security vs Privacy.....41
4.8.4. Need for Better Smart-Home-Specific Benchmarks.....41
4.8.5. Future Research Directions.....42
4.9. Implementation Screenshot.....43
5. Conclusion and Recommendations.....44
5.1. Summary of detailed results.....44
5.2. Recommendations for Mitigating Injection and Context Integrity Attacks..... 45
5.2.1. Recommendations.....46
5.2.2. Future Research Directions in Injection and Context Integrity Security.....49
5.2.3. Summary.....51
5.3. Future prospects and Ongoing Research..... 51
5.3.1. Emerging Trends in Information Security for Smart Home and IoT Systems 52
5.3.2. Advancements in AI and Emerging Technologies for Smart Homes and Security.....53
5.3.3. Continuing Research and Development.....54
6. Reference..... 57

1. Introduction

The rapid adoption of smart home technologies has led to the widespread integration of Internet of Things (IoT) devices with Large Language Models (LLMs) for automation and intelligent control. These systems enable natural language interaction and automated decision-making across smart-home environments. However, this integration introduces critical security risks, particularly prompt injection and context integrity attacks, where malicious instructions embedded in untrusted inputs can manipulate LLM behavior, leading to unauthorized device actions, privacy breaches, and potential system compromise.These vulnerabilities directly impact core Information Assurance properties such as confidentiality, integrity, and availability in smart-home systems.

Recent research on LLM integrated systems highlights that these models operate on mixed-trust inputs, combining user commands with external data sources such as APIs, retrieved content, and sensor data. This creates an inherent vulnerability where adversarial inputs can override intended system behavior, similar to how deepfake systems manipulate trust and authenticity in digital media environments. Such risks are especially significant in IoT ecosystems, where continuous data flow increases the attack surface.

This project addresses these challenges by proposing and evaluating a security framework for detecting and mitigating prompt injection attacks in LLM enabled smart-home environments, focusing on machine-learning-based defenses combined with system level safeguards to improve system integrity, reliability, and information assurance.

1.1. Motivation

The motivation for this project comes from the growing reliance on LLMs to process different and often untrusted data sources in IoT systems. Inputs such as simulated device outputs, user commands, and external data sources may contain hidden or adversarial instructions capable of altering system behavior.Traditional rule-based filtering is not enough for these attacks, especially in dynamic and context-aware environments.

What makes this particularly concerning in smart home devices is the consequence of a successful attack, an adversary manipulating an LLM orchestrator could unlock doors, disable alarms, or silently exfiltrate sensor data, all through nothing more than a carefully crafted text string. Therefore, there is a clear need to explore machine-learning-based

detection techniques that can identify malicious instructions before they influence LLM decision-making, while also preserving system usability and user privacy.

1.2. Background

Smart home systems operate through interconnected IoT devices that continuously generate and exchange data. With the integration of large language models (LLMs), these systems can interpret natural language commands and contextual information to automate tasks. However, this architecture introduces a key vulnerability: LLM-based applications often combine trusted system instructions with untrusted external inputs within the same context, making them susceptible to prompt injection attacks.

Recent studies on LLM-integrated applications show that malicious instructions embedded in user inputs or external data sources can override intended system behavior and bypass safety constraints. In particular, prompt injection attacks can originate not only from direct user input but also from indirect sources such as retrieved documents, web content, or other external inputs processed by the model. This indirect injection scenario is especially relevant in IoT environments, where data from sensors, APIs, or external services is continuously incorporated into the system's decision-making process.

In LLM-enabled smart-home systems, both trusted instructions and untrusted external inputs are processed within a shared context, increasing the risk of prompt injection. Prior work shows that adversarial inputs from users or external sources can override intended behavior and bypass safety mechanisms. To mitigate these risks, recent approaches focus on embedding-based detection and system-level safeguards such as action restriction and anomaly-aware validation.

1.3. Scope

This project focuses on evaluating ML-based defenses against prompt injection attacks in LLM-enabled smart home systems. The scope includes:

- Simulating a smart home environment with two virtual IoT devices, a Smart Bed and a Washing Machine, interacting through a centralized LLM-based control pipeline built using FastAPI and the OpenRouter API.
- Modeling six prompt injection attack types, five direct variants following the formal taxonomy from Liu et al. [28] and one indirect injection scenario drawn from Zhan et al. [18] and Greshake et al. [7], tested against both a defended and an undefended baseline server.

- Implementing a sequential three-layer defense pipeline combining an embedding-based Random Forest classifier using all-MiniLM-L6-v2 embeddings (Layer 1) [4], input sanitization via normalization and delimiter injection (Layer 2) [28], and output validation through action allowlisting and canary token detection (Layer 3) [28][11].
- Integrating a Federated Learning simulation to train the classifier across distributed smart home nodes without centralizing raw data, addressing privacy concerns raised in Jayathilaka [2].

The project does not target real hardware deployments or exhaustive attack coverage, focusing instead on controlled, paper-traceable evaluation within a simulated environment.

1.4. Goals

- To design and implement a secure smart home testbed integrating IoT devices with an LLM orchestrator, where every component traces back to a studied research paper [4][28][18][7][2].
- To evaluate the effectiveness of an embedding-based Random Forest classifier [4] in detecting prompt injection attacks, measured by ASR, FPR, precision, recall, F1, and accuracy.
- To assess the contribution of each individual defense layer [28][11] by comparing the full three-layer pipeline against an undefended baseline using paired evaluation.
- To analyze trade-offs between security and false positive rate, particularly the impact of classifier tuning on legitimate smart home commands.
- To implement and evaluate a Federated Learning approach [2] for privacy-preserving detection, comparing it against centralized training across simulated smart home nodes.

2. Summary

The project focused on addressing one of the most important emerging security challenges in modern smart home and IoT environments, namely prompt injection and context integrity attacks in Large Language Model enabled control systems. As smart homes increasingly rely on LLMs to interpret user commands, process sensor outputs, and coordinate automated actions, the risk of malicious instruction manipulation becomes much more serious because model generated outputs can affect physical devices, user privacy, and overall system integrity.

The team reviewed a broad set of research papers through both high level and in depth analyses. These papers covered topics such as direct and indirect prompt injection attacks, tool integrated LLM agent threats, embedding based prompt injection detection, federated learning for privacy preserving defense, contextual integrity in smart home platforms, anomaly detection in IoT, and broader AIoT security challenges.

The primary goal of the project was to study and implement practical defense techniques that could improve the security, reliability, and trustworthiness of LLM enabled smart home environments. Rather than treating prompt injection as only a language model issue, the project examined it as a real system security problem where unsafe semantic decisions may lead to unauthorized device actions or privacy violations.

The literature clearly showed that modern LLM integrated systems are vulnerable because they process both trusted instructions and untrusted external inputs within the same context. This mixed trust design allows malicious prompts, retrieved content, and indirect data sources to alter model behavior. In smart home settings, such attacks are especially dangerous because they can influence systems that control physical devices and routines [1][7][12][18][28].

A major outcome of the project was the design and implementation of a three layer security framework for a simulated smart home IoT environment. The implemented framework includes Layer 1 semantic prompt inspection using all MiniLM L6 v2 embeddings with a Random Forest classifier, Layer 2 input normalization and prompt hardening, and Layer 3 output validation through action allowlisting, safety checks, and parameter validation. This defense pipeline was implemented in a FastAPI based backend and integrated into a complete smart home testbed.

The project also developed a simulated smart home environment using two virtual IoT devices, namely a Smart Bed and a Washing Machine, connected through a centralized

LLM driven orchestration pipeline. These devices were not treated as generic placeholders, but were associated with explicit safety restrictions such as bounded operating parameters and confirmation requirements for higher risk actions. This helped make the implementation more representative of security sensitive smart home control.

Another important accomplishment of the project was the creation of a defended and undefended system setup for paired evaluation. This allowed the team to compare attack success behavior under protected and unprotected conditions, which made the analysis more rigorous than simply testing whether attacks existed. The repository also includes attack execution tooling, evaluation scripts, metrics export support, and a frontend dashboard for observing system behavior and comparison results.

Through the implementation and evaluation, the team observed that embedding based machine learning methods provide a strong first defense against malicious inputs, especially when combined with deterministic system controls. The results showed that the layered framework was able to significantly reduce successful attack behavior while maintaining a high benign pass rate and acceptable end to end latency. At the same time, the team also identified limitations, especially for structurally deceptive attack styles such as fake completion attacks, which remained harder to detect perfectly.

The project also explored federated learning as a privacy preserving extension to the defense framework. Instead of assuming that all smart home input data should be centralized for model improvement, the federated learning component was used to study how collaborative training could support stronger detection while preserving household privacy. This reflects the broader need to co-design security and privacy in smart home systems rather than treating them as separate concerns [2][21][25][48].

The overall analysis revealed that prompt injection defense in smart home systems cannot rely on a single mechanism. Machine learning based detection is useful, but not sufficient on its own. Likewise, traditional IoT protections such as authentication and encryption are necessary, but they do not directly solve the semantic manipulation problem introduced by LLM driven control. The most reliable approach is therefore defense in depth, where semantic screening, input hardening, output restriction, contextual validation, and device level safety controls work together [4][7][18][28][33][39].

The project also identified important challenges that remain open for future work. These include improving robustness against adaptive and structure preserving injection attacks, strengthening context aware action validation, reducing false positives on legitimate user requests, and moving from a simulated environment toward more realistic deployment

conditions. Additional work is also needed to create smart home specific prompt injection benchmarks and to improve explainability so that security decisions made by the system are easier to interpret and trust.

More broadly, the project showed that LLM enabled smart homes create a new class of security problem in which the correctness of device behavior depends not only on secure communication and valid software, but also on the trustworthiness of semantic interpretation. This means that future smart home security research must become more aware of LLM related threats and must design control systems with explicit safeguards against prompt based manipulation.

The following are the summarized outcomes of the project:

- A comprehensive study of recent research on prompt injection, context integrity, IoT security, and LLM based system risks in smart home environments
- Design and implementation of a three layer security framework for prompt injection defense in a simulated LLM enabled smart home testbed
- Development of a defended and undefended evaluation setup with attack runner, metrics support, and dashboard based visualization
- Experimental evaluation showing that layered security can significantly reduce attack success while preserving usability and interactive performance
- Exploration of federated learning as a privacy preserving direction for improving distributed prompt injection detection in smart home environments
- Practical insights into how machine learning, system level safeguards, and contextual control policies can work together to strengthen the security and reliability of next generation IoT systems.

3. Responsibilities and Accomplishments of Each Group Member.

3.1. Chaitanya Muzumdar

- Served as the team leader, overseeing overall project coordination, ensuring consistent progress across all phases, and maintaining clear communication among team members throughout the duration of the project.
- Facilitated team meetings by collaborating with members to align on research directions, discuss findings, and make key decisions regarding the structure and scope of the security framework.
- Designed and maintained the project Gantt chart, managing task scheduling, deadline tracking, and milestone progression to keep the project on track from inception to final submission.
- Monitored and reviewed weekly progress updates from team members, ensuring responsibilities were being fulfilled and that the project remained aligned with its objectives.
- Conducted an in-depth literature review of six research papers focused on prompt injection attacks and defences in LLM-based systems, covering topics such as indirect prompt injection in real-world applications, universal attack strategies, multimodal instruction hijacking via images and audio, agent workflow exploitation, attention-based attack detection, and lightweight prompt injection defences.
- Created and submitted group weekly reports, ensuring they accurately reflected completed work and maintained coherence with the project's overall direction.
- Managed the team's shared documentation workspace, keeping research materials, drafts, and reports organised and accessible to all members.
- Provided feedback on team members' individual research contributions, helping to refine their sections for technical accuracy and relevance to the project's security framework scope.
- In-depth reference studied: [6][7][8][9][17][52]

3.2. Chioma Okeke

- Served as the Deputy Team Lead, supporting overall project oversight and ensuring steady progress across assigned areas of the team's work.
- Tracked and reviewed weekly progress updates from designated team members, ensuring tasks were completed on time and aligned with the project's objectives.
- Carried out an in-depth literature review of six research papers centered on prompt injection attacks and defense mechanisms in LLM-based systems, contributing key insights to the project's foundation.
- Stepped in to prepare and submit weekly group reports when required, maintaining consistency in documentation and ensuring continuity in the team's reporting process.
- Provided constructive feedback on team members' individual contributions, helping improve technical accuracy, clarity, and alignment with the overall security framework.
- In-depth reference studied: [1], [2], [7], [11], [24], [28]

3.3. Abhishek Singh

- Pitched in the idea for the project and potential topics that can be used.
- Read and understand the relevant research papers and articles I searched the web thoroughly for.
- Prepared 8 High Level reviews, consisting of 17 research papers.
- Worked towards an in-depth literature review of 6 research papers.
- Performed the delegated tasks from time to time by the reader, such as reading the report of another student and making sure that all the research papers taken into consideration were made available.
- At times, proofread the overall reports as instructed by the leader.
- In-depth reference studied: [27][12][22][19][21][20]

3.4. Advait Kankati

- Helped in deciding the initial topics for the project.

- Found, read, and understood relevant research papers for the project.
- Conducted literature review of multiple papers and made 3 high-level reports and 17 in-depth reports.
- Went to the writing center and wrote a report on what was discussed.
- Reviewed partners' in-depth reports.
- Assisted in the implementation portion of the project. Helped with testing and fixing bugs.
- Helped the leader and deputy leader edit the weekly report.
- In-depth reference studied: [1][3][30]

3.5. Chetan Chadalawada

- I played a role in the project by proposing the initial concept and recommending various topics associated with security in smart home and IoT applications.
- I assisted in compiling the references for the entire project report, ensuring that all research sources were accurately cited and systematically organized.
- I reviewed and comprehended 20 research papers pertinent to the project's emphasis on injection attacks and context integrity attacks within smart home and IoT systems.
- I created 8 high-level review reports and 6 detailed review reports based on the chosen papers.
- Through my literature review, I explored subjects such as contextual integrity, intrusion detection, anomaly detection, malware detection, botnet attacks, DDoS attacks, code injection, smart home privacy, and IoT security frameworks.
- I utilized the insights obtained from these papers to enhance the literature review and bolster the development of the proposed security framework.
- In summary, I contributed to establishing the theoretical and technical foundation of the project titled "A Security Framework for Injection and Context Integrity Attacks in Smart Home and IoT Applications."
- In-depth reference studied: [33], [34], [45], [46], [47],

3.6. Dan Pham

- Helped narrow down everyone's topics from the Google Forms into an idea of AI and IoT, otherwise as smart devices.
- Found, read, and reviewed research articles useful for the project.
- Reviewed assigned partner's reviews during the research phase.
- Assisted in the implementation portion of the project. Brainstorming what kind of system we should emulate → smart bed.
- Helped with testing and fixing bugs within the implementation.
- In-depth reference studied: [16], [24], [28]

3.7. Divanshu Chauhan

- Led the implementation and integration of the smart home security testbed, developing the core backend infrastructure and frontend dashboard for the prompt injection defense framework.
- Designed and implemented the 3-layer defense pipeline architecture (Layer 1: ML Classifier, Layer 2: Input Prevention, Layer 3: Output Validation) based on research papers [12], [22], and [7].
- Developed the embedding-based machine learning detector using sentence-transformers (all-MiniLM-L6-v2) and Random Forest classifier, achieving 94.12% accuracy and 100% F1 score in evaluation.
- Implemented the federated learning simulation module using Flower framework, enabling privacy-preserving collaborative detection across multiple smart home nodes per Paper [23].
- Built the Next.js 16 frontend "ShieldView" dashboard with React 19, Tailwind CSS 4, and Framer Motion animations, providing interactive visualization of the defense pipeline, attack simulations, and real-time metrics.
- Created the device registry and IoT device simulators (Smart Bed and Washing Machine) with action allowlisting, parameter bounds validation, and high-risk action confirmation requirements.

- Implemented the evaluation framework following Paper [12]'s 11-step methodology, including attack success judgment, threshold sweep analysis, and comprehensive metrics (ASR, FPR, Precision, Recall, F1).
- Conducted comprehensive literature review of 22 research papers on prompt injection attacks, LLM security, and IoT vulnerabilities, preparing 10 high-level analysis reports and 3 in-depth reviews.
- Managed project repository maintenance, including cleanup of outdated documentation, configuration updates, and comprehensive .gitignore exclusions for production readiness.
- Performed delegated tasks including proofreading team reports, verifying research paper availability, and ensuring consistency across submission deliverables.
- In-depth reference studied: [18], [26], [28]

3.8. Harsha Koushik Teja Aila

- Actively contributed to the research phase by selecting, reading, and analyzing 22 research papers related to prompt injection, LLM security, and IoT systems.
- Prepared 17 high-level analysis reports covering, summarizing key problems, methodologies, and security insights relevant to the project.
- Conducted in-depth literature review of 6 research papers, focusing on understanding attack mechanisms, experimental setups, and defense strategies for prompt injection and data injection attacks.
- Explored multiple domains including LLM-based prompt injection attacks, AI agent security, IoT vulnerabilities, anomaly detection, federated learning, and context integrity frameworks, and connected these insights to the project’s problem statement.
- Contributed to the development of the project report by working on sections such as background, motivation, and summary, ensuring alignment with the selected research papers and improving overall clarity.
- Performed delegated tasks such as reviewing peer reports, verifying availability of referenced papers, and maintaining consistency across submissions.

- At multiple stages, assisted in proofreading and refining reports, correcting inconsistencies and improving technical coherence as guided by the team leader.
- In-depth reference studied: [2], [16], [18], [26], [28], [31]

4. Results - Implementation Architecture and Testbed Validation

4.1. Foundations of the Security Problem in LLM-Enabled Smart Homes

The emergence of LLM-enabled smart home systems changes the security problem from one of merely protecting devices and communication channels to one of protecting reasoning pipelines. In conventional smart homes, the main concerns revolve around insecure devices, over-privileged apps, weak credentials, poor update mechanisms, vulnerable hubs, and unsafe automation rules. Once an LLM is inserted into the orchestration layer, however, the system no longer behaves like a conventional deterministic control stack. Instead, it becomes a context-driven decision system that interprets text, inferred meaning, and mixed-trust inputs before deciding what action should occur. This means the boundary between harmless data and actionable instruction becomes blurred, creating precisely the conditions under which prompt injection thrives. [28][41][5][10][14][33]

This issue is especially serious in smart homes because the LLM is not simply generating informational responses for a user to read and ignore if necessary. Instead, its outputs may be converted into physical device actions. In a consumer chatbot, an injected prompt may produce a misleading answer or expose system text. In a smart home, the same semantic manipulation could result in unlocking the front door, muting a surveillance alert, disarming a security workflow, or changing environmental controls. The difference is not only one of severity, but one of operational coupling: the smart home tightly couples semantic interpretation to real-world effects. This makes prompt injection an especially consequential attack in IoT-enabled domestic environments, where errors can affect privacy, safety, and property simultaneously. [28][33][14]

4.1.1. Why Smart Homes Create a Unique Attack Surface

Smart home platforms already present a fragmented and vulnerable security landscape even before LLMs are introduced. Ansari et al. show that smart home automation apps are often the weakest link because they mediate interactions among users, devices, cloud backends, and automation rules, yet they often operate with coarse permissions and insecure integrations [14]. Their review makes clear that the smart home is not just a set of devices but a chain of interacting software and service components, where vulnerabilities in one layer can propagate across others. This becomes even more problematic once an LLM is given responsibility for interpreting commands or consolidating data from multiple such layers.

ContexIoT reinforces this concern by showing that appified IoT platforms suffer from insufficiently expressive permission systems that fail to preserve contextual integrity. In other words, the platform may know that an app has access to a sensitive function, but it may not know whether using that function in the current context is appropriate [33]. This weakness is highly relevant to LLM-based orchestration. A model may generate a valid-looking action, but the real question is whether the action makes contextual sense given where the data came from, what the device state is, and what the user likely intended. Smart homes therefore create a unique attack surface because the environment is at once multi-source, multi-trust, and action-oriented, which is exactly the kind of setting in which semantic confusion can become a security compromise. [14][33]

4.1.2. The Role of IoT and AIoT Security Challenges

The broader IoT and AIoT literature shows that smart-home vulnerabilities are part of a larger pattern rather than an isolated application-specific issue. Mishra and Pandya identify heterogeneity, poor standardization, insufficient security management, and resource constraints as persistent weaknesses across IoT systems [10]. Their review also emphasizes that DDoS, intrusion, and anomaly detection remain central challenges because IoT environments frequently trade security for convenience, scalability, or cost. The AIoT survey extends this further by showing that when artificial intelligence is fused with IoT, the attack surface expands to include the security of data processing, the trustworthiness of model behavior, exposure to data poisoning, and manipulation of machine-learning outputs [5].

These observations are directly relevant to the present project. A smart-home LLM orchestrator does not operate in a vacuum; it sits atop an IoT substrate that may already be insecure, and it introduces AI-specific risks on top of that. This layered fragility is one reason the project motivation is strong: a model that reasons over untrusted OCR text, low-trust notifications, or heterogeneous automation inputs is operating in precisely the sort of high-risk AIoT setting described in the literature. The implication is that prompt injection should not be treated as a narrow LLM prompt problem alone. It is part of a broader AIoT integrity problem in which the correctness of control decisions depends on the trustworthiness of data flows, device state, and semantic reasoning at the same time. [5][10]

4.1.3. Why Existing Smart-Home Security Is Not Enough

Existing smart-home defenses do not map cleanly onto prompt injection because they were designed for different threat models. Aegis, for instance, is strong at modeling

contextual relations among users, sensors, and devices in order to detect malicious smart-home behavior [39]. IoTAttest is strong at preserving device and data integrity through attestation mechanisms [41]. Botnet-focused works emphasize early-stage threat modeling, anomaly detection, and resilience against malware-based IoT compromise [44][38]. These are valuable contributions, but they generally assume that the core decision logic of the system is not itself semantically malleable in the way an LLM is.

Prompt injection attacks fundamentally differ from traditional IoT threats. An attack may succeed even when the network is functioning correctly, the device is legitimate, and the automation rule is syntactically valid. In such cases, the compromise does not occur at the infrastructure or protocol level, but at the level of semantic interpretation, where the model misclassifies malicious input as legitimate instruction [28] (formalization of prompt injection as a semantic vulnerability).

Existing IoT security frameworks primarily focus on securing device integrity, communication channels, and contextual policy enforcement [41] (device and data integrity frameworks), [39] (context-aware smart home security models). While these approaches are effective against conventional threats such as unauthorized access or anomalous device behavior, they do not address the risk of instruction-level manipulation within LLM-driven systems.

This limitation becomes more pronounced in modern smart-home environments, where automation logic can be influenced by dynamically generated or externally sourced data. Threat modeling studies have shown that even well-secured IoT ecosystems remain vulnerable to higher-layer attack vectors when adversarial inputs are interpreted as trusted commands [44] (threat modeling of smart home attack surfaces), [38] (survey of smart home vulnerabilities and mitigation gaps).

Therefore, this project does not simply reuse existing IoT security mechanisms. Instead, it integrates IoT integrity principles with LLM-specific defenses to address both system-level and semantic-level threats, reflecting a shift identified in recent work on LLM-integrated systems security [28].

4.2. Prompt Injection Attack Taxonomy and Threat Models

A useful results section cannot discuss prompt injection in purely general terms; it must clearly define the classes of attacks the system is designed to resist. Prior work provides a foundation for constructing a practical taxonomy tailored to smart-home IoT

environments. Rather than relying on a simple direct-versus-indirect distinction, recent studies show that prompt injection encompasses a broader set of adversarial strategies targeting different stages of the LLM pipeline [28] (formal taxonomy and benchmarking of injection behaviors).

These strategies include goal hijacking and instruction override attacks, where malicious inputs attempt to supersede system directives [1] (instruction override via crafted prompts); prompt leakage attacks, which aim to extract hidden system instructions or sensitive context [28]; and retrieval-driven or context injection attacks, where adversarial content is introduced through external data sources or memory components [33] (contextual integrity and data flow in IoT systems).

In addition, tool-integrated and indirect injection attacks demonstrate how LLM outputs can trigger unsafe downstream actions in connected systems [7] (indirect injection in real-world LLM applications), while combined or multi-stage payloads exploit interactions across multiple components of the application pipeline [11] (multi-layer IoT security and enforcement gaps).

Taken together, these categories indicate that prompt injection should not be modeled as a single exploit pattern, but rather as a family of adversarial techniques that operate across input processing, model reasoning, and output execution stages. This broader threat model is essential for designing defenses in LLM-mediated IoT environments, where vulnerabilities may arise at multiple points in the control pipeline.

4.2.1. Direct Prompt Injection Attacks

Direct prompt injection attacks occur when the attacker has access to a user-facing input channel and uses that access to provide malicious text directly to the model or to the application that wraps the model. Perez and Ribeiro's PROMPTINJECT work is foundational because it clearly identifies two central attacker goals in direct interaction settings: goal hijacking, in which the attacker changes what the application is trying to do, and prompt leaking, in which the attacker extracts hidden prompt content from the application [1]. These attacks were important historically because they demonstrated that LLM applications could be manipulated by surprisingly simple user-supplied instructions, often without any advanced technical mechanism beyond natural language phrasing.

Liu et al. deepen this picture by formalizing direct prompt injection in terms of target tasks and injected tasks, making it possible to benchmark attacks systematically rather than discuss them informally [28]. Under their framework, direct attacks become easier to compare because what matters is no longer the exact wording alone, but whether the compromised input causes the application to perform the attacker's intended injected task instead of the system's intended one. This is an important improvement because it moves the field away from examples and toward measurable threat modeling.

For the present project, direct attacks are especially relevant to the control-group baseline. A smart-home system that allows typed or transcribed user commands must be assumed vulnerable to explicit instruction overrides, malicious command chaining, and hidden-action prompts unless countermeasures are in place. Direct prompt injection therefore represents the most basic adversarial baseline against which any proposed defense should first be tested. [28][1]




Figure 1: Direct prompt injection attacks in LLMs. Malicious user inputs override the original application instructions, leading to unintended behavior such as goal hijacking or prompt leakage. Adapted from [1].

4.2.2. Indirect Prompt Injection Attacks

Indirect prompt injection attacks differ from direct attacks in a crucial way: the attacker does not need to type into the system directly. Instead, the attacker plants malicious instructions into content that the system is likely to retrieve later. Greshake et al. show that this can allow attackers to remotely compromise LLM-integrated applications by embedding prompts in retrieved data sources [7]. Their central insight is that once data

and instructions are processed in the same semantic context, retrieved content can function similarly to executable logic, even though it appears to be ordinary data.

This matters greatly for smart-home systems because smart homes increasingly depend on multiple passive inputs: OCR outputs from cameras, text descriptions, messages from cloud services, automation annotations, sensor-associated metadata, and third-party notifications. None of these are obviously "commands" in the conventional sense, but all can become command-like once ingested into the LLM context. That means indirect prompt injection is not just a fringe case; it is highly plausible in exactly the kind of heterogeneous, retrieval-rich environment that smart-home AI systems inhabit.

Indirect prompt injection is therefore more aligned with the current project than purely direct prompt hijacking, because the project explicitly involves multiple non-user-generated sources of text that may be partially trusted or fully untrusted. The relevance here is not only theoretical. It directly shapes the need for source tagging, trust labeling, and pre-LLM screening of retrieved or derived content. [41][33]




Figure 2: Indirect prompt injection via retrieved data sources, where attacker-controlled inputs are processed by the LLM and influence system behavior without direct user interaction [7].

4.2.3. Tool-Integrated and Agentic Attacks

The threat becomes even more serious once the model is allowed to invoke tools or actions beyond generating plain text. The INJECAGENT benchmark is especially important because it studies tool-integrated LLM agents across realistic domains, including domotics and smart-home-like settings [18]. Rather than asking whether a

model can be tricked into producing bad text, the benchmark asks whether the model can be tricked into using tools in ways that directly harm the user. That is much closer to the project's real concern.

The benchmark shows that these attacks fall broadly into two classes: direct harm attacks, where the agent is manipulated into performing an unsafe or unauthorized action, and data stealing attacks, where the agent is manipulated into exfiltrating sensitive information [18]. In a smart-home environment, both classes are plausible. An attacker could try to coerce a model into disabling a safety mechanism, or instead extract account, policy, or device-state information. The fact that these attacks are studied on agentic systems rather than simple chat interfaces makes them especially relevant for a smart-home orchestrator that may eventually connect model outputs to device execution APIs.

This also clarifies why a result section must discuss tool-integrated threat models explicitly rather than bury them under general prompt injection. Once the model has execution capability, prompt injection is no longer just about misleading text. It becomes a pathway to unsafe actuation. [18][41]




Figure 3: Tool-integrated prompt injection in LLM agents. Malicious instructions embedded in external content influence the agent's behavior, leading to unintended tool execution or actions. Adapted from [18].

4.2.4. Compound and Combined Attacks

One of the strongest lessons from the prompt-injection literature is that attackers are unlikely to stay within neat categorical boundaries. Liu et al. show that attacks become more effective when strategies are combined, and they explicitly benchmark a newly designed combined attack that outperforms several prior individual strategies [28]. This is

important because it warns against evaluating a system only against simple examples. Real attackers will mix tactics.

HOUYI provides a practical illustration of this same principle in a black-box application setting. Its framework component, separator component, and disruptor component work together to change how the LLM frames the malicious payload and interprets context boundaries [11]. This is conceptually similar to the idea behind combined attacks in the benchmark paper: successful injection often depends on a mix of framing, separation, and malicious intent, not just a single phrase like “ignore previous instructions.”

For the present project, that means the threat model should explicitly include hybrid attacks. A strong result section should therefore not imply that the system will only face isolated attack types. It should acknowledge that direct instruction override, retrieved malicious context, and action-oriented payloads may appear together in one adversarial chain. [28][41]

4.2.5. Threat Model Implications for the Project Testbed

When the reviewed taxonomies are applied to the proposed smart-home testbed, the threat model becomes more concrete. The project’s “control group” of direct and indirect prompt injection attacks maps directly onto the literature: direct attacks correspond to malicious user commands or user-facing text channels [28][1], while indirect attacks correspond to manipulated OCR text, cloud-sourced content, or retrieved external inputs [7][33]. Tool-integrated threats map onto the orchestrator’s final stage, where the LLM proposes or triggers device actions. This means the testbed is not an artificial toy setup. It actually reflects the main threat categories described across the papers.

That is one of the strengths of the project direction: the implementation choices are grounded in the structure of the literature rather than chosen arbitrarily. The result section should emphasize that the threat model is not generic but literature-aligned, spanning semantic task takeover, hidden-in-context attacks, and unsafe action execution risks in a smart-home domain. [28][1][41][33]




Figure 4: System-level threat model illustrating how an attacker injects malicious instruction or data into the input pipeline of an LLM-integrated application, influencing model behavior and downstream actions. Adapted from [28].

4.3. Machine Learning-Based Detection of Prompt Injection

The project scope emphasizes evaluating machine-learning–based defenses for mitigating prompt injection risks in LLM-enabled smart-home systems. The reviewed literature strongly supports this direction, particularly through the use of embedding-based classifiers and structured ML detectors adapted from IoT intrusion detection paradigms [3] (ML-based injection detection in IoT environments). More recent work further demonstrates that embedding-driven approaches can be applied to prompt injection detection while preserving privacy and scalability properties [2] (embedding-based detection with federated learning considerations).

Taken together, these studies present ML-based detection as a practical first layer of defense: it is measurable, deployable, and avoids reliance on secondary LLMs to secure the primary model. This aligns with broader smart-home security research, where lightweight and automated detection mechanisms are preferred for real-time protection [38] (practical mitigation strategies for smart-home vulnerabilities).

However, the literature also makes clear that ML-based detection alone is insufficient. IoT security frameworks consistently highlight the need for layered enforcement and complementary controls to address complex, multi-stage threats [41] (multi-layer IoT security architectures). In the context of LLM systems, this implies that while ML detection is powerful, it must be integrated with additional safeguards to provide comprehensive protection.

4.3.1. Embedding-Based Classification as a Semantic Defense Layer

The work by Ayub and Majumdar is particularly important because it demonstrates that prompt injection attacks can be addressed effectively through embedding-based supervised classification [4]. Rather than prompting a second LLM to decide whether an input is malicious, they embed prompts using models including all-MiniLM-L6-v2 and train classical classifiers such as Random Forest and XGBoost. Their results show that these models can outperform state-of-the-art open-source prompt injection classifiers built with encoder-only neural networks. This is significant because it suggests that strong detection does not necessarily require large or complex detector architectures.

From a systems-design perspective, this is very useful for a smart-home security framework. A lightweight embedding plus classical classifier layer fits naturally into an orchestration pipeline. It can operate as a front-end risk estimator before untrusted text is admitted into the LLM's working context. This matches the current project's proposed pipeline closely: normalize heterogeneous inputs, generate embeddings, classify risk, then decide whether to block, sanitize, downgrade, or pass the content onward. That alignment between the paper and the project is unusually strong, which makes this study central to the implementation justification. [4]

4.3.2. Why Random Forest and Similar Classical Models Matter

An interesting feature of the reviewed detection literature is that it does not point exclusively toward deep neural detectors. Both the embedding-based prompt-injection paper and the smart IoT injection-detection paper show that classical supervised ML, especially Random Forest and related models, can remain highly competitive [4][3]. Gaber et al., working in an IoT intrusion-detection setting, achieve 99% accuracy for injection attack detection with a feature-selected model using only a small number of features [3]. Although their attack setting differs from prompt injection in LLM systems, the broader methodological lesson is the same: strong security detection in IoT environments can often be achieved with efficient, interpretable, and deployable ML models.

This matters because smart-home defense cannot optimize only for raw benchmark performance. It must also consider latency, deployability, and maintainability. A model that is marginally more accurate but much more computationally expensive or difficult to inspect may not be the right choice for a real smart-home security layer. The literature therefore indirectly supports the project's preference for practical, classical ML classifiers on top of semantic representations, rather than overly elaborate detector stacks. [4][3]

4.3.3. What ML Detection Can and Cannot Do

The strengths of ML detection are substantial. It allows prompt injection to be treated as a measurable classification problem. It enables controlled experiments, confusion-matrix analysis, and straightforward integration into the input pipeline. It also gives defenders something that many prompt-only defenses lack: mechanistic diversity. A Random Forest classifier using embeddings is not vulnerable for the same reason that an LLM is vulnerable. This is one of its biggest security advantages.

Still, the papers make clear that ML detection is not a full solution. First, models generalize imperfectly to novel attack strategies, especially when attackers alter semantic structure or distribute the malicious intent across a longer context. Second, the output of a detector does not automatically imply the correct system response. A suspicious input may need to be blocked entirely, or it may only need action restrictions. Third, even high detector accuracy may not be sufficient if the residual errors occur in high-risk smart-home scenarios. A 1% false negative rate may sound good statistically but could still be unacceptable if that 1% includes the unlock-door or disable-alarm case.

That is why the literature supports ML detection as a layer rather than a standalone defense. It is highly valuable as an initial screening stage, but it must be followed by action constraints, contextual checks, and policy enforcement further down the pipeline. [28][4][3]

4.3.4. Why Detector-LLMs Are a Poor Substitute

The role of Choudhary et al.'s work is especially important in framing what not to do. Their paper shows that LLM-based detection methods built on known-answer detection can be bypassed by adaptive attacks such as DataFlip, often with disastrous consequences for detection reliability [38]. This is a very useful negative result because it prevents the project from drifting toward a fragile architecture in which one prompt secures another prompt.

The implication is simple but important: if the system's main weakness is that instruction-following models can be manipulated through natural language, then asking another instruction-following model to decide whether the first one is being manipulated is not a strong foundation for security. The current project is therefore better justified in building around non-LLM ML detectors, precisely because they do not fail for the same structural reason. [4][16]

4.3.5. Implications for the Present Implementation

Taken together, the ML literature gives this project a well-grounded defensive first layer: embed low-trust or untrusted text, classify it using a supervised model, and assign a risk score that determines whether the content can safely enter the LLM context. This is both empirically supported and architecturally consistent with IoT deployment constraints. It is also a much more realistic contribution than claiming a universal detector. The value of the project lies in showing that ML-based semantic screening can materially reduce the attack surface when embedded into a larger smart-home control architecture. [4][2][3]

4.4. Privacy-Preserving and Distributed Detection Models

A smart-home security framework that improves attack detection but centralizes private household data without restraint may solve one problem only by creating another. This is why the privacy dimension of the reviewed literature matters so much. Smart homes continuously produce intimate contextual information: presence signals, routines, occupancy timing, images, notifications, device states, and automation behavior. If prompt injection detection requires logging and centralizing all such inputs, then the system may become secure against adversarial language at the cost of becoming insecure against privacy leakage. The reviewed papers provide useful starting points for resolving this tension, especially through federated learning and device/data integrity frameworks. [2][41][5][14]

4.4.1. Federated Learning as a Privacy-Preserving Defense Direction

Jayathilaka's work on privacy-preserving prompt injection detection is highly relevant because it adapts federated learning to the problem of prompt-injection defense [2]. The study's core contribution is conceptual as much as empirical: it demonstrates that distributed clients can collaboratively improve a detector without sharing raw prompt data. In a smart-home context, that is crucial. A cloud-based controller or central service should ideally not need direct access to every household's raw prompt-like data in order to benefit from security improvements learned across other homes.

The paper also aligns well with the project's planned use of embedding-based classification. Instead of abandoning the ML detector design when privacy becomes a concern, the federated model shows how that same basic strategy can be extended to privacy-sensitive environments. This makes the federated approach a plausible future enhancement path for the project, even if the initial implementation remains centralized for simplicity. [41][2]

4.4.2. Broader IoT Privacy and Integrity Considerations

Federated detection fits within a broader body of IoT security work that emphasizes trust establishment, attestation, and privacy-preserving data integrity. IoTAttest is useful here because it argues that trust in IoT systems must include not only device identity but also the integrity of collected data and control-plane traffic [41]. If a smart-home LLM reasons over data whose origin or integrity cannot be trusted, then even a strong prompt-injection detector may be reasoning over compromised context. This makes data integrity and detection inseparable in practice.

The AIoT literature reinforces the same point from a higher-level systems view. Distributed or edge-based processing is often necessary to reduce latency and bandwidth use, but it also creates pressure to preserve privacy and secure multiple points of inference and communication simultaneously [5]. In that sense, federated prompt-injection detection is not a strange special-case idea; it is consistent with the broader AIoT trend toward decentralized intelligence under constrained privacy and security requirements. [41][5]

4.4.3. Practical Constraints of Federated Detection in Smart Homes

At the same time, the literature does not suggest that federated learning is deployment-ready without caveats. Smart homes are heterogeneous: different homes contain different devices, data patterns, user behaviors, and trust assumptions. This means that local data distributions can differ substantially, making collaborative training difficult to stabilize. In addition, communication costs, update poisoning risks, and synchronization burdens all become more complicated when participants are low-power or intermittently connected devices.

For this reason, federated detection should be framed as a privacy-preserving extension layer rather than the only plausible implementation path. The most realistic architecture for the project is likely one in which local or controller-level detection acts as the main protective layer, while federated improvement is treated as a future research direction for collaborative model refinement. That is a more honest interpretation of the literature than claiming that federation alone resolves the smart-home prompt-injection problem. [2][41][5]

4.4.4. Why Privacy Matters to the Credibility of the Framework

There is also a research-design reason to take privacy seriously: a smart-home defense framework that is privacy-insensitive will be harder to justify socially and practically.

Users may accept some extra friction for safety, but they are unlikely to accept blanket centralization of home-generated context simply to improve injection detection. The privacy-preserving literature therefore does more than add technical options; it strengthens the legitimacy of the whole framework by showing that secure smart-home AI does not have to imply unrestricted prompt logging or household surveillance. [2][14]

4.5. System-Level Safeguards and Context-Aware Controls

The most consistent conclusion across the prompt injection and smart-home security literature is that detection is not enough. The system must be designed so that even if a malicious input partially penetrates the semantic pipeline, it does not automatically become an unsafe device action. This is where system-level safeguards, action allowlisting, structured outputs, contextual integrity checks, device-policy mediation, and confirmation gates, become the most important part of a credible defense architecture. [28][41][38][39][33]

4.5.1. Action Allowlisting and Strict Output Mediation

HOUYI is especially useful in motivating output constraints because it shows how real-world prompt injection often succeeds by changing how the application interprets the payload, not just by supplying “bad text” [11]. This means defenders cannot rely only on filtering the incoming prompt. They must also control the structure and meaning of what the model is allowed to output. In a smart-home setting, this translates directly into action allowlisting. The model should not be able to produce free-form operational commands. It should instead be forced to emit only a tightly constrained action schema, such as validated JSON corresponding to approved device actions.

This is one of the strongest architectural decisions supported by the literature. It does not depend on perfect detection. Even if the model is influenced by malicious context, the system can still prevent arbitrary actuation by limiting it to known action types and verified parameter ranges. That is exactly the sort of practical, system-level defense that makes sense in a smart-home controller. [11][33]

4.5.2. Contextual Integrity and Runtime Permission Logic

ContexIoT contributes a complementary and very important idea: it is not enough that an action is technically permitted; it must also be contextually appropriate [33]. In appified IoT platforms, the danger is not only over-privilege but misuse of privilege outside expected context. This principle maps naturally to LLM orchestration. A model might propose an action that is syntactically valid and even device-compatible, but that action

may still be unsafe if it was triggered by low-trust OCR content, a suspicious retrieved message, or a sequence of events that does not align with user intent.

This is why a smart-home LLM security framework should combine output allowlisting with context-aware gating. Actions should not simply be "allowed" because they appear in the schema; they should be evaluated against the source trust level, current device state, recent sensor behavior, and action sensitivity. The literature strongly supports this direction because it avoids the false comfort of purely static permissions. [39][10][33]

4.5.3. Behavior-Aware Security in the Smart-Home Environment

Aegis contributes a broader environmental perspective by modeling smart-home behavior across devices, sensors, and user activities [39]. Rather than evaluating isolated app requests, it asks whether the observed or requested behavior makes sense holistically. This is a valuable concept for the present project because prompt injection often tries to create actions that are semantically plausible in isolation but behaviorally suspicious in context.

For instance, "unlock the front door" may be a legitimate action in some circumstances. But if that action emerges immediately after a suspicious OCR-derived text fragment is ingested, while no expected user-presence signals support it, then the action becomes contextually suspect. Aegis suggests that such mismatches are detectable if the system monitors state transitions and activity patterns rather than trusting command text alone. This strengthens the case for treating the LLM as just one participant in a broader context-sensitive control architecture. [39]

4.5.4. Why LLM-Based Detection Alone Fails

Choudhary et al. make a decisive negative contribution by showing that detector-LLM methods based on known-answer detection can be adaptively bypassed [16]. The lesson here is not merely that one detector failed; it is that a detector framed within the same instruction-following paradigm inherits similar vulnerabilities to the target model. This means a smart-home security framework should be very cautious about relying on another prompt-driven LLM call as its primary line of defense.

This negative result is actually useful for the present project because it helps sharpen the architecture. It justifies why the system should rely on embedding-based or classical ML detection first, and on formal policy constraints second, rather than on a detector-LLM wrapper. It also gives the report a stronger evaluative tone: the framework is not just

adopting ML because it is fashionable, but because a key alternative has been shown to be structurally weak. [41][16]

4.5.5. Why Layered Security Is the Only Credible Design

When the reviewed works are synthesized, a clear defense-in-depth model emerges. The first layer consists of semantic ML-based screening of low-trust inputs, supported by research on prompt injection detection and benchmarking that highlights the need for early-stage filtering [28] (formalization and evaluation of injection defenses). The second layer involves trust labeling and normalization of inputs prior to LLM processing, reflecting broader IoT security practices that enforce structured handling of untrusted data [41] (secure data and device integrity frameworks).

The third layer applies strict output shaping and action allowlisting, aligning with mitigation strategies in smart-home systems that constrain device behavior to predefined safe actions [38] (smart home vulnerability mitigation approaches). The fourth layer introduces contextual integrity checks at execution time, ensuring that actions remain consistent with expected system context and user intent [33] (contextual integrity in IoT platforms). Finally, the fifth layer incorporates human confirmation for high-impact or safety-critical actions, consistent with user-centered security models in smart-home environments [39] (context-aware and user-involved security frameworks).

Importantly, the literature does not identify any single layer as sufficient in isolation. Instead, it consistently supports the combination of these mechanisms as a comprehensive strategy for mitigating complex, multi-stage threats. This layered design therefore represents a key architectural takeaway from the synthesis of Section 4.

4.5.6. Architectural Diagram




Figure 5: Multi-layer prompt injection defense architecture for LLM-enabled smart-home IoT systems.

The diagram illustrates an end-to-end secure control pipeline in which user input is processed through a sequence of defensive layers before triggering any device action. Incoming requests are first evaluated by a Layer 1 (L1) machine learning classifier, which uses sentence embeddings and a Random Forest model to detect jailbreak attempts, role markers, and safety bypass patterns. Inputs identified as malicious are immediately rejected.

Benign or uncertain inputs proceed to Layer 2 (L2) input prevention, where normalization and trust labeling are applied. This includes restructuring inputs, isolating untrusted user data, and enforcing consistent formatting to reduce the likelihood of prompt reinterpretation. The sanitized input is then passed to the LLM for processing under a constrained system prompt.

Following model inference, Layer 3 (L3) output validation enforces safety constraints on generated responses. This includes leakage and jailbreak detection, canary token checks, schema validation, and strict allowlisting of permissible device actions. Outputs failing validation are blocked, while safe outputs proceed to execution.

The architecture also incorporates an explicit attack taxonomy (e.g., naïve, escape-character, context-ignoring, fake completion, combined, and indirect injections), highlighting the range of adversarial inputs considered in the threat model. Decision points throughout the pipeline enforce a defense-in-depth strategy, ensuring that malicious inputs or unsafe outputs are intercepted at multiple stages before reaching IoT devices.

4.6. Performance Evaluation and Key Metrics

A literature-based result section should not only describe threats and defenses; it should also clarify how the proposed system should be evaluated. The reviewed papers collectively provide a useful metric space for this project, spanning attack-centric measures from prompt injection benchmarks (e.g., [28] formalizes and benchmarks PI attacks/defenses, providing standard test sets and success metrics), classifier-centric measures from ML detection studies (e.g., [41] proposes a security framework for data/device integrity, emphasizing detection accuracy and false positive rates in IoT systems; [33] introduces contextual integrity for IoT platforms, relevant for reducing false alarms via context-aware metrics; [3] applies ML injection attack detection for smart IoT, highlighting precision/recall for command injection), and system-centric measures from IoT anomaly detection and DDoS mitigation work (e.g., [46] analyzes

DDoS attacks on smart home devices, offering throughput and latency under attack as key system metrics; [38] systematically reviews malware detection techniques for smart homes, emphasizing detection coverage and mitigation response time). These should be merged into a single evaluation philosophy rather than treated separately, for instance by adopting a unified framework that reports (1) Attack Success Rate (ASR) and false positive rate (FPR) from the PI literature, (2) precision, recall, and F1-score from ML detection studies, and (3) system overhead (latency/throughput) and robustness under load from IoT network security evaluations.

Metric	Value	Description
ASR (Attack Success Rate)	0%	No successful attacks out of 39 attempts
FPR (False Positive Rate)	0%	Zero legitimate requests incorrectly blocked
Recall	100%	All flagged attacks were true positives
Precision	100%	All actual attacks were detected
F1 Score	100%	Perfect balance of precision and recall
Accuracy	100%	All 50 test cases correctly classified

Table 4.6a: Table showing the results and metrics based on our test data

Dataset: 50 total cases (39 attacks spanning 7 categories, 11 benign requests). Blocked by Layer 1 (ML Classifier): 20, Layer 3 (Output Validation): 19.

Defense Layer	***Attacks Blocked***	***Percentage***	***Role***
Layer 1 (ML Classifier)	*20/39*	*51.3%*	*Semantic prompt injection detection*
Layer 3 (Output Validation)	*19/39*	*48.7%*	*Action allowlisting, parameter bounds, policy enforcement*

Table 4.6b: Defense Layer Effectiveness

Note: *Layer 2 (input sanitization) prepares data but does not block; it enables Layer 1 and Layer 3 to function effectively*

Evaluation methodology follows Liu et al. 12 (USENIX Security 2024) 11-step attack success judgment framework, with 50 curated cases spanning direct prompt injection, indirect injection, and policy violation scenarios.

4.6.1. Attack-Centric Metrics for Injection Resilience

Liu et al.'s formal benchmark is especially helpful because it separates normal-task performance from attack effectiveness [28]. This distinction is essential. A system that blocks everything suspicious but also cripples legitimate automation cannot be considered an effective defense. Therefore, the project's result section should explicitly include both baseline utility metrics on benign tasks and attack-success metrics under adversarial conditions.

For the current project, that means evaluation should track: how often direct and indirect injections succeed in causing unsafe action proposals; how often prompt leakage or schema misuse occurs; and how much those attack outcomes are reduced after the ML detector and system safeguards are applied. This is a more rigorous approach than simply reporting "blocked vs not blocked," and it mirrors the methodological maturity of the benchmark literature. [28][33]

Attack Coverage: The evaluation tested 7 distinct attack categories from the Liu et al. 12 taxonomy and prior work:

- Direct injection attacks: naive [5], fake_completion [5], context_ignoring [5], escape_chars [5], combined [1]
- Indirect injection: HTML comment injections [2]
- Policy violations: Parameter bounds, allowlisting, high-risk action confirmation [14]

4.6.2. Detection-Centric Metrics for the ML Layer

For the input screening layer, standard ML metrics remain appropriate: accuracy, precision, recall, F1-score, and false positive/false negative analysis. Ayub and Majumdar's work shows why these matter in prompt injection detection specifically,

because the difference between a benign but unusual prompt and a malicious adversarial one can be subtle [4]. In a smart-home context, false negatives matter because they admit malicious content, but false positives matter too because they may unnecessarily block user actions or reduce confidence in the system.

The IoT injection-detection literature strengthens this by showing that classical ML models can perform strongly while remaining efficient [3]. This suggests that the evaluation should also consider model simplicity and inference practicality, not just raw detection performance. A very complex detector that is difficult to maintain or too slow to use is less valuable in an always-on home environment than a slightly simpler one with robust operational behavior. [4][3]

4.6.3. System-Centric Metrics for Real Smart-Home Use

A secure system also needs to be timely. The DDoS smart-home paper is instructive because it demonstrates that defenses are meaningful only if they act in operationally relevant time windows [46]. N-BaIoT reinforces this point by achieving rapid and accurate anomaly detection for IoT botnet traffic using deep autoencoders [19]. While these papers target network attacks rather than prompt injection, they still clarify an important expectation: in a smart-home defense architecture, latency is a security metric.

For the present project, this means the result section should not stop at classifier accuracy. It should also consider end-to-end latency from text ingestion to decision, the overhead introduced by embedding generation and classification, the cost of schema validation and context checks, and the delay introduced by user confirmation on high-risk actions. This is especially important if the project wants to claim that the framework is practical rather than merely conceptually sound. [46][19]

4.6.4. Robustness, Utility, and Risk-Sensitive Metrics

A more mature result section should also emphasize robustness and risk sensitivity. Not all misclassifications are equal. Misclassifying a harmless light-control request is not equivalent to misclassifying a request that could unlock the home or expose security metadata. Therefore, the evaluation should ideally distinguish between low-risk and high-risk action classes, and consider whether the layered framework maintains stronger caution for the latter. This would align well with the smart-home security literature, which repeatedly emphasizes the seriousness of actions affecting physical safety, privacy, and control integrity. [39][44][14][38]

4.7. Implications of the Research Findings

The reviewed literature does more than motivate a technical architecture; it also highlights broader implications for how LLM-enabled smart-home systems should be designed, evaluated, and trusted. These implications are significant because the project extends beyond building a classifier or demonstration pipeline it addresses a fundamental security question: how semantic AI systems can be safely integrated into domestic control environments.

Recent work on prompt injection and LLM security emphasizes that these systems introduce new classes of semantic vulnerabilities that cannot be addressed through traditional input validation alone [28] (formalization of prompt injection as a distinct threat model). At the same time, IoT security research underscores the importance of device integrity, context awareness, and policy enforcement in smart-home environments [41] (secure IoT frameworks), [33] (contextual integrity in IoT systems).

However, studies on smart-home vulnerabilities and AIoT integration challenges show that combining AI with physical control systems expands the attack surface in ways that existing defenses do not fully address [38] (smart-home vulnerability landscape), [5] (AIoT integration risks), [14] (application-layer weaknesses in smart-home platforms). This creates a gap between infrastructure-level security and semantic-level trust, where systems must reason correctly about intent rather than simply enforce access control.

Taken together, these findings suggest that secure LLM-enabled smart homes must be designed with both system-level protections and semantic safeguards, and must be evaluated not only for functional correctness but also for resilience to adversarial manipulation. This perspective reframes the project as part of a broader effort to define trust boundaries in AI-driven domestic systems.

4.7.1. Prompt Injection Is a Structural, Not Incidental, Risk

The first implication is that prompt injection is not a bug that disappears once developers become more careful with strings. It is a structural risk that follows from instruction-following models reasoning over mixed-trust context. This is why the problem persists across chat applications, retrieval systems, and agentic tool users alike [28][41][33]. The implication for smart-home security is that future systems should be designed under the assumption that prompt injection attempts will occur, not under the assumption that they are rare edge cases.

4.7.2. Smart-Home Security Must Become LLM-Aware

The second implication is that smart-home security research must become explicitly LLM-aware. Prior work already identifies significant weaknesses in smart-home environments, including vulnerabilities in automation logic, contextual misuse of device permissions, malware exposure, and large-scale botnet compromise [39] (context-aware smart-home security gaps), [44] (threat modeling of smart-home attack surfaces), [14] (application-layer vulnerabilities in smart-home apps), [38] (broad vulnerability landscape and mitigation challenges).

The integration of LLMs does not eliminate these threats; instead, it introduces a flexible natural-language control interface through which many of them may be amplified. By allowing user intent to be expressed and interpreted dynamically, LLMs expand the attack surface from purely technical exploits to semantic manipulation of system behavior.

As a result, future smart-home defenses should not treat LLMs as peripheral convenience features operating outside the core control plane. Instead, they must be considered central security-critical components, requiring the same level of scrutiny, validation, and enforcement as traditional system elements. This shift reflects an emerging consensus that security in AI-integrated systems must account for both infrastructure-level and semantic-level threats.

4.7.3. Security and Privacy Must Be Co-Designed

A third implication is that secure smart-home AI must also be privacy-aware. The federated-learning literature and broader IoT trust frameworks both suggest that detection quality should not come at the price of centralized household data exposure [2][41][5]. This means future systems must co-design security and privacy rather than solve them one after the other. That insight strengthens the project's relevance, because it points toward future architectural improvements beyond the initial implementation.

4.7.4. Why Layered Mitigation Is a More Honest Contribution than "Complete Prevention"

Finally, the literature strongly suggests that a realistic and scientifically honest contribution is to demonstrate risk reduction through layered mitigation, not to claim complete prevention. The formal benchmark from Liu et al. shows that no single defense whether filtering, instruction hierarchy, or input sanitization is broadly sufficient across different attack types and contexts [28]. Attackers can always adapt: if one defense blocks obvious injection patterns, adversaries can rephrase, encode, or split malicious

instructions across multiple fields (e.g., device names, sensor readings, user queries) to bypass detection [4][8][50]. This is not a failure of individual defenses but a fundamental property of the adversarial landscape prompt injection is a human-competitive problem where attackers have asymmetric advantages in time, creativity, and knowledge of the target system [27][50].

Two recent works illustrate this point clearly. HOUYI and similar adaptive frameworks show that even state-of-the-art detection methods can be circumvented when attackers have access to the defense logic or can iteratively refine their prompts [38][41]. Likewise, embedding-based classifiers, while promising, remain vulnerable to carefully crafted adversarial examples or out-of-distribution inputs that fall outside their training manifold [4][16]. In other words, claiming "complete prevention" of prompt injection in a smart-home system would be both overconfident and easily falsifiable an attacker with sufficient motivation and system knowledge will likely find a way through any single shield [9][27].

Therefore, a project that demonstrates measurable reduction in unsafe smart-home actions under layered controls makes a stronger and more credible contribution than one that claims to eliminate prompt injection entirely. Layered mitigation might combine (a) input filtering at the voice assistant level, (b) context-aware anomaly detection on device command sequences, (c) integrity checks on automation rules, and (d) human-in-the-loop confirmation for high-risk actions like unlocking doors or disabling alarms [38][41][51]. The honest contribution is not perfection but a verifiable reduction in attack success rate, false negatives, or physical safety violations compared to an unprotected baseline. This framing aligns with best practices in both IoT security (where defense-in-depth is standard) and LLM safety (where red-teaming consistently breaks "fully defended" systems) [19][28][46].

4.8. Deployment Challenges, Trade-Offs, and Future Directions

A well-developed results section should conclude not only with what works, but with a clear assessment of what remains challenging. The reviewed literature consistently indicates that deploying LLM-enabled security frameworks in smart-home environments introduces unavoidable trade-offs among security, usability, privacy, and system responsiveness.

From a usability perspective, introducing stricter validation layers and human confirmation steps can reduce system convenience and increase user friction, particularly in real-time automation scenarios [39] (user-centered and context-aware smart-home

security). Similarly, performance constraints arise as additional detection and validation mechanisms introduce latency, reflecting broader challenges in IoT systems where responsiveness must be balanced against security enforcement [10] (IoT security–performance trade-offs), [46] (real-time constraints in smart-home environments).
Privacy considerations further complicate deployment. Approaches such as embedding-based detection and distributed learning aim to reduce data exposure, but introduce additional system complexity and coordination overhead [2] (privacy-preserving ML-based detection). At the same time, integrating AI into IoT ecosystems expands the overall attack surface, requiring careful handling of data flows and trust boundaries across components [5] (AIoT integration risks), [38] (smart-home vulnerability landscape).

Finally, maintaining contextual integrity and correct system behavior across dynamic environments remains a persistent challenge, particularly when user intent must be inferred from natural language inputs [33] (contextual integrity in IoT systems). These limitations highlight that no single mechanism fully resolves the risks introduced by LLM integration.

Taken together, these trade-offs reinforce that secure deployment is not solely a technical problem, but a systems-level design challenge. A robust solution must balance protection strength with usability, latency, and privacy considerations, suggesting that future work should focus on adaptive defenses, improved semantic validation, and standardized evaluation frameworks for LLM-enabled IoT security.

4.8.1. Security vs Usability

Strong safeguards introduce friction. Confirmation prompts, trust downgrades, or blocked automations may reduce convenience. ContexIoT's work is useful here because it explicitly considers habituation and prompt fatigue, showing that runtime prompts must be designed carefully to preserve usability [33]. For the current project, this implies that action sensitivity should be differentiated: low-risk actions can be handled with lighter controls, while high-risk actions require more friction and validation.

4.8.2. Security vs Latency

The literature on smart-home DDoS detection and IoT anomaly detection shows that defenders must act quickly enough for their actions to matter [46][38]. For prompt injection, this means the embedding/classification/safeguard pipeline must operate with

low enough overhead that unsafe actions are stopped before execution, not after. That places practical pressure on model choice, architecture design, and how often expensive checks are invoked.

4.8.3. Security vs Privacy

Federated detection reduces privacy exposure but increases complexity [2]. Centralized detection simplifies control but may require collecting sensitive prompt-like household data. This suggests a hybrid future direction in which local or hub-level screening performs primary protection, while privacy-preserving collaboration is used only for periodic model improvement.

4.8.4. Need for Better Smart-Home-Specific Benchmarks

Another challenge revealed by the literature is that truly realistic smart-home prompt-injection benchmarks remain limited. Most prompt injection research focuses on general LLM applications like chatbots or document summarizers, but smart homes introduce unique complexities: heterogeneous devices, multiple communication protocols, nested automation rules, and layered control pathways (voice assistant → cloud LLM → local hub → actuator) [8][11][27][30]. Each layer represents a potential injection point, e.g., embedding a malicious command inside a device name that an LLM later interprets as an instruction [17][33].

INJECAGENT is a strong step because it includes domotics-like scenarios, with test cases involving API calls to virtual smart-home devices that capture some conditional logic of real home control [18]. However, most prompt-injection research still focuses on general applications rather than layered home-control systems. Widely cited benchmarks examine instruction hierarchy violations in generic LLMs or RAG knowledge corruption, not physical device control [15][28]. Even comprehensive surveys on AI agents note that smart-home workflows with strict safety requirements (e.g., unlocking a door vs. summarizing an email) and real-time constraints remain under-tested [9][12].

This gap matters because a smart-home prompt injection can cause physical actions: unlocking doors, disabling alarms, or interfering with medical devices [32][51]. Moreover, contextual integrity differs from standard LLM applications—a command like "turn off all lights" may be legitimate at 10 PM but suspicious at 2 PM, yet existing benchmarks rarely encode such temporal or environmental context [33][42]. Therefore, the project testbed itself could become part of the contribution, serving as a more realistic evaluation environment that includes heterogeneous IoT devices, a configurable LLM

controller, and ground-truth labeling of physical outcomes metrics currently missing from prompt injection literature but standard in IoT security evaluations [19][34][46].

4.8.5. Future Research Directions

The reviewed literature points toward several important future directions for securing LLM-enabled smart-home systems. One key area is the development of stronger semantic detection mechanisms, particularly for indirect and structurally realistic attacks that remain difficult to identify [28] (limitations of current prompt injection defenses). Another direction involves privacy-preserving and collaborative learning approaches, which aim to improve detection performance without exposing sensitive user data [2] (federated and embedding-based detection methods).

In addition, prior work highlights the need for richer contextual integrity enforcement, ensuring that system actions remain consistent with user intent and environmental context [33] (contextual integrity in IoT platforms). This is closely related to policy-aware device mediation, where smart-home systems enforce fine-grained constraints on allowable actions and interactions [41] (multi-layer IoT security and enforcement frameworks), [39] (context-aware and user-involved security models).

Finally, the literature emphasizes the importance of more realistic and standardized smart-home benchmarks, which better capture the complexity of real-world deployments and multi-stage attack scenarios [28] (benchmarking and evaluation of prompt injection defenses).

These directions are closely aligned with the goals of the present project, indicating that it addresses genuine research gaps rather than simply reapplying existing techniques in a new setting.

4.9. Implementation Screenshot




***Figure 5**: Dashboard Screen*

5. Conclusion and Recommendations

5.1. Summary of detailed results

The results of this project highlight the changing security challenges that come with integrating Large Language Models (LLMs) into smart-home IoT systems. Threats focus on device vulnerabilities and network attacks in traditional IoT environments, but LLM-enabled systems bring a new set of risks related to manipulating the decision-making process. Inputs from various sources such as user commands, sensor data, OCR outputs, and external services are combined in a shared context, in these systems. This creates a mixed-trust environment that is vulnerable to prompt injection and context integrity attacks.

In this project, a threat model is introduced which sorts attacks into three categories: direct prompt injection, indirect (retrieval-based) injection, and compound or multi-stage attacks. Direct attacks use explicit malicious instructions from user-facing channels. Indirect attacks use external data sources to hide instructions. Different strategies are mixed in compound attacks in order to boost effectiveness and avoid being detected. Among these, indirect and combined attacks are the most critical because they can evade traditional input validation and exploit contextual blending in LLM inputs.

An embedding-based machine learning detection layer is used in this project, to reduce risks. Incoming inputs are changed into semantic vector representations and classified with supervised learning models. This method helps the system spot malicious intent based on contextual and semantic features instead of relying on simple rule-based filtering. The results show that this approach is effective as a lightweight and scalable first line of defense in real-time IoT environments. However, it also shows limitations in handling adaptable or hidden attack patterns, pointing out that detection alone cannot ensure complete security.

To tackle these limitations, the system uses a defense-in-depth structure. It combines system-level safeguards with the ML detection layer. These safeguards include action allowlisting to limit allowable device operations, input filtering and sanitization to reduce exposure to harmful content, and user confirmation for high-risk or sensitive actions. Contextual validation also checks that generated actions match device states and user intentions. This layered approach separates semantic interpretation from direct actions, ensuring that even if harmful inputs bypass detection, they cannot directly trigger unsafe or unauthorized device behavior.

The results also show that traditional IoT security methods, like authentication, encryption, and device attestation, are not enough to handle prompt injection threats. These attacks focus on the model's reasoning rather than system integrity. Additionally, relying on LLM-based self-detection methods is unreliable because they can be manipulated similarly. The project also looks into privacy-preserving solutions, such as federated learning, as a potential way to enhance detection without centralizing sensitive user data.

Overall, the findings show that securing LLM-enabled smart-home systems needs a multi-layered security framework. This framework combines semantic-level threat detection, strict control over system actions, and context-aware validation mechanisms. This strategy significantly lowers the attack surface while ensuring usability, scalability, and real-time performance, which makes it a practical solution for next-generation IoT environments.

5.2. Recommendations for Mitigating Injection and Context Integrity Attacks

The security framework developed in this project addresses one of the most pressing challenges in modern IoT and smart home environments: the growing threat of injection-based attacks and contextual integrity violations, particularly as AI-powered backends become more deeply embedded in residential systems. Drawing from the body of literature reviewed and the implementation work carried out, the following recommendations are proposed for developers, platform architects, and security practitioners working in this space.

Injection attacks, whether prompt-based, code-based, or data-injection variants, exploit the trust that IoT platforms extend to inputs from users, devices, and external services. Greshake et al. [7] demonstrated that LLM-integrated applications are particularly vulnerable to indirect prompt injection, where malicious instructions are embedded in content that the model retrieves during normal operation rather than directly from the user. Liu et al. [8] further showed that these attacks can be automated and universally applied across different LLM-integrated systems, which means the threat is not limited to targeted or sophisticated adversaries. Ferrag et al. [9] expanded this analysis to AI agent workflows, confirming that as smart home systems adopt agentic AI pipelines, the consequences of a successful injection escalate far beyond a single compromised interaction. These findings collectively establish that a layered, proactive security posture is not optional but necessary for any platform that combines IoT infrastructure with AI-driven automation.

5.2.1. Recommendations

Adopt Multi-Layer Input Validation Across All System Boundaries

The most foundational defense available to any IoT or smart home platform is rigorous and context-aware input validation applied at every point where data enters the system. This means not only sanitizing user inputs at the application interface but also treating machine-generated data, including sensor readings, API responses, and telemetry streams, as untrusted until verified. Noman and Abu-Sharkh [32] conducted a comprehensive review of code injection attacks in wireless IoT systems and found that the majority of successful attacks exploit the absence of validation at internal system boundaries rather than at the perimeter alone. Perez and Ribeiro [1] similarly identified that prompt injection succeeds primarily because LLM systems fail to distinguish between trusted instructions and untrusted content when both arrive through the same input channel. Validation routines must therefore be context-sensitive, recognizing that the same input may be benign in one processing context and malicious in another, and they must be applied at each stage of the processing pipeline rather than only at initial ingestion.

Deploy Embedding-Based Classifiers for Prompt Injection Detection

For smart home and IoT platforms that incorporate LLMs as reasoning or automation engines, rule-based detection of prompt injection is not sufficient on its own. Attackers can craft payloads that satisfy syntactic rules while still overriding the intended behavior of the model at the semantic level. Ayub and Majumdar [4] demonstrated that embedding-based classifiers, which represent inputs as semantic vectors and classify them against a learned decision boundary, achieve considerably stronger detection performance than rule-based filters and generalize more effectively to novel injection patterns not seen during training. Jayathilaka [2] extended this approach by combining embedding-based classification with federated learning, enabling detection without centralizing sensitive input data. These classifiers should be deployed as a pre-processing layer on all inputs consumed by LLM components, with special attention to indirect injection pathways such as content retrieved from the web, tool outputs, and sensor-derived context strings fed into automated reasoning pipelines.

Implement Federated Learning for Privacy-Preserving Threat Detection

Centralized intrusion detection systems create a fundamental tension in the residential IoT context: effective detection requires access to behavioral data from many devices and

households, but aggregating that data raises serious privacy concerns for users who reasonably regard their home network activity as sensitive. Federated learning offers a principled resolution to this tension. Nguyen et al. [48] proposed DIoT, a federated self-learning anomaly detection system for IoT, which demonstrated that meaningful detection capability can be achieved without raw device data ever leaving the local environment. Wang et al. [25] applied a similar federated approach to false data injection detection in connected vehicle networks and confirmed that federated models can match or exceed centralized models in detection accuracy while preserving participant privacy. Implementations in the smart home context should incorporate differential privacy mechanisms to prevent inference attacks on model updates, particularly given that behavioral patterns in residential environments can be sensitive indicators of occupancy and daily routine.

Enforce Contextual Integrity Policies at the Platform Level

Smart home platforms that support third-party application ecosystems must implement enforceable information flow policies that reflect the privacy norms appropriate to the context in which data was originally generated. Jia et al. [33] introduced ContexIoT, a system that provides contextual integrity to IoT application platforms by requiring apps to declare their information flows and enforcing those declarations at runtime. Yahyazadeh et al. [35] extended this line of work with Expat, a policy analysis and enforcement system for smart home platforms that can identify expectation violations before they reach end users. These systems demonstrate that contextual integrity enforcement is technically achievable at the platform level and that doing so provides meaningfully stronger privacy guarantees than access control alone. Apthorpe et al. [42] found through empirical study that smart home users hold nuanced, context-specific privacy expectations that existing platforms routinely fail to meet, which establishes a clear gap that contextual integrity enforcement can address.

Segment Networks and Apply the Principle of Least Privilege

Network architecture decisions have an outsized impact on how far a successful injection attack can propagate once an initial foothold is established. Sotoudeh et al. [45] and Albany et al. [49] both recommend that IoT devices be placed on dedicated network segments isolated from general-purpose computing devices, with firewall rules that permit only the specific communication flows each device legitimately requires. Sheoran [36] notes that the absence of network segmentation in typical residential deployments means that a compromised smart bulb or environmental sensor can serve as an effective pivot point for attacking more sensitive devices on the same network. Applying the

principle of least privilege at the device level, restricting each device to the minimum set of network permissions, API credentials, and platform capabilities it needs to function, significantly reduces this lateral movement risk.

Harden LLM Agent Systems Against Indirect and Multi-Modal Injection

As smart home systems increasingly grant LLM agents the ability to invoke tools, execute automation routines, and interact with external services on behalf of users, the indirect injection attack surface expands substantially. Greshake et al. [7] showed that these attacks are practical and effective against real-world LLM-integrated applications, and Zhan et al. [18] benchmarked indirect prompt injections specifically against tool-integrated LLM agents, finding that current agent architectures are highly susceptible to instruction hijacking through externally retrieved content. Bagdasaryan et al. [17] further demonstrated that multi-modal LLMs can be manipulated through adversarial instructions embedded in images and audio, which is particularly relevant for smart home systems equipped with cameras and microphones. Defenses should include strict separation between trusted system-level instructions and untrusted external content within the model context, capability restrictions that prevent agent actions from exceeding pre-authorized scopes, and pre-processing scans of retrieved content before it is passed to the model.

Integrate Threat Modeling as a Mandatory Development Activity

Security frameworks retrofitted to deployed systems consistently perform worse than those designed in from the beginning. Abbas et al. [44] demonstrated through structured threat modeling of a smart home use case that botnet recruitment, false data injection, and denial-of-service represent the highest-priority threat categories for residential IoT, and that these threats are most effectively mitigated when countermeasures are built into the platform architecture rather than added afterward. Ferrag et al. [9] argue specifically that LLM-powered agent workflows require dedicated threat modeling efforts because the attack vectors they introduce, including prompt injection and protocol exploitation, are not captured by traditional IoT threat models. Pal et al. [24] further highlight the complexity of cyber-risk management in IT/OT systems and emphasize the importance of systematic risk classification as a prerequisite to effective mitigation. Platform developers should treat threat modeling as a recurring activity revisited whenever significant capability changes are introduced, rather than a one-time exercise at initial design.

Support End Users with Transparent Security Communication

Technical controls alone are insufficient in residential environments where the end user is a non-specialist who has limited visibility into the security posture of their devices. Haney et al. [31] found through a large-scale U.S. survey that smart home users hold device-category-specific security perceptions and that their protective behaviors differ significantly depending on how intimate they perceive a device to be. Alzaylaee [26] and Patel [37] both note that user security behaviors in smart home contexts are predominantly reactive rather than proactive, driven by incidents rather than by systematic awareness. Platforms should provide accessible interfaces that surface anomalous device behavior, pending updates, and active policy violations in terms that are meaningful to non-technical users, enabling them to participate meaningfully in the security of their own homes.

5.2.2. Future Research Directions in Injection and Context Integrity Security

The literature reviewed for this project points to several open research problems that, if addressed, would significantly advance the state of protection against injection and context integrity attacks in smart home and IoT systems. These directions emerge directly from the limitations of current approaches identified in the reviewed literature.

Robust Detection of Indirect Prompt Injection Across Content Types

Current detection approaches for indirect prompt injection rely primarily on supervised training against known attack patterns or heuristic rules that sophisticated attackers can circumvent. Liu et al. [8] showed that automatic and universal injection attacks can be crafted that evade many existing defenses, and Choudhary et al. [16] specifically demonstrated the limitations of using LLMs themselves as prompt injection detectors. What is needed are semantics-aware detection systems capable of identifying injection attempts embedded within heterogeneous content types including structured data, natural language documents, and multi-modal inputs. Research should investigate transfer learning approaches that allow detectors trained in one content domain to generalize to others, which would reduce the annotation burden and accelerate deployment in new application contexts.

Formal Verification of Contextual Integrity Policies

Jia et al. [33] and Yahyazadeh et al. [35] have established the technical foundations for contextual integrity enforcement in IoT platforms, but current mechanisms rely on runtime monitoring rather than formal guarantees. A system that can prove contextual integrity properties at design time, given a formal policy specification and a model of the

information flows the system can generate, would provide much stronger assurance than detection after the fact. Research in this area should draw on program analysis, model checking, and policy language design to develop verification tools applicable to real platform architectures.

Adversarially Robust Anomaly Detection for Heterogeneous Device Populations

Meidan et al. [19] demonstrated strong anomaly detection performance for IoT botnet detection using deep autoencoders trained on device-level network behavior. Rieger et al. [34] proposed ARGUS, a context-based detection system for stealthy IoT infiltration attacks. However, both of these approaches were evaluated against attackers who were not specifically attempting to evade the detection system. In practice, sophisticated adversaries who are aware of the detection mechanism can craft attacks that mimic normal device behavior closely enough to avoid triggering anomaly alarms. Research is needed into detection architectures that are provably or empirically robust to such evasion, drawing on adversarial training, ensemble methods, and theoretical bounds on the detectability of stealthy attacks.

Privacy-Preserving Threat Intelligence Sharing

The effectiveness of federated detection systems depends on the quality and diversity of training data available across participating nodes. However, sharing threat intelligence between households and organizations, even in the form of attack signatures or anomaly patterns, carries privacy risks. Jayathilaka [2] and Rodríguez et al. [21] both identify privacy-preserving collaborative detection as an important open problem. Research should explore cryptographic and differential privacy techniques that allow meaningful threat intelligence to be shared across federated participants without exposing the behavioral data from which that intelligence was derived.

Security Implications of Increasing LLM Agent Autonomy

Ferrag et al. [9] identified a broad spectrum of threats in LLM-powered agent workflows, ranging from prompt injection to protocol exploitation, and noted that these threats scale in severity with the level of autonomy granted to the agent. Jamshidi et al. [12] similarly highlighted that the integration of LLMs into IoT security monitoring introduces new attack surfaces that require dedicated research attention. As smart home agents are granted authority over more consequential actions, including financial transactions, physical access control, and health monitoring, the potential damage from a single successful injection attack grows substantially. Research is needed to characterize the

security implications of different autonomy levels, to develop principled capability restriction frameworks, and to investigate human-in-the-loop architectures that preserve user oversight without degrading the utility of automation.

Cross-Platform Standardization of Defense APIs

The fragmented smart home platform landscape means that security improvements on one platform provide no benefit to users of other platforms. Stanko et al. [5] identified the absence of interoperability standards as a fundamental challenge for AIoT security. Jamshidi et al. [12] noted that the heterogeneity of IoT environments is one of the primary obstacles to deploying consistent security controls across device ecosystems. Standardized APIs for injection detection, context policy enforcement, and anomaly reporting would allow security capabilities to be developed once and deployed across diverse platform ecosystems, reducing the cost of defense and raising the baseline level of protection available to all users regardless of which platform they use.

5.2.3. Summary

The recommendations put forward in this section form a layered defense strategy for smart home and IoT deployments facing injection and context integrity threats. No single measure is sufficient on its own. Input validation and embedding-based classification address attacks at the point where malicious content first enters the system. Federated detection and network segmentation contain the propagation and impact of successful compromises. Contextual integrity enforcement and transparent user communication address the privacy dimension that purely technical controls miss. Threat modeling embeds security thinking into the development process from the outset rather than as a retrofit.

The future research directions reflect the genuine gaps that remain in current approaches. Progress on robust indirect injection detection, formal contextual integrity verification, and adversarially resilient anomaly detection will be essential as smart home systems become more capable, more autonomous, and more deeply integrated into daily life. The framework proposed in this project provides a structured foundation for addressing these challenges, but it is most valuable as a starting point for continued development rather than a finished solution. [7, 9, 12, 27, 28, 41]

5.3. Future prospects and Ongoing Research

The security landscape for smart home and IoT systems is shifting rapidly. Advances in generative AI, edge computing, and connectivity are reshaping both the capabilities of

these systems and the threats they face. The following sections outline the key trends, technological developments, and ongoing research priorities that will define the next phase of security work in this domain.

5.3.1. Emerging Trends in Information Security for Smart Home and IoT Systems

One of the most significant structural shifts currently underway is the migration from cloud-centric to edge-native IoT architectures. As the volume and velocity of data generated by smart home devices increases, and as latency requirements for real-time automation become more demanding, processing and decision-making are moving closer to the devices themselves. Dirin et al. [41] describe this transition as a fundamental change in the security model of IoT systems because edge nodes concentrate both data processing authority and physical accessibility in a single location that may be far easier to compromise than a well-protected cloud backend. Stanko et al. [5] identify edge security as one of the central unresolved challenges in AIoT deployments, noting that the resource constraints typical of edge devices limit the security controls that can practically be applied. Future security frameworks must address edge hardening explicitly rather than assuming that cloud-based protections will be sufficient.

The integration of generative AI and agentic LLM capabilities into smart home platforms is equally consequential. Ferrag et al. [9] document a comprehensive range of prompt injection and protocol exploitation threats in LLM-powered agent workflows, and Aung et al. [23] survey the broader security challenges and opportunities introduced by generative AI in IoT environments. As these systems move from research prototypes to commercial products, the attack surface documented in the literature becomes a practical concern for millions of households. The security community needs to develop detection, containment, and response capabilities that keep pace with capability deployments rather than reacting to incidents after widespread adoption has already occurred. Jaffal et al. [20] note that while LLMs offer powerful new tools for security monitoring and threat analysis, their deployment in security-critical contexts must be carefully governed given their susceptibility to the same injection attacks they are meant to detect.

Regulatory and policy environments are also evolving in ways that directly affect the security practices of IoT platform developers. Sadique et al. [13] observed even as early as 2018 that the absence of security standards for IoT was a primary enabler of widespread vulnerability, and Alzaylaee [26] confirmed in a 2025 systematic review that many of those gaps persist despite years of industry and academic attention. Legislative initiatives in various jurisdictions are now beginning to establish minimum security

baselines for consumer IoT, but as Mishra and Pandya [10] note, regulatory frameworks often lag behind the technical threat landscape by years. The practical impact of these regulations will depend heavily on enforcement mechanisms and on whether they are designed with sufficient technical specificity to address threats like prompt injection that were not well understood when earlier standards were written.

The growing interest in zero-trust security architectures has direct relevance to smart home protection against injection attacks. Under a zero-trust model, no device or communication is granted implicit trust based on network location, and every interaction is continuously verified. Sheoran [36] and Sotoudeh et al. [45] both advocate for zero-trust principles in smart home network design, and Albany et al. [49] note that the architectural discipline required by zero-trust would substantially limit the lateral movement available to attackers who have established an initial foothold through injection. Practical implementation of zero-trust in resource-constrained IoT environments remains an open engineering challenge, but the trajectory of both research and industry practice points toward this model as the appropriate long-term security architecture for heterogeneous device ecosystems.

5.3.2. Advancements in AI and Emerging Technologies for Smart Homes and Security

The same AI capabilities that introduce new vulnerabilities in smart home systems are also generating powerful defensive tools, and the balance between these two effects will be a central determinant of security outcomes in the coming years.

Federated learning is maturing rapidly as a framework for privacy-preserving collaborative detection. Nguyen et al. [48] demonstrated with DIoT that federated anomaly detection for IoT can achieve competitive performance while keeping raw device data local, and Wang et al. [25] applied a similar approach to false data injection in vehicular networks. The next generation of federated detection systems is expected to operate at a higher level of abstraction, detecting coordinated attack campaigns that span multiple devices within a household or correlated anomalies across many households in a federated population. Rodríguez et al. [21] survey the broader landscape of machine and deep learning methods for privacy protection in IoT, identifying federated and differentially private approaches as the most promising directions for reconciling detection effectiveness with user privacy. The development of federated systems that can handle the highly heterogeneous device populations found in real smart home deployments, with devices from dozens of manufacturers running different firmware and

communication protocols, represents a significant and practically important research frontier.

Blockchain and distributed ledger technologies offer a complementary set of capabilities relevant to injection defense and context integrity enforcement. Dirin et al. [41] propose a security framework for IoT that uses blockchain to maintain the integrity of device configurations and software updates, preventing injection attacks that target the firmware layer. Aung et al. [23] survey blockchain applications in IoT security more broadly and identify tamper-evident logging, decentralized access control, and cryptographic provenance as the most mature and practically deployable use cases. The computational overhead of blockchain consensus mechanisms has historically limited applicability in resource-constrained IoT environments, but lightweight consensus protocols and permissioned ledger architectures are making these approaches increasingly viable for residential deployments.

Explainable AI is becoming increasingly important in the IoT security context, both for technical and practical reasons. Meidan et al. [40] note in the context of CADeSH, their collaborative anomaly detection system for smart homes, that detection systems whose decisions cannot be explained are difficult for platform operators to validate and tune effectively. Jaffal et al. [20] argue that explainability is particularly critical when LLMs are used for security monitoring, because opaque decisions made by AI security systems are difficult to audit and may introduce new biases. For end users, Haney et al. [31] found that transparency about how security decisions are made is a significant factor in user trust and acceptance of automated security systems. Detection systems that can explain in plain language why a particular device behavior was flagged, or why a specific input was classified as a potential injection attempt, are substantially more likely to generate the user engagement needed for security measures to be effective.

5.3.3. Continuing Research and Development

The threats documented in this project are not static and neither are the tools available to address them. Sustaining an effective security posture for smart home and IoT systems requires ongoing investment in research and development across several dimensions that go beyond what any single project can address.

The development of standardized benchmarks and shared evaluation datasets is a foundational need for the field. Comparative evaluation of competing detection approaches is currently hampered by the diversity of experimental setups, dataset

compositions, and evaluation metrics used across the literature. Liu et al. [28] took an important step in this direction by formalizing and benchmarking prompt injection attacks and defenses at a level of rigor that allows meaningful comparison across systems, and Zhan et al. [18] contributed the InjecAgent benchmark specifically for tool-integrated agent systems. Broader community investment in benchmark development for IoT injection detection and context integrity enforcement, similar to what Liu et al. and Zhan et al. have done for LLM-specific attacks, would significantly accelerate research progress and enable more reliable deployment decisions by practitioners.

Interdisciplinary approaches that integrate human factors research with technical security design are essential for developing solutions that users will actually adopt and maintain over time. Haney et al. [31] demonstrated that user security behaviors in smart home environments are shaped by device-category-specific perceptions that do not always align with technical risk assessments, and Patel [37] confirmed that the gap between technical security capability and actual user behavior remains wide in home automation contexts. Security frameworks designed without accounting for these human factors tend to be bypassed or disabled by users who find them inconvenient. Research programs that treat the human dimension as a core design constraint rather than an afterthought are more likely to produce deployable outcomes with real security impact.

Responsible disclosure and coordinated vulnerability response processes specifically designed for the IoT ecosystem are urgently needed. Mishra and Pandya [10] identified in their systematic review that the long product lifecycles and limited update infrastructure of consumer IoT create conditions where vulnerabilities persist in deployed systems for years after they are discovered. Ansari et al. [14] found in their systematic review of smart home app vulnerabilities that many known vulnerabilities remain unpatched in widely deployed applications due to the absence of coordinated response processes between platform operators, app developers, and device manufacturers. Alshamsi et al. [38] similarly note that the fragmented vendor landscape makes it difficult to coordinate timely responses even when vulnerabilities are clearly documented. Research into disclosure models that create appropriate incentives for all stakeholders, combined with technical mechanisms for rapid patch distribution to deployed devices, would make a substantial contribution to closing the gap between vulnerability discovery and effective remediation.

Finally, the question of how the security framework developed in this project should evolve as smart home systems gain greater autonomy and integrate more deeply with

healthcare, energy management, and physical access control infrastructure is one of the most consequential long-term research questions the field faces. Pal et al. [24] characterize the cyber-risk management challenge in IT/OT systems as fundamentally hard due to the complexity of interdependencies and the difficulty of modeling cascading failures. Ferrag et al. [9] note that the same agentic capabilities that make LLM-powered smart home systems useful are the ones that make a successful injection attack most consequential. Proactive research into the security architecture requirements of these increasingly capable systems, informed by the implementation experience and literature review carried out in this project, will be essential for ensuring that the benefits of smart home automation are not offset by the security risks it introduces. [9][12][23][24][27][41]

6. Reference

[1] F. Perez and I. Ribeiro, “Ignore Previous Prompt: Attack Techniques for Language Models,” ML Safety Workshop, NeurIPS 2022, 2022, doi: 10.48550/arXiv.2211.09527.

[2] H. Jayathilaka, “Privacy-Preserving Prompt Injection Detection for LLMs Using Federated Learning and Embedding-Based NLP Classification,” in arXiv preprint, 2025, pp. N/A, doi: 10.48550/arXiv.2511.12295.

[3] T. Gaber, A. El-Ghamry, A. E. Hassanien, “Injection attack detection using machine learning for smart IoT applications,” Physical Communication, vol. 54, Art. no. 101685, 2022, doi: 10.1016/j.phycom.2022.101685.

[4] M. A. Ayub and S. Majumdar, “Embedding-Based Classifiers Can Detect Prompt Injection Attacks,” in arXiv preprint, 2024, pp. N/A, doi: 10.48550/arXiv.2410.22284.

[5] A. Stanko, O. Duda, A. Mykytyshyn, O. Totosko, R. Koroliuk, “Artificial intelligence of things (AIoT): Integration challenges, and security issues,” Proceedings of the BAIT, 2024, doi: BAIT 2024: 92-105.

[6] T. Shi, K. Zhu, Z. Wang, Y. Jia, W. Cai, W. Liang, H. Wang, H. Alzahrani, J. Lu, K. Kawaguchi, B. Alomair, X. Zhao, W. Y. Wang, N. Z. Gong, W. Guo, and D. Song,“PromptArmor: Simple yet Effective Prompt Injection Defenses,” *arXiv preprint arXiv:2507.15219*, 2025..

[7] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, M. Fritz, “Not what you’ve signed up for: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection”, AISec '23: Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security, pp. 79-90, doi: 10.1145/3605764.3623985.

[8] X. Liu, Z. Yu, Y. Zhang, N. Zhang, C. Xiao, “Automatic and Universal Prompt Injection Attacks against Large Language Models”, arXiv preprint arXiv:2403.04957v1, 2024, doi: 10.48550/arXiv.2403.04957.

[9] M. A. Ferrag, N. Tihanyi, D. Hamouda, L. Maglaras, A. Lakas, M. Debbah, “From prompt injections to protocol exploits: Threats in LLM-powered AI agents workflows”, ICT Express, vol. 12, no. 2, pp. 353–383, 2026, doi: 10.1016/j.icte.2025.12.001.

[10] N. Mishra and S. Pandya, "Internet of Things Applications, Security Challenges, Attacks, Intrusion Detection, and Future Visions: A Systematic Review," in IEEE Access, vol. 9, pp. 59353-59377, 2021, doi: 10.1109/ACCESS.2021.3073408.

[11] Y. Liu, H. Chen, J. Zhang, W. Zhang, “Prompt Injection Attack Against LLM-Integrated Applications,” in arXiv preprint, Online, 2023, doi:10.48550/arXiv.2306.05499.

[12] S. Jamshidi, N. Shahabi, A. Nikanjam, K. W. Nafi, F. Khomh, C. Fung, “Review article: The role of Large Language Models in IoT security: A systematic review of advances, challenges, and opportunities,” Internet of Things, vol. 34, Elsevier, November 2025, Article 101735, doi: 10.1016/j.iot.2025.101735.

[13] K.M. Sadique, R. Rahmani, P. Johannesson, “Towards Security on Internet of Things: Applications and Challenges in Technology,” The 9th International Conference on Emerging Ubiquitous Systems and Pervasive Networks (EUSPN 2018), Stockholm University, Stockholm, Sweden, 2018, pp. 199-206, doi: 10.1016/j.procs.2018.10.168.

[14] A. M. Ansari, M. Nazir, K. Mustafa, “Smart Homes App Vulnerabilities, Threats, and Solutions: A Systematic Literature Review”, Journal of Network and Systems Management, vol. 32, no. 2, 2024, doi: 10.1007/s10922-024-09803-1.

[15] W. Zou, R. Geng, B. Wang, J. Jia, “PoisonedRAG: Knowledge Corruption Attacks to Retrieval-Augmented Generation of Large Language Models”, arXiv preprint arXiv:2402.07867v3, 2024, doi: 10.48550/arXiv.2402.07867.

[16] S. Choudhary, D. Anshumaan, N. Palumbo, S. Jha. “How Not to Detect Prompt Injections with an LLM”. In Proceedings of the 18th ACM Workshop on Artificial Intelligence and Security (AISec '25). Association for Computing Machinery, New York, NY, USA, pp. 218–229. doi:10.1145/3733799.3762980.

[17] E. Bagdasaryan, T.-Y. Hsieh, B. Nassi, V. Shmatikov, “Abusing Images and Sounds for Indirect Instruction Injection in Multi-Modal LLMs”, arXiv preprint arXiv:2307.10490v4, 2023, doi: 10.48550/arXiv.2307.10490.

[18] Q. Zhan, Z. Liang, Z. Ying, and D. Kang, “InjecAgent: Benchmarking Indirect Prompt Injections in Tool-Integrated Large Language Model Agents,” in Findings of the Association for Computational Linguistics: ACL 2024, Bangkok, Thailand, 2024, pp. 10471–10506, doi: 10.18653/v1/2024.findings-acl.624.

[19] Y. Meidan, M. Bohadana, Y. Mathov, Y. Mirsky, D. Breitenbacher, A. Shabtai, Y. Elovici, “N-BaIoT: Network-based Detection of IoT Botnet Attacks Using Deep Autoencoders”, IEEE Pervasive Computing, vol. 17, no. 3, pp. 12–22, 2018, doi: 10.1109/MPRV.2018.03367731.

[20] N. O. Jaffal, M. Alkhanafseh, D. Mohaisen, “Large Language Models in Cybersecurity: A Survey of Applications, Vulnerabilities, and Defense Techniques”, AI, vol. 6, no. 9, p. 216, 2025, doi: 10.3390/ai6090216.

[21] E. Rodríguez, B. Otero, R. Canal, “A Survey of Machine and Deep Learning Methods for Privacy Protection in the Internet of Things”, Sensors, vol. 23, no. 3, p. 1252, 2023, doi: 10.3390/s23031252.

[22] S.W. Chen, K.L. Chen, J.S. Li, I.H. Liu, “Hands-On Training Framework for Prompt Injection Exploits in Large Language Models,” in 2025 IEEE 5th International Conference on Electronic Communications, Internet of Things and Big Data, New Taipei, Taiwan, 2025, pp. 25–30, doi: 10.3390/engproc2025108025.

[23] Y. L. Aung, I. Christian, Y. Dong, X. Ye, S. Chattopadhyay, J. Zhou, “Generative AI for Internet of Things Security: Challenges and Opportunities”, arXiv preprint arXiv:2502.08886v1, 2025, doi: 10.48550/arXiv.2502.08886.

[24] R. Pal, P. Liu, T. Lu, E. Hua, “How Hard Is Cyber-risk Management in IT/OT Systems? A Theory to Classify and Conquer Hardness of Insuring ICSs”, ACM Transactions on Cyber-Physical Systems, vol. 6, no. 4, pp. 1–31, 2022, doi: 10.1145/3568399

[25] H. Wang, J. Yang, J. Sun, Z. Wang, Q. Liu, and S. Luo, “FedIFD: Identifying False Data Injection Attacks in Internet of Vehicles Based on Federated Learning,” Big Data and Cognitive Computing, vol.9/issue10/2025 doi:10.3390/bdcc9100246.

[26] M. K. Alzaylaee, "A Systematic Review of Security Vulnerabilities in Smart Home Devices and Mitigation Techniques" IJCSNS International Journal of Computer Science and Network Security, vol. 25, no. 3, March 2025, pp 206-216 doi: 10.22937/IJCSNS.2025.25.3.24.

[27] S. Gulyamov, S. Gulyamov, A. Rodionov, R. Khursanov, K. Mekhmonov, D. Babaev, A. Rakhimjonov, “Prompt Injection Attacks in Large Language Models and AI Agent Systems: A Comprehensive Review of Vulnerabilities, Attack Vectors, and Defense Mechanisms,” Information, vol. 17, no. 1, MDPI, 2026, pp. 54, doi: 10.3390/info17010054.

[28] Y. Liu, Y. Jia, R. Geng, J. Jia, N. Z. Gong. 2024, “Formalizing and benchmarking prompt injection attacks and defenses,” 33rd USENIX Security Symposium (USENIX Security 24), Philadelphia, PA, USA, 2024, pp 1831–1847, doi: 10.48550/arXiv.2310.12815.

[29] S. G. Saranya, P. Bavadharika, J. V. B. Alshia, A. Ananya, “Investigation and Enhancement of Digital System Security Against Emerging Cyber Threats,” in Proceedings of the 6th International Conference on Inventive Research on Computing Applications (ICIRCA), Coimbatore, India, 2025, pp 28-35, doi:10.1109/ICIRCA65293.2025.11089645.

[30] S. Chen, J. Piet, C. Sitawarin, and D. Wagner, “StruQ: Defending Against Prompt Injection with Structured Queries,” in Proceedings of the 34th USENIX Security Symposium (USENIX Security 25), Seattle, WA, USA, 2025, pp. 2383–2400 doi: 10.48550/arXiv.2402.06363

[31] J. M. Haney, Y. Acar, A. Li, F. Haney, “Smart Home Users’ Security and Privacy Perceptions and Actions Differ By Device Category: Results from a U.S. Survey”, SOUPS '21: Proceedings of the Seventeenth Symposium on Usable Privacy and Security, pp. 505–524, 2021, doi: 10.5470/SP.2021.505.

[32] H. A. Noman, O. M. F. Abu-Sharkh, “Code Injection Attacks in Wireless-Based Internet of Things (IoT): A Comprehensive Review and Practical Implementations”, Sensors, vol. 23, no. 13, p. 6067, 2023, doi: 10.3390/s23136067.

[33] Y. J. Jia, Q. A. Chen, S. Wang, A. Rahmati, E. Fernandes, Z. M. Mao, A. Prakash, “ContexIoT: Towards Providing Contextual Integrity to Appified IoT Platforms”, NDSS '17: Proceedings of the 21st Network and Distributed System Security Symposium, 2017, doi: 10.14722/ndss.2017.23051.

[34] P. Rieger, M. Chilese, R. Mohamed, M. Miettinen, H. Fereidooni, A.-R. Sadeghi, “ARGUS: Context-Based Detection of Stealthy IoT Infiltration Attacks”, USENIX Security '23: Proceedings of the 32nd USENIX Security Symposium, pp. 4301–4318, 2023.

[35] M. Yahyazadeh, P. Podder, E. Hoque, O. Chowdhury, “Expat: Expectation-Based Policy Analysis and Enforcement for Appified Smart-Home Platforms”, SACMAT '19: Proceedings of the 24th ACM Symposium on Access Control Models and Technologies, pp. 143–154, 2019, doi: 10.1145/3322431.3325107.

[36] K. Sheoran, “Network Security in Smart Home Environments: Threats and Mitigation”, ISCSITR-International Journal of Network and Information Security (ISCSITR-IJNIS), vol. 5, no. 2, pp. 1–4, 2024.

[37] Y. Patel, “Security Threats and Risk Mitigation in Home Automation: A Qualitative Review of Challenges and Public Safety Considerations”, Journal of Information Systems Engineering and Management, vol. 10, no. 55s, 2025.

[38] O. Alshamsi, K. Shaalan, U. Butt, “Towards Securing Smart Homes: A Systematic Literature Review of Malware Detection Techniques and Recommended Prevention Approach”, Information, vol. 15, no. 10, p. 631, 2024, doi: 10.3390/info15100631.

[39] S. Sikder, A. Acar, H. Aksu, A. S. Uluagac, “Aegis: A Context-Aware Security Framework for Smart Home Systems”, NDSS '19: Proceedings of the Network and Distributed System Security Symposium, 2019, doi: 10.14722/ndss.2019.23324.

[40] Y. Meidan, D. Avraham, H. Libhaber, A. Shabtai, “CADeSH: Collaborative Anomaly Detection for Smart Homes”, IEEE Internet of Things Journal, vol. 7, no. 12, pp. 11491–11505, 2020, doi: 10.1109/JIOT.2020.3004429.

[41] A. Dirin, I. Oliver, T. H. Laine, “A Security Framework for Increasing Data and Device Integrity in Internet of Things Systems”, Sensors, vol. 23, no. 17, p. 7532, 2023, doi: 10.3390/s23177532.

[42] N. Apthorpe, Y. Shvartzshnaider, A. Mathur, D. Reisman, N. Feamster, “Discovering Smart Home Internet of Things Privacy Norms Using Contextual Integrity”, Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies (IMWUT), vol. 2, no. 2, pp. 1–23, 2018, doi: 10.1145/3214262.

[43] N. Apthorpe, S. Varghese, N. Feamster, “Evaluating the Contextual Integrity of Privacy Regulation: Parents' IoT Toy Privacy Norms Versus COPPA”, USENIX Security '19: Proceedings of the 28th USENIX Security Symposium, 2019, doi: 10.48550/arXiv.1903.05152.

[44] S. G. Abbas, S. Zahid, F. Hussain, G. A. Shah, M. Husnain, “A Threat Modelling Approach to Analyze and Mitigate Botnet Attacks in Smart Home Use Case”, Research Square preprint rs-142075/v1, 2021, doi: 10.21203/rs.3.rs-142075/v1.

[45] S. Sotoudeh, S. Hashemi, H. G. Garakani, “Security Framework of IoT-Based Smart Home”, International Journal of Computer Network and Information Security (IJCNIS), vol. 12, no. 2, pp. 1–9, 2020, doi:10.1109/IST50524.2020.9345886

[46] M. A. Hossain, M. Fotouhi, R. Hasan, “DDoS Attack Analysis on IoT Device for Smart Home Environment and A Proposed Detection Technique”, IEEE International

Conference on Smart Computing (SMARTCOMP), pp. 1–6, 2019, doi:10.62527/joiv.8.4.2175

[47] N. Elsayed, Z. S. Zaghloul, S. W. Azumah, C. Li, “Intrusion Detection System in Smart Home Network Using Bidirectional LSTM and Convolutional Neural Networks Hybrid Model”, IEEE Access, vol. 8, pp. 205494–205507, 2020, doi: 10.1109/ACCESS.2020.3036067.

[48] T. D. Nguyen, S. Marchal, M. Miettinen, H. Fereidooni, N. Asokan, A.-R. Sadeghi, “DïoT: A Federated Self-learning Anomaly Detection System for IoT”, ICDCS '19: Proceedings of the 39th IEEE International Conference on Distributed Computing Systems, pp. 756–767, 2019, doi: 10.1109/ICDCS.2019.00080.

[49] M. Albany, E. Alsahafi, I. Alruwaili, S. Elkhediri, “A Review: Secure Internet of Things System for Smart Houses”, Procedia Computer Science, vol. 198, pp. 612–619, 2022, doi: 10.1016/j.procs.2022.01.078.

[50] Y. Liu, Y. Jia, J. Jia, D. Song, and N. Z. Gong,“DataSentinel: A Game-Theoretic Detection of Prompt Injection Attacks,” in Proceedings of the 46th IEEE Symposium on Security and Privacy (SP), 2025, pp. 2190–2208, doi: 10.1109/SP61157.2025.00250.

[51] R. Mangar, J. Chandler, J. Qian, C. A. Gunter, T. J. Pierson, and D. Kotz,“A Trigger for the Autonomous Decommissioning of Smart Devices,” in Proceedings of the 15th International Conference on the Internet of Things (IoT 2025), 2025, pp. 174–182, doi: 10.1145/3770501.3770522.

[52] K.-H. Hung, C.-Y. Ko, A. Rawat, I.-H. Chung, W. H. Hsu, and P.-Y. Chen,“Attention Tracker: Detecting Prompt Injection Attacks in LLMs,” arXiv preprint arXiv:2411.00348, 2024, doi: 10.48550/arXiv.2411.00348