```
smacc::ISmaccClient
# stateMachine
# components
+ ISmaccClient()
+ ~ISmaccClient()
+ initialize()
+ setStateMachine()
+ getName()
+ postEvent()
+ postEvent()
+ getComponent()
+ configureEventSourceTypes()
  smacc::client bases
     ::ISmaccActionClient
   # name
   + ISmaccActionClient()
   + ~ISmaccActionClient()
   + getNamespace()
   + cancelGoal()
   + getState()
                   smacc::client bases
                   ::SmaccActionClientBase
                           < ActionType >
                   + name
                   + onSucceeded_
                   + onAborted
                   + onPreempted_
                   + onRejected
                   + postSuccessEvent
                   + postAbortedEvent
                   + postPreemptedEvent
                   + postRejectedEvent
                   + postFeedbackEvent
                   + done_cb
                   + active cb
                   + feedback cb
                   # client
                   + ACTION_DEFINITION()
                   + SmaccActionClientBase()
                   + ~SmaccActionClientBase()
                   + initialize()
                   + postResultEvent()
                   + configureEventSourceTypes()
                   + onSucceeded()
                   + onSucceeded()
                   + onAborted()
                   + onAborted()
                   + onPreempted()
                   + onPreempted()
                   + onRejected()
                   + onRejected()
                   + cancelGoal()
                   + getState()
                   + sendGoal()
                   + getEventLabel()
                   # onFeedback()
                   # onResult()
                           < move_base_msgs::MoveBase
                                      Action >
smacc::client bases
::SmaccActionClientBase
< move_base_msgs::MoveBaseAction >
+ name
+ onSucceeded_
+ onAborted
+ onPreempted
+ onRejected_
+ postSuccessEvent
+ postAbortedEvent
+ postPreemptedEvent
+ postRejectedEvent
+ postFeedbackEvent
+ done_cb
+ active_cb
+ feedback_cb
# client
+ ACTION_DEFINITION()
+ SmaccActionClientBase()
+ ~SmaccActionClientBase()
+ initialize()
+ postResultEvent()
+ configureEventSourceTypes()
+ onSucceeded()
+ onSucceeded()
+ onAborted()
+ onAborted()
+ onPreempted()
+ onPreempted()
+ onRejected()
+ onRejected()
+ cancelGoal()
+ getState()
+ sendGoal()
+ getEventLabel()
# onFeedback()
# onResult()
```

Δ

move_base_z_client ::ClMoveBaseZ

+ ClMoveBaseZ() + ~ClMoveBaseZ()

+ initialize() + getName()