

master document for generating PDF

= GOBii API

Table of Contents

Overview	1
Version information	1
License information	1
URI scheme	1
System Architecture	1
DTO Models	1
Data Access	1
DTO Mapping	1
Services	1
The Web Controller	1
Web Service Operations	2
Request/Response Structure	2
Authentication	3
Error Handling	3
Documentation Tools	4
Paths	4
/analyses	4
/auth	5
/configsettings	5
/jobs/matrices/{jobName}	6
Definitions	6
AnalysisDTO	6
ConfigSettingsDTO	8
EntityPropertyDTO	8
Header	8
HeaderAuth	9
HeaderStatusMessage	9
JobDTO	9
Link	10
LinkCollection	10
MatrixDTO	10
MatrixUrlDTO	11
Pagination	11
PayloadAnalysisDTO	11
PayloadConfigSettingsDTO	12
PayloadEnvelopeAnalysisDTO	12
PayloadEnvelopeConfigSettingsDTO	12
PayloadEnvelopeJobDTO	12

PayloadEnvelopeMatrixDTO	12
PayloadJobDTO	12
PayloadMatrixDTO	13
ServerConfigItem	13
Status	13

Overview

The GOBii web service API provides a comprehensive set of RESTful methods for accomplishing the following core tasks in the GOBii Genomic Data Management (GDM) system. This manual explains the GOBii web architecture and its web service operations.

Version information

Version : 1.0

License information

License : Apache 2.0

License URL : <http://www.apache.org/licenses/LICENSE-2.0.html>

URI scheme

Host : localhost:8081

BasePath : /api

Schemes : HTTP

System Architecture

DTO Models

Content TBD

Data Access

Content TBD

DTO Mapping

Content TBD

Services

Content TBD

The Web Controller

Content TBD

Web Service Operations

Request/Response Structure

The http body structure is the same for all responses as well as for the body of POST and PUT requests. Here is a high level schematic of the body structure:

```
{
  "payload":{
    "linkCollection":{
      "linksPerDataItem":[

      ],
      "exploreLinksPerDataItem":[

      ]
    },
    "data":[

    ]
  },
  "header":{
    "gobiiProcessType":"","
    "dtoHeaderAuth":{
      "userName":null,
      "password":null,
      "token":"","
      "gobiiCropType":""
    },
    "status":{
      "succeeded":true,
      "statusMessages":[

      ],
      "statusMessagesByCode":{

      }
    },
    "pagination":null,
    "gobiiVersion":"2.0_2018-07-31",
    "cropType":""
  }
}
```

For requests, the following keys can be omitted:

- payload.linkCollection
- header

The content of the "data" array will vary depending on the type of the call. For example, for a POST to the the /project resource, it will contain a project object.

After a successful POST to the /auth resource, the "token" key in "dtoHeaderAuth" contains the token value, which should be used to set the X-Auth-Token header for subsequent requests.

Authentication

A valid token may be acquired by doing a POST to the /auth resource with an empty body and the following request headers set:

X-Username X-Password

The username and password depend on how the destination GOBii server is configured (per the gobii-web.xml file):

If gobiiAuthenticationType of the server is TEST, the username and password are hard-coded to USER_READER and reader, respectively. If the server is configured for LDAP authentication: The username/password must be provisioned in the configured LDAP server (if it is not, the error from the server will be 401: Unauthorized) There must be an entry for the user in contact table, where the username value matches the ldap user name; NOTE: if no such record is found, the error will be 403: Forbidden: Missing contact info for user <user-name> in crop database <crop-db>; a contact record must have username = <user-name>

When authentication succeeds, the response headers will contain a X-Auth-Token key whose value is a valid token. For subsequent requests, it is sufficient to supply X-Auth-Token in the request headers with the token that was received from the /auth POST. Some browsers prevent the client code from reading custom response headers. In this case, the token can also be retrieved from the meta data portion of the response body (see below).

Error Handling

Errors internal to GOBii are reported in the "header" key accompanying the response. An example of how to retrieve error data is provided in the following code fragment.

```

if (!header.getStatus().isSucceeded() ||
    header
        .getStatus()
        .getStatusMessages()
        .stream()
        .filter(headerStatusMessage ->
            headerStatusMessage.getGobiiStatusLevel().equals(GobiiStatusLevel.VALIDATION))
        .count() > 0) {
    returnVal = true;
    System.out.println();
    System.out.println("*** Header errors: ");
    for (HeaderStatusMessage currentStatusMessage :
        header.getStatus().getStatusMessages()) {
        System.out.println(currentStatusMessage.getMessage());
    }
}

```

Documentation Tools

The toolchain used to produce this documentation is swagger compatible. It is

Paths

/analyses

POST /gobii/v1/analyses

Description

Creates an analysis entity. The request and response bodies are wrapped in a PayloadEnvelopeDTO. Consult the [Request/Response Section](#) for further details.

Parameters

Type	Name	Description	Schema	Default
Body	body		PayloadEnvelopeAnalysisDTO	

Responses

HT TP Co de	Description	Schema
200	successful operation	PayloadEnvelopeAnalysisDTO

/auth

POST /gobii/v1/auth

Description

The user credentials are specified in the request headers; the response and the response headers include the token, which can which the client will include in the request headers for subsequent requests.

Parameters

Type	Name	Description	Schema	Default
Body	body		string	

Responses

HT TP Co de	Description	Schema
200	successful operation	string

/configsettings

GET /gobii/v1/configsettings

Description

Provides generic configuration information about the GOBii instance

Responses

HT TP Co de	Description	Schema
200	successful operation	PayloadEnvelopeConfigSettingsDTO

/jobs/matrices/{jobName}

POST /gobii/v1/jobs/matrices/{jobName}

Description

Initiates a genomic matrix load for the specified jobName. The keys for the urlsByPayloadType in the POST body are constrained to "CV_PAYLOADTYPE_SAMPLES", "CV_PAYLOADTYPE_SAMPLE_KEYS", "CV_PAYLOADTYPE_MARKERMAP", "CV_PAYLOADTYPE_MARKER_KEYS", "CV_PAYLOADTYPE_MATRIX", "CV_PAYLOADTYPE_MARKERSAMPLES", "CV_PAYLOADTYPE_ALLMETA" The request and response bodies are wrapped in a PayloadEnvelopeDTO. Consult the [Request/Response Section](#) for further details.

Parameters

Type	Name	Description	Schema	Default
Path	jobName		string	
Body	body		PayloadEnvelopeMatrixDTO	

Responses

HT TP Co de	Description	Schema
200	successful operation	PayloadEnvelopeJobDTO

Definitions

AnalysisDTO

Name	Description	Schema
algorithm		string
allowedProcessesTypes		< enum (CREATE, READ, UPDATE, DELETE, NONE) > array
analysisDescription		string
analysisId		integer(int32)
analysisName		string
analysisTypeId		integer(int32)
createdBy		integer(int32)
createdDate		string(date-time)
entityNameType		enum (UNKNOWN, ANALYSIS, CONTACT, DATASET, CV, CVGROUP, PROJECT, ORGANIZATION, PLATFORM, MANIFEST, MAPSET, MARKER_GROUP, EXPERIMENT, REFERENCE, ROLE, DISPLAY, MARKER, PROTOCOL, VENDOR_PROTOCOL, DNASAMPLE, LINKAGE_GROUP, DNARUN)
id		integer(int32)
modifiedBy		integer(int32)
modifiedDate		string(date-time)
parameters		< EntityPropertyDTO > array
program		string
programVersion		string
referenceId		integer(int32)
sourceName		string
sourceUri		string
sourceVersion		string
statusId		integer(int32)

Name	Description	Schema
timeExecuted		string(date-time)

ConfigSettingsDTO

Name	Description	Schema
allowedProcessesTypes		< enum (CREATE, READ, UPDATE, DELETE, NONE) > array
id		integer(int32)
maxUploadSizeMbytes		integer(int32)
serverCapabilities		< string, boolean > map
serverConfigs		< string, ServerConfigItem > map

EntityPropertyDTO

Name	Description	Schema
entityIdId		integer(int32)
propertyId		integer(int32)
propertyName		string
propertyValue		string

Header

Name	Description	Schema
cropType		string
dtoHeaderAuth		HeaderAuth
gobiiProcessType		enum (CREATE, READ, UPDATE, DELETE, NONE)
gobiiVersion		string
maxGet		integer(int32)
maxPost		integer(int32)
maxPut		integer(int32)
pagination		Pagination

Name	Description	Schema
status		Status

HeaderAuth

Name	Description	Schema
gobiiCropType		string
password		string
token		string
userName		string

HeaderStatusMessage

Name	Description	Schema
gobiiStatusLevel		enum (ERROR, VALIDATION, WARNING, INFO, OK)
gobiiValidationStatusType		enum (NONE, UNKNOWN, VALIDATION_COMPOUND_UNIQUE, VALIDATION_NOT_UNIQUE, NONEXISTENT_FK_ENTITY, BAD_REQUEST, MISSING_REQUIRED_VALUE, ENTITY_DOES_NOT_EXIST, ENTITY_ALREADY_EXISTS, UNKNOWN_ENUM_VALUE)
message		string

JobDTO

Name	Description	Schema
allowedProcessesTypes		< enum (CREATE, READ, UPDATE, DELETE, NONE) > array

Name	Description	Schema
datasetIds		< integer(int32) > array
id		integer(int32)
jobId		integer(int32)
jobName		string
message		string
payloadType		string
status		string
submittedBy		integer(int32)
submittedDate		string(date-time)
type		string

Link

Name	Description	Schema
description		string
href		string
methods		< enum (GET, POST, PUT, PATCH, DELETE, OPTIONS) > array

LinkCollection

Name	Description	Schema
exploreLinksPerDataItem		< < Link > array > array
linksPerDataItem		< Link > array

MatrixDTO

Name	Description	Schema
allowedProcessTypes		< enum (CREATE, READ, UPDATE, DELETE, NONE) > array
datasetName		string

Name	Description	Schema
experimentName		string
id		integer(int32)
projectName		string
protocolName		string
referenceGenomeName		string
urlsByPayloadType		< string, MatrixUrlDTO > map
vendorName		string

MatrixUrlDTO

Name	Description	Schema
allowedProcessTypes		< enum (CREATE, READ, UPDATE, DELETE, NONE) > array
fileName		string
id		integer(int32)
md5Sum		string
url		string

Pagination

Name	Description	Schema
currentPage		integer(int32)
pageSize		integer(int32)
pagedQueryId		string
queryTime		string(date-time)
totalPages		integer(int32)

PayloadAnalysisDTO

Name	Description	Schema
data		< AnalysisDTO > array
linkCollection		LinkCollection

PayloadConfigSettingsDTO

Name	Description	Schema
data		< ConfigSettingsDTO > array
linkCollection		LinkCollection

PayloadEnvelopeAnalysisDTO

Name	Description	Schema
header		Header
payload		PayloadAnalysisDTO

PayloadEnvelopeConfigSettingsDTO

Name	Description	Schema
header		Header
payload		PayloadConfigSettingsDTO

PayloadEnvelopeJobDTO

Name	Description	Schema
header		Header
payload		PayloadJobDTO

PayloadEnvelopeMatrixDTO

Name	Description	Schema
header		Header
payload		PayloadMatrixDTO

PayloadJobDTO

Name	Description	Schema
data		< JobDTO > array
linkCollection		LinkCollection

PayloadMatrixDTO

Name	Description	Schema
data		< MatrixDTO > array
linkCollection		LinkCollection

ServerConfigItem

Name	Description	Schema
confidentialityNotice		string
contextRoot		string
domain		string
fileLocations		< string, string > map
gobiiCropType		string
port		integer(int32)

Status

Name	Description	Schema
statusMessages		< HeaderStatusMessage > array
statusMessagesByCode		< string, string > map
succeeded	Default : false	boolean