

**Industrial Displays** 

**PIM-125-C** 



PN: CS-D125

Revision 1.1 www.chipsee.com

### **Contents**

| PIM-125-C                    | 3 |
|------------------------------|---|
| 1. Product Overview          | 6 |
| 2. Ordering Options          | 6 |
| 3. Specification             | 7 |
| 4. Mounting Procedure        | 8 |
| 5. Mechanical Specifications | 8 |
| 6. Disclaimer                | 9 |
| 7. Technical Support         | 9 |

## PIM-125-C

## Front View



# Rear View



## Side View



PIM-125-C Product Overview



**EOL PRODUCT:** This product has been discontinued, due to market demand and shifts in technology. Please **Contact us** if you would like to purchase it.

#### **Product Overview**

PIM-125-C (PN: CS-D125) is a 12.5" industrial display that features a 10-point capacitive touch screen with a resolution of 1920 x 1080 (16:9) pixels and brightness of 220 cd/ $m^2$ . The 3mm tempered glass cover with black silk-screen ensures the screen is water and steam resistant.

The typical power consumption is  $\leq$  15W, while in standby mode, PIM-125-C uses around  $\leq$  2W, making it ideal for all kinds of applications.

### **Ordering Options**

Most of the Chipsee products can be customized during the ordering process. The product will be shipped with the pre-installed factory defaults if no extra requirements are specified. The table in the Specification section provides information about the product.



You can order PIM-125-C from the official Chipsee Store or from your nearest distributor.

PIM-125-C Specification

### **Specification**

| PIM-125-C             |  |                                 |  |
|-----------------------|--|---------------------------------|--|
| Backlight             | Led  | Type of Pen                     | Fingers, Hands with Gloves,<br>Conductive Stylus               |
| Brightness            | 220 cd/m <sup>2</sup>  | Waterproof                      | Touch surfaces will not be affected by water droplets or steam |
| Contrast<br>Ratio     | 800:1  | Calibration                     | No Calibration Tool  |
| Viewing Angle         | Horizontal: 170° / Vertical:<br>170°                             | Response Time                   | 7ms to 12ms  |
| Response<br>Time      | 35ms (GTG)   | Connect                         | 1 x USB 2.0 (Type-B)   |
| Display Color         | 16.2M Colors   | Multi Touch<br>Protocol Support | Windows  |
| Display<br>Resolution | 1920 x 1080 (16:9)   | Operating System                | Windows 7/8, Android, Linux                                    |
| Refresh<br>Frequency  | 60Hz   | Dimensions                      | 305 x 185.4 x 29.5mm   |
| Input<br>Resolution   | 1920 x 1080 (16:9) @ 60Hz  | Packaging Size                  | 362 x 230 x 70mm   |
| Connector             | VGA / HDMI   | Weight                          | 1540g  |
| Built-in<br>Speaker   | N/A  | Mounting Methods                | VESA, MIS-D, 100, C  |
| OSD Control           | Button   | Power Input                     | 12V 3A DC  |
| OSD<br>Language       | English, Chinese   | Power Supply                    | ≤ 15W  |
| Glass                 | 3mm Tempered Glass with<br>Black Silk-screen                     | Standby Power                   | ≤ 2W   |
| Touch Point           | 10   | Work Environment<br>(temp.)     | From 0°C to +40°C, 90% RH                                      |
| Touch<br>Technology   | Projecting Capacitance (G+G)                                     | Storage<br>Environment          | From -20°C to +60°C, 90% RH                                    |
| Accessories           | Bracket / Power Line / VGA<br>Line / USB Line / Power<br>Adapter |                                 |  |

Table 459 Key Features

PIM-125-C Mounting Procedure

### **Mounting Procedure**

The PIM-125-C industrial display supports VESA 100 x 100 mounting pattern with 4 x M4 screws, enabling simplified installation onto any standard VESA mounting rack. Other mounting options might also be supported according to the table in the Specification section.

You can find detailed information about mounting in the Mount IPC Guide.

### **Mechanical Specifications**

The outer mechanical dimensions of The PIM-125-C industrial display are  $305 \times 185.4 \times 29.5$ mm (W x L x H). Please refer to the technical drawing in the figure below for details related to the specific product measurements.




Figure 1066: Technical Drawing

PIM-125-C Disclaimer

#### **Disclaimer**

This document is provided strictly for informational purposes. Its contents are subject to change without notice. Chipsee assumes no responsibility for any errors that may occur in this document. Furthermore, Chipsee reserves the right to alter the hardware, software, and/or specifications set forth herein at any time without prior notice and undertakes no obligation to update the information contained in this document.

While every effort has been made to ensure the accuracy of the information contained herein, this document is not guaranteed to be error-free. Further, it does not offer any warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document, and no contractual obligations are formed either directly or indirectly by this document.

Despite our best efforts to maintain the accuracy of the information in this document, we assume no responsibility for errors or omissions, nor for damages resulting from the use of the information herein. Please note that Chipsee products are not authorized for use as critical components in life support devices or systems.

#### **Technical Support**

If you encounter any difficulties or have questions related to this document, we encourage you to refer to our other documentation for potential solutions. If you cannot find the solution you're looking for, feel free to contact us. Please email Chipsee Technical Support at **support@chipsee.com**, providing all relevant information. We value your queries and suggestions and are committed to providing you with the assistance you require.