


Industrial PC

PPC-CM4-156



PN: CS19108RA4156

Contents

I. PPC-CM4-156	3
1.1. Product Overview	4
1.2. Ordering Options	5
1.2.1. Pi [®] CM4 Module	5
1.2.2. Operating System	5
1.2.3. Optional Features	5
1.3. Specifications	6
1.4. Power Input	7
1.5. Touch Screen	8
1.6. Connectivity	9
1.6.1. RS232/RS485/CAN	9
1.6.2. GPIO Port	10
1.6.3. USB Connectors	12
1.6.4. LAN Connectors	13
1.6.5. WiFi & BT Module	13
1.6.6. 3G/4G/LTE Module	14
1.6.7. Zigbee Module	15
1.7. TF Card Slot	17
1.8. Audio Connectors	17
1.9. Boot DIP Button	18
1.10. Mounting Procedure	18
1.11. Mechanical Specifications	19
1.11.1. CS19108RA4156P	19
1.12. Disclaimer	19
1.13. Technical Support	19

PPC-CM4-156



Front View



Rear View

PPC-CM4-156 Product Overview



Side View 1



Side View 2

Product Overview

The Cortex[®]-A72 Raspberry Pi[®] series PPC-CM4-156 (PN: CS19108RA4156) is a high-quality industrial Pi PC. It features a 15.6" Ten-point capacitive touch screen with a resolution of 1920 x 1080 pixels and brightness of 400 cd/m².

Key Applications

- Human Machine Interface HMI
- Process Control
- Process Monitoring
- HMI
- IIoT node
- Environmental Monitoring
- PLC
- Automotive applications

PPC-CM4-156 Ordering Options

• ATM...

It is available both as an embedded solution and as a device hosed in a casing with bezels, thus facilitating different installation options:

- Installation on an industrial cabinet
- Integration with the existing equipment

The PPC-CM4-156 industrial Pi PC is based around the powerful Raspberry Pi[®] Compute Module 4, powered by the Quad Cortex[®]-A72 processor with a processor speed of 1.5GHz.

Ordering Options

Chipsee products can be customized during the ordering process. The product will be shipped with the pre-installed factory defaults if no extra requirements are specified. The table in the Specifications section provides information about the default options bundled with the product.



You can order PPC-CM4-156 from the official **Chipsee Store** or from your nearest distributor.

Pi® CM4 Module

The Pi[®] Compute Module 4 appears in different versions depending on the size of the DDR4 and eMMC.

The PPC-CM4-156 industrial Pi PC does not include the CM4 Raspberry Pi[®] module by default. If you would like to purchase it with a CM4, you can select it at the Chipsee store during the ordering process.

Operating System

This product comes with a pre-installed Debian OS. Chipsee software engineers have created all the drivers, so every hardware feature is readily available for any standard development tool.

If your project requires a different OS, please **Contact us**, and we'll make a customized version that suits your needs.

Optional Features

The PPC-CM4-156 industrial Pi PC does not include the 3G/4G/LTE modules by default. These modules are optional and can be selected at the Chipsee store during the ordering process.

Specifications PPC-CM4-156



Warning

Installation, repair, and maintenance tasks should be performed by trained personnel only. Chipsee does not bear any responsibility for damage caused by inadequate handling of the product.

Specifications

The PPC-CM4-156 industrial Pi PC offers a broad range of performance and connectivity options for scalable integration, providing expandability according to future needs. Some of the key features are listed in the table below.

	PPC-CM4-156				
CPU	Raspberry Pi [®] CM4, CM4 Lite; Quad Cortex-A72 at 1.5GHz				
Storage	1 TF Cards slots <mark>3</mark>				
RAM	2GB DDR				
еММС	16GB				
Display	15.6" IPS LCD, 1920 x 1080 resolution px, brightness 400 cd/m ²				
Touch	10-point capacitive touch with 1mm Armored Glass				
USB	2 x USB 3.0 Host, 1 x USB OTG				
LAN	1 x Channel Giga LAN				
Audio	3.5mm Audio Out Connector, 2W Speaker Internal				
Buzzer	Onboard Buzzer, driven by GPIO				
RTC	Yes, High Accuracy RTC with Lithium Button Coin battery (lithium battery not included)				
RS232	2 x RS232				
RS485	2 x RS4851				
CAN	1 x CAN-BUS				
GPIO	8 Channels, 4 Input, 4 Output				
WiFi/BT	Supported but depending on the CM4 selected2				
ZIGBEE	Onboard Zigbee module, not mounted by default				
HDMI	Not Supported				
SATA II	Not Supported				
3G/4G/LTE	Supported, not mounted by default				
Camera No					
Power Input	From 12V to 36V				
Current at 12V	1400mA Max				
Power Consumption	17W Typical				

PPC-CM4-156 Power Input


PPC-CM4-156					
Working Temperature	From 0°C to +80°C				
os	Debian				
Dimensions	CS19108RA4156P: 422 × 271 × 52.5mm				
Weight	CS19108RA4156P: 4500g				

Table 238 Key Features

- 1 The RS485 circuit controls the Input and Output direction automatically, there's no need to control it from within the software.
- The default product without the CM4 does not include a Wi-Fi/BT module. You can include a CM4 that has the Wi-Fi/BT module at the Chipsee store during the ordering process.
- 3 This TF card is designed for storage expansion, as the TF card uses the same pins with WiFi, it can't be used with WiFi at the same time

Power Input

The PPC-CM4-156 industrial Pi PC can be powered by a wide range of input voltages: From 12V to 36V DC. It is a **3 Pin, 3.81mm screw terminal** connector. The polarity and the pinout is clearly marked on the housing of the CS19108RA4156P version, as shown in the figures below.



Power Input

PPC-CM4-156 Touch Screen

Note that the "+" sign represents the positive power input, and it is printed both at the casing and as a silk-screen on the board of the embedded version. The "-" terminal is shorted to the ground.

Power Input Definition				
Pin Number	Definition	Description		
Pin 1	Positive Input	DC Power Positive Terminal		
Pin 2	Negative Input	DC Power Negative Terminal		
Pin 3	Ground	Power System Ground		

Table 239 Power Connector



Note

The system ground "**G**" is connected to power negative "-" on board. The central pin is positive.

Touch Screen

The PPC-CM4-156 industrial Pi PC uses a 10-point capacitive touch screen. However, the Debian OS supports only One-Point touch.

The figure below shows the capacitive touch screen connected to the motherboard via the **USB connector**.




Figure 970: Capacitive Touch Connector



Attention

PPC-CM4-156 Connectivity

A capacitive touch screen is susceptible to power noise and Electromagnetic Radiation (EMR). It may cause LCD ripples or even capacitive touch malfunction. If using a capacitive multi-touch test application, you might notice the touch points float erratically across the display. There are several solutions to this problem:


- 1. Use a high-quality Power Adapter Unit (PSU) with low EMR. You can also provide power from a battery.
- 2. Make sure that the PPC-CM4-156 Power Input connector (pin 3) is properly connected to the Power System Ground to provide sufficient EMI shielding and eliminate the problem entirely.
- 3. Bad GND problems can also be confirmed by touching pin 3 of the Power Input connector with one hand while operating the capacitive touch screen with the other hand. In this case, the operator's body acts as the Power System Ground.

Connectivity

There are many connectivity options available on the PPC-CM4-156 industrial Pi PC. It has 2 x USB 3.0 Host, 1 x USB OTG, 1 x Channel Giga LAN (RJ45) Ethernet connector supporting up to 1 Gbps, and 4×1000 x UART and 1×1000 c (RS232/RS485/CAN).

RS232/RS485/CAN

The serial communication interfaces (RS485, RS232, and CAN) are routed to a **12-pin 3.81mm terminal**, as illustrated on the figure below.



RS232-RS485-CAN on the PPC-CM4-156 Industrial PC

The table below offers more detailed description of every pin and its definition:

RS232 / RS485 / CAN Pin Definition:				
Pin Number	Definition	Description		
Pin 1	CAN_H	CAN BUS "H" signal		
Pin 2	CAN_L	CAN BUS "L" signal		

PPC-CM4-156 GPIO Port

RS232 / RS485 / CAN Pin Definition:					
Pin 3	RS485_5-	CPU UART5, RS485 –(B) signal			
Pin 4	RS485_5+	CPU UART5, RS485 +(A) signal			
Pin 5	RS485_3-	CPU UART3, RS485 –(B) signal			
Pin 6	RS485_3+	CPU UART3, RS485 +(A) signal			
Pin 7	RS232_2_RXD	CPU UART2, RS232 RXD signal			
Pin 8	RS232_2_TXD	CPU UART2, RS232 TXD signal			
Pin 9	RS232_0_RXD	CPU UARTO, RS232 RXD signal			
Pin 10	RS232_0_TXD	CPU UARTO, RS232 TXD signal			
Pin 11	GND	System Ground			
Pin 12	+5V	System +5V Power Output, No more than 1A Current output			

Table 240 Connectivity Section



Attention

- 1. RS485_3 and RS485_5 can control the input and output direction automatically. There's no need to control it from within the software.
- 2. The 120Ω match resistor for the RS485 and CAN bus is **NOT** mounted by default.

GPIO Port

The PPC-CM4-156 industrial Pi PC has a 10 Pin 3.81mm **GPIO Connector**, as shown in the figure below. The table below gives details about the definition of every Pin.

PIN1	PIN2	PIN3	PIN4	PIN5	PIN6	PIN7	PIN8	PIN9	PIN10	PIN11	PIN12
		IN4	IN3	IN2	IN1	OUT4	ОПТЗ	OUT2	OUT1	GND_ISO	24V_ISO




GPIO Connector

PPC-CM4-156 GPIO Port

GPIO Connector Pin Definition:						
Pin Number	Definition	Description				
Pin 12	24V_ISO	Isolated Power +24V Input				
Pin 11	GND_ISO	Isolated Ground				
Pin 10	OUT1	Isolated Output 1				
Pin 9	OUT2	Isolated Output 2				
Pin 8	OUT3	Isolated Output 3				
Pin 7	OUT4	Isolated Output 4				
Pin 6	IN1	Isolated Input 1				
Pin 5	IN2	Isolated Input 2				
Pin 4	IN3	Isolated Input 3				
Pin 3	IN4	Isolated Input 4				

Table 241 GPIO Connector Pin-out



Isolated GPIO reduced schematic

PPC-CM4-156 **USB Connectors**

Attention

- 1. In order to use the Isolated Output, you need to add an external Isolated Power to the VDD_ISO and GND_ISO. The power voltage should not exceed 24V.
- 2. The output current can achieve 500mA for every channel, but it also depends on the isolated power that is connected.
- 3. In order to use the Isolated Input, you need to add a signal to the ISO_InputX and GND_ISO. A $2.4 \mathrm{K}\Omega$ resistor, as R6, can be added to limit the input current, as shown in the figure above. This resistor should work well for the 5-24V input signal. If your input signal is less than 5V, please change this input resistor.

USB Connectors

There are 2 x Type A **USB3.0 HOST connectors** onboard, as shown in the figure below.



USB HOST Connectors (enclosed PC version)



Attention

- 1. These two USB hosts come from the same USB HUB. The Zigbee and 4G/LTE signals come from the same USB
- 2. These two USB host connectors can drive 500mA for each channel at most.

The product has one USB OTG connector that works as a slave by default. You can use it to establish a connection with the host PC and for downloading the system to the eMMC of CM4 module.



USB OTG Connector



Warning

Be careful not to touch surrounding electronic components accidentally while plugging in USB devices into the embedded Industrial PC version.

PPC-CM4-156 LAN Connectors

LAN Connectors

LAN (RJ45) connector provides Ethernet connectivity over standardized Ethernet cables as shown in the figure below. The integrated Ethernet interface supports up to 1 Gbps data throughput. These Giga LAN signals come from the CM4 module directly.




Figure 971: RJ45 LAN Connectors (embedded/enclosed PC version)



Use CAT5 or better cables to achieve full data throughput over maximum distance defined by the 1000BASE-T standard (100m).

WiFi & BT Module

The default PPC-CM4-156 without the CM4 does not include a Wi-Fi/BT module. If you include a CM4 that has the Wi-Fi/BT module, the product will have Wi-Fi/BT feature. The enclosed (CS19108RA4156P) variant of the product also includes an SMA connector for an external WiFi/BT antenna, as illustrated in the figure below.

PPC-CM4-156 3G/4G/LTE Module



Figure 972: WiFi+BT Antenna



Attention

The product does not come shipped with the Wi-Fi/BT module by default.

3G/4G/LTE Module

The PPC-CM4-156 industrial Pi PC is equipped with a **mini-PCle connector** that can connect to a 3G/4G module. The customer will also need a SIM Card Holder and a 3G/4G Antenna Connector to ensure 3G/4G works on the PPC-CM4-156. SIM card does **NOT** support hot plug. **Power off** before inserting or removing SIM card.



SIM Card Direction

PPC-CM4-156 Zigbee Module



Figure 973: 3G/4G Module





Figure 974: SIM Card Holder and 3G/4G Antenna Connector



Attention

The product does not come shipped with the 3G/4G module by default.

Zigbee Module

The PPC-CM4-156 industrial Pi PC supports an onboard Zigbee module. The Zigbee controller is TI CC2531, and the Raspberry Pi forum supports it.

For CS19108RA4156P, there is a connector on the backside of the case that you can use to connect the external Zigbee antenna, as described in the figure below.

PPC-CM4-156 Zigbee Module

Internal Zigbee Antenna



External Zigbee Antenna Connector

Zigbee Controller

Figure 975: Zigbee controller



Figure 976: Zigbee Antenna

A

Attention

The product does not come with the Zigbee module by default.

PPC-CM4-156 TF Card Slot

TF Card Slot

The PPC-CM4-156 industrial Pi PC features 1 x **TF Card (micro SD) slot**. It can address up to 32GB of memory.



TF (micro SD) Card Slot



Attention

- 1. The SD is used for memory extension. It can't be used for system boot-up.
- 2. The product does not come shipped with the TF Card by default.
- 3. This SD uses the same pins with WiFi on CM4, they can't be used at the same time.

Audio Connectors

The PPC-CM4-156 industrial Pi PC features some audio peripherals. It has 1 x 3.5mm audio output jack.

Also, the PPC-CM4-156 industrial Pi PC has a miniature 2W internal speaker for audio reproduction, as well as a small buzzer for alarm/notification sounds.



Audio Connector (enclosed PC version)

PPC-CM4-156 Boot DIP Button

Attention

By plugging in the headphone cable, the internal speaker will be disabled automatically.

Boot DIP Button

The PPC-CM4-156 industrial Pi PC has one button for entering usb download mode, as shown in the figure below.

When booting **with** the button being pressed, the Raspberry Pi will boot from the USB connector. You can use this feature to download the OS software to the internal eMMC. When booting **without pressing** the button, the Raspberry Pi will boot from the internal eMMC.

There is no need to alter the Boot DIP Button during regular operation. However, if you need to reinstall the OS, please refer to the detailed information on how to reflash the OS from the Software Documentation.



Boot DIP Button

Mounting Procedure

The PPC-CM4-156 industrial Pi PC can be mounted with $4 \times M4$ (6mm) screws using the **VESA** (100x100mm or 75x75mm) mount.

The PPC-CM4-156 industrial Pi PC can be mounted with **panel mount** method, enabling simplified installation onto any standard mounting fixture.



Attention

Please make sure the display is not exposed to high pressure when mounting into an enclosure.

You can find detailed information about mounting in the Mount IPC Guide.

PPC-CM4-156 Mechanical Specifications

Mechanical Specifications

CS19108RA4156P

For CS19108RA4156P, the outer mechanical dimensions are $422 \times 271 \times 52.5$ mm (W x L x H).

Disclaimer

This document is provided strictly for informational purposes. Its contents are subject to change without notice. Chipsee assumes no responsibility for any errors that may occur in this document. Furthermore, Chipsee reserves the right to alter the hardware, software, and/or specifications set forth herein at any time without prior notice and undertakes no obligation to update the information contained in this document.

While every effort has been made to ensure the accuracy of the information contained herein, this document is not guaranteed to be error-free. Further, it does not offer any warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document, and no contractual obligations are formed either directly or indirectly by this document.

Despite our best efforts to maintain the accuracy of the information in this document, we assume no responsibility for errors or omissions, nor for damages resulting from the use of the information herein. Please note that Chipsee products are not authorized for use as critical components in life support devices or systems.

Technical Support

If you encounter any difficulties or have questions related to this document, we encourage you to refer to our other documentation for potential solutions. If you cannot find the solution you're looking for, feel free to contact us. Please email Chipsee Technical Support at **support@chipsee.com**, providing all relevant information. We value your queries and suggestions and are committed to providing you with the assistance you require.