



Industrial Displays

PIM-170-C



PN: CS-D170

Revision 1.1

www.chipsee.com

Contents

PIM-170-C	3
1. Product Overview	6
2. Ordering Options	6
3. Specification	7
4. Mounting Procedure	8
5. Mechanical Specifications	8
6. Disclaimer	10
7. Technical Support	10

PIM-170-C

Front View



Rear View



Side View



Product Overview

PIM-170-C (PN: CS-D170) is a 17" industrial display that features a 10-point capacitive touch screen with a resolution of 1280 x 1024 (4:3) pixels and brightness of 250 cd/m². The 3mm tempered glass with black silk-screen ensures the screen is water and steam resistant.

The typical power consumption is $\leq 15\text{W}$, while in standby mode, PIM-170-C uses around $\leq 2\text{W}$, making it ideal for all kinds of applications.

Ordering Options

Most of the Chipsee products can be customized during the ordering process. The product will be shipped with the pre-installed factory defaults if no extra requirements are specified. The table in the [Specification](#) section provides information about the product.

Note

You can order [PIM-170-C](#) from the official [Chipsee Store](#) or from your nearest distributor.

Specification

PIM-170-C			
Backlight	Led	Type of Pen	Fingers, Hands with Gloves, Conductive Stylus
Brightness	250 cd/m ²	Waterproof	Touch surfaces will not be affected by water droplets or steam
Contrast Ratio	1000:1	Calibration	No Calibration Tool
Viewing Angle	Horizontal: 170° / Vertical: 160°	Response Time	7ms to 12ms
Response Time	5ms (GTG)	Connect	1 x USB 2.0 (Type-B)
Display Color	16.7M Colors	Multi Touch Protocol Support	Windows
Display Resolution	1280 x 1024 (4:3)	Operating System	Windows 7/8, Android, Linux
Refresh Frequency	60Hz	Dimensions	385.3 x 317.8 x 47.1mm
Input Resolution	1280 x 1024 (4:3) @ 60Hz	Packaging Size	505 x 460 x 165mm
Connector	VGA / DVI / HDMI	Weight	5000g / 7000g
Built-in Speaker	N/A	Mounting Methods	VESA, MIS-D, 100, C
OSD Control	Button	Power Input	12V 3A DC
OSD Language	English, Chinese	Power Supply	≤ 15W
Glass	3mm Tempered Glass with Black Silk-screen	Standby Power	≤ 2W
Touch Point	10	Work Environment (temp.)	From 0°C to +40°C, 90% RH
Touch Technology	Projecting Capacitance (G+G)	Storage Environment	From -20°C to +60°C, 90% RH
Accessories	Bracket / Power Line / VGA Line / USB Line / Power Adapter		

Table 497 Key Features

The PIM-170-C industrial display supports VESA 100 x 100 mounting pattern with 4 x M4 screws, enabling simplified installation onto any standard VESA mounting rack. Other mounting options might also be supported according to the table in the [Specification](#) section.

Mechanical Specifications

Technical drawing of the supere700 monitor, showing front, side, and rear views with dimensions in millimeters.

Front View Dimensions:

- Overall width: 393.02
- Inner width: 316
- Inner height: 158
- Bottom bezel width: 12.8
- Bottom bezel height: 180
- Bottom bezel depth: 382.2
- Bottom bezel material: 4-m4

Side View Dimensions:

- Height: 42.5
- Depth: 20.8

Rear View Dimensions:

- Overall width: 393.02
- Inner width: 382.2
- Inner height: 338.92
- Bottom bezel width: 169.46
- Bottom bezel height: 135.67
- Bottom bezel depth: 326.4
- Bottom bezel material: 4-m4
- Bottom bezel height: 12.8
- Bottom bezel depth: 314.84
- Bottom bezel material: 4-R11.2B
- Bottom bezel material: 4-R5.5
- Bottom bezel material: Black screen printing

Top View Dimensions:

- Overall width: 100
- Inner width: 75
- Inner height: 37.5
- Bottom bezel width: 160
- Bottom bezel height: 75
- Bottom bezel depth: 30
- Bottom bezel material: 4-R11.2B
- Bottom bezel material: 4-R5.5
- Bottom bezel material: Black screen printing

Bottom View Dimensions:

- Overall width: 393.02
- Inner width: 382.2
- Inner height: 338.92
- Bottom bezel width: 169.46
- Bottom bezel height: 135.67
- Bottom bezel depth: 326.4
- Bottom bezel material: 4-m4
- Bottom bezel height: 12.8
- Bottom bezel depth: 314.84
- Bottom bezel material: 4-R11.2B
- Bottom bezel material: 4-R5.5
- Bottom bezel material: Black screen printing



Figure 1071: Technical Drawing

Disclaimer

This document is provided strictly for informational purposes. Its contents are subject to change without notice. Chipsee assumes no responsibility for any errors that may occur in this document. Furthermore, Chipsee reserves the right to alter the hardware, software, and/or specifications set forth herein at any time without prior notice and undertakes no obligation to update the information contained in this document.

While every effort has been made to ensure the accuracy of the information contained herein, this document is not guaranteed to be error-free. Further, it does not offer any warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document, and no contractual obligations are formed either directly or indirectly by this document.

Despite our best efforts to maintain the accuracy of the information in this document, we assume no responsibility for errors or omissions, nor for damages resulting from the use of the information herein. Please note that Chipsee products are not authorized for use as critical components in life support devices or systems.

Technical Support

If you encounter any difficulties or have questions related to this document, we encourage you to refer to our other documentation for potential solutions. If you cannot find the solution you're looking for, feel free to contact us. Please email Chipsee Technical Support at support@chipsee.com, providing all relevant information. We value your queries and suggestions and are committed to providing you with the assistance you require.