

Industrial PC

PPC-A72-125-C



PN: CS19108R125

Contents

I. PPC-A72-125-C	3
1.1. Product Overview	4
1.2. Ordering Options	5
1.2.1. Operating System	5
1.2.2. Optional Features	6
1.3. Hardware Features	6
1.4. Power Input	7
1.5. Touch Screen	8
1.6. Connectivity	8
1.6.1. DB9 Connectors	8
1.6.2. USB Connectors	9
1.6.3. LAN Connectors	9
1.6.4. WiFi & BT Module	10
1.6.5. 4G/LTE Module	10
1.6.6. Expansion Connector	11
1.7. TF Card Slot	13
1.8. Audio Connectors	13
1.9. HDMI Connector	13
1.10. Power Button	13
1.11. Measurements and Mounting Procedure	14
1.12. 3D Model	14
1.13. Disclaimer	15
1.14. Technical Support	15

PPC-A72-125-C




Front View



Rear View

PPC-A72-125-C Product Overview



Side View 1



Side View 2

Product Overview

The Cortex $^{\$}$ -A72/53 series PPC-A72-125-C (PN: CS19108R125) is a high-quality industrial panel PC. It features a 12.5" ten-point capacitive touch screen with a resolution of 1920 x 1080 pixels and brightness of 250 cd/m 2 .

Key Applications

- Human Machine Interface HMI
- Mobile Applications
- Video Processing

PPC-A72-125-C Ordering Options

- Machine Learning
- Video Gaming
- Process Control
- Process Monitoring
- ATM...

It is available both as an embedded solution and as a device hosed in an aluminum casing with bezels, thus facilitating different installation options:

- Installation on an industrial cabinet
- Integration with the existing equipment

The PPC-A72-125-C Industrial Panel PC is based around the powerful CS-SOM-RK3399 System on Module (SoM), powered by the Rockchip RK3399 low-power processor which integrates a dual-core Cortex[®]-A72 and a quad-core Cortex[®]-A53 with a separate NEON coprocessor.

The RK3399 supports multi-format video decoders and has a high-performance dual-channel external memory interface (DDR3/DDR3L/LPDDR3/LPDDR4) capable of sustaining demanding memory bandwidths. It also provides a complete set of peripheral interfaces.

Ordering Options

Chipsee products can be customized during the ordering process. The product will be shipped with the pre-installed factory defaults if no extra requirements are specified. The table in the Hardware Features section provides information about the default options bundled with the product.



You can order The PPC-A72-125-C Industrial Panel PC from the official **Chipsee Store** or from your nearest distributor.

Operating System

This product comes with a pre-installed OS of your choice. Please see the list below for the supported OSes, which can be also obtained from the Software Documentation section, along with the detailed installation instructions.

- Chipsee Linux*
- Android 7.1
- Debian 10

PPC-A72-125-C Optional Features

- * Chipsee Linux is based on buildroot that has been integrated with:
 - 1. Chipsee Hardware Test Application
 - 2. An initialization script for GPIO/Buzzer/Audio
 - 3. Multiple libraries, such as the libQt5Sql to develop Qt application with SQL
 - 4. Various packages, such as the ntfs-3g to use NTFS file system



Warning

The Software Documentation section provides a detailed instruction on how to install different OSes on your own. However, bear in mind that Chipsee can't take the responsibility of inadequate installation procedure. If you "brick" your device, please contact Chipsee Technical Support at support@chipsee.com for further assistance

Optional Features

The PPC-A72-125-C Industrial Panel PC does not include 4G/LTE module by default. The module is optional and can be selected at the Chipsee store during the ordering process.



Warning

Installation, repair, and maintenance tasks should be performed by trained personnel only. Chipsee does not bear any responsibility for damage caused by inadequate handling of the product.

Hardware Features

The PPC-A72-125-C Industrial Panel PC offers a broad range of performance and connectivity options for scalable integration, providing expandability to meet future needs. Some of the key features are listed in the table below.

PPC-A72-125-C				
СРИ	Rokchip RK3399, Dual-core Cortex-A72 (1.8GHz), Quad-core Cortex-A53 (1.4GHz)			
RAM	4GB DDR3			
еММС	16GB			
Storage	TF Card, Supports up to 32GB SDHC			
Display	12.5" LCD, 1920 x 1080, High Brightness: 250 cd/m ²			
Touch	10-point capacitive touch screen			
USB	4 x USB 2.0 HOST, 1 x USB 3.0 HOST, 1 x USB Type-C			
LAN	1 x RJ45, GbE			
Audio	3.5mm Audio Out Connector, 2W Internal Speaker			
Buzzer	Yes			

PPC-A72-125-C Power Input

PPC-A72-125-C				
RTC	Yes			
RS232	5 x RS2321			
RS485	2 x RS485 (4 at most, 1 debug port)1			
GPIO	8 Channels			
WiFi/BT	Integrated WiFi/BT Module			
НДМІ	1 x HDMI			
4G/LTE	Supported, Optional			
Power Input	From 15V to 36V			
Current at 15V	800mA Max			
Power Consumption	12W Typical			
Working Temperature	From 0°C to +70°C			
OS	Android 7.1			
Dimensions	306 x 187 x 37mm			
Weight	1700g			
Mounting	VESA & Panel methods			

Table 87 Key Features

1(1,2)This product has 7 x UART channels in total. The default configuration is 5 x RS232 and 2 x RS485. UART can be swapped between RS232 and RS485 modes easily, so if you need different RS232/RS485 configuration, please get in touch with the Chipsee Technical Support at **support@chipsee.com**

Power Input

The PPC-A72-125-C Industrial Panel PC can be powered by a wide range of input voltages: From 15V to 36V DC. The power input connector is a **3-pin, 3.81mm terminal**. The polarity and the pinout is clearly marked on the housing of the product as shown on the figure below.




Figure 423: Power Input

PPC-A72-125-C Touch Screen

Note that the "+" sign represents the positive power input, and it is printed both at the casing and as a silk-screen on a PCB of the embedded version. The "-" terminal is shorted to the ground.

Power Input Definition				
Pin Number	Definition	Description		
Pin 1	Positive Input	DC Power Positive Terminal		
Pin 2	Negative Input	DC Power Negative Terminal		
Pin 3	Ground	Power System Ground		

Table 88 Power Connector



Note

The system ground "**G**" is connected to power negative "-" on board.

Touch Screen

The PPC-A72-125-C Industrial Panel PC uses a 10-point capacitive touch screen.



Attention

A capacitive touch screen is susceptible to power noise and Electromagnetic Radiation (EMR). It may cause LCD ripples or even capacitive touch malfunction. If using a capacitive multi-touch test application, you might notice the touch points float erratically across the display. There are several solutions to this problem:

- 1. Use a high-quality Power Adapter Unit (PSU) with low EMR. You can also provide power from a battery.
- 2. Make sure that the PPC-A72-125-C Power Input connector (pin 3) is properly connected to the Power System Ground to provide sufficient EMI shielding and eliminate the problem entirely.
- 3. Bad GND problem can also be confirmed by touching pin 3 of the Power Input connector with one hand while operating the capacitive touch screen with the other hand. In this case, the operator's body acts as the Power System Ground.

Connectivity

There are many connectivity options available on the PPC-A72-125-C industrial PC. It has $4 \times 4 \times 1000$ HOST, 1×1000 HOST, 1×1000 HOST, 1×1000 Type-C, 1×1000 RJ45, GbE Ethernet connector, and 6×1000 Connectors.

DB9 Connectors

The PPC-A72-125-C Industrial Panel PC has 6 x DB9 connectors that are configured as RS232 by default as shown on the figure below. You can configure **COM3/COM4/COM5/COM6** as

PPC-A72-125-C USB Connectors

RS485. If you need different RS232/RS485 configuration, contact the Chipsee Technical Support at **support@chipsee.com**.



Figure 424: DB9 Connectors

USB Connectors

There are 4 x dual **USB 2.0 HOST connectors** onboard, as shown on the figure below.



Figure 425: USB 2.0 HOST Connectors

There is also 1 x **USB 3.0 HOST connector** and 1 x **USB Type-C connector**, as shown below.



Figure 426: USB 3.0 HOST Connector



Figure 427: USB Type-C Connector

LAN Connectors

LAN (RJ45) connector provides Ethernet connectivity over standardized Ethernet cables as shown the figure below. The integrated Ethernet interface supports up to 1 Gbps data throughput.

PPC-A72-125-C WiFi & BT Module



Figure 428: RJ45 LAN Connector



Use CAT5 or better cables to achieve full data throughput over maximum distance defined by the 1000BASE-T standard (100m).

WiFi & BT Module

The PPC-A72-125-C Industrial Panel PC is equipped with the popular **Realtek RTL8723 WiFi/BT module** that supports BT/BLE 4.0 (with backward compatibility), as well as 802.11bgn 2.4 GHz Wireless LAN (WLAN).

The product includes an SMA connector for an external WiFi/BT antenna, as illustrated in the figure below.



Figure 429: WiFi+BT Antenna

4G/LTE Module

The PPC-A72-125-C Industrial Panel PC is equipped with a **mini-PCle connector** that can connect to a 4G/LTE module. The customer will also need a SIM Card Holder and a 4G/LTE Antenna Connector to ensure 4G/LTE works on the PPC-A72-125-C.

PPC-A72-125-C Expansion Connector



Figure 430: SIM Card Holder



Attention

The product does not come shipped with the 4G/LTE module by default.

Expansion Connector

The PPC-A72-125-C Industrial Panel PC has 1 x **Expansion Connector** (closed by default), as shown on the figure below. This connector has connected to isolated GPIO signals. The table below gives details about the definition of every Pin.



Figure 431: Expansion Connector

PPC-A72-125-C Expansion Connector



Isolated GPIO reduced schematic

Expansion Connector Pinout				
PIN	Function	PIN	Function	
1	VDD, Isolated Power Input (+5V – +24V)	2	GND_ISO	
3	OUT1	4	OUT2	
5	OUT3	6	OUT4	
7	IN1	8	IN2	
9	IN3	10	IN4	

Table 89 Expansion Connector Pinout



Warning

Since the PCB traces of the port are connected to the processor directly, be careful not to cause electrostatic discharge or over voltage on the pins, as it may damage the processor. Take all the necessary precautions while working with electrostatic-sensitive equipment.

PPC-A72-125-C TF Card Slot

TF Card Slot

The PPC-A72-125-C Industrial Panel PC features 1 x **TF Card (micro SD) slot**. It can address up to 32GB of memory.



Figure 432: TF (micro SD) Card Slot



The product does not come shipped with the TF Card by default.

Audio Connectors

The PPC-A72-125-C Industrial Panel PC features some audio peripherals, as well. It has 1 x **3.5mm audio output jack**.



Figure 433: Audio Out Connector

HDMI Connector

The PPC-A72-125-C Industrial Panel PC is equipped with 1 x **HDMI connector**. The HDMI connector allows connecting an additional (external) monitor. HDMI output resolution can be configured by the software.



Figure 434: HDMI Connector

Power Button

The PPC-A72-125-C Industrial Panel PC has a power button, as shown on the figure below. You can use the button to power ON or OFF the industrial PC.



Measurements and Mounting Procedure

The outer mechanical dimensions of PPC-A72-125-C are 306 x 187 x 37mm (W x L x H).

The PPC-A72-125-C Industrial Panel PC can be mounted with 8 x M4 screws or 4 x M4 screws using the VESA (100x100cm or 75x75cm) and Panel mounting methods, enabling simplified installation onto any standard mounting fixture.




Figure 436: Mounting Method



Please make sure the display is not exposed to high pressure when mounting into an enclosure.

You can find detailed information about mounting in the Mount IPC Guide.

3D Model

PPC-A72-125-C 3D model can be viewed in the online doc in a web browser, if you are reading from the **PDF** version, please visit the online doc.

PPC-A72-125-C Disclaimer

Disclaimer

This document is provided strictly for informational purposes. Its contents are subject to change without notice. Chipsee assumes no responsibility for any errors that may occur in this document. Furthermore, Chipsee reserves the right to alter the hardware, software, and/or specifications set forth herein at any time without prior notice and undertakes no obligation to update the information contained in this document.

While every effort has been made to ensure the accuracy of the information contained herein, this document is not guaranteed to be error-free. Further, it does not offer any warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document, and no contractual obligations are formed either directly or indirectly by this document.

Despite our best efforts to maintain the accuracy of the information in this document, we assume no responsibility for errors or omissions, nor for damages resulting from the use of the information herein. Please note that Chipsee products are not authorized for use as critical components in life support devices or systems.

Technical Support

If you encounter any difficulties or have questions related to this document, we encourage you to refer to our other documentation for potential solutions. If you cannot find the solution you're looking for, feel free to contact us. Please email Chipsee Technical Support at **support@chipsee.com**, providing all relevant information. We value your queries and suggestions and are committed to providing you with the assistance you require.