RV College of Engineering®

Go, change the world®

Implement configurable First-order and MASH 1-1 Digital Delta-Sigma Modulator (DDSM) blocks for fractional frequency command generation.

Phase I Presentation

Amrut R **USN: 1RV24EC025**
Anurag **USN: 1RV24EC031**
Chirag R Karanth **USN: 1RV24EC054**

Guide Name:
Designation:
Department of Electronics and Communication Engineering

Outline

- Introduction
- Problem statement
- Objectives
- Methodology with Design specifications
- Tools used

Introduction

- A Digital Delta-Sigma Modulator (DDSM) is a digital hardware block used inside Fractional-N Phase Locked Loops (PLLs). Instead of generating a constant integer divide ratio, it generates a sequence of integers whose average value equals the desired fractional value.

Problem Statement

- State the problem definition

Objectives

- List the objectives of the project (3 to 4 objectives)

➢ Methodology with Design specifications

- Discuss about the methodology you identified to execute the objectives
- **Methodology** is a system of practices, techniques, procedures, and rules used to execute the project
- Discuss with your guide to finalize the methodology
- You can present in the form of a flow diagram

Design Methodology

- Keep your flow diagram here

Details of Software / Hardware

- Present the details of the software and hardware requirements for your project
- If expenses are there, present a budget estimate also

Thank You