


REBAR CUTTER DAIA SAW

SDC-32D2B



Applied rebar size: D19-D32

Power: 230V

Approx Size: L 447 X H 216 X W 202 mm

Approx Weight: 8 kg




Carrying case

Easy to Carry, Easy to Store!
Best for Professionals, Best for Starters too!




HYDRAULIC PUMP SET

DSP-120WFNA



B-2885 : PUMP CASE

WEIGHT : 5kg TOTAL GROSS WEIGHT : 24kg



#	Item code	Item name
1	RW-0763D	RAM CYLINDER FOR D19-D32 DIA=36 NEW TYPE WELDING BASE
	BH133600	HIGH PRESSURE OIL HOSE (6 METER)
	B-0571	MALE COUPLER WITH BALL FOR RAM CYLINDER/DSP PUMP
2	SS-01	SAKAGUCHI TYPE GAS MIXTURE TUBE WT-03L
	SVS-01	SUPER VALVE FOR SS-01 GAS MIXTURE TUBE
3	BS01E5	ON/OFF SWITCH PISTOL SEESAW TYPE FOR GAS MIXTURE TUBE
4	BC07N5	OPERATION CORD (ELECTRIC CORD) 7 METERS
5	----	OPERATION MANUAL
6	DSP-120WFN	HYDRAULIC PUMP DSP-120W 220V/50HZ SPEC
7	B-2885	PUMP CASE

*Specifications are subject ot change without notice.

ELECTRIC MOTOR DRIVE PUMP

For Gas Pressure Welding




MODEL	DSP-120WFN
PRESSURE RANGE	D19 - D51 (REBAR DIAMETER) SD345 - SD490 (CLASS of REBAR) Number is yield strength.
MOTOR & OUTPUT	SINGLE PHASE AC COMMUTATOR ELECTRIC MOTOR 300W
VOLTAGE	220V / 50Hz INPUT 540W 2.6A
PUMP TYPE	HIGH & LOW PRESSURE 2 STAGE AUTO CHANGE-OVER FIX CAPACITY TYPE
PRESSURE ADJUST RANGE	0 - 60 Mpa
OIL FLOW	LOWER : 2.0 liter / min. @0.35 MPa HIGH : 0.21 liter / min. @50 MPa
OIL TANK CAPACITY	1.2 liter
OPTION	OPERATION SWITCH, POWER CORD, OIL HOSE
BOUNDARY DIMESIONS	H313 W148 D296
MASS	10.0 kg


*Specifications are subject to change without notice.

SBD Ring burners


For acetylene gas




SBD-32D



"Kangen-en"
Reducing flame




"Chusei-en"
Neutral flame



Item code	Rebar size	Chips	a	b	c	d	f	g	h	"I" Thickness	Weight (kg)
SBD-19	D16~D19	8	109	53	70	12	175	70	33	2	0.29
SBD-22D	D19~D22	8	109	63	70	12	175	70	42	2	0.32
SBD-25D	D25	8	114	68	70	12	182	74	45	2	0.32
SBD-29D	D29	10	119	73	70	12	189	78	46	2	0.34
SBD-32D	D32	10	124	78	70	12	196	80	49	2	0.34
SBD-35D	D35	12	134	85	87	12	212	84	50	2	0.38
SBD-38D	D38	14	139	89	87	12	219	88	52	2	0.38
SBD-41D	D41	16	149	99	87	12	234	92	59	2	0.40
SBD-51D	D51	18	164	114	95	12	256	100	66	2	0.43

* Specifications are subject to change without notice.

Gas mixture & Super valve




SVS-01
SUPER VALVE FOR SS-01 GAS MIXTURE TUBE



SS-01
SAKAGUCHI TYPE GAS MIXTURE TUBE

Operation switch




BS01E5
PISTOL SEESAW TYPE ON/OFF SWITCH
FOR GAS MIXTURE TUBE


* Specifications are subject to change without notice.

RAM CYLINDER




For rebar welding base



	RW-0763D	RW-0860D	RW-1480D
Diameter of hydraulic cylinder	36 mm	40 mm	51 mm
Cross section of cylinder	10.17 cm ²	12.56 cm ²	20.42 cm ²
Stroke of cylinder	63 mm	60 mm	80 mm
Mass	2.0 kg	2.5 kg	4.3 kg
A	207 mm	232 mm	265 mm
B	20 mm	21 mm	24 mm
C	13.5 mm	17 mm	18 mm
φD1	49 mm	53.5 mm	64 mm
φD2	47.4 mm	47.5 mm	55.5 mm
φD3	20 mm	20 mm	25 mm
φD4	12.8 mm	17 mm	18 mm
φd	36 mm	40 mm	51 mm



REBAR WELDING BASE



ROUND HEAD FIXING BOLT



**** EZ: Export version comes with Z-0304B FIXING BOLT which is an optional part for SD-51EC**

MODEL	REBAR SIZE	A	B	C	D	E	F	G	ϕ d1	ϕ d2	MASS
SD-19EZ	D12 - D18	317	147	50	70	34	54	134.5	50	65	4.8 kg
SD-25EZ	D19 - D25	364	168	63	70	34	66	146.7	50	65	6.8 kg
SD-32EZ	D19 - D32	380	170	70	70	39	70	148	52	65	8.4 kg
SD-38EZ	D32 - D41	446	200	90	66	50	87	179	60	70	14.0 kg
SD-51EC	D41 - D51	480	260	110	82	59	95	200	77	82	23.8 kg

* Specifications are subject to change without notice.

ACCESSORY For Gas pressure welding

High pressure oil hose



H133600 HIGH PRESSURE OIL HOSE, length 6 meters

Coupler



B-0571
Male

B-0570
Female

Operation cord



BC07N5 OPERATION CORD (ELECTRIC CORD) 7 meters

Metal socket



751-NJC34-RM
Female

751-NJC34-PF
Male


Ratchet wrench



Best for fastening clamp bolts and fixing bolts!!


Z-2620A RATCHET WRENCH RN21A FOR
FIXING BOLT (WELDING BASE)

* Specifications are subject to change without notice.



ONE TOUCH COUPLER DETAILS

Gas cylinder setting




No	Item code	Item
1	840-90P20-00	One touch coupler for gas mixture tube, acetylene
2	840-90P10-00	One touch coupler for gas mixture tube, oxygen
3	SKANS122-603	One touch coupler for gas hose, oxygen
4	SKANS122-604	One touch coupler for gas hose, acetylene
5	130-M0000-00	Hose band
6	147-SGV10-00	One touch coupler for gas gauge, oxygen
7	840-9AP10-00	Coupler AP-1 used with SGV10, oxygen
8	SKANS122-607	Oxygen gas flow gauge
9	147-SGV20-00	One touch coupler for gas gauge, acetylene
10	840-9AP20-00	Coupler AP-2 used with SGV20, acetylene
11	SKANS122-606	Acetylene gas flow gauge with flash back arrester
12	SKANSA08-056	Acetylene/oxygen twin hose 20 meteers

*Specifications are subject to change without notice

BENDING TEST MACHINE FOR D38

MODEL : SBT-38C



* Specifications are subject to change without notice.