Transformers from Scratch: Mixture of Experts, Pretraining Optimizers, and Autoregressive Decoding

Name: Chiranjeevi Kumaravadivel **Roll Number:** 2024101107
Advanced Natural Language Processing (ANLP) — Monsoon 2026
International Institute of Information Technology, Hyderabad (IIIT-H)

Abstract

This report details an architectural and empirical investigation of three core components in neural language model design: (1) **Sparse Mixture of Experts (MoE)** feed-forward layers evaluated across five capacity-controlled ablations on non-romanized translation; (2) **First- and Second-Order Pretraining Optimizers from Scratch** implemented strictly via `torch.optim.Optimizer` subclassing; and (3) **Autoregressive Decoding Strategies** built exclusively on top of `model.forward()` on `EleutherAI/Pythia-160M` using 1,000 narrative stories from `hamishivi/ROCStories`. We present analytical derivations for load-balancing regularizers, orthogonal matrix polar iterations, and length-normalized beam search, complemented by empirical validation on GPU hardware. All code, checkpoints, and logs are publicly available.

1 Problem Formulation and Datasets

Our experimental workflow investigates model architecture, optimization dynamics, and inference generation across three distinct datasets:

1. Multilingual Translation (`belumind/en-vi-ja-curated-500k-triplets`): We train a causal decoder-only model to translate Vietnamese and Japanese texts into English. A key challenge is that input texts are non-romanized: Japanese uses Kanji ideograms and Kana syllabaries, while Vietnamese utilizes multi-accent Latin diacritics. Standard character tokenizers produce severe out-of-vocabulary (OOV) rates, while standard word tokenizers result in intractable vocabularies. We train a custom Byte-Level BPE tokenizer with a vocabulary size of 16,384, mapping arbitrary UTF-8 byte streams into compact subwords without OOV tokens. Each triplet generates two directed training pairs (Vietnamese–English and Japanese–English), prepended with language control tokens `<vi>` and `<ja>`.

2. Pretraining Dynamics Benchmark (`browndw/human-ai-parallel-corpus`): To analyze pretraining optimizer dynamics (replicating Figure 2 of Wen et al., 2025), a dense causal Transformer is trained on next-token prediction across 1.0× dataset tokens. Validation cross-entropy loss and test BLEU are evaluated at intervals of 0.1× dataset tokens to measure convergence rates per unit of processed data.

3. Narrative Story Continuation (`hamishivi/ROCStories`): To evaluate decoding strategies without high-level library wrappers, 1,000 four-sentence narrative prompts are passed to `EleutherAI/Pythia-160M`. Each strategy generates fifth-sentence completions, measuring statistical perplexity, token accuracy, BLEU-4, and runtime latency.

2 Common Model Architecture

In compliance with assignment guidelines, all Transformer components are implemented from fundamental PyTorch tensor operations. The baseline model is a causal decoder-only Transformer

with $D_{\text{model}} = 256$, 8 attention heads, 4 layers, and a context window of $N_{\text{ctx}} = 256$.

Causal Multi-Head Attention: Scaled dot-product attention computes query-key similarity scaled by head dimension $d_k = D_{\text{model}}/H = 32$:

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}} + M\right)V \tag{1}$$

where the causal mask $M_{ij} = -\infty$ for $j > i$ prevents positions from attending to future tokens.

Pre-Layer Normalization and Weight Tying: Every sub-layer applies Pre-LayerNorm to stabilize gradient flow through deep residual paths:

$$x^{(l)} = x^{(l-1)} + \text{Attention}(\text{LN}(x^{(l-1)})), \quad x^{(l)} = x^{(l)} + \text{FFN}(\text{LN}(x^{(l)})) \tag{2}$$

Input embedding weights are tied with the final unembedding projection matrix ($W_{\text{unembed}} = W_{\text{embed}}^T$), reducing parameter count and tying semantic representations.

3 Task 1: Mixture of Experts (MoE) Architecture

The standard dense feed-forward network (FFN) applies a two-layer MLP with intermediate expansion $D_{\text{model}} \to D_{\text{ff}} \to D_{\text{model}}$ ($256 \to 1024 \to 256$) and GELU activation:

$$\text{FFN}_{\text{dense}}(x) = \text{GELU}(xW_1 + b_1)W_2 + b_2 \tag{3}$$

To investigate routing sparsity and capacity scaling, we develop a drop-in MoE module supporting five architectural variants.

Table 1: Architectural FFN configurations and capacity accounting ($D_{\text{model}} = 256, D_{\text{ff}} = 1024$).

Config.	Variant Description	Experts (N)	Active (k)	Expert Dim (d_{ff})	Total Params	Active Params
C1	Dense Baseline	1	1	1024	8,900,608	8,900,608 (100%)
C2	MoE Top-1	4	1	256	8,911,360	6,542,848 (73.5%)
C3	MoE Top-2	4	2	256	8,911,360	7,332,352 (82.4%)
C4	Shared + Routed MoE	1+3	1+1	256	8,909,824	7,330,816 (82.4%)
C5	Matched-Active MoE	4	2	512	12,063,232	8,908,288 (100.08%)

3.1 Architectural Configurations

- **C1 (Dense Baseline):** Standard two-layer MLP with hidden dimension $D_{\text{ff}} = 1024$.
- **C2 (MoE Top-1):** 4 experts with reduced width ($d_{\text{ff}} = 256$), activating exactly 1 expert per token.
- **C3 (MoE Top-2):** 4 experts ($d_{\text{ff}} = 256$), activating 2 experts per token with weighted combining.
- **C4 (Shared + Routed MoE):** 1 shared expert ($d_{\text{ff}} = 256$) always active on all tokens, combined with 3 routed experts (1 active per token). This provides an invariant contextual baseline while allowing specialist adaptation.
- **C5 (Matched-Active MoE):** 4 experts ($d_{\text{ff}} = 512$) with Top-2 routing, sized such that total active FFN parameters match the dense baseline.

3.2 Mathematical Capacity and Parameter Parity

To conduct a fair scientific ablation, model capacity must be strictly controlled:

- **Total Parameter Parity (C1 to C4):** A dense FFN contains $2D_{\text{model}}D_{\text{ff}} + D_{\text{ff}} + D_{\text{model}} = 525,568$ parameters per layer. By setting each expert's intermediate width to $d_{\text{expert}} = D_{\text{ff}}/4 = 256$, four experts collectively possess $4 \times (2D_{\text{model}}d_{\text{expert}} + d_{\text{expert}} + D_{\text{model}}) = 526,336$ parameters. Adding the linear router projection matrix ($D_{\text{model}} \times N = 256 \times 4 = 1,024$ weights), total parameters differ from the dense baseline by only **+0.12%**, ensuring differences stem from routing dynamics rather than parameter scale.
- **Active Parameter Parity (C5):** With $k = 2$ active experts per token, matching the dense FFN width ($D_{\text{ff}} = 1024$) requires each expert to have $d_{\text{expert}} = D_{\text{ff}}/2 = 512$. This provides active capacity parity within **+0.08%** (8,908,288 vs. 8,900,608), enabling direct comparison of sparse compute efficiency against dense execution.

3.3 Router Dynamics and Switch Auxiliary Load-Balancing Loss

A linear router projects hidden representations x to expert logits $H(x) = xW_g$. Gating weights are calculated via softmax over expert logits:

$$P_i(x) = \frac{\exp(H(x)_i)}{\sum_{j=1}^{N} \exp(H(x)_j)} \tag{4}$$

Standard softmax gating exhibits a known vulnerability: **representation collapse**. Early in training, minor initialization variance causes one expert to receive slightly lower loss. The router responds by routing more tokens to it, starving other experts of gradient updates and leaving them untrained.

Task-level cross-entropy cannot prevent this because starving an expert incurs no task loss penalty. We address this by incorporating the **Switch Transformer / GShard auxiliary loss**:

$$\mathcal{L}_{\text{aux}} = \alpha \cdot N \sum_{i=1}^{N} f_i \cdot P_i, \quad f_i = \frac{1}{T} \sum_{t=1}^{T} \mathbb{I}(\text{token } t \to \text{expert } i), \quad P_i = \frac{1}{T} \sum_{t=1}^{T} P_i(x_t) \tag{5}$$

where $\alpha = 0.01$ is the penalty weight, f_i is the empirical token fraction dispatched to expert i, and P_i is the average routing probability. Crucially, P_i is smoothly differentiable while f_i is non-differentiable (treated as a constant). Backpropagation adjusts router weights W_g to minimize non-uniformity, achieving an optimal loss when $f_i = P_i = 1/N$ (uniform load) without interfering with translation task gradients.

4 Task 2: Custom Optimizers from Scratch

In strict accordance with guidelines, all optimizers were implemented strictly by subclassing `torch.optim.Optimizer` without importing predefined PyTorch optimizer modules. We implemented one optimizer from each of the four categories from Wen et al. (2025), plus the Sophia second-order bonus:

4.1 Category 1: Decoupled Weight Decay (CustomAdamW)

Standard L2 regularization adds $\lambda\theta$ directly to the gradient g_t, which is subsequently scaled by $\sqrt{v_t}$. Consequently, weights with large gradients receive attenuated regularization, while sparse weights are overly decayed. Decoupled weight decay separates parameter shrinkage from adaptive variance scaling:

$$\theta_t = \theta_{t-1} - \eta\lambda\theta_{t-1} \tag{6}$$

$$m_t = \beta_1 m_{t-1} + (1-\beta_1) g_t, \quad v_t = \beta_2 v_{t-1} + (1-\beta_2) g_t^2 \tag{7}$$

$$\theta_t = \theta_t - \eta \frac{\hat{m}_t}{\sqrt{\hat{v}_t} + \epsilon}, \quad \text{where } \hat{m}_t = \frac{m_t}{1-\beta_1^t},\ \hat{v}_t = \frac{v_t}{1-\beta_2^t} \tag{8}$$

4.2 Category 2: Variance-Reduced Nesterov Momentum (CustomAdan)

Adan accelerates convergence by incorporating gradient difference terms ($g_k - g_{k-1}$) as finite-difference approximations to the Hessian-vector product, dampening high-frequency oscillations:

$$v_k = (1-\beta_2)v_{k-1} + \beta_2(g_k - g_{k-1}), \quad m_k = (1-\beta_1)m_{k-1} + \beta_1 g_k \tag{9}$$

$$n_k = (1-\beta_3)n_{k-1} + \beta_3[g_k + (1-\beta_2)(g_k - g_{k-1})]^2 \tag{10}$$

$$\theta_k = \frac{\theta_{k-1} - \eta\frac{\hat{m}_k + (1-\beta_2)\hat{v}_k}{\sqrt{\hat{n}_k}+\epsilon}}{1+\eta\lambda} \tag{11}$$

4.3 Category 3: Memory-Efficient Sign Momentum (CustomLion)

Standard adaptive optimizers maintain two state buffers per parameter (m_t, v_t), requiring 8 bytes/param in float32. Lion completely discards the second-moment buffer v_t, tracking solely momentum m_t and using coordinate-wise signs for parameter updates:

$$c_t = \beta_1 m_{t-1} + (1-\beta_1)g_t \tag{12}$$

$$\theta_t = \theta_{t-1} - \eta(\text{sign}(c_t) + \lambda\theta_{t-1}), \quad m_t = \beta_2 m_{t-1} + (1-\beta_2)g_t \tag{13}$$

This reduces optimizer state memory by exactly **50%**. The sign operation acts as uniform step quantization, serving as an effective gradient noise regularizer.

4.4 Category 4: Matrix-Based Polar Decomposition (CustomMuon)

AdamW treats parameters as independent 1D scalars, ignoring the linear algebraic structure of 2D weight matrices $W \in \mathbb{R}^{d_{\text{out}} \times d_{\text{in}}}$. Muon computes a polar decomposition via a 5-step quintic Newton-Schulz polynomial iteration to map the momentum matrix to the nearest orthogonal matrix:

$$M_t = \mu M_{t-1} + G_t, \quad X_0 = \frac{M_t}{\|M_t\|_F} \tag{14}$$

$$X_{k+1} = X_k(aI + bX_k^T X_k + c(X_k^T X_k)^2), \quad (a,b,c) = (3.4445, -4.7750, 2.0315) \tag{15}$$

Because orthogonal transformations preserve Euclidean norms ($\|Ux\|_2 = \|x\|_2$), Muon updates act as pure rotations, preventing representation collapse and gradient explosion in deep attention projections. 1D biases and embeddings fall back to decoupled AdamW.

4.5 Bonus Category: Second-Order Diagonal Curvature (CustomSophia)

Sophia incorporates diagonal Hessian estimates h_t with coordinate clipping bound $\rho = 0.04$, preventing destructive parameter leaps across ill-conditioned loss ravines:

$$\theta_t = \theta_{t-1} - \eta \cdot \text{clip}\left(\frac{m_t}{\max(h_t, \gamma)}, -\rho, \rho\right) - \eta\lambda\theta_{t-1} \tag{16}$$

5 Task 3: Autoregressive Decoding Strategies from Scratch

All generation algorithms were implemented strictly using `model.forward()` without calling `model.generate()` on `EleutherAI/Pythia-160M`:

- **Greedy Decoding:** Deterministically chooses the highest-probability token: $x_t = \arg\max_{v \in V} \log P(v \mid x_{<t})$.
- **Top-k Sampling ($k = 40, T = 0.8$):** Truncates logits to the top k candidates, re-normalizes with temperature T, and samples from the categorical distribution.

- **Top-p (Nucleus) Sampling ($p = 0.90, T = 0.8$):** Dynamically isolates the smallest set $V^{(p)}$ whose cumulative probability mass satisfies $\sum_{v \in V^{(p)}} P(v \mid x_{<t}) \geq p$, setting excluded logits to $-\infty$.
- **Beam Search ($B \in \{1, 2, 4\}$):** Tracks B candidate hypotheses with length normalization:

$$\text{Score}(h) = \frac{\sum_{t=1}^{T} \log P(x_t \mid x_{<t})}{\left(\frac{5+T}{6}\right)^{\alpha}}, \quad \alpha = 0.6 \tag{17}$$

  The length penalty prevents the search from favoring unnaturally short sequences, as joint log-probabilities monotonically decrease with length.

6 Evaluation Metrics and Measurement Framework

To ensure precise interpretation of results, our evaluation relies on the following standard NLP metrics:

- **Perplexity (PPL):** The exponentiated cross-entropy loss, $\text{PPL} = \exp(\mathcal{L})$. It represents the effective branching factor, or the number of equally likely tokens between which the model is uncertain. Lower perplexity denotes a more confident, accurate model.
- **BLEU Score (Papineni et al., 2002):** Evaluates machine translation and generation quality by computing precision over modified n-grams (1-gram through 4-gram) against ground-truth references, multiplied by a brevity penalty $\text{BP} = \min(1, \exp(1 - r/c))$. Higher BLEU is better, with scores above 20 indicating coherent semantic alignment.
- **Next-Token Accuracy (%):** The percentage of generated tokens that match the exact ground-truth token at the same sequential position.
- **Routing Entropy:** Measures expert dispatch uniformity, defined as $H = -\sum_{i=1}^{N} f_i \log f_i$. Maximum entropy ($\log 4 \approx 1.386$) indicates perfect load balancing across all 4 experts.

7 Empirical Results and Comparative Analysis

7.1 MoE Translation Performance and Routing Specialization

Table 2: Empirical translation results on `belumind/en-vi-ja-curated-500k-triplets` (Colab Pro GPU).

Configuration	Active Gating	Val Loss	Val Perplexity	BLEU	Routing Entropy	Active Compute
Dense Baseline	1 of 1 (100%)	2.882	17.84	0.0160	N/A	100% (Baseline)
MoE Top-1	1 of 4 (Top-1)	2.962	19.34	0.0158	1.32	73.5% (-26.5%)
MoE Top-2	2 of 4 (Top-2)	2.964	19.37	0.0114	1.36	82.4% (-17.6%)
Shared + Routed MoE	1 Shared + 1 of 3	2.957	19.23	0.0002	1.35	82.4% (-17.6%)
Matched-Active MoE	2 of 4 (Doubled)	2.937	18.85	0.0160	1.37	100.08% (+0.08%)

As shown in Figure 1, early layers display clear language specialization: Expert 0 handles 68% of Vietnamese tokens, while Expert 2 captures 72% of Japanese tokens. In upper layers, routing distributes uniformly (24–26% per expert), demonstrating that lower layers specialize in non-romanized orthography, whereas deeper layers converge toward shared English semantics.

7.2 Pretraining Optimizer Dynamics (Figure 2 Replication)

As shown in Figure 2 and Table 3, **CustomMuon** and **CustomAdan** achieved superior loss descent compared to AdamW. Muon's polar updates maintain transformation spectrum bounds, while Adan's gradient difference terms dampen oscillations. **CustomLion** attained near-AdamW performance while cutting optimizer state memory in half.




Figure 1: Layer-wise expert routing heatmap on Vietnamese vs. Japanese translation inputs.




Figure 2: Validation loss and test BLEU across dataset token intervals (Figure 2 replication).

7.3 Autoregressive Decoding Benchmark (1,000 ROCStories Evaluations)

Mathematical Equivalence Proof ($B = 1$ vs. Greedy): When $B = 1$, the candidate pool size is 1, and hypothesis pruning simplifies to $\arg\max_v \log P(v \mid x_{<t})$. Our empirical test verifies that Beam-1 and Greedy yield **100.0% identical token sequences, identical perplexity (2.80), and identical accuracy (7.19%)**.

Beam Search Time Complexity Proof: Generating T tokens with beam width B requires evaluating B sequences through the model:

$$\mathcal{O}\Big(B \cdot T \cdot \text{Cost}(\text{Forward}) + B \cdot \log(B \cdot V)\Big) \approx \mathcal{O}(B \cdot T \cdot \text{Cost}(\text{Forward})) \tag{18}$$

Execution times on 1,000 stories confirm exact linear scaling ($R^2 > 0.999$): $B = 1$ took 475.3s, $B = 2$ took 918.0s (1.93x), and $B = 4$ took 1804.5s (3.80x).

Qualitative Narrative Analysis (`raw_generations.json`):

- **Prompt:** *Marcus was excited to try out for the basketball team. He practiced his jump shots every day after school.*
- **Greedy:** *He made the team and he was very happy. He was very happy.* (Degenerate Markov absorbing loop).
- **Top-k ($k = 40$):** *When tryout day arrived, his hard work paid off and the coach gave him a jersey.* (Coherent).
- **Top-p ($p = 0.9$):** *During tryouts, Marcus sank five consecutive three-pointers, earning the starting spot.* (Highest narrative quality).
- **Beam Search ($B = 4$):** *On the day of tryouts, he played exceptionally well and was selected for the varsity squad.* (Fluent).

Table 3: Optimizer performance and memory comparison on `human-ai-parallel-corpus`.

Optimizer	Taxonomy Category	Val Loss	Val PPL	Test BLEU	Memory Overhead	Convergence
CustomAdamW	Decoupled Adaptive Moments	3.75	42.5	22.8	2× params (m, v)	Baseline (1.0x)
CustomAdan	Variance-Reduced Nesterov	3.62	37.3	24.1	3× params (m, v, n)	Fastest (-18% tokens)
CustomLion	Memory-Efficient Sign	3.81	45.1	21.6	**1x params (m only)**	**-50% Memory**
CustomMuon	Matrix Polar Newton-Schulz	**3.58**	**35.9**	**24.9**	2× params + Schulz	Best Generalization
CustomSophia	Hessian Clipped (Bonus)	3.69	40.0	23.4	2× params (m, h)	Highest Stability

Table 4: 1,000-sample ROCStories benchmark on `EleutherAI/Pythia-160M` (Colab Pro GPU).

Strategy	Parameters	Perplexity	Accuracy (%)	BLEU	Total Latency	Speed / Sample
Greedy Search	Deterministic (argmax)	2.80	7.19%	0.446	474.3s	0.474s (1.0x)
Top-k Sampling	$k = 40, T = 0.8$	11.13	8.39%	0.461	483.3s	0.483s (1.02x)
Top-p Nucleus	$p = 0.90, T = 0.8$	10.17	8.37%	0.435	487.1s	0.487s (1.03x)
Beam Search ($B = 1$)	$B = 1, \alpha = 0.6$	**2.80**	**7.19%**	**0.446**	475.3s	**0.475s (Greedy Match)**
Beam Search ($B = 2$)	$B = 2, \alpha = 0.6$	2.52	5.74%	0.381	918.0s	0.918s (**1.93x**)
Beam Search ($B = 4$)	$B = 4, \alpha = 0.6$	3.14	5.03%	0.373	1804.5s	1.804s (**3.80x**)

8 Compute Budget, Scaling, and Limitations

Parameter Sizing and Compute Justification: Section 1 of the assignment PDF provides a "Low Compute Tip" suggesting restricting models between 10M and 100M parameters, noting that a 30M model requires 1 hour per 30M tokens on a 2080 Ti. This advice is intended to prevent memory exhaustion and prolonged runs. Our dense baseline contains **8.90M parameters** and Matched-Active MoE reaches **12.06M parameters**. This configuration strikes the optimal balance: it enabled complete multi-epoch sweeps in 1.5 hours on Colab Pro while strictly adhering to all three grading constraints: (1) total parameter parity across C1–C4, (2) active parameter parity for C5, and (3) identical token budgets.

Memory and Latency Trade-offs: CustomLion saves 50% optimizer memory, making it well-suited for edge pretraining. Beam search, while achieving lower perplexity, incurs a strict linear latency penalty (4× slower at $B = 4$). Nucleus sampling provides the best practical trade-off between speed and human narrative quality.

9 Deliverables and Public Repositories

In accordance with General Instructions 5 and 6, all model artifacts, code, and logs are publicly hosted:

- **Code Repository:** https://github.com/Chiranjeevi-2020/ANLP_assignment2
- **Weights & Biases (WandB) Runs:** https://wandb.ai/Chiranjeevi-2020/ANLP-Assignment-2
- **Hugging Face Model Checkpoints:** https://huggingface.co/Chiranjeevi-2020/ANLP-Assignment-

10 Conclusion

This study validates key design principles in modern language modeling: sparse MoE achieves compute-efficient capacity when active parameters are matched; polar matrix optimization (Muon) delivers substantial pretraining acceleration; and nucleus sampling balances entropy and fluency in open-ended generation.

References

[1] A. Vaswani et al., "Attention Is All You Need," *NeurIPS*, 2017.




Figure 3: Empirical beam search execution time scaling vs. beam width B on 1,000 test stories.

[2] N. Shazeer et al., "Outrageously Large Neural Networks: The Sparsely-Gated Mixture-of-Experts Layer," *ICLR*, 2017.

[3] W. Fedus et al., "Switch Transformers: Scaling to Trillion Parameter Models with Simple and Efficient Sparsity," *JMLR*, 2022.

[4] K. Wen et al., "Fantastic Pretraining Optimizers and Where to Find Them," *arXiv:2509.02046*, 2025.

[5] X. Xie et al., "Adan: Adaptive Nesterov Momentum Algorithm for Faster Optimizing Deep Models," *arXiv:2208.06677*, 2022.

[6] X. Chen et al., "Symbolic Discovery of Optimization Algorithms (Lion)," *arXiv:2302.06675*, 2023.

[7] H. Liu et al., "Sophia: A Simple, Fast, Hessian-Free Second-Order Optimizer for Language Models," *arXiv:2305.14342*, 2023.

[8] S. Biderman et al., "Pythia: A Suite for Analyzing Large Language Models Across Training and Scaling," *ICML*, 2023.

[9] K. Papineni et al., "BLEU: a Method for Automatic Evaluation of Machine Translation," *ACL*, 2002.