MAT2440, Classwork26, Spring2025

ID:______ Name:_____

1. The definition of an **Algorithm**:

An <u>algorithm</u> is a finite sequence of precise instructions for performing a computation or for solving a problem.

2. The introduction of **Pseudocode**:

Algorithms in English — → Pseudo Code — → Programming language

3. The structure of a pseudocode (procedure, statements, and return):

Procedure: Name of the code (input: description of input(s))

Statements : Assignments

Conditional statement (if condition then statement)

Loop Constructions (for loop, while loop)

Yeturn : Variable which is the output(s)

4. A pseudocode of summation:

```
procedure summation(a_1, a_2, \dots, a_n): a list of n numbers)
n \coloneqq \text{the length of } \{a_i\}
sum \coloneqq \bigcirc \bigcirc \text{ (which is a variable to store the summation)}
\text{for } i \coloneqq 1 \text{ to } \bigcirc \bigcirc \text{ (a for loop)}
sum \coloneqq sum + a_i \text{ (adding each number to } sum)
\text{return } \underline{Sum}
```

How does this pseudocode work?

Initialization: Sum = O

Return: $sum = Q_1 + Q_2 + W + Q_M$

5. Algorithm and Pseudocode of Finding the Maximum Element in a Finite Sequence.

Problem: Let a_1, a_2, \dots, a_n be a list of n numbers. Find the largest value of them.

Algorithm:

- (1) Set temporary maximum tempMax equals the $\frac{1}{1}$ element $\frac{1}{1}$
- (2) Compare a_2 to *tempMax*:

if $a_2 > tempMax$, then $tempMax = Q_2$. if $a_2 < tempMax$, then do <u>nothing</u>.

- (3) Repeat the previous step for $\underline{Q_3}$, $\underline{Q_{\mu}}$, ..., $\underline{Q_{\mu}}$.
- (4) The variable *tempMax* at this point contains the largest value in the sequence.

Pseudocode:

procedure
$$max(a_1, a_2, \dots, a_n)$$
: a list of n numbers)
$$n \coloneqq \text{the } \underbrace{|e_{M} \in M|}_{\text{emp}} \text{ of } \{a_i\}$$

$$tempMax \coloneqq \underbrace{Q_1}_{\text{for } i := Q_1} \text{ to } \underbrace{M}_{\text{if } tempMax} < a_i \text{ then } tempMax \coloneqq a_i$$

$$return \underbrace{|e_{M} \in M|}_{\text{emp}} \text{ for } i := a_i$$

$$return \underbrace{|e_{M} \in M|}_{\text{emp}} \text{ for } i := a_i$$

6. An example of finding the maximum element in a finite sequence:

Let the sequence be {3, 1, 5, 6, 4}.

Let the sequence be $\{3, 1, 5, 6, 4\}$.

Initialization: tempMax = 3 and n = 5.

i	a_i	$tempMax < a_i \text{ (T or F?)}$	tempMax
i = 2		3<1 (F)	3
i = 3	دا.	3 < 5 (T)	5
i = 4	6	5<6 (T)	6
i = 5	4	6<4 (F)	6

Return: tempMax = 6.

7. Write down an algorithm of finding the Minimum Element in a Finite Sequence.