

Platform API Reference

Frontend developer guide to the Auth, Reports, and Organization & Dashboard endpoints — requests, responses, and error cases.

This document covers three feature areas end to end: **Auth** (invites, onboarding, login, tokens, password reset), **Reports** (Sunday report submission, editing, export, and approval), and **Organization & Dashboard** (compliance summaries, drill-downs, trends, and exports). Every entry gives the method, path, auth requirement, request body, a success example, and the error statuses to handle in the UI.

NOTE

Request/response shapes are taken directly from the DRF serializers and views. Fields marked **write_only** never appear in a response. Where a view has no visible `permission_classes`, that's called out so you can confirm the effective auth requirement with backend.

Contents

Section 1 — Auth (8 endpoints)

Section 2 — Reports (10 endpoints)

Section 3 — Organization & Dashboard (6 endpoints)

Appendix — Full endpoint cheat sheet

Section 1: Auth

Invites, onboarding, login, tokens, and password reset.

Endpoints in this section

- 1.1 POST /user/invite/ — Invite a user
- 1.2 POST /user/complete-profile/ — Complete profile onboarding
- 1.3 POST /user/login/ — Login
- 1.4 POST /user/refresh/ — Refresh access token
- 1.5 POST /user/logout/ — Logout
- 1.6 POST /user/password-reset/ — Request password reset
- 1.7 POST /user/password-reset/confirm/ — Confirm password reset
- 1.8 GET /roles/ — List roles

1.1 Invite a User

Admin-only: creates an invite and assigns the new leader to an organization unit.

Creates an invite record for a new leader linked to a Region/District/Zone/Area/Section/Cell. Requires `is_staff` and `is_superuser` — anyone else gets a 403. Only confirms the invite was sent; it does not return the user or token.

Request Body

Field	Type	Notes
email	email	Must not already belong to a user.
role_id	UUID	Must reference an existing UserRole.
organization_unit_type	enum	region / district / zone / area / section / cell
organization_unit_id	UUID	Must exist for the chosen unit type.

Example Request

```
{
  "email": "leader@example.com",
  "role_id": "8c8a...5e6f",
  "organization_unit_type": "cell",
  "organization_unit_id": "3f1e...4a5b"
}
```

Success Response — 201 Created

```
{
  "message": "Invitation sent successfully."
}
```

Error Responses

Status	Meaning
403	Caller is not both staff and superuser.
400	Email/role/org unit invalid — see field errors.

400 — email exists

```
{
  "email": [
    "A user with this email already exists."
  ]
}
```

1.2 Complete Profile Onboarding

Public: sets the invited user's password using their magic-link token.

Validates the onboarding token from the invite email and sets the account password. Does not log the user in — send them to the login screen afterward.

Request Body

Field	Type	Notes
token	string	Magic-link token from the email URL.
password	string	write_only, min length 8.
password_confirmation	string	write_only, must match password.

Example Request

```
{
  "token": "eyJhbGciOi...",
  "password": "StrongPass123",
  "password_confirmation": "StrongPass123"
}
```

Success Response — 200 OK

```
{
  "message": "Profile completed successfully."
}
```

Error Responses

Status	Meaning
400	Passwords don't match, too short, or token invalid/expired.

400 — bad token

```
{
  "detail": "Invalid or expired magic link."
}
```

POST /user/login/

PUBLIC

1.3 Login

Public: authenticate with email or cell_code + password, returns a JWT pair.

Accepts **either** email **or** cell_code (never both) plus a password. Requires a verified, active account. Returns the serialized user plus tokens nested under data.tokens.

Request Body

Field	Type	Notes
email	email	One of email/cell_code.
cell_code	string	One of email/cell_code.
password	string	write_only.

Example Request

```
{
  "email": "leader@example.com",
  "password": "StrongPass123"
}
```

Success Response — 200 OK

```
{
  "message": "Login successful.",
  "data": {
    "id": "8c8a...5e6f",
    "email": "leader@example.com",
    "first_name": "John",
    "last_name": "Doe",
    "role": "CELL_LEADER",
    "cell": {
      "id": "3f1e...4a5b",
      "name": "Cell 12"
    },
    "tokens": {
      "access": "eyJ...",
      "refresh": "eyJ..."
    }
  }
}
```

Error Responses

Status	Meaning
400	Missing/duplicate identifier, bad credentials, unverified email, or inactive account.

400 — bad credentials

```
{
  "non_field_errors": [
    "Invalid email or password"
  ]
}
```

NOTE

LoginUserSerializer adds one extra key matching the user's role — `region/district/zone/area/section/cell` — holding that unit or null.

POST `/user/refresh/`

AUTHENTICATED*

1.4 Refresh Access Token

Exchanges a valid refresh token for a new access/refresh pair.

Returns a fresh token pair directly (no message envelope). *Not listed in the view's public actions, so it falls back to `IsAuthenticated` — confirm with backend whether a live access token is really required alongside the refresh token.

Request Body

Field	Type	Notes
refresh	string	A valid, non-blacklisted refresh token.

Example Request

```
{
  "refresh": "eyJhbGciOi..."
}
```

Success Response — 200 OK

```
{
  "access": "eyJhbGciOi...",
  "refresh": "eyJhbGciOi..."
}
```

Error Responses

Status	Meaning
400	Refresh token missing, invalid, expired, or blacklisted.

POST /user/logout/

AUTHENTICATED*

1.5 Logout

Blacklists a refresh token to log the user out.

Invalidates the given refresh token. Discard both tokens client-side regardless of response. *Also requires IsAuthenticated, same as /refresh/.

Request Body

Field	Type	Notes
refresh	string	The refresh token to invalidate.

Example Request

```
{
  "refresh": "eyJhbGciOi..."
}
```

Success Response — 200 OK

```
{
  "message": "Logged out successfully."
}
```

Error Responses

Status	Meaning
400	Refresh token missing or already invalid.

POST /user/password-reset/

PUBLIC

1.6 Request Password Reset

Public: emails a reset link if the account exists.

Always returns the same generic message whether or not the email is registered, to avoid leaking which emails have accounts.

Request Body

Field	Type	Notes
email	email	—

Example Request

```
{
  "email": "leader@example.com"
}
```

Success Response — 200 OK

```
{
  "message": "If the email exists, a password reset link has been sent."
}
```

Error Responses

Status	Meaning
400	Email missing or invalid format.

POST /user/password-reset/confirm/

PUBLIC

1.7 Confirm Password Reset

Public: sets a new password using the token + uidb64 from the reset email.

Both token and uidb64 come from the reset email link.

Request Body

Field	Type	Notes
token	string	Reset token from the email link.
uidb64	string	Base64-encoded user id from the link.
password	string	write_only, min length 8.
password_confirmation	string	write_only, must match.

Example Request

```
{
  "token": "c1d2...",
  "uidb64": "0A",
  "password": "NewStrongPass123",
  "password_confirmation": "NewStrongPass123"
}
```

Success Response — 200 OK

```
{
  "message": "Password reset successfully."
}
```

Error Responses

Status	Meaning
400	Passwords don't match, too short, or token/uid invalid/expired.

1.8 List Roles

Admin-only: returns every user role, for populating a role picker.

Restricted to IsAdminUser. permission_ids is write_only on the serializer, so GET only returns id and name.

Success Response — 200 OK

```
[
  {
    "id": "9d8c...bbcc",
    "name": "REGION_LEADER"
  },
  {
    "id": "1a2b...ff00",
    "name": "CELL_LEADER"
  }
]
```

Error Responses

Status	Meaning
403	Caller is not an admin.

Section 2: Reports

Sunday report submission, review, approval, and export.

Endpoints in this section

- 2.1 POST /reports/ — Submit a Sunday report
- 2.2 GET /reports/ · /reports/{id}/ — List / retrieve reports
- 2.3 PATCH /reports/{id}/ — Edit a rejected report
- 2.4 POST /reports/whatsapp/ — Submit via WhatsApp
- 2.5 GET /reports/mine/ — My report history
- 2.6 POST /reports/export/ — Export reports (XLSX)
- 2.7 GET /approvals/queue/ — Approval queue
- 2.8 POST /reports/{id}/approve/ — Approve a report
- 2.9 POST /reports/{id}/reject/ — Reject a report

2.1 Submit a Sunday Report

Creates one report for the authenticated Cell Leader's assigned cell.

service_date must be a Sunday and not in the future. New reports start with PENDING approval status. Field requirements can be tightened per-field by an admin (FieldRequirementMixin).

Request Body

Field	Type	Notes
service_date	date	Must be a Sunday, not in the future.
meeting_held	boolean	Whether the cell met.
members_present	integer	—
total_offering	decimal	Must be ≥ 100 if currency is NGN/naira and meeting_held.
currency	string	e.g. NGN.
guests_cards, decisions_card, guest_visitation, decisions_visitation, physical_checkup, phone_checkup, text_checkup, email_checkup, no_of_meeting_held, holy_ghost_baptism, communion_service, community_project, less_priviledged_visit, cell_leader_visit, cell_members_visit, new_cells, converts, guests, outreach	integer	Counters, default 0. Admin-configured requirements may make some optional.
comment	string	Optional.

Example Request

```
{
  "service_date": "2026-09-06",
  "meeting_held": true,
  "members_present": 10,
  "total_offering": 15000,
  "currency": "NGN",
  "comment": "Normal Sunday service"
}
```

Success Response — 201 Created

```
{
  "id": "uuid",
  "cell": {
    "...": "nested cell/section/.../leader"
  },
  "service_date": "2026-09-06",
  "approval_status": "PENDING",
  "...": "remaining fields"
}
```

Error Responses

Status	Meaning
403	Caller has no assigned cell (not a Cell Leader).
400	Validation failure (e.g. offering below 100 NGN).
409	A report already exists for this cell and Sunday.

GET /reports/ · /reports/{id}/

NOT EXPLICIT

2.2 List / Retrieve Reports

Default ModelViewSet list and retrieve actions — no custom filtering applied.

These use DRF's default list/retrieve behavior (no `@extend_schema` override), returning `SundayReportSerializer` data. The queryset is not scoped to the caller here — use `/reports/mine/` for a leader's own history.

Success Response — 200 OK

```
[
  {
    "id": "uuid",
    "cell": "{...}",
    "service_date": "2026-09-06",
    "approval_status": "PENDING"
  }
]
```

Error Responses

Status	Meaning
404	Report not found (retrieve only).

HEADS UP

No `permission_classes` is visible on this ViewSet — confirm the effective default with backend before assuming it's open to any authenticated user.

2.3 Edit a Rejected Report

Lets the submitting Cell Leader correct a **REJECTED** report.

Only the report's own cell leader can edit it, and only while status is **REJECTED**. On edit, status resets to **PENDING** before the normal partial update is applied.

Success Response — 200 OK

```
{
  "id": "uuid",
  "approval_status": "PENDING",
  "...": "updated fields"
}
```

Error Responses

Status	Meaning
403	Caller is not this report's cell leader.
400	Report status is not REJECTED .

2.4 Submit a Report via WhatsApp

Creates a report using a *cell_code* instead of the caller's own assigned cell.

Used by the WhatsApp bot integration. The caller must be a leader somewhere in the target cell's leadership hierarchy (cell/section/area/zone/district/region).

Request Body

Field	Type	Notes
cell_code	string	Must match exactly one existing cell.
...	—	Same report fields as 2.1 (service_date, meeting_held, etc.).

Example Request

```
{
  "cell_code": "CELL-001",
  "service_date": "2026-09-06",
  "meeting_held": true,
  "members_present": 10,
  "total_offering": 15000,
  "currency": "NGN"
}
```

Success Response — 201 Created

```
{
  "id": "uuid",
  "approval_status": "PENDING"
}
```

Error Responses

Status	Meaning
400	cell_code not found or ambiguous.
403	Caller is not a leader within this cell's hierarchy.
409	A report already exists for this cell and Sunday.

GET /reports/mine/

AUTHENTICATED

2.5 My Report History

Returns reports submitted under the authenticated leader's role scope.

The lookup path used depends on the caller's role (cell/section/area/zone/district/region leader). Paginated.

Query Parameters

Param	Type	Notes
date	string (date)	Filter by service date, YYYY-MM-DD.
page	integer	Optional page number.

Success Response — 200 OK

```
{
  "count": 1,
  "next": null,
  "previous": null,
  "results": [
    {
      "id": "uuid",
      "approval_status": "PENDING"
    }
  ]
}
```

Error Responses

Status	Meaning
400	Invalid date format.

POST /reports/export/

**REGION / DISTRICT
LEADER / SUPER
ADMIN**

2.6 Export Reports (XLSX)

Downloads all reports for one Sunday, one worksheet per zone, as an XLSX file.

region_id is required when the caller is a super admin (region leaders use their own region automatically). Response is a binary spreadsheet, not JSON.

Request Body

Field	Type	Notes
date	date	Must be a Sunday.
region_id	UUID	Required for super admin only.

Example Request

```
{
  "date": "2026-09-06"
}
```

Success Response — 200 OK (binary XLSX)

Error Responses

Status	Meaning
403	Caller's role is not Region/District Leader or Super Admin.
400	Date is not a Sunday, region_id missing for super admin, or region not found.

GET**/approvals/queue/****AUTHENTICATED**

2.7 Approval Queue

Lists pending reports the current user is eligible to approve right now.

Filters PENDING reports through can_approve() — section leaders can approve immediately; area/zone/district/region leaders only after the configured deadline passes.

Query Parameters

Param	Type	Notes
page	integer	Optional page number.

Success Response — 200 OK

```
{
  "count": 1,
  "results": [
    {
      "id": "uuid",
      "approval_status": "PENDING"
    }
  ]
}
```

POST **/reports/{id}/approve/****AUTHENTICATED**

2.8 Approve a Report

Approves a pending report.

Only succeeds if can_approve() allows it for the caller (see 2.7).

Request Body

Field	Type	Notes
comment	string	Optional.

Success Response — 200 OK

```
{
  "id": "uuid",
  "approval_status": "APPROVED"
}
```

Error Responses

Status	Meaning
403	Caller cannot approve this report yet.
409	Report has already been decided.

POST `/reports/{id}/reject/`

AUTHENTICATED

2.9 Reject a Report

Sends a pending report back for correction.

Same eligibility rule as approve. An optional comment explains what needs correcting.

Request Body

Field	Type	Notes
comment	string	Optional correction note.

Example Request

```
{
  "comment": "Please correct members_present."
}
```

Success Response — 200 OK

```
{
  "id": "uuid",
  "approval_status": "REJECTED"
}
```

Error Responses

Status	Meaning
403	Caller cannot approve/reject this report yet.
409	Report has already been decided.

GET · PATCH `/approval-settings/`

AUTHENTICATED

2.10 Approval Interval Settings

Reads or updates the single global approval-deadline setting.

GET returns the current interval; PATCH updates it. Always operates on the one settings row (pk=1), created on first access.

Request Body

Field	Type	Notes
approval_interval	integer (seconds)	Delay before area/zone leaders may approve.

Example Request

```
{
  "approval_interval": 86400
}
```

Success Response — 200 OK

```
{
  "approval_interval": 86400
}
```

Section 3: Organization & Dashboard

Compliance summaries, drill-downs, trends, and exports for the org hierarchy.

Endpoints in this section

- 3.1 GET /organization/dashboard/ — Compliance summary
- 3.2 GET /organization/dashboard/{unit_type}/{id}/ — Drill into a unit
- 3.3 GET /organization/dashboard/trends/ — Compliance trends
- 3.4 GET /organization/dashboard/non-submitters/ — Non-submitting cells
- 3.5 GET /organization/dashboard/approvals/ — Approval waiting times
- 3.6 GET /organization/dashboard/export/ — CSV export

3.1 Compliance Summary

Returns a nested compliance breakdown for the authenticated leader's scope.

Defaults to the most recent Sunday when service_date is omitted. Response nests down through whichever levels sit under the caller (region → district → zone → area → section), each with submitted/total counts and missing-cell detail at the lowest level.

Query Parameters

Param	Type	Notes
service_date	date	Must be a Sunday; defaults to the latest one.

Success Response — 200 OK

```
{
  "region": {
    "id": "uuid",
    "leader_name": "Jane Doe",
    "total_cells": 40,
    "submitted_cells": 33,
    "compliance_percentage": 82.5,
    "districts": [
      "...",
    ]
  }
}
```

Error Responses

Status	Meaning
400	service_date is not a valid Sunday.

3.2 Drill Into a Unit

Compliance data scoped to one region/district/zone/area/section/cell.

unit_type is one of region/district/zone/area/section/cell. Leaders may only request their own level or a descendant of it.

Query Parameters

Param	Type	Notes
unit_type	path (enum)	region / district / zone / area / section / cell
pk	path (UUID)	Id of the unit.
service_date	query (date)	Must be a Sunday.

Success Response — 200 OK

```
{
  "service_date": "2026-09-06",
  "total_cells": 12,
  "submitted_cells": 10,
  "missing_cells": [],
  "pending_approval": 3,
  "approved": 7,
  "compliance_percentage": 83.33,
  "scope": {
    "type": "zone",
    "id": "uuid",
    "name": "Zone A"
  }
}
```

Error Responses

Status	Meaning
404	Unknown unit_type or unit not found.
403	Unit is outside the caller's scope.
400	service_date is not a valid Sunday.

GET /organization/dashboard/trends/

AUTHENTICATED

3.3 Compliance Trends

One compliance summary per Sunday over the selected period.

Returns a paginated list, oldest Sunday first, ending at the most recent.

Query Parameters

Param	Type	Notes
weeks	integer	One of 4, 8, or 12. Default 4.

Success Response — 200 OK

```
{
  "count": 4,
  "results": [
    {
      "service_date": "2026-08-16",
      "total_cells": 40,
      "submitted_cells": 30,
      "compliance_percentage": 75.0
    }
  ]
}
```

Error Responses

Status	Meaning
400	weeks is not 4, 8, or 12.

3.4 Non-Submitting Cells

Cells in scope that haven't submitted for the selected Sunday.

With `chronic=true`, narrows the list to cells that missed three consecutive Sundays ending on the selected date.

Query Parameters

Param	Type	Notes
service_date	date	Defaults to the latest Sunday.
chronic	boolean	true to return only 3-week consecutive misses.

Success Response — 200 OK

```
{
  "count": 2,
  "results": [
    {
      "id": "uuid",
      "name": "Cell 7",
      "code": "CELL-007"
    }
  ]
}
```

Error Responses

Status	Meaning
400	service_date is not a valid Sunday.

3.5 Approval Waiting Times

Pending reports the caller can act on, with wait time and overdue flag.

`overdue` is true once `waiting_seconds` exceeds the global `approval_interval` setting.

Success Response — 200 OK

```
{
  "count": 1,
  "results": [
    {
      "id": "uuid",
      "cell": "Test Cell",
      "submitted_at": "2026-09-06T12:00:00Z",
      "waiting_seconds": 90000,
      "overdue": true
    }
  ]
}
```

3.6 CSV Compliance Export

Downloads report statuses within a date range for the caller's scope.

Response is a CSV attachment (cell_id, cell, code, service_date, approval_status) — not JSON.

Query Parameters

Param	Type	Notes
start_date	date	Required.
end_date	date	Required, must be ≥ start_date.

Success Response — 200 OK (CSV)

Error Responses

Status	Meaning
400	Dates missing/invalid, or start_date after end_date.

Appendix: Full Endpoint Cheat Sheet

Auth

Endpoint	Method	Auth
/user/invite/	POST	Staff + Superuser
/user/complete-profile/	POST	Public
/user/login/	POST	Public
/user/refresh/	POST	Authenticated*
/user/logout/	POST	Authenticated*
/user/password-reset/	POST	Public
/user/password-reset/confirm/	POST	Public
/roles/	GET	Admin (staff)

Reports

Endpoint	Method	Auth
/reports/	GET, POST	Not explicit / Cell Leader
/reports/{id}/	GET, PATCH	Not explicit / owning Cell Leader
/reports/whatsapp/	POST	Authenticated (hierarchy leader)
/reports/mine/	GET	Authenticated
/reports/export/	POST	Region/District Leader, Super Admin
/approvals/queue/	GET	Authenticated
/reports/{id}/approve/	POST	Authenticated (eligible approver)
/reports/{id}/reject/	POST	Authenticated (eligible approver)

Endpoint	Method	Auth
/approval-settings/	GET, PATCH	Authenticated

Organization & Dashboard

Endpoint	Method	Auth
/organization/dashboard/	GET	Authenticated
/organization/dashboard/{unit_type}/{id}/	GET	Authenticated (in-scope units)
/organization/dashboard/trends/	GET	Authenticated
/organization/dashboard/non-submitters/	GET	Authenticated
/organization/dashboard/approvals/	GET	Authenticated
/organization/dashboard/export/	GET	Authenticated

* /user/refresh/ and /user/logout/ require IsAuthenticated (not in the view's public_actions) — confirm with backend whether a live access token is genuinely needed alongside the refresh token. Several Reports/Organization views also have no visible permission_classes — confirm the effective default before relying on it.