

# The Whacky World of Undefined Behaviour

Beck, Calvin  
hobbes@seas.upenn.edu

October 17, 2019

# What is this Talk about?

Undefined behaviour! With a smack of LLVM.

We'll cover things like:

- What is undefined behaviour?
- What happens when you encounter UB?
- How is UB useful? Should we avoid it?
  - ▶ Optimizations?
- UB in LLVM (and indeterminate values)
- How this all fits into Vellvm

Not for anything in particular! It's just a fun topic, and hopefully talking about it will clarify some things for myself and you!

# What is undefined behaviour (UB)?

It's behaviour...

# What is undefined behaviour (UB)?

It's behaviour...

That's undefined.

# What is undefined behaviour (UB)?

It's behaviour...

That's undefined.

Done.

# What is undefined behaviour (UB)?

Why does this seem hard?

# What is undefined behaviour (UB)?

Why does this seem hard?

- Easy to conflate with things like implementation defined behaviour... Which is sort of different.

# What is undefined behaviour (UB)?

Why does this seem hard?

- Easy to conflate with things like implementation defined behaviour... Which is sort of different.
- Language dependent.
  - ▶ Array out of bounds in Python? Exception, not UB.



# What is undefined behaviour (UB)?

Why does this seem hard?

- Easy to conflate with things like implementation defined behaviour... Which is sort of different.
- Language dependent.
  - ▶ Array out of bounds in Python? Exception, not UB.
  - ▶ Array out of bounds in C? ... Pray.

# What happens when you encounter UB?

What happens when you encounter UB?

ANYTHING.

What happens when you encounter UB?

ANYTHING.

Yes.

What happens when you encounter UB?

ANYTHING.

Yes. Anything.

# What happens when you encounter UB?

Compiler will do whatever it finds easiest or most efficient.

- noop, and then continue
- halt
- halt **and** catch fire
- erase the hard drive

# What happens when you encounter UB?

Compiler will do whatever it finds easiest or most efficient.

- noop, and then continue
- halt
- halt **and** catch fire
- erase the hard drive
  - ▶ No, seriously. Erase the hard drive.
  - ▶ <https://kristerw.blogspot.com/2017/09/why-undefined-behavior-may-call-never.html>

# What happens when you encounter UB?

Compiler will do whatever it finds easiest or most efficient.

- noop, and then continue
- halt
- halt **and** catch fire
- erase the hard drive
  - ▶ No, seriously. Erase the hard drive.
  - ▶ <https://kristerw.blogspot.com/2017/09/why-undefined-behavior-may-call-never.html>
- time travel



# What happens when you encounter UB?

Compiler will do whatever it finds easiest or most efficient.

- noop, and then continue
- halt
- halt **and** catch fire
- erase the hard drive
  - ▶ No, seriously. Erase the hard drive.
  - ▶ <https://kristerw.blogspot.com/2017/09/why-undefined-behavior-may-call-never.html>
- time travel
  - ▶ no, really.
  - ▶ <https://devblogs.microsoft.com/oldnewthing/?p=633>

# What happens when you encounter UB?

Compiler will do whatever it finds easiest or most efficient.

- noop, and then continue
- halt
- halt **and** catch fire
- erase the hard drive
  - ▶ No, seriously. Erase the hard drive.
  - ▶ <https://kristerw.blogspot.com/2017/09/why-undefined-behavior-may-call-never.html>
- time travel
  - ▶ no, really.
  - ▶ <https://devblogs.microsoft.com/oldnewthing/?p=633>
- nasal demons?

# What happens when you encounter UB?

Compiler will do whatever it finds easiest or most efficient.

- noop, and then continue
- halt
- halt **and** catch fire
- erase the hard drive
  - ▶ No, seriously. Erase the hard drive.
  - ▶ <https://kristerw.blogspot.com/2017/09/why-undefined-behavior-may-call-never.html>
- time travel
  - ▶ no, really.
  - ▶ <https://devblogs.microsoft.com/oldnewthing/?p=633>
- nasal demons?
  - ▶ [https://en.wikipedia.org/wiki/Nasal\\_demons](https://en.wikipedia.org/wiki/Nasal_demons)

# What happens when you encounter UB?

Compiler will do whatever it finds easiest or most efficient.

- noop, and then continue
- halt
- halt **and** catch fire
- erase the hard drive
  - ▶ No, seriously. Erase the hard drive.
  - ▶ <https://kristerw.blogspot.com/2017/09/why-undefined-behavior-may-call-never.html>
- time travel
  - ▶ no, really.
  - ▶ <https://devblogs.microsoft.com/oldnewthing/?p=633>
- nasal demons?
  - ▶ [https://en.wikipedia.org/wiki/Nasal\\_demons](https://en.wikipedia.org/wiki/Nasal_demons)
  - ▶ So far I'm pretty sure this is just a joke, but I wouldn't rule it out.

# Why is this useful?

Why have UB at all? Isn't it... crazy?

# Why is this useful?

Why have UB at all? Isn't it... *crazy?*

- PL without UB might have a lot of dynamic sanity checks.
  - ▶ Bounds checking.

# Why is this useful?

Why have UB at all? Isn't it... *crazy?*

- PL without UB might have a lot of dynamic sanity checks.
  - ▶ Bounds checking.
- What about type systems?
  - ▶ Static checks can eliminate some dynamic checks
  - ▶ Bounds checking still common.

Instead, why not...

# Why is this useful?

Why have UB at all? Isn't it... *crazy?*

- PL without UB might have a lot of dynamic sanity checks.
  - ▶ Bounds checking.
- What about type systems?
  - ▶ Static checks can eliminate some dynamic checks
  - ▶ Bounds checking still common.

Instead, why not...

Do nothing?



# Why is this useful?

UB may seem somewhat unprincipled, but it has advantages:

- Gives compiler an axiom.
- Puts burden on programmer, or other tools

# UB can reflect programmer intent

I want to change this...

```
a + b < a + c
```

# UB can reflect programmer intent

I want to change this...

```
a + b < a + c
```

To this:

```
b < a
```

After all, who wants to do 2 extra additions?

# UB can reflect programmer intent

I want to change this...

```
a + b < a + c
```

To this:

```
b < a
```

After all, who wants to do 2 extra additions?

But this is sort of wrong...

```
1 + INT_MAX < 1 + 3
// This evaluates to
INT_MIN < 4 == True

// But...
INT_MAX < 3 == False
```

# Pointer aliasing — optimizations with undecidability

Undefined behaviour allows compilers to make optimizations based on undecidable invariants.

# Pointer aliasing — optimizations with undecidability

Undefined behaviour allows compilers to make optimizations based on undecidable invariants.

It might be nice to optimize this:

```
void sum(double *total, double *array, size_t len )
{
    *total = 0;
    for (size_t i=0; i<len; i++) {
        *total += array[i];
    }
}
```

To this:

```
void sum(double *total, double *array, size_t len )
{
    double local_total = 0;
    for (size_t i=0; i<len; i++) {
        local_total += array[i];
    }

    *total = local_total;
}
```

# C's restrict keyword

```
void sum(double* restrict total, double* restrict array, size_t len )
{
    *total = 0;
    for (size_t i=0; i<len; i++) {
        *total += array[i];
    }
}
```

Allows optimization to

```
void sum(double *total, double *array, size_t len )
{
    double local_total = 0;
    for (size_t i=0; i<len; i++) {
        local_total += array[i];
    }

    *total = local_total;
}
```

Because restrict says “these pointers don’t alias with anything”. If they happen to alias, then it’s UB, and the program can do whatever.

# WHERE WE'RE GOING WE DON'T NEED ROADS



# WHERE WE'RE GOING WE DON'T NEED ROADS

So, how powerful is undefined behaviour?

# WHERE WE'RE GOING WE DON'T NEED ROADS

So, how powerful is undefined behaviour?

Can we optimize this:

```
char inp = getchar();  
if ('A' == inp) {  
    printf("Hello, world!\n");  
    x = 1 / 0;  
}
```

# WHERE WE'RE GOING WE DON'T NEED ROADS

So, how powerful is undefined behaviour?

Can we optimize this:

```
char inp = getchar();  
if ('A' == inp) {  
    printf("Hello, world!\n");  
    x = 1 / 0;  
}
```

To this?

```
getchar();
```

# References



In: ().



.



.

These are all good resources! You should look at them!