- **1. Install Nmap from the official website.**
- **Explanation**: A candidate should demonstrate familiarity with securely obtaining and installing tools. Nmap, a network scanning tool, is available at `nmap.org`.
- **Steps**:
- 1. Visit https://nmap.org/download.html.
- 2. Select the appropriate installer for your OS (e.g., Windows `.exe`, Linux `.rpm` or source, macOS `.dmg`).
- 3. Verify the download's integrity using checksums (e.g., SHA256) provided on the site to ensure it's not tampered.
- 4. Install Nmap following the installer prompts (e.g., `sudo apt install nmap` for Debian-based Linux or run the Windows installer).
- 5. Confirm installation by running 'nmap --version' in a terminal or command prompt.
- **2. Find your local IP range (e.g., 192.168.146.0/24).**
- **Explanation**: Identifying the local IP range requires understanding network configurations and basic command-line skills.
- **Steps**:
- 1. On Windows, open Command Prompt and run 'ipconfig'. Look for the IPv4 address (e.g., 192.168.146.100) and subnet mask (e.g., 255.255.255.0, which indicates a /24 range).
- 2. On Linux/macOS, open a terminal and run `ifconfig` or `ip addr`. Identify the network interface (e.g., `eth0` or `wlan0`) and note the IP and subnet mask.
- 3. The range is derived from the IP and subnet mask. For example, an IP of 192.168.146.100 with a 255.255.255.0 mask means the range is 192.168.146.0/24 (256 addresses from 192.168.146.0 to 192.168.146.255).
- **3. Run: nmap -sS 192.168.146.0/24 to perform TCP SYN scan.**

- **Explanation**: The `-sS` flag performs a TCP SYN scan, a stealthy scan that sends SYN packets to detect open ports without completing a full TCP handshake.
- **Steps**:
- 1. Open a terminal or command prompt with administrative/root privileges (required for SYN scans).
- 2. Run the command: `nmap -sS 192.168.146.0/24`.
- 3. Wait for the scan to complete, which identifies active hosts and their open TCP ports within the specified range.
- **4. Note down IP addresses and open ports found.**
- **Explanation**: Documenting results is a key skill for reporting vulnerabilities in cybersecurity roles.
- **Steps**:
- 1. Review Nmap's output, which lists active IP addresses (e.g., 192.168.146.10, 192.168.146.20) and their open ports (e.g., 22, 80, 443).
- 2. Record details manually or use Nmap's output option
- 3. Example output might show:
 - 192.168.146.10: Ports 22 (SSH), 80 (HTTP)
- 192.168.146.20: Port 445 (SMB)
- **5. Optionally analyze packet capture with Wireshark.**
- **Explanation**: Wireshark is used to capture and analyze network traffic, providing deeper insight into scan results or services.
- **Steps**:
- 1. Install Wireshark from `https://www.wireshark.org` (verify checksums for security).
- 2. Open Wireshark, select the active network interface (e.g., `eth0` or Wi-Fi), and start capturing.

- 3. Re-run the Nmap scan or interact with a specific IP/port (e.g., access 192.168.1.10:80 via a browser) to generate traffic.
- 4. Filter packets in Wireshark (e.g., `tcp.port == 80` for HTTP) to analyze communication patterns, headers, or anomalies.
- **6. Research common services running on those ports. **
- **Steps**:
- 1. Use a port reference (e.g., IANA list or Nmap's service detection) to identify services. Common examples:
 - Port 22: SSH (remote access).
 - Port 80: HTTP (web server).
 - Port 445: SMB (file sharing, Windows).
- 2. Run `nmap -sV 192.168.146.0/24` for service version detection to get specifics (e.g., Apache 2.4.41 on port 80).
- **7. Identify potential security risks from open ports.**
- **Explanation**: Open ports can expose vulnerabilities if services are misconfigured or outdated.
- **Steps**:
- 1. Analyze each open port and service:
- Port 22 (SSH): Risk of brute-force attacks if weak credentials or outdated SSH versions are used.
- Port 80 (HTTP): Vulnerable to web-based attacks (e.g., SQL injection) if the server lacks security patches.
- Port 445 (SMB): High risk due to exploits like EternalBlue if unpatched (e.g., WannaCry ransomware).
- 2. Check for unnecessary open ports (e.g., SMB on a device that doesn't need file sharing).
- 3. Recommend mitigation: Update software, use strong credentials, or close unused ports via firewall rules.

8. Save scan results as a text or HTML file.

Saving results ensures documentation for reporting or audits.

- **Steps**:
- 1. Modify the Nmap command to save output:
 - Text file: `nmap -sS 192.168.146.0/24 -oN /home/kali/Downloads/scan_results.txt`
- HTML file: `nmap -sS 192.168.146.0/24 -oX /home/kali/Downloads/scan_results.xml && xsltproc scan_results.xml -o scan_results.html`
- 2. Verify the file contains IPs, ports, and service details.