TR34 (3rd edition) Free Movement Floor Tolerance Report

Allen Face Europe TR34 Analysis, ©Allen Face Europe, www.allenface-europe.com

1. Project Name: 방초리

2. Concrete Floor Installer:

5. Floor Tolerance Requirements:

3. Testing Organization:

안성시 일죽 방초리 221 **Project Location:**

인천광역시

일도티씨에스㈜

지상1층 #3 4. Slab ID: #REF!

Date of Pouring: 2024-03-06 Date of Testing:

D-Meter® Manufactured by Allen Face&Company, Serial Number: 098 **Test Apparatus:**

ALLENFACE KOREA

Testing Technician: TAEHYUN LEE (ALLEN FACE KOREA)

ALLEN FACE KOREA			Test Area	:	89 m ² (for test area organization see attached drawing)										
TR3	4 (3rd Edition) FRE	E MOVEMENT FLOC	R TOLERANCES ±ฉี	t	TR34 3rd Edition convert into FF/FL ±값										
Floor Classification	Property II (mm)	Property IV (mm)	Property II (mm)	Property IV (mm)	등급	Property II		Property IV		OAFF	OAEL	MILEE	MLFL		
FIOOT Classification	95% limit	95% limit	100% limit	100% limit	ਰਜ	95%(mm)	100%(mm)	95%(mm)	100%(mm)	UAFF	OAFL	MLFF 18.6 15.6 13.2	IVILEL		
FM1	2.5	4.5	4.0	7.0	FM1	2.5	4.0	4.5	7.0	31	47	18.6	28.2		
FM2(special)	3.0	6.5	4.5	10.0	FM2 Special	3.0	4.5	6.5	10.0	26	32	15.6	19.2		
FM2	3.5	8.0	5.5	12.0	FM2	3.5	5.5	8.0	12.0	22	26	13.2	15.6		
FM3	5.0	10.0	7.5	15.0	FM3	5.0	7.5	10.0	15.0	15	21	9	12.6		

6. Analysis:

							TR	34 3rd E	dition FRE	E MOVEN	IENT RESU	ILTS				
Run #:		13	14	15	16	17	18									All Runs:
Run Length (m):		5.70	5.70	5.70	5.70	5.70	5.70							<u> </u>		 34.20
	Property II (95%)	YES	YES	YES	YES	YES	YES									YES
FM1	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%									0.00%
FIVII	Property IV (95%)	NO	NO	NO	NO	YES	YES							<u> </u>		 NO
	% Defective	44.44%	55.56%	22.22%	11.11%	0.00%	0.00%	į	-					į		22.22%
	Property II (95%)	YES	YES	YES	YES	YES	YES									YES
5142/G : D	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%							į		0.00%
FM2(Special)	Property IV (95%)	YES	NO	YES	YES	YES	YES							<u> </u>		 YES
	% Defective	0.00%	22.22%	0.00%	0.00%	0.00%	0.00%									3.70%
	Property II (95%)	YES	YES	YES	YES	YES	YES									YES
FM2	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%									0.00%
FIVIZ	Property IV (95%)	YES	YES	YES	YES	YES	YES	! !						<u> </u>		 YES
	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	İ								0.00%
	Property II (95%)	YES	YES	YES	YES	YES	YES									YES
5140	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%									0.00%
FM3	Property IV (95%)	YES	YES	YES	YES	YES	YES									YES
	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%									0.00%

FM2(Special) the floor tolerance requirements. 7. Summary: The analysed D-Meter® Runs satisfy

TR34 (3rd edition) Free Movement Floor Tolerance Report

Allen Face Europe TR34 Analysis, ©Allen Face Europe, www.allenface-europe.com

1. Project Name: 방초리

2. Concrete Floor Installer:

5. Floor Tolerance Requirements:

3. Testing Organization:

안성시 일죽 방초리 221 **Project Location:**

인천광역시

일도티씨에스㈜

지상1층 #3 4. Slab ID: #REF!

Date of Pouring: Date of Testing: 2024-03-06

D-Meter® Manufactured by Allen Face&Company, Serial Number: 098 **Test Apparatus:**

Testing Technician: TAEHYUN LEE (ALLEN FACE KOREA)

ALLEN FACE KOREA			Test Area	est Area: 89 m ² (for test area organization see attached drawing)									
TR	34 (3rd Edition) FRE	TR34 3rd Edition convert into FF/FL ±값											
Floor Classification	Property II (mm)	Property IV (mm)	Property II (mm)	Property IV (mm)	등급	Property II		Property IV		OAFF	OAEL	MIEE	MLFL
Floor Classification	95% limit	95% limit	100% limit	100% limit	- Б н	95%(mm)	100%(mm)	95%(mm)	100%(mm)	UAFF	J.	IVILFF	IVILFL
FM1	2.5	4.5	4.0	7.0	FM1	2.5	4.0	4.5	7.0	31	47	18.6	28.2
FM2(special)	3.0	6.5	4.5	10.0	FM2 Special	3.0	4.5	6.5	10.0	26	32	15.6	19.2
FM2	3.5	8.0	5.5	12.0	FM2	3.5	5.5	8.0	12.0	22	26	13.2	15.6
FM3	5.0	10.0	7.5	15.0	FM3	5.0	7.5	10.0	15.0	15	21	9	12.6

6. Analysis:

							TF	34 3rd Edition	REE MOVE	MENT RESU	JLTS						
Run #:		13	14	15	16	17	18										All Runs:
Run Length (m):		5.70	5.70	5.70	5.70	5.70	5.70							 <u> </u>			34.20
	Property II (100%)	YES	YES	YES	YES	YES	YES										YES
FM1	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%										0.00%
FIVII	Property IV (100%)	YES	NO	YES	YES	YES	YES					1					NO
	% Defective	0.00%	22.22%	0.00%	0.00%	0.00%	0.00%							<u> </u>			3.70%
	Property II (100%)	YES	YES	YES	YES	YES	YES										YES
F140/G : D	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%							•			0.00%
FM2(Special)	Property IV (100%)	YES	YES	YES	YES	YES	YES				<u> </u>	1	<u> </u>		·		YES
	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%										0.00%
	Property II (100%)	YES	YES	YES	YES	YES	YES										YES
FM2	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%							<u> </u>			0.00%
FIVIZ	Property IV (100%)	YES	YES	YES	YES	YES	YES					1		 		T	YES
	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%										0.00%
	Property II (100%)	YES	YES	YES	YES	YES	YES										YES
5140	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%										0.00%
FM3	Property IV (100%)	YES	YES	YES	YES	YES	YES				Ť					İ	YES
	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%										0.00%

7. Summary: The analysed D-Meter® Runs satisfy FM2(Special) the floor tolerance requirements.

ALLENFACE KOREA







