TR34 (3rd edition) Free Movement Floor Tolerance Report

Allen Face Europe TR34 Analysis, ©Allen Face Europe, www.allenface-europe.com

1. Project Name: 방초리

2. Concrete Floor Installer:

5. Floor Tolerance Requirements:

3. Testing Organization:

안성시 일죽 방초리 221 **Project Location:**

인천광역시

일도티씨에스㈜

지상1층 #2 4. Slab ID: #REF!

Date of Pouring: Date of Testing: 2024-03-06

D-Meter® Manufactured by Allen Face&Company, Serial Number: 098 **Test Apparatus:**

TAEHYUN LEE (ALLEN FACE KOREA) **Testing Technician:**

ALLEN FACE KOREA Test Area:					89 m ² (for test area organization see attached drawing)								
TR3	TR34 3rd Edition convert into FF/FL ±값												
Floor Classification	Property II (mm)	Property IV (mm)	Property II (mm)	Property IV (mm)	등급	□ Property II			erty IV	OAFF	OAFL	MLFF	MLFL
FIOOI Classification	95% limit	95% limit	100% limit	100% limit	ਰਜ	95%(mm)	100%(mm)	95%(mm)	100%(mm)	UAFF	UAFL	IVILEE	IVILEL
FM1	2.5	4.5	4.0	7.0	FM1	2.5	4.0	4.5	7.0	31	47	18.6	28.2
FM2(special)	3.0	6.5	4.5	10.0	FM2 Special	3.0	4.5	6.5	10.0	26	32	15.6	19.2
FM2	3.5	8.0	5.5	12.0	FM2	3.5	5.5	8.0	12.0	22	26	13.2	15.6
FM3	5.0	10.0	7.5	15.0	FM3	5.0	7.5	10.0	15.0	15	21	9	12.6

6. Analysis:

							TF	34 3rd E	dition FRE	E MOVEN	IENT RESU	LTS						
Run #:		7	8	9	10	11	12		1									All Runs:
Run Length (m):		18.00	18.00	18.00	18.00	18.00	18.00								<u> </u>			 108.00
	Property II (95%)	YES	NO	NO	NO	YES	YES							İ			i i	NO
FM1	% Defective	1.72%	5.17%	12.07%	15.52%	1.72%	0.00%											6.03%
FIVII	Property IV (95%)	NO	NO	NO	NO	NO	YES								<u> </u>			 NO
	% Defective	6.00%	36.00%	42.00%	64.00%	28.00%	0.00%							į	į			29.33%
	Property II (95%)	YES	YES	NO	NO	YES	YES							•	•			YES
FM2(Special)	% Defective	0.00%	0.00%	10.34%	6.90%	1.72%	0.00%							İ	İ	1		3.16%
riviz(Special)	Property IV (95%)	YES	NO	NO	NO	YES	YES							 	<u> </u>			 NO
	% Defective	0.00%	16.00%	16.00%	38.00%	4.00%	0.00%											12.33%
	Property II (95%)	YES	YES	NO	NO	YES	YES											YES
FM2	% Defective	0.00%	0.00%	8.62%	6.90%	1.72%	0.00%							İ				2.87%
FM2	Property IV (95%)	YES	NO	NO	NO	YES	YES				<u> </u>		ļ		<u> </u>	T	†	 NO
	% Defective	0.00%	10.00%	10.00%	16.00%	0.00%	0.00%											6.00%
	Property II (95%)	YES	YES	YES	YES	YES	YES											YES
5142	% Defective	0.00%	0.00%	0.00%	1.72%	0.00%	0.00%											0.29%
FM3	Property IV (95%)	YES	NO	YES	NO	YES	YES											 YES
	% Defective	0.00%	6.00%	4.00%	6.00%	0.00%	0.00%											2.67%

7.	Summary:	The analysed D-Meter® Runs satisfy	FM3	the floor tolerance requirements.	
					ALLENFACE KOREA

TR34 (3rd edition) Free Movement Floor Tolerance Report

Allen Face Europe TR34 Analysis, ©Allen Face Europe, www.allenface-europe.com

١.	Project Name:	방초리

2. Concrete Floor Installer:

5. Floor Tolerance Requirements:

3. Testing Organization:

안성시 일죽 방초리 221 **Project Location:**

인천광역시 일도티씨에스㈜

지상1층 #2 4. Slab ID: #REF!

Date of Pouring: 2024-03-06 Date of Testing:

D-Meter® Manufactured by Allen Face&Company, Serial Number: 098 **Test Apparatus:**

Testing Technician: TAEHYUN LEE (ALLEN FACE KOREA)

ALLEN FACE KOREA	:	89 m ² (for test area organization see attached drawing)											
TR3	TR34 3rd Edition convert into FF/FL ±값												
Floor Classification	Property II (mm)	Property IV (mm)	Property II (mm)	Property IV (mm)	등급 Property II		erty II	Prop	erty IV		OAFL	NAL EE	NALEL
Floor Classification	95% limit	95% limit	100% limit	100% limit	о н	95%(mm)	100%(mm)	95%(mm)	100%(mm)	UAFF	OAFL	IVILEE	IVILIL
FM1	2.5	4.5	4.0	7.0	FM1	2.5	4.0	4.5	7.0	31	47	18.6	28.2
FM2(special)	3.0	6.5	4.5	10.0	FM2 Special	3.0	4.5	6.5	10.0	26	32	15.6	19.2
FM2	3.5	8.0	5.5	12.0	FM2	3.5	5.5	8.0	12.0	22	26	13.2	15.6
FM3	5.0	10.0	7.5	15.0	FM3	5.0	7.5	10.0	15.0	15	21	9	12.6

6. Analysis:

							TF	R34 3rd E	dition FR	EE MOVEN	IENT RESU	JLTS						
Run #:		7	8	9	10	11	12		T									All Runs:
Run Length (m):		18.00	18.00	18.00	18.00	18.00	18.00				<u> </u>			 				108.00
	Property II (100%)	YES	YES	NO	NO	YES	YES			İ	İ						i i	NO
FM1	% Defective	0.00%	0.00%	3.45%	1.72%	0.00%	0.00%											0.86%
FIVI	Property IV (100%)	YES	NO	NO	NO	YES	YES							 		<u> </u>	1	NO
	% Defective	0.00%	12.00%	16.00%	36.00%	0.00%	0.00%		ļ		ļ							10.67%
	Property II (100%)	YES	YES	NO	NO	YES	YES											NO
FM2(Special)	% Defective	0.00%	0.00%	1.72%	1.72%	0.00%	0.00%											0.57%
riviz(Special)	Property IV (100%)	YES	NO	NO	NO	YES	YES							 			1	NO
	% Defective	0.00%	6.00%	4.00%	6.00%	0.00%	0.00%				•							2.67%
	Property II (100%)	YES	YES	YES	YES	YES	YES											YES
FM2	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%											0.00%
FM2	Property IV (100%)	YES	NO	YES	NO	YES	YES	†			1	†	-	 <u> </u>		<u> </u>	-†	NO
	% Defective	0.00%	2.00%	0.00%	2.00%	0.00%	0.00%		•		•							0.67%
	Property II (100%)	YES	YES	YES	YES	YES	YES											YES
F142	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%											0.00%
FM3	Property IV (100%)	YES	YES	YES	YES	YES	YES	İ			<u> </u>	Ť		<u> </u>		Ť	T T	YES
	% Defective	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%											0.00%

7.	Summary:	The analysed D-Meter® Runs satisfy	FM3	the floor tolerance requirements.	
					ALLENFACE KOREA









