TR34 (3rd edition) Free Movement Floor Tolerance Report

Allen Face Europe TR34 Analysis, ©Allen Face Europe, www.allenface-europe.com

1. Project Name: 방초리

2. Concrete Floor Installer:

5. Floor Tolerance Requirements:

3. Testing Organization:

안성시 일죽 방초리 221 **Project Location:**

인천광역시

일도티씨에스㈜

지상1층 #14 4. Slab ID:

#REF! Date of Pouring: 2024-03-06 Date of Testing:

D-Meter® Manufactured by Allen Face&Company, Serial Number: 098 **Test Apparatus:**

Testing Technician: TAEHYUN LEE (ALLEN FACE KOREA)

ALLENFACE KOREA

ALLEN FACE KOREA		Test Area: 89 m ² (for test area organization see attached drawing)											
TR3	4 (3rd Edition) FRE	E MOVEMENT FLOC	R TOLERANCES ±ฉี	t			TR34 3rd	d Edition co	nvert into FF	/FL ±값			
Floor Classification	Property II (mm)	Property IV (mm)	Property II (mm)	Property IV (mm)	등급	Property II		Property IV		OAFF	OAFL	MLFF	MLFL
FIOOT Classification	95% limit	95% limit 100% limit		100% limit	ਰਜ	95%(mm)	100%(mm)	95%(mm) 100%(mm)				IVILEE	IVILEL
FM1	2.5	4.5	4.0	7.0	FM1	2.5	4.0	4.5	7.0	31	47	18.6	28.2
FM2(special)	3.0	6.5	4.5	10.0	FM2 Special	3.0	4.5	6.5	10.0	26	32	15.6	19.2
FM2	3.5	8.0	5.5	12.0	FM2	3.5	5.5	8.0	12.0	22	26	13.2	15.6
FM3	5.0	10.0	7.5	15.0	FM3	5.0	7.5	10.0	15.0	15	21	9	12.6

6. Analysis:

						Т	R34 3rd E	dition FRE	E MOVEN	IENT RESU	LTS				
Run #:		89	90	91	92										All Runs:
Run Length (m):		7.80	7.80	7.80	7.80								<u> </u>		 31.20
	Property II (95%)	YES	YES	NO	YES		İ	İ							YES
FM1	% Defective	0.00%	0.00%	12.50%	0.00%										3.13%
FIVII	Property IV (95%)	YES	YES	NO	NO										NO
	% Defective	0.00%	0.00%	25.00%	31.25%										 14.06%
	Property II (95%)	YES	YES	NO	YES		•								YES
5142/G : D	% Defective	0.00%	0.00%	8.33%	0.00%										2.08%
FM2(Special)	Property IV (95%)	YES	YES	YES	NO						<u></u>			<u> </u>	 YES
	% Defective	0.00%	0.00%	0.00%	6.25%										1.56%
	Property II (95%)	YES	YES	YES	YES										YES
FM2	% Defective	0.00%	0.00%	4.17%	0.00%										1.04%
FIVIZ	Property IV (95%)	YES	YES	YES	YES		<u> </u>						<u> </u>		 YES
	% Defective	0.00%	0.00%	0.00%	0.00%										0.00%
	Property II (95%)	YES	YES	YES	YES										YES
F1.42	% Defective	0.00%	0.00%	0.00%	0.00%										0.00%
FM3	Property IV (95%)	YES	YES	YES	YES										YES
	% Defective	0.00%	0.00%	0.00%	0.00%										0.00%

FM2(Special) the floor tolerance requirements. 7. Summary: The analysed D-Meter® Runs satisfy

TR34 (3rd edition) Free Movement Floor Tolerance Report

Allen Face Europe TR34 Analysis, ©Allen Face Europe, www.allenface-europe.com

1. Project Name: 방초리

2. Concrete Floor Installer:

5. Floor Tolerance Requirements:

3. Testing Organization:

안성시 일죽 방초리 221 **Project Location:**

인천광역시

일도티씨에스㈜

지상1층 #14 4. Slab ID:

#REF! Date of Pouring: Date of Testing: 2024-03-06

D-Meter® Manufactured by Allen Face&Company, Serial Number: 098 **Test Apparatus:**

ALLENFACE KOREA

Testing Technician: TAEHYUN LEE (ALLEN FACE KOREA)

ALLEN FACE KOREA			Test Area	89 m ² (for test area organization see attached drawing)										
TR3	4 (3rd Edition) FRE	E MOVEMENT FLOC	R TOLERANCES ±นี	t			TR34 3rd Edi	tion conver	t into FF/FL	±값				
Floor Classification	Property II (mm)	Property IV (mm)	Property II (mm)	Property IV (mm)	등급	Prop	perty II	Prop	erty IV	OAFF	OAEI	MLFF	NALEL	
Floor Classification	95% limit	95% limit	100% limit	100% limit	<u></u>	95%(mm)	100%(mm)	95%(mm)	100%(mm)	UAFF	OAFL	IVILEE	IVILFL	
FM1	2.5	4.5	4.0	7.0	FM1	2.5	4.0	4.5	7.0	31	47	18.6	28.2	
FM2(special)	3.0	6.5	4.5	10.0	FM2 Special	3.0	4.5	6.5	10.0	26	32	15.6	19.2	
FM2	3.5	8.0	5.5	12.0	FM2	3.5	5.5	8.0	12.0	22	26	13.2	15.6	
FM3	5.0	10.0	7.5	15.0	FM3	5.0	7.5	10.0	15.0	15	21	9	12.6	

6. Analysis:

						Т	R34 3rd I	Edition FRI	E MOVEN	IENT RESU	JLTS					
Run #:		89	90	91	92			į					i			All Runs
Run Length (m):		7.80	7.80	7.80	7.80	 <u> </u>				<u> </u>			 			31.20
	Property II (100%)	YES	YES	YES	YES		İ					İ				YES
FM1	% Defective	0.00%	0.00%	0.00%	0.00%											0.00%
FIVII	Property IV (100%)	YES	YES	YES	NO	Ī										NO
	% Defective	0.00%	0.00%	0.00%	6.25%	ļ				ļ						1.56%
	Property II (100%)	YES	YES	YES	YES											YES
F14245 : IX	% Defective	0.00%	0.00%	0.00%	0.00%											0.00%
FM2(Special)	Property IV (100%)	YES	YES	YES	YES	 T	<u> </u>			1	<u> </u>					YES
	% Defective	0.00%	0.00%	0.00%	0.00%					•						0.00%
	Property II (100%)	YES	YES	YES	YES											YES
FM2	% Defective	0.00%	0.00%	0.00%	0.00%											0.00%
FIVIZ	Property IV (100%)	YES	YES	YES	YES	 T				1			 		<u> </u>	YES
	% Defective	0.00%	0.00%	0.00%	0.00%					•						0.00%
	Property II (100%)	YES	YES	YES	YES											YES
	% Defective	0.00%	0.00%	0.00%	0.00%											0.00%
FM3	Property IV (100%)	YES	YES	YES	YES	 Ť	<u> </u>		Ť	<u> </u>	Ť				T T	YES
	% Defective	0.00%	0.00%	0.00%	0.00%											0.00%

FM2(Special) the floor tolerance requirements. 7. Summary: The analysed D-Meter® Runs satisfy

