TR34 (3rd edition) Free Movement Floor Tolerance Report

Allen Face Europe TR34 Analysis, ©Allen Face Europe, www.allenface-europe.com

1. Project Name: 방초리

2. Concrete Floor Installer:

5. Floor Tolerance Requirements:

3. Testing Organization:

안성시 일죽 방초리 221 **Project Location:**

인천광역시

일도티씨에스㈜

지상1층 #4 4. Slab ID:

#REF! Date of Pouring: Date of Testing: 2024-03-06

D-Meter® Manufactured by Allen Face&Company, Serial Number: 098 **Test Apparatus:**

Testing Technician: TAEHYUN LEE (ALLEN FACE KOREA)

ALLENFACE KOREA

ALLEN FACE KOREA			Test Area	89 m ² (for test area organization see attached drawing)									
TR3	TR34 3rd Edition convert into FF/FL ±값												
Floor Classification	Property II (mm)	Property IV (mm)	Property II (mm)	Property IV (mm)	등급	Property II		Property IV		OAFF	OAFL	MLFF	MLFL
Floor Classification	95% limit	95% limit	100% limit	100% limit	ਰਜ	95%(mm)	100%(mm)	95%(mm) 100%(mm)		UAFF	UAFL	IVILEE	IVILIT
FM1	2.5	4.5	4.0	7.0	FM1	2.5	4.0	4.5	7.0	31	47	18.6	28.2
FM2(special)	3.0	6.5	4.5	10.0	FM2 Special	3.0	4.5	6.5	10.0	26	32	15.6	19.2
FM2	3.5	8.0	5.5	12.0	FM2	3.5	5.5	8.0	12.0	22	26	13.2	15.6
FM3	5.0	10.0	7.5	15.0	FM3	5.0	7.5	10.0	15.0	15	21	9	12.6

6. Analysis:

						Т	R34 3rd I	Edition FRI	EE MOVEN	IENT RESU	JLTS				
Run #:		37	38	39	40			į	i				1		All Runs:
Run Length (m):		9.90	9.90	9.90	9.90								 		39.60
	Property II (95%)	NO	YES	YES	YES	İ	İ				İ				YES
FM1	% Defective	6.45%	0.00%	3.23%	3.23%									•	3.23%
FIVI	Property IV (95%)	NO	YES	NO	YES						<u> </u>		 		 NO
	% Defective	30.43%	0.00%	26.09%	4.35%						ļ	İ		•	15.22%
	Property II (95%)	YES	YES	YES	YES	•	•				•				YES
FN42/Ci-l)	% Defective	3.23%	0.00%	3.23%	0.00%						İ				1.61%
FM2(Special)	Property IV (95%)	YES	YES	NO	YES	 <u> </u>									 YES
	% Defective	4.35%	0.00%	8.70%	0.00%										3.26%
	Property II (95%)	YES	YES	YES	YES										YES
FM2	% Defective	3.23%	0.00%	3.23%	0.00%	İ	İ				İ				1.61%
FM2	Property IV (95%)	YES	YES	YES	YES	 ·			T	1			 	 <u> </u>	 YES
	% Defective	0.00%	0.00%	4.35%	0.00%										1.09%
	Property II (95%)	YES	YES	YES	YES										YES
FM3	% Defective	0.00%	0.00%	0.00%	0.00%										0.00%
	Property IV (95%)	YES	YES	YES	YES										 YES
	% Defective	0.00%	0.00%	0.00%	0.00%										0.00%

7. Summary: The analysed D-Meter® Runs satisfy FM2(Special) the floor tolerance requirements.

TR34 (3rd edition) Free Movement Floor Tolerance Report

Allen Face Europe TR34 Analysis, ©Allen Face Europe, www.allenface-europe.com

1. Project Name: 방초리

2. Concrete Floor Installer:

5. Floor Tolerance Requirements:

3. Testing Organization:

안성시 일죽 방초리 221 **Project Location:**

인천광역시

일도티씨에스㈜

지상1층 #4 4. Slab ID:

#REF! Date of Pouring: 2024-03-06 Date of Testing:

D-Meter® Manufactured by Allen Face&Company, Serial Number: 098 **Test Apparatus:**

Testing Technician: TAEHYUN LEE (ALLEN FACE KOREA)

ALLENFACE KOREA

ALLEN FACE KOREA			:	89 m² (for test area organization see attached drawing)									
TR3	TR34 3rd Edition convert into FF/FL ±값												
Floor Classification	Property II (mm)	Property IV (mm)	Property II (mm)	Property IV (mm)	등급	Property II		Property IV		OALL	OAFL	MILL	MILL
FIOOI Classification	95% limit	95% limit	100% limit	100% limit	ਰਜ	95%(mm)	100%(mm)	95%(mm)	100%(mm)	UAFF	UAFL	IVILFF	IVILEL
FM1	2.5	4.5	4.0	7.0	FM1	2.5	4.0	4.5	7.0	31	47	18.6	28.2
FM2(special)	3.0	6.5	4.5	10.0	FM2 Special	3.0	4.5	6.5	10.0	26	32	15.6	19.2
FM2	3.5	8.0	5.5	12.0	FM2	3.5	5.5	8.0	12.0	22	26	13.2	15.6
FM3	5.0	10.0	7.5	15.0	FM3	5.0	7.5	10.0	15.0	15	21	9	12.6

6. Analysis:

							Т	R34 3rd I	Edition FRI	E MOVEN	IENT RESU	JLTS					
Run #:		37	38	39	40				į			1					All Run
Run Length (m):		9.90	9.90	9.90	9.90						<u> </u>				 		39.60
	Property II (100%)	NO	YES	NO	YES											i i	NO
FM1	% Defective	3.23%	0.00%	3.23%	0.00%												1.61%
FIVII	Property IV (100%)	YES	YES	NO	YES		T						 		 	<u> </u>	NO
	% Defective	0.00%	0.00%	4.35%	0.00%	<u> </u>					ļ						1.09%
	Property II (100%)	YES	YES	YES	YES												YES
FN42/C	% Defective	0.00%	0.00%	0.00%	0.00%												0.00%
FM2(Special)	Property IV (100%)	YES	YES	YES	YES						1	<u> </u>	 		 	<u> </u>	YES
	% Defective	0.00%	0.00%	0.00%	0.00%	<u> </u>					•						0.00%
	Property II (100%)	YES	YES	YES	YES												YES
FM2	% Defective	0.00%	0.00%	0.00%	0.00%												0.00%
FIVIZ	Property IV (100%)	YES	YES	YES	YES						1		 		 	t <u>†</u> -	YES
	% Defective	0.00%	0.00%	0.00%	0.00%						•						0.00%
	Property II (100%)	YES	YES	YES	YES												YES
5142	% Defective	0.00%	0.00%	0.00%	0.00%												0.00%
FM3	Property IV (100%)	YES	YES	YES	YES	Ì	Ť			Ť	<u> </u>	Ť	<u> </u>	<u></u>	<u> </u>	i	YES
	% Defective	0.00%	0.00%	0.00%	0.00%												0.00%

FM2(Special) the floor tolerance requirements. 7. Summary: The analysed D-Meter® Runs satisfy