2022년 IoT기반 스마트 솔루션 개발자 양성과정



Embedded Application

4-ATmel Studio 7

담당 교수 : 윤 종 이
010-9577-1696
ojo1696@naver.com
https://cafe.naver.com/yoons2022

충북대학교 공동훈련센터

www.microchip.com



Request a Quote for High-Volume Pricing

Find a product

Explore an application

Start developing

Design Week 2022

Join us online for our free virtual event from April 26 - 28, 2022, to elevate your Artificial Intelligence/Machine Learning (AI/ML), embedded connectivity

Adopt SiC with Ease, Speed and Confidence

Eliminate design compromises and reduce complexity in high-voltage switching solutions with

Secure Position, Navigation and Time (PNT) Solutions

Time is the cornerstone of all Secure PNT solutions and we

MPLAB® Code Configurator - Unified Configurator for all MCUs

Microchip Studio for AVR



MICROCHIP | Products | Solutions | Tools and Resources | Support | Education | About | Order Now

- Dev Tool Deals
- Reference Designs
- Search and Discover
- Configure
- Develop
- Debug
- Evaluation Boards
- Qualify
- Production
- Documentation
- Archives

Browse Develop

Analog Development Tool Ecosystem

MPLAB® Analog Designer

MPLAB® Mindi™ Analog Simulator

Analog and Interface Treelink Selection Tool

Ensemble Graphics Toolkit

K2L Automotive Tools

OptoLyzer® Studio

OptoLyzer® Tool MOCCA Family

MOST150 Slim Board Family

INICnet™ Technology 50utp Slim Board Family

Microchip Studio for AVR® and SAM Devices

AVR® and SAM MCU Downloads Archive

Microchip Gallery

MPLAB® Cloud Tools Ecosystem

MPLAB® Device Blocks for Simulink®

MPLAB® PowerSmart™ Development Suite

MPLAB® X IDE

MPLAB® Ecosystem Downloads Archive

Microchip Studio



Tools and Resources / Develop / Microchip Studio for AVR® and SAM Devices
Key Features
Getting Started
Downloads

Microchip Studio for AVR® and SAM Devices

Microchip Studio is an Integrated Development Environment (IDE) for developing and debugging AVR® and SAM microcontroller applications. It merges all of the great features and functionality of Atmel Studio into Microchip's well-supported portfolio of development tools to give you a seamless and easy-to-use environment for writing, building and debugging your applications written in C/C++ or assembly code. Microchip Studio can also import your Arduino® sketches as C++ projects to provide you with a simple transition path from makerspace to marketplace.

You can use Microchip Studio with the debuggers, programmers and development kits that support AVR and SAM devices. Extend your development environment with Microchip Gallery, an online app store for Microchip Studio plug-ins developed by Microchip as well as third-party tool and embedded software vendors.

Even though it comes with a new name and look, you will still be able to use any existing documentation and videos about Atmel Studio to learn how to use Microchip Studio.

Please refer to this link for information about our security advisories.

Atmel Studio 7 Down Load



Downloads and Documents

Download Microchip Studio

Title	Date	Download
Microchip Studio for AVR and SAM Devices v7.0.2542 Offline Installer	24 Jan 2022	Download
Microchip Studio for AVR and SAM Devices v7.0.2542 Web Installer	24 Jan 2022	Download

Release Notes

Title	Date	Download
Microchip Studio Release Notes	09 Nov 2020	Download
Microchip Studio for AVR and SAM Devices 7.0.2542 Web Installer	01 Nov 2020	Download

setup install



Microchip Studio for AVR and SAM Devices

Microchip Studio

Select Architecture

☑ AVR

☑ UC3

☑ SAM

Unchecking a component will uninstall it if it was previously installed.



Microchip Studio for AVR and SAM Devices

Microchip Studio

Installing...

Please wait while setup installs Microchip Studio on your computer

Package: Microchip Studio Development Environment Applying

Details

Initializing environment



Microchip Studio for AVR and SAM Devices

Microchip Studio

Installation complete

Thank you for choosing Microchip Studio!

☑ Launch Microchip Studio

System Requirements

- **Supported Operating Systems**
  - Windows 7 Service Pack 1 or higher
  - Windows Server 2008 R2 Service Pack 1 or higher
  - Windows 8/8.1
  - Windows Server 2012 and Windows Server 2012 R2
  - Windows 10
- **Supported Architectures**
  - 32-bit (x86)
  - 64-bit (x64)
- **Hardware Requirements**
  - A computer that has a 1.6 GHz or faster processor
  - RAM
    - 1 GB RAM for x86
    - 2 GB RAM for x64
    - An additional 512 MB RAM if running in a Virtual Machine
  - 6 GB available hard disk space

Start Page



Start Page - Microchip Studio (Administrator)

Discover Microchip Studio for AVR® and SAM Devices

Start

- New Project...
- New Example Project...
- Open Project...

Recent

- V461_LED
- V474

□ Keep page open after project load
☑ Show page on startup

- Getting started with Microchip Studio
- Getting started with AVR development
- Upgrade to MPLAB® XC8 C PRO compiler for AVR® microcontrollers for r
- Open START Configurator
- Download Microchip Studio Extensions
- Download documentation
- Open Microchip Production Center

New Project



새 프로젝트

▷ 최근 항목

◢ 설치됨

- C/C++
- Assembler
- AtmelStudio Solution

정렬 기준: 기본값

설치된 템플릿 검색(Ctrl+E)

GCC C ASF Board Project	C/C++
GCC C Executable Project	C/C++
GCC C Static Library Project	C/C++
GCC C++ Executable Project	C/C++
GCC C++ Static Library Project	C/C++
Create project from Arduino sketch	C/C++

형식: C/C++

Creates an AVR 8-bit or AVR/ARM 32-bit C project

이름(N):	GccApplication1	
위치(L):	c:₩users₩jiyoon₩Documents₩Atmel Studio₩7.0	찾아보기(B)...
솔루션 이름(M):	GccApplication1	□ 솔루션용 디렉터리 만들기(D)

Device Selection



Device Selection

Device Family: All

Search for device

Name	App./Boot Memory (Kbytes)	Data Memory (bytes)	EEPROM (by
ATA8515	N/A	1024	1153
ATBTLC1000WLCSP	N/A	139264	N/A
ATmega128	128	4096	4096
ATmega1280	128	8192	4096
ATmega1281	128	8192	4096
ATmega1284	128	16384	4096
ATmega1284P	128	16384	4096
ATmega1284RFR2	128	16384	4096
ATmega128A	128	4096	4096
ATmega128RFA1	128	16384	4096
ATmega128RFR2	128	16384	4096
ATmega16	16	1024	512
ATmega162	16	1024	512
ATmega164A	16	1024	512
ATmega164P	16	1024	512
ATmega164PA	16	1024	512
ATmega165A	16	1024	512
ATmega165P	16	1024	512
ATmega165PA	16	1024	512

Device Info:

Device Name:	ATmega128A
Speed:	N/A
Vcc:	N/A
Family:	ATmega

Datasheet (Summary)

Device Page

Supported Tools

- Atmel-ICE
- AVR Dragon
- AVRISP mkII
- AVR ONE!
- EDBG
- EDBG MSD
- JTAGICE3

main.c



GccApplication1 - Microchip Studio (Administrator)

D:₩AworkCom₩학사업무₩2022학사₩충북대학교₩AVR₩Program₩GccApplication1₩main.c

```
/*
 * GccApplication1.c
 *
 * Created: 2022-04-12 오후 7:25:01
 * Author : user
 */

#include <avr/io.h>


int main(void)
{
    /* Replace with your application code */
    while (1)
    {
    }
}

```

Debug | ATmega128 | None on | USARTC0_BAUDCTRLB

Solution 'GccApplication1' (1 project)
- GccApplication1
  - Dependencies
  - Output Files
  - Libraries
  - main.c

Error List: Entire Solution | 0 Errors | 0 Warnings | 0 Messages | Build + IntelliSense

IDE Window



Menu

ToolBar

소스코드 탭

출력창

솔루션탐색기

GccApplication1 - AtmelStudio (관리자)
Standard Mode
빠른 실행(Ctrl+Q)
파일(F) 편집(E) 보기(V) 프로젝트(P) 빌드(B) 디버그(D) 도구(T) 도움말(H)
Debug
ATmega128
No Tool
main.c
c:₩users₩jiyoon₩Documents₩Atmel Studio₩7.0₩GccApplication1₩main.c
Go
솔루션 탐색기
솔루션 탐색기 검색(Ctrl+;)
솔루션 'GccApplication1' (1개 프로젝트)
GccApplication1
Dependencies
Output Files
Libraries
main.c
출력
출력 보기 선택(S): 빌드
오류 목록 작업 목록 출력
준비
줄: 1 열: 1 문자: 1 INS

```
/*
 * GccApplication1.c
 *
 * Created: 2016-03-23 오후 4:48:10
 * Author : Jiyoon
 */

#include <avr/io.h>


int main(void)
{
    /* Replace with your application code */
    while (1)
    {
    }
}
```

```
빌드했습니다.
========== 빌드: 성공 또는 최신 상태 1, 실패 0, 생략 0 ==========
```

Add Defined Symbols



Configuration: Active (Debug)

Platform: Active (AVR)

AVR/GNU C Compiler ➡ Symbols

Defined symbols (-D)

DEBUG

Add Defined symbols (-D)

Defined symbols (-D)

F_CPU=14745600UL

F_CPU=1474560
0UL

Program Coding



```c
/*
 * LED_Out.c
 *
 * Created: 2022-04-17 오전 10:12:18
 * Author : user
 */

#include <avr/io.h>
#include <util/delay.h>

int main(void)
{
    DDRB=0xff;

    while (1)
    {
        PORTB=0x66;
        _delay_ms(500);

        PORTB=0x99;
        _delay_ms(500);
    }
}
```

Build



```
Target "PreBuildEvent" skipped, due to false condition; ('$(PreBuildEvent)'!='') was evaluated as (''!='').
Target "CoreBuild" in file "C:₩Program Files (x86)₩Atmel₩Studio₩7.0₩Vs₩Compiler.targets" from project "D:₩AworkCom₩학사업무₩2022학사₩충북대학교₩AVR₩Program₩B_Port_LED₩LEC
    Using "RunCompilerTask" task from assembly "C:₩Program Files (x86)₩Atmel₩Studio₩7.0₩Extensions₩Application₩AvrGCC.dll".
    Task "RunCompilerTask"
        Shell Utils Path C:₩Program Files (x86)₩Atmel₩Studio₩7.0₩shellUtils
        C:₩Program Files (x86)₩Atmel₩Studio₩7.0₩shellUtils₩make.exe all --jobs 4 --output-sync
        Building file: ../main.c
        Invoking: AVR/GNU C Compiler : 5.4.0
        "C:₩Program Files (x86)₩Atmel₩Studio₩7.0₩toolchain₩avr8₩avr8-gnu-toolchain₩bin₩avr-gcc.exe"  -x c -funsigned-char -funsigned-bitfields -DDEBUG -DF_CPU=14745600  -
        Finished building: ../main.c
        Building target: LED_Out.elf
        Invoking: AVR/GNU Linker : 5.4.0
        "C:₩Program Files (x86)₩Atmel₩Studio₩7.0₩toolchain₩avr8₩avr8-gnu-toolchain₩bin₩avr-gcc.exe" -o LED_Out.elf  main.o   -Wl,-Map="LED_Out.map" -Wl,--start-group -Wl,
        Finished building target: LED_Out.elf
        "C:₩Program Files (x86)₩Atmel₩Studio₩7.0₩toolchain₩avr8₩avr8-gnu-toolchain₩bin₩avr-objcopy.exe" -O ihex -R .eeprom -R .fuse -R .lock -R .signature -R .user_signat
        "C:₩Program Files (x86)₩Atmel₩Studio₩7.0₩toolchain₩avr8₩avr8-gnu-toolchain₩bin₩avr-objcopy.exe" -j .eeprom  --set-section-flags=.eeprom=alloc,load --change-sectic
        "C:₩Program Files (x86)₩Atmel₩Studio₩7.0₩toolchain₩avr8₩avr8-gnu-toolchain₩bin₩avr-objdump.exe" -h -S "LED_Out.elf" > "LED_Out.lss"
        "C:₩Program Files (x86)₩Atmel₩Studio₩7.0₩toolchain₩avr8₩avr8-gnu-toolchain₩bin₩avr-objcopy.exe" -O srec -R .eeprom -R .fuse -R .lock -R .signature -R .user_signat
        "C:₩Program Files (x86)₩Atmel₩Studio₩7.0₩toolchain₩avr8₩avr8-gnu-toolchain₩bin₩avr-size.exe" "LED_Out.elf"
           text    data     bss     dec     hex filename
            212       0       0     212      d4 LED_Out.elf
    Done executing task "RunCompilerTask".
    Using "RunOutputFileVerifyTask" task from assembly "C:₩Program Files (x86)₩Atmel₩Studio₩7.0₩Extensions₩Application₩AvrGCC.dll".
    Task "RunOutputFileVerifyTask"
                Program Memory Usage    :   212 bytes   0.2 % Full
                Data Memory Usage       :   0 bytes   0.0 % Full
                Warning: Memory Usage estimation may not be accurate if there are sections other than .text sections in ELF file
    Done executing task "RunOutputFileVerifyTask".
Done building target "CoreBuild" in project "LED_Out.cproj".
Target "PostBuildEvent" skipped, due to false condition; ('$(PostBuildEvent)' != '') was evaluated as ('' != '').
Target "Build" in file "C:₩Program Files (x86)₩Atmel₩Studio₩7.0₩Vs₩Avr.common.targets" from project "D:₩AworkCom₩학사업무₩2022학사₩충북대학교₩AVR₩Program₩B_Port_LED₩LED_C
Done building target "Build" in project "LED_Out.cproj".
Done building project "LED_Out.cproj".

Build succeeded.
========== Build: 1 succeeded or up-to-date, 0 failed, 0 skipped ==========
```

Output Files



```
E Å . . K Å . . I Å . . G Å . .        :1000000045C000004BC0000049C0000047C00000D0
E Å . . C Å . . A Å . . ? Å . .        :1000100045C0000043C0000041C000003FC00000D8
= Å . . ; Å . . 9 Å . . 7 Å . .        :100020003DC000003BC0000039C0000037C00000E8
5 Å . . 3 Å . . 1 Å . . / Å . .        :1000300035C0000033C0000031C000002FC00000F8
- Å . . + Å . . ) Å . . ' Å . .        :100040002DC000002BC0000029C0000027C0000008
% Å . . # Å . . ! Å . . . Å . .        :1000500025C0000023C0000021C000001FC0000018
. Å . . . Å . . . Å . . . Å . .        :100060001DC000001BC0000019C0000017C0000028
. Å . . . Å . . . Å . . . Å . .        :1000700015C0000013C0000011C000000FC0000038
. Å . . . Å . . . Å . . . $ . ¾        :100080000DC000000BC0000009C0000011241FBEFD
Ï ï Ð á Þ ¿ Í ¿ . Ð . Å ± Ï .         :10009000CFEFD0E1DEBFCDBF02D01AC0B1CF85E532
. » . å . ê . » / ï 9 æ H á ! P        :1000A00084BB95E58AEA95BB2FEF39E648E12150FC
0 @ @ @ á ÷ . Å . . . » / ï 9 æ        :1000B00030404040E1F700C0000085BB2FEF39E63B
H á ! P 0 @ @ @ á ÷ . Å . . ë Ï        :1000C00048E1215030404040E1F700C00000EBCF54
ø . ÿ Ï                                :04000D000F894FFCFD2
No data for this line                  :00000001FF
```

충북대학교 공동훈련센터

Wiring



장치관리자



- RND7
  - Atmel
    - AVRISP mkII
  - IDE ATA/ATAPI 컨트롤러
  - WSD 인쇄 공급자
  - 네트워크 어댑터
  - 디스크 드라이브
  - 디스플레이 어댑터
  - 마우스 및 기타 포인팅 장치
  - 모니터
  - 범용 직렬 버스 컨트롤러
  - 사운드, 비디오 및 게임 컨트롤러
  - 센서
    - Microsoft Visual Studio Location Simulator Sensor
  - 소프트웨어 장치
  - 시스템 장치
  - 오디오 입력 및 출력
  - 이미징 장치
  - 인쇄 대기열
  - 저장소 컨트롤러
  - 컴퓨터
  - 키보드
  - 포트(COM & LPT)
    - 통신 포트(COM1)
    - 프린터 포트(LPT1)
  - 프로세서

Device programming

- [Tool]-[Device programming]



AVRISP mkII (000200212345) - Device Programming

Tool: AVRISP mkII

Device: ATmega128A

Interface: ISP

Device signature: 0x1E9702

Target Voltage: 3.3 V

ISP Clock: 125 kHz

The ISP Clock frequency must be lower than 1/4 of frequency the device is operating on.

```
Reading device ID...OK
```

Reading device ID...OK

Fuses



Fuse Name	Value
EXTENDED.M103C	☐
EXTENDED.WDTON	☐
HIGH.OCDEN	☐
HIGH.JTAGEN	☐
HIGH.SPIEN	☑
HIGH.EESAVE	☐
HIGH.BOOTSZ	Boot Flash size=4096 words start address=$F000
HIGH.BOOTRST	☐
HIGH.CKOPT	☑
LOW.BODLEVEL	Brown-out detection level at VCC=2.7 V
LOW.BODEN	☐
LOW.SUT_CKSEL	Ext. Crystal/Resonator High Freq.; Start-up time: 16K CK + 64 ms

Lock bits



Lock Bit	Value
✓ LOCKBIT.LB	No memory lock features enabled
✓ LOCKBIT.BLB0	No lock on SPM and LPM in Application Section
✓ LOCKBIT.BLB1	No lock on SPM and LPM in Boot Section

Memories



Flash (128 KB)

c:₩users₩user₩Documents₩Atmel Studio₩7.0₩GccApplication1₩Debug₩GccApplication1.e

☑ Erase device before programming

☑ Verify Flash after programming

Advanced

EEPROM (4 KB)

☑ Verify EEPROM after programming

Advanced

Run


PB
PE
PF
PA
DC5V
USB
PG
PD
PC