

XML & DTDs

csc343, Introduction to Databases

Slides from Diane Horton, originally based on slides by Jeff Ullman

Fall 2015



UNIVERSITY OF
TORONTO

DCS50

Introduction

- The **relational model** is very rigid:
 - Everything must be a table.
 - The schema must be defined in advance.
 - Everything must conform to the schema.
- Relational DBMSs exploit this to give us data we can count on and efficient queries.
- But some data doesn't fit the model well. For example, we may have
 - missing information, and
 - indeterminate quantities.

HTML to XML

- XML grew out of HTML, and is intentionally similar:
 - Tags and attributes
 - Tree-structured format
- But there are important differences:
 - XML data must be **well-formed**.
 - You define your own **tags** and **attributes**.
 - These describe the *meaning* of the data, and imply nothing about its presentation.
 - "XML was designed to *carry* data;
HTML was designed to *display* data."

What's XML for?

- XML is great for
 - Recording data that **software** needs.
 - Exchange of information between pieces of software.
- XML is said to be “**self-describing**”.

- Example:

```
<student stnum="1234" name="Cindylou Who">  
  <address>  
    <street>99 Alfalfa Way</street>  
    <city>Whoville</city>  
  </address>  
</student>
```

Well-formed **vs** valid XML

- Well-formed XML

- Just need a single *root* element and proper *nesting* (all elements must have a closing tag).
- Any tag or attribute can go anywhere.

- Valid XML

- A valid XML must be **well-formed** + conforms to a **DTD**
- A “DTD” (**document type definition**) specifies what tags and attributes are permitted, where they can go, and how many there must be.
- A valid XML file is one that has a DTD and follows the rules specified in its DTD.

Well-formed XML

- Begin the document with a **declaration**, surrounded by `<?xml ... ?>`
- Declaration for a document that is merely well-formed (i.e., it has no DTD):
`<?xml version="1.0" standalone="yes" ?>`
- The rest of the document is a single **root tag** with tags nested inside it.

Tags



- Tags can be *matched* pairs, leaving room for text or nested tags in between. Example:

```
<tf-question qid="Q637" solution="False">  
  <question>  
    The Prime Minister, Stephen Harper,  
    is Canada's Head of State.  
  </question>  
</tf-question>
```

Tags



- Tags can be *matched* pairs, leaving room for text or nested tags in between. Example:

```
<tf-question qid="Q637" solution="False">
```

```
<question>
```

The Prime Minister, ~~Stephen Harper~~
Justin Trudeau, is Canada's Head of State.

```
</question>
```

```
</tf-question>
```

- Or they may be unmatched. Example:

```
<response qid="Q637" answer="False" />
```

Note the placement of the slash.

- Tag names are case-sensitive.

Attributes

- As we saw, an opening **tag** can have **attribute** name-value pairs within it. Example:

```
<tf-question qid="Q637" solution="False">  
  <question>  
    The Prime Minister, Justin Trudeau,  
    is Canada's Head of State.  
  </question>  
</tf-question>
```

- The pairs are separated by blanks.
- If all the information is in the attributes, the tag becomes empty.

We don't *need* to use attributes

```
<tf-question qid="Q637" solution="False">
  <question>
    The Prime Minister...
  </question>
</tf-question>
```

could become:

```
<tf-question>
  <qid>Q637</qid>
  <solution>False</solution>
  <question>
    The Prime Minister...
  </question>
</tf-question>
```

The other extreme: all data via attributes

```
<tf-question qid="Q637" solution="False">  
  <question>  
    The Prime Minister ...  
  </question>  
</tf-question>
```

could become:

```
<tf-question qid="Q637" solution="False"  
  question="The Prime Minister ..." />
```

It's a design decision

- In most cases, something in between makes more sense.
- Matched **tags** make sense when you need structure within.
- **Attributes** make sense when you want something like keys and foreign keys. (More on that later.)

Checking for well-formedness

- <http://validator.w3.org>

- `xmllint` command on cdf.

Default is to check merely for well-formedness.

- `xmllint --debug`

Outputs an annotated tree of the parsed document.


Useful for diagnosis of problems.

```
dbsrv1:~/myjdbc/xml% xmllint --debug quiz.xml
DOCUMENT
version=1.0
URL=quiz.xml
  DTD(quiz), SYSTEM quiz.dtd
    ELEMENT quiz
      TEXT compact
      content=
        ELEMENT questions
          TEXT compact
          content=
            ELEMENT mc-question
              ATTRIBUTE qid
              TEXT compact
              content=Q516
              ATTRIBUTE solution
              TEXT compact
              content=1
              TEXT compact
              content=
                ELEMENT question
                  TEXT
                  content=What do you promise when you take the oa...
```

XML documents have a tree structure

```
<?xml version="1.0" ?>
<!-- Some comment -->
<Students>
  <Student StudId="111111111" >
    <Name><First>John</First><Last>Doe</Last></Name>
    <Status>U2</Status>
    <Crstaken CrsCode="CS308" Semester="F1997" />
    <Crstaken CrsCode="MAT123" Semester="F1997" />
  </Student>
  <Student StudId="987654321" >
    <Name><First>Bart</First><Last>Simpson</Last></Name>
    <Status>U4</Status>
    <Crstaken CrsCode="CS308" Semester="F1994" />
  </Student>
</Students>
<!-- Some other comment -->
```

The document tree



Problems with merely **well-formed** XML

- There are no restrictions on
 - what tags are allowed
 - what order, nesting
 - what attributes each tag can have
 - what is mandatory and what is optional
- If a *program* is to process our XML, this information would be very useful to know..

Valid XML with DTDs

Content of a DTD

- A series of rules.
- An `ELEMENT` rule defines an element that may occur, and what can be within its opening and closing tags.
- An `ATTLIST` rule defines an attribute of an element.
- Order of the rules doesn't matter.

ELEMENT rules

- Form: `<!ELEMENT «name» («subcomponents»)>`
- *name*: the element's tag.
- *subcomponents*: can be
 - A comma-separated list of elements. Meaning: the elements must occur inside, and in the order given.
 - #PCDATA
Meaning: The element contains simply text (no subelements).
 - EMPTY
Meaning: This is an “empty” element. It may have attributes, but not matching opening & closing tags.

Examples

<!ELEMENT INGREDIENT (NAME, QUANTITY)>

<!ELEMENT NAME (#PCDATA)>

<!ELEMENT QUANTITY EMPTY>

More expressiveness for subcomponents

- We can use the pipe symbol `|` to indicate alternatives. (*something* | *something2*)
- We specify multiplicity as follows:
 - `*` means zero or more
 - `+` means one or more
 - `?` means zero or one
(i.e., the subcomponent is optional)
- We can use brackets for grouping.

ATTLIST rules

- Form:

```
<!ATTLIST «elName» «attName» «type» «optionalty» >
```

- *elname*: the element whose attribute this is.
- *attName*: the name of this attribute.
- *type*: either **CDATA** or a list of possible values, e.g., True|False.
- *optionalty*: Either **#REQUIRED** or **#IMPLIED** (which means optional).
- You can define multiple attributes at once.

```
<!ATTLIST person SIN CDATA #REQUIRED  
age CDATA #IMPLIED >
```

DTD Example

```
<!ELEMENT RECIPES (RECIPE)+>
<!ELEMENT RECIPE (INGREDIENTS, STEPS)>
<!ATTLIST RECIPE name CDATA #REQUIRED>
<!ATTLIST RECIPE type CDATA #IMPLIED>
<!ATTLIST RECIPE keywords CDATA #IMPLIED>
<!ELEMENT INGREDIENTS (INGREDIENT)+>
<!ELEMENT INGREDIENT (NAME, QUANTITY)>
<!ELEMENT NAME (#PCDATA)>
<!ELEMENT QUANTITY EMPTY>
<!ATTLIST QUANTITY amount CDATA #REQUIRED>
<!ATTLIST QUANTITY units CDATA #IMPLIED>
<!ELEMENT STEPS (STEP+)>
<!ELEMENT STEP (#PCDATA)>
```

Using a DTD

- The XML declaration must say that the document is not standalone:

```
<?xml version="1.0" standalone="no" ?>
```

- Three possible places for the DTD:
 - In the same file, between the declaration and the XML content.
 - In a separate file on the same computer. Specify the filename, or give the full or relative path.
 - At a URL.
- In all cases, you must specify what the root element will be.

DTD in the same file

```
<?xml version="1.0" standalone="no" ?>
```

```
<!DOCTYPE People [  
    <!ELEMENT People (Person*)>  
    <!ELEMENT Person (#PCDATA)>  
>
```

```
<People>
```

```
    <Person>Tommy Douglas</Person>
```

```
    <Person>Terry Fox</Person>
```

```
    <Person>Louise Arbour</Person>
```

```
    <Person>Chris Hadfield</Person>
```

```
</People>
```

DTD in another file

```
<?xml version="1.0" standalone="no" ?>  
<!DOCTYPE People SYSTEM "people.dtd">  
<People>  
    <Person>Tommy Douglas</Person>  
    <Person>Terry Fox</Person>  
    <Person>Louise Arbour</Person>  
    <Person>Chris Hadfield</Person>  
</People>
```

DTD at a URL

```
<?xml version="1.0" standalone="no" ?>  
<!DOCTYPE People SYSTEM "  
http://www.cs.utoronto.ca/xyz/people.dtd">  
<People>  
    <Person>Tommy Douglas</Person>  
    <Person>Terry Fox</Person>  
    <Person>Louise Arbour</Person>  
    <Person>Chris Hadfield</Person>  
</People>
```

“Keys” and “foreign keys”

Motivation

- Just as in the relational model, we sometimes want
 - **unique** identifiers.
 - the ability to **refer** in one place to some data in another place.
- We would like the DTD to express these rules and our tools to enforce them.
- DTDs don't have this full capability, but they do have some modest features in this direction.

Using ID to enforce uniqueness

- To specify that values must be unique:
 - Make an attribute of type ID rather than CDATA.
 - Example:
`<!ATTLIST mc-question qid ID #REQUIRED>`
- Values of ID attributes are restricted.
 - Must not begin with a digit.
 - Must not have blanks.

Limitations of ID

- Uniqueness is enforced across *all* IDs in the file.
- Example: If within quiz.xml:
 - questions have an ID attribute called `qid` and
 - students have an ID attribute called `sid`.
- Implications:
 - If two questions have the same `qid`, or if two students have the same `sid`, is considered an error. ✓
 - If a question's `qid` is the same as a student's `sid`, this is considered an error. ✗

Quiz.xml (Example)

```
<?xml version="1.0" standalone="no" ?>
<!DOCTYPE Quiz SYSTEM "quiz.dtd">
<Quiz quizID="csc343" title="Homework Set 1">
  <Question QID="N-15" weight="2"/>
  <Question QID="TF-01" weight="1"/>
  <Question QID="MC-05" weight="3"/>
  <Question QID="MC-08" weight="2"/>
</Quiz>
```


Quiz.dtd Example

```
<!ELEMENT Quiz (Question+)>
<!ATTLIST Quiz quizID CDATA #REQUIRED>
<!ATTLIST Quiz title CDATA #REQUIRED>
<!ATTLIST Quiz hints (yes|no) #REQUIRED>
<!ELEMENT Question EMPTY>
<!ATTLIST Question QID ID #REQUIRED>
<!ATTLIST Question weight CDATA #REQUIRED>
```

Using IDREF to enforce referential integrity

- To specify that a value must refer to some ID:
 - Make an attribute of type `IDREF`.
 - Example:
`<!ATTLIST response qid IDREF #REQUIRED>`
 - We can allow an attribute to have a *list* of values, each of which references some ID:
`<!ATTLIST response qid IDREFS #REQUIRED>`

Limitations of IDREF

- An IDREF attribute needs only to refer to **any ID** in the file, not specifically to one of a particular type.
- Example: In quiz.xml,
 - If a response has a `qid` that is an IDREF
- **Implications:**
 - If a response's `qid` refers to nothing, this is considered an error. ✓
 - If a response's `qid` refers to a student's `sid`, this is considered fine. ✗

Checking for validity

- `xmllint --valid` command on cdf.

Limitations of DTDs

- **ID** and **IDREF** are a pale imitation of keys and foreign keys.
 - All ID values are treated as a single set.
- **ID** and **IDREF** only work within a single file.
 - References to an ID in another file are flagged as errors.
 - Duplicate ID values across files cannot be detected.
- There are no other types of constraints.
- The only data type is string.
- It is very inconvenient to specify contents but allow them in any order.

XML Schema

- XML Schema has greater expressive power.
 - Rich set of built-in types, plus user-defined types
 - Finer control over sequences of sub-elements.
 - More effective keys and foreign keys
- It is also much more complex.
- Note: XML Schema Definitions (XSDs) are themselves XML documents.
 - They describe “elements” and
 - the things doing the describing are themselves “elements”.