

CSC108H Lists and While Loops Lab

At the end of the lab, please show your work to your TA and return this handout. As usual, we will post the handout on the course website at the end of the week.

1 Objectives

- Practice manipulating lists using indexing, slicing and list methods
- Practice using `while`

2 Lists

In this section, you will write short functions or statements that involve lists. In most of the exercises, you will need to use list methods so that you can become familiar with the tools available to you. Remember to use the Python functions `dir` and `help` to get information about methods.

1. Type this assignment statement into the Python shell:

```
names = ['Bob', 'Ho', 'Zahara', 'Amitabha', 'Dov', 'Maria']
```

For the following steps, use `names` and slice notation:

- (a) Write a slicing expression that produces this new list: `['Zahara', 'Amitabha', 'Dov']`
 - (b) Write a slicing expression that produces this new list: `['Bob']`
 - (c) Write a slicing expression that produces this new list: `['Amitabha', 'Dov', 'Maria']`
2. Given a list `L` and a value `v`, write an expression that removes the first occurrence of `v` from `L`. Remember that slicing always returns a new list and you want change `L`. You can do this with either slicing or with a list method.
 3. Write an expression that adds the string "How are you?" to the **front** of the list `["I am well. "]` so that you end up with the list `["How are you?", "I am well. "]`

Switch driver and navigator.

4. Write code that turns `[2, 4, 99, 0, -3.5, 86.9, -101]` into `[99, 86.9, 4, 2, 0, -3.5, -101]`. You should use just two method calls.
5. Write a function `every_third` that takes a list as a parameter and returns a new list that contains every third element of the original list, starting at index 0. For example, the call `every_third(1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11)` should return `[1, 4, 7, 10]`. Don't use slice notation.
6. Write a function `every_ith` that takes a list `L` and an integer `i` as parameters and returns a list consisting of every *i*th element of `L`, starting at index 0. Don't use slice notation.

Show your TA your work and continue with the `while` exercises in the next section.

3 while loops

Use `while` loops to complete the following functions. Do *not* use `for` loops and do *not* use list methods.

<code>print_list:</code> (list) -> NoneType	Print the elements of the list on different lines. The list is unchanged.
<code>print_list_even:</code> (list) -> NoneType	Print the elements of the list that occur at even indices. The list is unchanged.
Switch driver and navigator.	
<code>print_list_reverse:</code> (list) -> NoneType	Print the elements of list from the end of the list to the front. The list is unchanged.
<code>sum_elements:</code> (list of ints) -> int	Sum the elements of the list, starting from the front of list, until the total is over 100 or the end of the list is reached, and return the sum at that point. Do not change the list.
<code>duplicates:</code> (list) -> bool	Return True iff the list contains at least two adjacent elements with the same value. For example, <code>duplicates([1,1,2])</code> returns True and <code>duplicates([1,2,1])</code> returns False.

4 Nested Lists

List elements may be lists themselves. When this happens it is called a *nested list* or a *list of lists*:

```
pets = [["Shoji", "cat", 18], ["Hanako", "dog", 15], ["Sir Toby", "cat", 10],
        ["Sachiko", "cat", 7], ["Sasha", "dog", 3], ["Lopez", "dog", 13]]
```

We can access each element of list `pets` using its index:

```
>>> pets[3]
["Sachiko", "cat", 7]
```

We can also access elements of the inner lists. For example, since `pets[3]` refers to a list, we can use `pets[3]` to access the element at position 2:

```
>>> pets[3][2]
7
```

This is saying that element 2 of element 3 of the list `pets` (the age of the cat named “Sachiko”) is 7.

Write the following for loops and functions and call each function to verify your work.

1. Write a for loop that prints each list from list `pets` on a separate line.
2. Write a for loop that prints the second element of each inner list in list `pets` on a separate line.

Switch driver and navigator.

3. Write a for loop that examines list `pets` and computes the number of dogs in the list.
4. Write a for loop that examines list `pets` and computes the sum of the ages of the animals in the list. Ages are the third element of the inner lists.
5. Write a function `nested_lengths` that takes a list `L` as a parameter and returns a list of the lengths of the sublists. For example if `L=[[1,2],['a','b'],'c']`, calling the function on `L` would return the list `[2,3]`.

Show your TA your work so that you can get credit for the lab.