

STA414 Assignment 2


Problem 5

Yuhao Zhao
999878342


February 9, 2015

1 Data Plot

To see how the data looks like, we first visualize the dataset. First we should convert each line of the datafile into a 8×8 Matrix, and then plot it as an image. As required, 25 plots were obtained below for both the 3 and 5 data.



1) Data plot for 3



2) Data plot for 5

2 Method Classification

From the question 4 we have derived that:

1. $p(C_k) = P(t = k) = \pi_k = \frac{N_k}{N}$
2. $p(x|t = k, \mu_k, \Sigma_k) = (2\pi)^{-D/2} |\Sigma|^{1/2} \exp(-\frac{1}{2}(x_n - \mu_k)^T \Sigma^{-1} (x_n - \mu_k))$,
where $\mu_k = \frac{1}{N_k} \sum_{n=1}^N t_{nk} x_n$
3. The log posterior
 $\ln p(t = k|x) = \ln(p(x|t = k, \mu_k, \Sigma_k) \pi_k) - \ln(p(x|t = 0, \mu_0, \Sigma_0) \pi_0 + p(x|t = 1, \mu_1, \Sigma_1) \pi_1)$
4. $\Sigma_k = \frac{1}{N_k} \sum_{n=1}^N t_{nk} (x_n - \mu_k)(x_n - \mu_k)^T$

3 Output analysis

Table below shows the average conditional probability of Test set and training set

Average Log Conditional Probability of Training data

	Conditional Gaussian	Regularized Conditional Gaussian
Number 3	-0.135151472698277	-0.049105198331912
Number 5	-0.276712498340588	-0.053870587663031
Overall	-0.205931985519433	-0.051487892997471

Average Log Conditional Probability of Test data

	Conditional Gaussian	Regularized Conditional Gaussian
Number 3	-0.032987865886690	-0.006468977130022
Number 5	-1.262579785698999	-0.212511104167940
Overall	-0.647783825792844	-0.109490040648981

Table below shows the training and testing error for the two different classifier

Error Counts and Rate of Training Data

	Conditional Gaussian		Regularized Conditional Gaussian	
	Error Count	Error Rate	Error Count	Error Rate
Number 3	5.0000	0.0125	3.0000	0.0075
Number 5	6.0000	0.0100	4.0000	0.0067
Overall	11.0000	0.0138	7.0000	0.0088

Error Counts and Rate of Testing Data

	Conditional Gaussian		Regularized Conditional Gaussian	
	Error Count	Error Rate	Error Count	Error Rate
Number 3	2.0000	0.0100	0	0
Number 5	9.0000	0.0450	6.0000	0.0300
Overall	11.0000	0.0275	6.0000	0.0150

From the result, it's obvious that regularization helps to reduce the overall error rate on both training data and testing data. In addition, we notice that the error rate for Number 3 is smaller than the error rate for Number 5 in both dataset and classifiers.

4 Appendic

```
train = textread('digitstrain.txt','','delimiter',' ');
test = textread('digitstest.txt','','delimiter',' ');
zero = [];
one = [];
for i = 1:length(train)
    if train(i,65) == 0;
        zero = [zero;train(i,:)];
    else
        one = [one;train(i,:)];
    end
end

figure;
for i = 1:25
    temp = vec2mat(zero(i,1:64),8);
    subplot(5,5,i)
    imagesc(temp);
    colormap(gray);
end

figure;
for i = 1:25
    temp = vec2mat(one(i,1:64),8);
    subplot(5,5,i)
    imagesc(temp);
    colormap(gray);
end

%MLE SOLUTION
N = length(train);
N5 = sum(one(:,65));
N3 = N - N5;
pi3 = N3/N;
pi5 = N5/N;
mu3 = sum(zero(:,1:64))/N3;
mu5 = sum(one(:,1:64))/N5;

%Determine the sigma matrix
S3 = zeros(64);
S5 = zeros(64);
for i=1:N3
    S3 = S3 + transpose(zero(i,1:64)-mu3)*(zero(i,1:64)-mu3);
end
```

```

S3 = S3/N3;

for i=1:N5
    S5 = S5 + transpose(one(i,1:64)-mu5)*(one(i,1:64)-mu5);
end
S5 = S5/N5;

%Regularization
S3_r = S3 + 0.01*eye(64) ;
S5_r = S5 + 0.01*eye(64) ;

%main
train_Cond = zeros(1,N);
train_RCond = zeros(1,N);
test_Cond = zeros(1,length(test));
test_RCond = zeros(1,length(test));

for i = 1:N
    train_Cond(i) = lnp_t(train(i,1:64),train(i,65),S3,S5,mu3,mu5);
    train_RCond(i) = lnp_t(train(i,1:64),train(i,65),S3_r,S5_r,mu3,mu5);

end
N_t = length(test);
for i = 1:N_t
    test_Cond(i) = lnp_t(test(i,1:64),test(i,65),S3,S5,mu3,mu5);
    test_RCond(i) = lnp_t(test(i,1:64),test(i,65),S3_r,S5_r,mu3,mu5);

end
train_Cond_3 = mean(train_Cond(find(train(:,65)==0)));
train_Cond_5 = mean(train_Cond(find(train(:,65)==1)));
train_RCond_5 = mean(train_RCond(find(train(:,65)==1)));
train_RCond_3 = mean(train_RCond(find(train(:,65)==0)));

test_Cond_3 = mean(test_Cond(find(test(:,65)==0)));
test_Cond_5 = mean(test_Cond(find(test(:,65)==1)));
test_RCond_5 = mean(test_RCond(find(test(:,65)==1)));
test_RCond_3 = mean(test_RCond(find(test(:,65)==0)));

res_train = transpose([train_Cond_3,train_Cond_5,mean(train_Cond);
    train_RCond_3,train_RCond_5,mean(train_RCond)]);
res_test = transpose([test_Cond_3,test_Cond_5,mean(test_Cond);
    test_RCond_3,test_RCond_5,mean(test_RCond)]);

```

```

train_Cond_pre = zeros(1,N);
train_RCond_pre = zeros(1,N);
test_Cond_pre = zeros(1,N_t);
test_RCond_pre = zeros(1,N_t);

for i=1:N

    if lnp_x(train(i,1:64),0,S3,S5,mu3,mu5)>
        lnp_x(train(i,1:64),1,S3,S5,mu3,mu5)
        train_Cond_pre(i) = 0;
    else train_Cond_pre(i) = 1;
    end
    if lnp_x(train(i,1:64),0,S3_r,S5_r,mu3,mu5)
        >lnp_x(train(i,1:64),1,S3_r,S5_r,mu3,mu5)
        train_RCond_pre(i) = 0;
    else train_RCond_pre(i) = 1;
    end
end

for i=1:N_t

    if lnp_x(test(i,1:64),0,S3,S5,mu3,mu5)> lnp_x(test(i,1:64),1,S3,S5,mu3,mu5)
        test_Cond_pre(i) = 0;
    else test_Cond_pre(i) = 1;
    end
    if lnp_x(test(i,1:64),0,S3_r,S5_r,mu3,mu5)>
        lnp_x(test(i,1:64),1,S3_r,S5_r,mu3,mu5)
        test_RCond_pre(i) = 0;
    else test_RCond_pre(i) = 1;
    end
end

%test error
e_test_3_Cond = abs(test_Cond_pre - transpose(test(:,65)));
e_test_3_Cond = sum(e_test_3_Cond(test(:,65)==0));
e_test_5_Cond = abs(test_Cond_pre - transpose(test(:,65)));
e_test_5_Cond = sum(e_test_5_Cond(test(:,65)==1));
e_test_total_Cond = sum(abs(test_Cond_pre - transpose(test(:,65))));

N_t3 = sum(test(:,65)==0);
N_t5 = N_t- N_t3;

e_test_3_RCond = abs(test_RCond_pre - transpose(test(:,65)));
e_test_3_RCond = sum(e_test_3_RCond(test(:,65)==0));
e_test_5_RCond = abs(test_RCond_pre - transpose(test(:,65)));

```

```
e_test_5_RCond = sum(e_test_5_RCond(test(:,65)==1));
e_test_total_RCond = sum(abs(test_RCond_pre - transpose(test(:,65))));
```

```
%training error
e_train_3_Cond = abs(train_Cond_pre - transpose(train(:,65)));
e_train_3_Cond = sum(e_train_3_Cond(train(:,65)==0));
e_train_5_Cond = abs(train_Cond_pre - transpose(train(:,65)));
e_train_5_Cond = sum(e_train_5_Cond(train(:,65)==1));
e_train_total_Cond = sum(abs(train_Cond_pre - transpose(train(:,65))));
```

```
e_train_3_RCond = abs(train_RCond_pre - transpose(train(:,65)));
e_train_3_RCond = sum(e_train_3_RCond(train(:,65)==0));
e_train_5_RCond = abs(train_RCond_pre - transpose(train(:,65)));
e_train_5_RCond = sum(e_train_5_RCond(train(:,65)==1));
e_train_total_RCond = sum(abs(train_RCond_pre - transpose(train(:,65))));
```

% %

% %

```
if t == 0;
    res = -D/2 * log(2*pi) - log(det(S0))/2 - ((x-mu0)*inv(S0)*transpose(x-mu0))/2;
else
    res = -D/2 * log(2*pi) - log(det(S1))/2 - ((x-mu1)*inv(S1)*transpose(x-mu1))/2;
end
end
% % % % % % % % % % % % % % % % % % % % % %
```