

Introduction to SQL-Part2 (Structured Query Language)

Introduction to Databases

Sina Meraji

Thanks to Ryan Johnson, John Mylopoulos, Arnold Rosenbloom
and Renee Miller for material in these slides

OTHER CONCEPTS



NULL values in SQL

- Values allowed to be NULL
 - Explicitly stored in relations
 - Result of outer joins
- Possible meanings
 - Not present (homeless man's address)
 - Unknown (Julian Assange's address)
- Effect: "poison"
 - Arithmetic: unknown value takes over expression
 - Conditionals: ternary logic (TRUE, FALSE, UNKNOWN)
 - Grouping: "not present"



Effect of NULL in expressions

- Arithmetic: NaN (Not a Number)
 - $NULL * 0 \rightarrow NULL$
 - $NULL - NULL \rightarrow NULL$
- Logic: TRUE, FALSE, NULL
 - $NULL \text{ OR } FALSE \rightarrow NULL$
 - $NULL \text{ OR } TRUE \rightarrow TRUE$
 - $NULL \text{ AND } TRUE \rightarrow NULL$
 - $NULL \text{ AND } FALSE \rightarrow FALSE$
 - $NOT \text{ NULL} \rightarrow NULL$

Ternary logic tricks:

TRUE = 1
FALSE = 0
NULL = ½
AND = min(...)
OR = max(...)
NOT = 1-x

Effects of NULL on grouping

- Short version: complicated
 - Usually, “not present”
- COUNT

– COUNT(R.*) = 2	COUNT(R.x) = 1
– COUNT(S.*) = 1	COUNT(S.x) = 0
– COUNT(T.*) = 0	COUNT(T.x) = 0
- Other aggregations (e.g. MIN/MAX)

– MIN(R.x) = 1	MAX(R.x) = 1
– MIN(S.x) = NULL	MAX(S.x) = NULL
– MIN(T.x) = NULL	MAX(T.x) = NULL

R x

⊥
1

S x

⊥

T x

⊥

SET Queries: Union, Intersection, Difference

- Operations on pairs of subqueries
- Expressed by the following forms
 - (<subquery>) **UNION [ALL]** (<subquery>)
 - (<subquery>) **INTERSECT [ALL]** (<subquery>)
 - (<subquery>) **EXCEPT [ALL]** (<subquery>)
- All three operators are **set-based**
 - Adding '**ALL**' keyword forces **bag semantics** (duplicates allowed)
- Another solution to the join selectivity problem!

```
(SELECT R.x FROM R JOIN S ON R.x=S.x)
UNION
(SELECT R.x FROM R JOIN T ON R.x=T.x)
```

Example: Union

→ “Find all first names and surnames of employees”

```
SELECT FirstName AS Name FROM Employee
UNION
SELECT Surname AS Name FROM Employee
```

Duplicates are removed, unless the **ALL** option is used:

```
SELECT FirstName AS Name FROM Employee
UNION ALL
SELECT Surname AS Name FROM Employee
```

Example: Intersection

→ “Find surnames of employees that are also first names”

```
SELECT FirstName AS Name FROM Employee
INTERSECT
SELECT Surname AS Name FROM Employee
```

equivalent to:

```
SELECT E1.FirstName AS Name
FROM Employee E1, Employee E2
WHERE E1.FirstName = E2.Surname
```

Example: Difference

→ “Find the surnames of employees that are not first names”

SELECT SurName **AS** Name **FROM** Employee

EXCEPT

SELECT FirstName **AS** Name **FROM** Employee

(Can also be represented with a nested query. See later)

Nested queries

- Scary-looking syntax, simple concept
 - Treat one query’s output as input to another query
 - Inner schema determined by inner SELECT clause
- Consider the expression tree



Nested queries – uses

- Explicit join ordering
 - `FROM (A join B)` is a (very simple) query to run first
 - Input relation for a set operation
 - Union, intersect, difference
 - Input relation for a larger query
 - Appears in FROM clause
 - Usually joined with other tables (or other nested queries)
- => `FROM A, (SELECT ...) B WHERE ...`
 => Explicit join ordering is a degenerate case

Nested queries – more uses

- Conditional relation expression
 - Dynamic list for [NOT] IN operator
- => `WHERE (E.id, S.name)`
`IN (SELECT id, name FROM ...)`
- Special [NOT] EXISTS operator
- => `WHERE NOT EXISTS (SELECT * FROM ...)`
- Scalar expression
 - Must return single tuple (usually containing a single attribute)
- => `0.13 * (SELECT sum(value)`
`FROM Sales WHERE taxable)`
 => `S.value > (SELECT average(S.value)`
`FROM Sales S)`



13

List comparisons: ANY, ALL, [NOT] IN

- Compares a value against many others
 - List of literals
 - Result of nested query

Let **op** be any comparator (>, <=, !=, etc.)

- **x op ANY** (a, b, c)
 - = **x op a OR x op b OR x op c**
- **x op ALL** (a, b, c)
 - = **x op a AND x op b AND x op c**
- **[NOT] IN**
 - **x NOT IN (...)** equivalent to **x != ALL(...)**
 - **x IN (...)** equivalent to **x = ANY(...)**

ANY is \exists (exist), ALL is \forall (for each) (English usage often different!)



15

Example: Another Nested Query

→ “Find employees of the Planning department, having the same first name as a member of the Production department”

```
SELECT FirstName,Surname
FROM Employee
WHERE Dept = 'Plan' AND FirstName = ANY (
    SELECT FirstName FROM Employee WHERE Dept = 'Prod')
```

equivalent to:

```
SELECT E1.FirstName,E1.Surname
FROM Employee E1, Employee E2
WHERE E1.FirstName=E2.FirstName AND E2.Dept='Prod' AND
E1.Dept='Plan'
```



14

Example: Simple Nested Query

→ “Find the names of employees who work in departments in London”

```
SELECT FirstName, Surname
FROM Employee
WHERE Dept = ANY(
    SELECT DeptName
    FROM Department
    WHERE City = 'London')
```

equivalent to:

```
SELECT FirstName, Surname
FROM Employee, Department D
WHERE Dept = DeptName AND D.City = 'London'
```



16

Example: Negation with Nested Query

→ “Find departments where there is no employee named Brown”

```
SELECT DeptName
FROM Department
WHERE DeptName <> ALL (
    SELECT Dept FROM Employee WHERE Surname = 'Brown')
```

equivalent to:

```
SELECT DeptName FROM Department
EXCEPT
SELECT Dept FROM Employee WHERE Surname = 'Brown'
```



17

Operators IN and NOT IN

- Operator **IN** is a shorthand for **= ANY**

```
SELECT FirstName, Surname
FROM Employee
WHERE Dept IN (
    SELECT DeptName FROM Department WHERE City = 'London')
```

- Operator **NOT IN** is a shorthand for **<> ALL**

```
SELECT DeptName
FROM Department
WHERE DeptName NOT IN (
    SELECT Dept FROM Employee WHERE Surname = 'Brown')
```



19

Operator: [NOT] EXISTS

- Checks whether a subquery returned results

“Find all persons who have the same first name and surname with someone else (synonymous folks) but different tax codes”

```
SELECT * FROM Person P
WHERE EXISTS (
    SELECT * FROM Person P1
    WHERE P1.FirstName = P.FirstName AND P1.Surname =
        P.Surname AND P1.TaxCode <> P.TaxCode)
```



18

max, min as Nested Queries

“Find the department of the employee earning the highest salary”

with max:

```
SELECT Dept FROM Employee
WHERE Salary IN (SELECT max(Salary) FROM Employee)
```

without max:

```
SELECT Dept FROM Employee
WHERE Salary >= ALL (SELECT Salary FROM Employee)
```



20

Operator: [NOT] EXISTS (cont.)

“Find all persons who have no synonymous persons”

```
SELECT * FROM Person P
WHERE NOT EXISTS (
    SELECT * FROM Person P1
    WHERE P1.FirstName = P.FirstName AND P1.Surname =
        P.Surname AND P1.TaxCode <> P.TaxCode)
```



Tuple Constructors

- The comparison within a nested query may involve several attributes bundled into a tuple
- A tuple constructor is represented in terms of a pair of angle brackets

– The previous query can also be expressed as:

```
SELECT * FROM Person P
WHERE <FirstName,Surname> NOT IN (
    SELECT FirstName,Surname
    FROM Person P1
    WHERE P1.TaxCode <> P.TaxCode)
```



What's next?

- The Data Definition Language (DDL)
 - Subset of SQL used to manage schema
 - CREATE, ALTER, RENAME, DROP
 - Data types
- Data Manipulation Language (DML)
 - Subset of SQL used to manipulate data
 - INSERT, UPDATE, DELETE



Comments on Nested Queries

- Use of nesting
 - (-) may produce **less declarative** queries
 - (+) often results in **improved readability**
- Complex queries can become very difficult to understand
- The use of variables must respect scoping conventions:
 - a variable can be used only within the query where it is defined, OR
 - within a query that is recursively nested within the query where it is defined